



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

USB 2.0 Hi-Speed Panel Mount Cable, 5-Pin Motherboard IDC to USB Type-A (F/F), 3 ft.

MODEL NUMBER: U024-003-5P-PM







Highlights

- Supports data transfer speeds up to 480 Mbps
- 5-pin PCB header connects to computer's motherboard
- USB-A port attaches with included screws
- Corrosion-resistant gold-plated contacts
- Backward compatible with previous USB generations

System Requirements

Computer with 5-pin motherboard connector

Package Includes

- U024-003-5P-PM USB 2.0
 Hi-Speed Panel Mount Cable, 3
 ff
- (2) Mounting screws

Description

The U024-003-5P-PM USB 2.0 Hi-Speed Panel Mount Cable connects to a computer's motherboard to add a panel-mounted USB Type-A port. In addition to the front panel of a computer, the USB-A port can be installed in

a trade show booth, retail kiosk or teacher's or lecturer's podium, allowing you to conveniently connect a thumb drive or other USB device. The PCB header terminates on almost any five-pin motherboard.

The three-foot cable supports data transfer rates up to 480 Mbps and is backward compatible with previous USB generations. Gold-plated contacts resist corrosion and ensure optimal signal transfer. Premium double-shielded cables with tinned copper braid and aluminum Mylar foil feature twisted 28 AWG data lines and 24 AWG power lines. PVC jacket with molded connectors and integral strain relief provides durability and long life. Mounting screws included.

Features

Adds a Panel-Mounted USB-A Port

- . Allows convenient USB access from a trade show booth, retail kiosk or lecturer's podium
- 5-pin PCB header terminates on computer's motherboard
- Supports data transfer speeds up to 480 Mbps
- Backward compatible with previous USB generations

Premium Construction for Premium Performance

- · Corrosion-resistant gold-plated contacts for optimal signal transfer
- Fully molded construction with strain relief for durability and long life
- Flexible PVC jacket easy to install in tight spaces
- Double shielding with tinned copper braid, aluminum Mylar foil and twisted 28/24 AWG data/power lines
- · Mounting screws included

Specifications





OVERVIEW	
Cable Type	Panel mount/Keystone Jack; USB
INPUT	
Cable Length (ft.)	3
Cable Length (m)	1
PHYSICAL	
Color	Black
CONNECTIONS	
Connector A	5 PIN IDC (FEMALE)
Connector B	USB A (FEMALE)
CERTIFICATIONS	
Certifications	RoHS compliant
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies