

FCC RF EXPOSURE REPORT

FCC ID: QIS-IPP8950

Project No. : 1406C208
Equipment : IP Phone
Model : eSpace 8950
Applicant : Huawei Technologies Co.,Ltd.
**Address : Administration Building, Headquarters of
Huawei Technologies Co., Ltd., Bantian,
Longgang District Shenzhen China**

**According: : FCC Guidelines for Human Exposure IEEE
C95.1**

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	Shenzhen Sunway Communication Co.,Ltd	111003WS322A	Integral	N/A	3.8

GENERAL CONCLUSION:

Maximum measured transmitter power:

OutputPower (dBm)	Output Power (mW)	Limit (mW)
1.57	1.44	10

According to FCC KDB447498 V05, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 1.44mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold