



# UniFlood M G2

## BVP354 120LED RGBWW 220V L50 10 DMX

UniFlood M G2 - 10720 lm - 240 W - -

The Philips UniFlood M gen2 is a cost-effective, exterior-rated architectural LED floodlight that's designed for façade, landscape and outdoor floodlighting applications. The robust, modular, rectangular design features highly-efficient optics, making it ideal for illuminating everything from multi-storey façades and bridges to landmarks and monuments. This LED floodlight is available in white, monochromatic colours, RGB, RGBW and tunable white. It comes with six different spread lenses ranging from narrow spot to wide flood and has DMX512/RDM control option. A truly modular floodlight that gives architects and designers the freedom to explore a wide range of concepts and designs with no limitations.

### Warnings and Safety

- For outdoor use only.

### Product data

General information		Operating and electrical	
Driver included	Yes	Input Voltage	220 to 240 V
Lighting Technology	LED	Line Frequency	50 to 60 Hz
<b>Light technical</b>		Input frequency	50 to 60 Hz
Luminous Flux	10,720 lm	Inrush current	60 A
Correlated Colour Temperature	-	Power Consumption	240 W
Luminous Efficacy (rated) (Nom)	45 lm/W	Power Factor (Fraction)	0.9
Colour rendering index (CRI)	>80	Connection	Flying leads/wires and 2 push-in connectors 4-pole
Light source colour	RGBW	Cable	Cable 0.5 m without plug 3-pole and 2 cables 0.5 m with connector 4-pole
Optical cover/lens type	Clear glass		

# UniFlood M G2

## Temperature

Ambient temperature range -40 to +50 °C

## Controls and dimming

Dimmable Yes

Control interface Dynamic DMX/RDM

## Mechanical and housing

Housing material Extruded aluminium

Optical cover/lens material Acrylate

Housing Colour Dark grey

Overall length 486 mm

Overall width 304 mm

Overall height 231 mm

Effective projected area 0.156 m<sup>2</sup>

Dimensions (height x width x depth) 231 x 304 x 486 mm

## Approval and application

Ingress protection code IP66 [Dust penetration-protected, jet-proof]

Mech. impact protection code IK06 [1 J]

Protection class IEC Safety class I

Flammability mark For mounting on normally flammable surfaces

CE mark CE mark

## Initial performance (IEC compliant)

Luminous flux tolerance +/-10%

Power consumption tolerance +/-10%

## Product data

Full EOC 871951492830500

Order product name BVP354 120LED RGBWW 220V L50 10 DMX

Order code 92830500

SAP numerator – quantity per pack 1

Numerator – packs per outer box 1

Material number (12NC) 911401749093

Full product name BVP354 120LED RGBWW 220V L50 10 DMX

EAN/UPC - Case 8719514928305



## Dimensional drawing

