



SAR Evaluation Report

Application No.: SZEM1901010009CR
Applicant: Huawei Technologies Co., Ltd.
Address of Applicant: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, China.
Manufacturer: Huawei Technologies Co., Ltd.
Address of Manufacturer: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, China.
Factory: Tiinlab Acoustic Technology (Shenzhen) Co., Ltd.
Address of Factory: Tianliao Building F14 East Block (New Materials Industrial Park), Xueyuan Road, Nanshan District, Shenzhen
Equipment Under Test (EUT):
EUT Name: Wireless Bluetooth Earphones
Model No.: AM-H1CL, CM-H1CL ♣
 ♣ Please refer to section 4.1 of this report which indicates which model was actually tested and which were electrically identical.
Trade mark: HUAWEI, HONOR
FCC ID: QISAM-H1CL
Standards: 47 CFR Part 1.1307
 47 CFR Part 2.1093
 KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2018-12-23
Date of Test: 2018-12-23 to 2018-12-26
Date of Issue: 2019-01-03

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu

Keny Xu
 EMC Laboratory Manager



2 Version

<i>Revision Record</i>				
<i>Version</i>	<i>Chapter</i>	<i>Date</i>	<i>Modifier</i>	<i>Remark</i>
01		2019-01-03		Original

Authorized for issue by:			
			
		<hr/> Powell Bao /Project Engineer	
			
		<hr/> Eric Fu /Reviewer	



3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF EUT	4
4.2 TEST LOCATION.....	5
4.3 TEST FACILITY.....	5
4.4 DEVIATION FROM STANDARDS.....	5
4.5 ABNORMALITIES FROM STANDARD CONDITIONS	5
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 SAR EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 <i>Standard Requirement</i>	6
5.1.2 <i>Limits</i>	6
5.1.3 <i>EUT RF Exposure</i>	6-7



4 General Information

4.1 General Description of EUT

Power Supply:	Powered by DC3.7V rechargeable battery and can be charged by charging base
Sample Type:	Portable production
For BT:	
Operation Frequency	2402MHz to 2480MHz
Bluetooth Version:	V4.2 Dual mode
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Antenna Gain:	-0.73dBi
Antenna Type:	Chip Antenna
For BLE:	
Operation Frequency	2402MHz to 2480MHz
Bluetooth Version:	V4.2 Dual mode
Modulation Type	GFSK
Number of Channels	40
Channel Spacing	2MHz
Antenna Gain:	-0.73dBi
Antenna Type:	Chip Antenna

Remark:

Model No.:AM-H1CL, CM-H1CL

Only the model AM-H1CL was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on brand names and model names.



4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.



5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06
 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

BT:

The Max. power (including tune-up tolerance) is	8.29	dBm on the lowest channel	2.402	GHz (*)
8.29 dBm logarithmic terms convert to numeric result is nearly	6.75	mW		
According to the formula. calculate the test exclusion thresholds:				
$\text{General RF Exposure} = \frac{(\text{Max. Power of channel, including tune-up tolerance, mW}) * \sqrt{f(\text{GHz})}}{(\text{min. test separation distance, mm})}$				
$\text{General RF Exposure} = (6.75 \text{ mW} / 5 \text{ mm}) * \sqrt{2.402 \text{ GHz}} = 2.09$			(1)	
SAR requirement:				
$S = 3.0$			(2)	
(1) < (2)				
So the SAR report is not required.				
(*) Max. power refer to Report No.:SZEM190101000901				



BLE:

The Max. power (including tune-up tolerance) is	0.15	dBm on the lowest channel	2.402	GHz (*)
0.15 dBm logarithmic terms convert to numeric result is nearly 1.04 mW				
According to the formula. calculate the test exclusion thresholds:				
$General\ RF\ Exposure = \frac{(Max.\ Power\ of\ channel,\ including\ tune\ -up\ tolerance,\ mW) * \sqrt{f\ (GHz)}}{(min.\ test\ separation\ distance,\ mm)}$				
$General\ RF\ Exposure = (1.04\ mW / 5\ mm) * \sqrt{2.402\ GHz} = 0.32$				
SAR requirement:				
S = 3.0				
(1) < (2)				
So the SAR report is not required.				
(*) Max. power refer to Report No.:SZEM190101000902				

- End of the Report -

