



### Main

Product brand	Clipsal
Range of product	Series 4
Earth-leakage protection class	Class A

### Complementary

Number of poles	2
[Ue] rated operational voltage	240 V AC
[In] rated current	16 A
Earth-leakage current	30 mA
Mounting support	DRA DIN rail
[Icw] rated short-time withstand current	6 kA
Size	92.5 x 18 x 71.5 mm DIN 43880
Number of modules	1
Depth	71.5 mm inner

### Environment

IP degree of protection	IP20 IP40
standards	AS/NZS 61009

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.