



# TEST REPORT

No. I1640549-CTE02

for

**TCL Communication Ltd.**

**HSUPA/HSDPA/UMTS Quad Band/GSM Quad Band/LTE Tri**

**Band/CDMA EVDO Tri Band mobile phone**

**Model Name: 4044T**

**FCC ID: 2ACCJN010**

with

**Hardware Version: 03**

**Software Version: A4J**

**Issued Date: 2016-11-14**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

**Test Laboratory:**

***FCC 2.948 Listed: No.525429***

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: [ctl\\_terminals@catr.cn](mailto:ctl_terminals@catr.cn), website: [www.chinattl.com](http://www.chinattl.com)



## **REPORT HISTORY**

Report Number	Revision	Description	Issue Date
-	-	-	-

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. TESTING LOCATION .....</b>	<b>4</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.3. PROJECT DATA .....</b>	<b>4</b>
<b>1.4. SIGNATURE .....</b>	<b>4</b>
<b>2. CLIENT INFORMATION .....</b>	<b>5</b>
<b>2.1. APPLICANT INFORMATION .....</b>	<b>5</b>
<b>2.2. MANUFACTURER INFORMATION .....</b>	<b>5</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>6</b>
<b>3.1. ABOUT EUT .....</b>	<b>6</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>6</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>6</b>
<b>3.4. NORMAL ACCESSORY SETTING .....</b>	<b>7</b>
<b>3.5. GENERAL DESCRIPTION .....</b>	<b>7</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>7</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING .....</b>	<b>7</b>
<b>5. LABORATORY ENVIRONMENT .....</b>	<b>8</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>7. TEST EQUIPMENTS UTILIZED .....</b>	<b>10</b>
<b>ANNEX A: MEASUREMENT RESULTS .....</b>	<b>11</b>
<b>A.1 OUTPUT POWER .....</b>	<b>11</b>
<b>A.2 FREQUENCY STABILITY .....</b>	<b>12</b>
<b>A.3 OCCUPIED BANDWIDTH .....</b>	<b>14</b>
<b>A.4 EMISSION BANDWIDTH .....</b>	<b>16</b>
<b>A.5 CONDUCTED SPURIOUS EMISSION .....</b>	<b>18</b>

## **1. Test Laboratory**

### **1.1. Testing Location**

Company Name: CTTL(huayuan North Road)  
Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China  
100191  
Postal Code: 100191

### **1.2. Testing Environment**

Normal Temperature: 15-35℃  
Relative Humidity: 20-80%

### **1.3. Project data**

Testing Start Date: Oct. 25th,2016  
Testing End Date: Nov. 14th,2016


### **1.4. Signature**



---

Zhu Jun

(Prepared this test report)



---

Li ChuanFeng

(Reviewed this test report)



---

Guo Gan

Deputy Director of the laboratory  
(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C building, No. 232, Liang Jing Road, ZhangJiang High-Tech  
Park, Pudong Area, Shanghai, P.R. China.  
City: Shanghai  
Postal Code: 201203  
Country: China  
Contact Person: Gong Zhizhou  
Contact Email: zhizhou.gong@tcl.com  
Telephone: +86 21 31363544  
Fax: +86 21 61460602

### **2.2. Manufacturer Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C building, No. 232, Liang Jing Road, ZhangJiang High-Tech  
Park, Pudong Area, Shanghai, P.R. China.  
City: Shanghai  
Postal Code: 201203  
Country: China  
Contact Person: Gong Zhizhou  
Contact Email: zhizhou.gong@tcl.com  
Telephone: +86 21 31363544  
Fax: +86 21 61460602

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

Description	HSUPA/HSDPA/UMTS Quad Band/GSM Quad Band/LTE Tri Band/CDMA EVDO Tri Band mobile phone
Model	4044T
FCC ID	2ACCJN010
Frequency	CDMA800MHz(BC0);CDMA1900MHz(BC1);CDMA2ND800MHz(BC10)
Antenna	Internal
Power supply	Battery or Charger (AC Adaptor)
Extreme vol. Limits	3.55VDC to 4.35VDC (nominal: 3.8 VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	SN or MEID	HW Version	SW Version
UT04a	35957107010387	03	A4J

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	B1350001C11009QO
AE2	Normal Charger	S003AWU0500055

##### AE1

Model	Tli013C1
Manufacturer	BYD
Capacitance	1350mAh
Nominal Voltage	3.8V

##### AE2

Model	Normal Charger
Manufacturer	Ten Pao Industrial Co Ltd

\*AE ID: is used to identify the test sample in the lab internally.

### **3.4. Normal Accessory setting**

Fully charged battery was used during the test.

### **3.5. General Description**

The Equipment Under Test (EUT) is a model of HSUPA/HSDPA/UMTS Quad Band/GSM Quad Band/LTE Tri Band/CDMA EVDO Tri Band mobile phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfil the test.

## **4. Reference Documents**

### **4.1. Reference Documents for testing**

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 90	PRIVATE LAND MOBILE RADIO SERVICES	10-1-15 Edition
FCC Part 2	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS;GENERAL RULES AND REGULATIONS	10-1-15 Edition
ANSI/TIA-603-D	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2015
KDB971168 D01	Measurement Guidance for Certification of Licensed Digital Transmitters	v02r02



## 5. LABORATORY ENVIRONMENT

**Shielding chamber** did not exceed following limits along the RF testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω



## 6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	90.635	P
2	Frequency Stability	2.1055/90.213	P
3	Occupied Bandwidth	2.1049	P
4	Emission Bandwidth	2.1049	P
5	Conducted Spurious Emission	2.1051/90.691	P



## **7. Test Equipments Utilized**

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CALIBRATION INTERVAL	CAL DUE DATE
1	Spectrum Analyzer	FSV30	101576	R&S	1 Year	2017-2-1
2	Wireless Communications Test Set	8960(E5515C)	MY483609 50	Agilent	1 Year	2017-7-17
3	Climatic chamber	SH-641	92009050	ESPEC	2 Years	2017-2-16

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 OUTPUT POWER**

#### **A.1.1 Summary**

During the process of testing, the EUT was controlled via Agilent Wireless Communications Test Set (8960(E5515C)) to ensure max power transmission and proper modulation.

This result is peak output power conducted measurements for the EUT. In all cases, output power is within the specified limits.

#### **A.1.2 Method of Measurements**

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSV30 (average).

These measurements were done at 2 frequencies of CDMA BC10 (bottom and top of operational frequency range) for 1xRTT and 1xEVDO.

The measurement method is from KDB 971168 D01 5.2.1:

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Set number of points in sweep  $\geq 2 \times$  span / RBW.
- e) Sweep time = auto-couple.
- f) Detector = RMS (power averaging).
- g) If the EUT can be configured to transmit continuously (i.e., burst duty cycle  $\geq 98\%$ ), then set the trigger to free run.
- h) If the EUT cannot be configured to transmit continuously (i.e., burst duty cycle  $< 98\%$ ), then use a sweep trigger with the level set to enable triggering only on full power bursts and configure the EUT to transmit at full power for the entire duration of each sweep. Ensure that the sweep time is less than or equal to the transmission burst duration.
- i) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- j) Compute the power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with the band limits set equal to the OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

#### **A.1.3 Measurement results**

##### **CDMA BC10**

##### **Measurement result**

Channel	Frequency(MHz)	Channel power(dBm)		
		1xRTT	1xEVDO	
			Rel0	RevA
476	817.9	23.94	24.01	24.54
684	823.1	24.64	24.66	24.34

## **A.2 FREQUENCY STABILITY**

### **A.2.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a “call mode”. This is accomplished with the use of Agilent 8960(E5515C) Wireless Communications Test Set.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the 8960(E5515C) and in a simulated call on mid channel of CDMA BC10, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the 8960(E5515C) and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C decrements from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

### **A.2.2 Measurement Limit**

#### **A.2.2.1 For Hand carried battery powered equipment**

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.6VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.

#### **A.2.2.2 For equipment powered by primary supply voltage**

For Part 90.213, the frequency stability of the transmitter shall be maintained within  $\pm 2.5$ ppm of the center frequency. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

**A.2.3 Measurement results****CDMA BC 10****Frequency Error vs Voltage**

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.55	0.72	0.001
3.8	0.76	0.001
4.35	0.54	0.001

**Frequency Error vs Temperature**

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-0.43	0.001
-20	-0.23	0.001
-10	-0.07	0.001
0	0.43	0.001
10	1.28	0.001
20	0.76	0.001
30	1.26	0.001
40	0.12	0.001
50	1.29	0.001

### A.3 OCCUPIED BANDWIDTH

#### A.3.1 Occupied Bandwidth Results

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the CDMA frequency band. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

#### Test Condition

RBW	VBW	Span	SweepTime	Detector	Trace Mode
20KHz	50KHz	5MHz	40ms	Peak	Max Hold


The EUT was set up for the max output power with pseudo random data modulation. Use the Occupied Bandwidth function of SA to measure the 99% bandwidth.

#### CDMA BC10 (99% BW)


Channel	Occupied Bandwidth (99% BW)(MHz)
476	1.266
684	1.266

#### CDMA BC10

#### Channel 476-Occupied Bandwidth (99% BW)



### Channel 684-Occupied Bandwidth (99% BW)



Date: 9.NOV.2016 09:33:12

## A.4 EMISSION BANDWIDTH

### A.4.1 Emission Bandwidth Results

Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the CDMA frequency band. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

#### Test Condition

RBW	VBW	Span	Sweptime	Detector	Trace Mode
20KHz	100KHz	3.84MHz	40ms	Peak	Max Hold


The EUT was set up for the max output power with pseudo random data modulation. Use the Occupied Bandwidth function of SA to measure the 26dBc bandwidth.

#### CDMA BC10 (-26dBc BW)

Channel	Emission Bandwidth (-26dBc BW) ( MHz)
476	1.428
684	1.423


#### CDMA BC10

#### Channel 476- Emission Bandwidth (-26dBc BW)





### Channel 684- Emission Bandwidth (-26dBc BW)



Date: 9.NOV.2016 09:42:36



## **A.5 CONDUCTED SPURIOUS EMISSION**

### **A.5.1 Measurement Method**

The spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For CDMA BC10, data taken from 30 MHz to 10GHz.

Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

For any frequency removed from the EA licensee’s frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $116\log_{10}(f/6.1)$  decibels or  $50 + 10 \log_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

For any frequency removed from the EA licensee’s frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10\log_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

#### **CDMA BC10 Transmitter**

Channel	Frequency (MHz)
476	817.9
684	823.1


## A.5.2 Measurement result

### CDMA BC10

#### A. 5.2.1 Channel 476: 30MHz –1GHz


Spurious emission limit –13dBm.

**NOTE:** peak above the limit line is the carrier frequency.




#### A.5.2.2 Channel 476: 1GHz –2.5GHz

Spurious emission limit –13dBm.



### A.5.2.3 Channel 476: 2.5GHz –7.5GHz


Spurious emission limit –13dBm.



Date: 10.NOV.2016 06:36:29

### A.5.2.4 Channel 476: 7.5GHz –10GHz


Spurious emission limit –13dBm.



Date: 10.NOV.2016 06:40:21


### A.5.2.5 Channel 476: Band Edge

Spurious emission limit -20dBm.



### A.5.2.6 Channel 476: Outer Extended Band Edge


Spurious emission limit -13dBm.



### A. 5.2.7 Channel 684: 30MHz –1GHz

Spurious emission limit –13dBm.


**NOTE:** peak above the limit line is the carrier frequency.



Date: 10.NOV.2016 06:31:48

### A.5.2.8 Channel 684: 1GHz –2.5GHz


Spurious emission limit –13dBm.



Date: 10.NOV.2016 06:33:36


#### A.5.2.9 Channel 684: 2.5GHz –7.5GHz

Spurious emission limit –13dBm.




#### A.5.2.10 Channel 684: 7.5GHz –10GHz

Spurious emission limit –13dBm.



### A.5.2.11 Channel 684: Band Edge


Spurious emission limit -20dBm.



Date: 9.NOV.2016 08:57:18

### A.5.2.12 Channel 684: Outer Extended Band Edge

Spurious emission limit -13dBm.



Date: 9.NOV.2016 09:24:37





**\*\*\*END OF REPORT\*\*\***