



ENERGY STAR® Verification Testing Cover Letter

PAGE

1 of 1

ENERGY STAR® Partner: SATCO/NUVO**ENERGY STAR® Partner ID:** 31858**Tested Model Number(s):** 62/1341**Brand name(s):** Satco NUVO**Laboratory Name:** UL Verification Services Inc.**Laboratory EPA ID:** 1119581**ENERGY STAR® Specification:** Program Requirements for Luminaires, Version 2.2**Pass or Fail:** Pass**Relevant Test Results:**

Efficacy	83.3	lumens/watt
Light Output	1920.9	lumens
Zonal Lumen Requirement (Directional Luminaires except Inseparable SSL Luminaire and Non-Directional SSL Surface Mount Retrofit)	N/A	%
Lumen Maintenance	>54,000	hours
CCT (Indoor Luminaires Only)	3028	K
CRI (Indoor Luminaires Only)	92.4	
R9 (Indoor Luminaires Only)	60	
Power Factor:	0.982	
Maximum Measured Ballast or Driver Case Temperature	85.9	°C
Start Time (Indoor Luminaires Only)	104.6	milliseconds
Run-Up Time (Fluorescent Luminaires Only)	N/A	seconds
Color Angular Uniformity (Directional Solid State Indoor Luminaires Only)	N/A	
Color Maintenance (Solid State Indoor Luminaires Only)	0.0015	
Off-State Power Consumption (Only Luminaires Employing an Integral Method of Switching)	N/A	watts

UL Project No.: 13807387**Evaluator:** Shivani Vyas**Reviewer:** Jeffery Lockner**Certifier:** Gorette Pacheco**Issued:** 2021-06-14
(yyyy-mm-dd)**Revised:** N/A
(yyyy-mm-dd)

00-VS-XXXXX Version 3.0, The information and documentation involving UL Mark services are provided on behalf of UL Verification Services Inc. or any authorized licensee of UL Verification Services Inc.. The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Copyright© UL LLC. All rights reserved. May not be reproduced without permission. **UL PROPRIETARY AND CONFIDENTIAL. FOR UL INTERNAL USE ONLY.** This document is controlled and has been released electronically. The version on the UL intranet is the up-to-date document. Hard copies are uncontrolled and may not be up-to-date. Users of hard copies should confirm the revision by comparing it with the electronically controlled version.