



UniFlood M G2

BVP353 60LED 27K 220V L50 15

9605 lm - 120 W - 2700 K

Philips UniFlood M gen2 is a cost-effective, exterior-rated architectural LED floodlight that's designed for facade, landscape and outdoor flood lighting applications. The robust, modular, rectangular design features highly efficient optics, making it ideal for illuminating everything from multi-storey facades and bridges to landmarks and monuments. ;This LED floodlight is available in white, monochromatic colours, RGB, RGBW and tunable white. It comes with six different spread lenses ranging from narrow spot to wide flood and has DMX512/RDM control option. A truly modular floodlight that gives architects and designers the freedom to explore a wide range of concepts and designs with no limitations.

Warnings and Safety

- For outdoor use only.

Product data

| General information | |
|--------------------------|--|
| Lamp colour code | 827 warm white |
| Driver included | Yes |
| Optical cover/lens type | GC [Clear glass] |
| Control interface | - |
| Connection | Flying leads/wires |
| Cable | Cable without plug 3-pole |
| Protection class IEC | Safety class I (I) |
| Flammability mark | F [For mounting on normally flammable surfaces] |
| CE mark | CE mark |
| Operating and electrical | |
| Input Voltage | 220 to 240 V |

| Input frequency | 50 to 60 Hz |
|-----------------------------|----------------------|
| Power factor (min.) | 0.9 |
| Controls and dimming | |
| Dimmable | No |
| Mechanical and housing | |
| Housing material | Aluminum extruded |
| Optical cover/lens material | Acrylate |
| Overall length | 486 mm |
| Overall width | 140 mm |
| Overall height | 149 mm |
| Effective projected area | 0.078 m ² |


UniFlood M G2

| | |
|--|---|
| Colour | Dark Grey |
| Approval and application | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |
| Initial performance (IEC compliant) | |
| Initial luminous flux (system flux) | 9605 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 80 lm/W |
| Lamp colour temperature | 2700 K |
| Colour Rendering Index | >80 |
| Initial chromaticity | 4 SDCM |
| Initial input power | 120 W |
| Power consumption tolerance | +/-10% |

| | |
|-----------------------------------|------------------------------|
| Application conditions | |
| Ambient temperature range | -40 to +50 °C |
| Product data | |
| Full product code | 871951492724799 |
| Order product name | BVP353 60LED 27K 220V L50 15 |
| EAN/UPC – product | 8719514927247 |
| Order code | 911401748033 |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 4 |
| SAP material | 911401748033 |
| Net Weight (Piece) | 6.200 kg |



Dimensional drawing



BVP353 60LED 27K 220V L50 15

