**XPression** 

# **XPression Tick-it Solo Hardware Specifications**



#### **Dimensions**

| Height          | Width             | Depth             |
|-----------------|-------------------|-------------------|
| 4.28 cm (1.68") | 48.20 cm (18.98") | 57.76 cm (22.74") |

### Weight

| Net Weight            | Gross Weight When<br>Shipped |
|-----------------------|------------------------------|
| 12.42 kg (27.38 lbs.) | 19.34 kg (42.63 lbs.)        |

#### **Hardware**

| Chassis             | 1 RU chassis (rack-mount)   |
|---------------------|---|
| Power Supply        | 550W redundant supplies<br>Voltage Range 100-240 VAC<br>Input Current 7.4 A- 3.7 A                      |
| System Drives       | 2x 256GB SSD RAID 1 (Mirrored)  |
| Media Drives        | 2x 1TB SSD RAID 1 (Mirrored)  |
| CPU                 | Intel© Core i7-8700K, 6 Core, 12MB<br>Cache, 3.7GHz, 4.7Ghz Turbo                                       |
| Memory              | 16GB (2x8GB) 2666MHz DDR4 UDIMM<br>Non-ECC  |
| GPU                 | NVIDIA® Quadro RTX <sup>™</sup> 4000, 8GB<br>GDDR6, 2304 CUDA® Cores, 3x<br>Display Port 1.4 Connectors |
| Video I/O           | Matrox® DSXLE4L/44/100F   |
| Operating<br>System | Microsoft® Windows® 10 Professional 64-bit  |

## **Image File Formats**

## **Clip File Formats**

AVI | MPEG† | QuickTime† | Sequential Images

#### **3D File Formats**

\*.3ds | \*.obj | \*.fbx | \*.c4d‡

## **Inputs / Outputs**

| Video     | Up to 3 Video/Key Pair Outs   2 Inputs                        |
|-----------|---|
| Audio     | Embedded Audio Only   |
| Reference | 1x Analog Black Burst (Bi-Level Sync) or Tri-Level Sync input |

#### **Control**

| Ethernet | 1x RJ-45 1G Ethernet Port<br>1x RJ-45 10G Ethernet Port   |
|----------|---|
| GPI      | RS-232 Serial GPI, RossTalk/Smart GPI through TCP/IP  |
| USB      | Front Panel:  2x USB 3.1 (Type A)  1x USB 3.1 (Type C)/iGFX Display Port Rear Panel:  2x USB 3.1 (Type C)/iGFX Display Port |

## **Temperature and Humidity**

| Temperature          | Operating: 10°C to 35°C (50°F to 95°F)  |
|----------------------|---|
| Range                | Storage: -40°C to 65°C (-40°F to 149°F)   |
| Relative<br>Humidity | Operating: 10% to 85% (Max dew point temperature = 40°C) (non-condensing) Storage: 10% to 90% (Max dew point temperature = 60°C) (non-condensing) |



<sup>\*.</sup>tga | \*.tif | \*.psd | \*.bmp | \*.jpg | \*.gif | \*.png

## **Included Accessories**

| Rackmount Kit            | Slide rails, handles, and mounting hardware                   |
|--------------------------|---|
| USB                      | 2x USB Type C to USB Type A Adapters                          |
| Keyboard                 | Standard USB PC Keyboard                                      |
| Mouse                    | USB mouse   |
| Security Key<br>Software | USB key pre-installed internally<br>XPression Software dongle |

#### **Video Formats**

480i 29.97Hz (NTSC) | 576i 25Hz (PAL) | 720p 50Hz | 720p 59.94Hz | 720p 60Hz | 1080i 25Hz | 1080i 29.97Hz | 1080i 30Hz | 1080p 29.97Hz | 1080p 50Hz | 1080p 59.94Hz | 1080p 60Hz | 1080psf 23.976Hz | 1080psf 24Hz | 1080psf 25Hz | 1080psf 29.97Hz | 1080psf 30Hz | Custom Formats

#### **Included Software**

- Microsoft® Windows® 10 Professional 64-bit O/S
- · XPression software package

## **Warranty**

12 Month System Warranty (parts / labor and software updates)

† Available in the 32-bit editions only ‡ Available in the 64-bit editions only Specifications subject to change.

