

Durable Design

- · Stainless steel interior & exterior
- Coated evaporator coil
- 3 height adjustable, heavy duty, PE coated wire shelves per door
- LED interior lighting
- Digital temperature display
- Door lock with keys
- · Simple plug-in installation

Energy Efficient

- Self-closing door with stay open feature
- Seals tight with magnetic vinyl gasket
- Open door alert beeps when door is open for 3 minutes
- · Foamed-in place high-density polyurethane insulated body, CFC-Free
- · Large evaporator & condenser for quick cooling and greater efficiency

Superior Quality

- Designed for mobility, reliability & efficiency in commercial kitchens
- Certifieed with ETL guaranteeing quality standards
- •4" heavy duty swivel & locking front casters
- · Easy grip handles
- Entirely self-contained system
- Automatic defrost system
- Digitally controlled temperature system
- · Accommodates full-size bun sheet pans
- Easily adjustable shelf height
- Internal storage capacity is 67 cu. ft.
- NEMA 5-15 plug
- •R-290 Natural Refrigerant
- Compressor: Refrigerator 1/2 HP / Freezer 1 HP
- Holding temperature: Refrigerator 33°F to 39°F /Freezer 5°F to -9.4°F



Refrigerator & Freezer **Top Mount Compressor Triple Door Series**

KTSR-3 | KTSF-3














Project Name:		
Location:		
Item:	Qty:	
Model:		







Refrigerator & Freezer **Top Mount Compressor Triple Door Series**

KTSR-3 | KTSF-3







Model Number	Description	# of Doors	# of Shelves	Capacity (cubic ft)	External Dimensions w/handle (W x D x H in)	Internal Dimensions (W x D x H in)	Compressor Size	Voltage / Frequency	Amps	Working Temp	Refrigerant	Ship Weight (lbs)
KTSSR -3	Top Mount Triple Door Refrigerator	3	9	67	81.1 x 32.75 x 81.8	77.2 x 24.3 x 53.8	1/2	115V 60 HZ	6.3	33₀F to 39₀F	R-290	571
KTSF -3	Top Mount Triple Door Freezer	3	9	67	81.1 x 32.75 x 81.8	77.2 x 24.3 x 53.8	1	115V 60 HZ	8.4	5₀F to -9°F	R-290	600







Nema 5-15P

These units are designed for maximum performance in an air-conditioned area of 75°F ambient temperature and 55% relative humidity. There must be adequate ventilation at the top, sides & rear of the unit for proper operation.

Warranty: 36 months parts and labor. Additional 24 months on compressor (part only)

KOOL-IT is a registered trademark of MVP Group. Specifications subject to change without notice.



5659 Royalmount Ave. Montreal, QC, Canada H4P 2P9 Telephone: 514.737.9701 / Toll Free: 888.275.4538 Miami, FL, United States 33181

Fax: 514.342.3854 / Toll Free: 877.453.8832 sales@mvpgroupcorp.com / mvpgroupcorp.com

12000 Biscayne Blvd., Suite # 108

Telephone: 786.600.4687 / Toll Free: 844.218.8477 Fax: 786.661.4100

06-2019