



0300642 Floodlight - 10W 800lm 4000K IP65 - Black

- 800 lumen
- Aluminium housing
- Mounting bracket

This floodlight is very robust and can easily be installed using the included mounting bracket. The floodlight is suitable for indoors as well as outdoors and is made of impact resistant material. Additionally, the lamp illuminates workplaces or outdoor spaces with neutral white light.

LED's light Basic

General

Brand	LED's light Basic
Collection	Functional
Manual language	Dutch
Package content	Multi language manual
PLC Status	Phase out
Warranty	2-Year

### Lighting

	Total lumens
800 lm	
Lamp efficacy	80
Color temperature	4000 K
Color description	Neutral white
Color rendering index	80
Beam angle	120 °

### Electrical

Power consumption	10.0 W
Input frequency	50/60 Hz
Input current	90 — 90 mA
Safety class	II
Control gear type	Driver on board
Type of dimming	Not dimmable
LED chip type	SMD 2835
LED chip quantity	12

### Performance

IP Rating	IP65
Operating Temperature	-10 — 50 °C
Energy class [EU 874/2012]	A+
Energy class [EU 2019/2015]	F
Eprel ID	851769

### Mechanical

Housing material	Aluminum
Diffuser material	Tempered glass
Mounting type	Surface

### Logistic Data

Packaging length	11.5 cm
------------------	---------

5.5 cm	Packaging width
Packaging height	8.5 cm
Packaging gross weight	188.0 g
EAN Product	8719323788596
Packaging paper material weight	34.0 g
Packaging plastic material weight	2.00 g
Master carton length	45 cm
Master carton width	30 cm
Master carton height	26 cm
CBM master carton	0.04 m <sup>3</sup>
Master carton quantity	50
Master carton gross weight	9.90 kg
Master carton paper material weight	1100.00 g
Master carton plastic material weight	0.00 g
Country of Origin	CN
HS Code	9405421000

View on the website: [shada.nl/p/0300642](https://shada.nl/p/0300642)