

Mikrotik Routerboard		
 <p>#06872 Net Price: 27,60 EUR Unit: pcs</p> <p>Mikrotik Level 4 Upgrade Mikrotik RouterOS WISP AP (Level 4) license</p>	 <p>#08090 Net Price: 45,80 EUR Unit: pcs</p> <p>Routerboard MikroTik RB411U CPU: Atheros AR7161 Memory: 32MB, SDRAM Copper ports: 1x 10/100 Mbps RJ-45 Auto MDI/MDI-X: yes Bootloader: RouterBOOT, 1Mbit Flash chip Data storage: 64MB NAND, build-in Number of SIM slots: 1 Modem (Mini SIM) MiniPCI slots: 1 MiniPCI-e slots: 1 Serial port: RS232 Number of USB ports: 1 USB slot type: USB type A Max USB current (A): 1 Serial port: asynchronous, RS-232C Speaker: beeper Dimensions: 105x105 mm Power: PoE 10 V + 28 V DC, 10 V + 28 V DC Power consumption: 12W Operating system: MikroTik Router OS 2.9 Level 3 Manufacturer: MikroTik</p>	 <p>#08132 Net Price: 36,10 EUR Unit: pcs</p> <p>Routerboard MikroTik RB711-5Hn-uFL CPU: Atheros AR7240 400MHz Memory: 32MB, SDRAM Wireless standards: Built in 5GHz AR9280 802.11a/n card, 1 MMCX/uFL connector (depends on model) Copper ports: 1x 10/100 Mbps RJ-45 Auto MDI/MDI-X: yes Bootloader: RouterBOOT Data storage: 64MB NAND, build-in Speaker: beeper Dimensions: 105x105 mm Power: PoE 10 V + 28 V DC Power consumption: 4.5W Operating system: MikroTik Router OS 2.9 Level 4 Manufacturer: MikroTik</p>
 <p>#07093 Net Price: 37,30 EUR Unit: pcs</p> <p>Routerboard MikroTik RB750 CPU: Atheros AR7240 300MHz (overlock 400MHz) Memory: 32MB DDR SDRAM Data storage: 64 MB onboard NAND memory chip Copper ports: 5x 10/100 Mbps RJ-45 Ethernet ports Bootloader: RouterBOOT Speaker: beeper Power: PoE 9V + 28V DC Power jack: 9V + 28V DC Power consumption: max. 3W Dimensions: 113x89x28mm Operating system: MikroTik Router OS v3 Level 4 Manufacturer: MikroTik</p>	 <p>#07070 Net Price: 66,80 EUR Unit: pcs</p> <p>Routerboard MikroTik RB951G-2HnD CPU: Atheros AR9344 600MHz CPU Memory: 128MB DDR2 onboard memory Copper ports: 5x 10/100/1000 Mbps RJ-45 Ethernet ports USB ports: 1 LED Indicators: Power, NAND activity, 5 Ethernet LEDs, wireless activity LED Power: PoE 9V + 28V DC on Ethernet port 1 (Non802.3af) Power jack: 9V - 28 V DC Power consumption: max. 7W Antennas: 2x2 MIMO PIF antennas, max gain 2.5dBi RX sensitivity 802.11g: -96dBm @ 6Mbit/s to -80dBm @ 54Mbit/s 802.11n: -96dBm @ MCS0 to -78dBm @ MCS7 TX power 802.11g: 30dBm @ 6Mbps to 25dBm @ 54 Mbps 802.11n: 30dBm @ MCS0 to 23dBm @ MCS7 Modulations OFDM: BPSK, QPSK, 16 QAM, 64QAM DSSS: DBPSK, DQPSK, CCK Dimensions: 113x138x29mm Operating system: MikroTik Router OS v4 Level 4</p>	 <p>#08919 Net Price: 7,51 EUR Unit: pcs</p> <p>Routerboard Power Adapter, PoE 24V, 1.25A</p>
 <p>#06640 Net Price: 36,00 EUR Unit: pcs</p> <p>Wireless access point 2.4GHz (MikroTik Routerboard RB951Ui-2nD) This small home access point is the perfect device for homes or small offices where all you need is a wireless AP and a few wired devices connected. Based on our popular RB951-2n, the new hAP is an improvement in many areas. The device can be powered from the power jack or with passive PoE from a PoE injector. The power adapter is included. hAP provides PoE output function for port #5 - it can power other PoE capable devices with the same voltage as applied to the unit. Maximum load on the port is 500mA. The hAP is preconfigured, so all you need to do, is plug in the internet cable, the power, and start using the internet by connecting to the MikroTik network. Standards: IEEE 802.11b/g/n Ports: 5x 10/100 Mbps RJ-45, 1x USB Chipset: MIPSBE, QCA9531, 650 MHz Operating memory: 64MB DDR SDRAM Storage size: 16 MB Frequency range: 2.4 - 2.5GHz Antenna: build-in, 2 dBi Beam width: 360° Dimensions: 113 x 89 x 28mm Mounting: mast or wall with the aid of antenna wall support Max. power consumption: 5 W Power: 6 V - 30 V (Jack or Passive PoE) Operating temperatures: -30°C + 70°C Operating humidity: 5% + 95%, non-condensing Certificates: CE, FCC, IC, EAC, ROHS Manufacturer: MikroTik</p>	 <p>#06472 Net Price: 2,41 EUR Unit: pcs</p> <p>Adapter Kit, Power over Ethernet</p>	 <p>#06406 Net Price: 3,27 EUR Unit: pcs</p> <p>Adapter Kit, Power over Ethernet (injector + splitter)</p>

 <p>#07031 Net Price: 5,05 EUR Unit: pcs</p> <p>Mikrotik Power Adapter, 24V, 0,75A, PoE</p>	 <p>#08058 Net Price: 3,44 EUR Unit: pcs</p> <p>Routerboard Power Adapter, 12V 1.0A</p>	 <p>#06869 Net Price: 3,46 EUR Unit: pcs</p> <p>Routerboard Power Adapter, 12V 1.2A</p>
 <p>#06404 Net Price: 5,59 EUR Unit: pcs</p> <p>Routerboard Power Adapter, 24V 1.0A</p>	 <p>#06611 Net Price: 13,80 EUR Unit: pcs</p> <p>Routerboard Power Adapter, 24V 1.6A</p>	 <p>#06378 Net Price: 12,60 EUR Unit: pcs</p> <p>Routerboard Power Adapter, 48V</p>
 <p>#06644 Net Price: 32,40 EUR Unit: pcs</p> <p>Routerboard RB604 extension card Extension card for 4 mini-PCI cards. Designed to use with RB600 and RB532A</p>	 <p>#06375 Net Price: 11,70 EUR Unit: pcs</p> <p>Routerboard RB411 indoor case</p>	 <p>#06497 Net Price: 19,30 EUR Unit: pcs</p> <p>Routerboard RB433 indoor case</p>
 <p>#06672 Net Price: 32,40 EUR Unit: pcs</p> <p>Routerboard RB433 outdoor case, IP66, AL</p>	 <p>#06938 Net Price: 11,90 EUR Unit: pcs</p> <p>Routerboard RB450 indoor case</p>	 <p>#07091 Net Price: 18,00 EUR Unit: pcs</p> <p>Routerboard RB493 indoor case</p>
 <p>#06372 Net Price: 13,30 EUR Unit: pcs</p> <p>Routerboard RB600 indoor case</p>	 <p>#06671 Net Price: 17,70 EUR Unit: pcs</p> <p>Routerboard RB600 outdoor case, IP66, AL</p>	 <p>Wireless access point 2.4GHz (MikroTik Routerboard RBwAP2nD) Small weatherproof wireless access point for mounting on a ceiling, wall or pole Standards: IEEE 802.11b/g/n Ports: 1x 10/100 Mbps RJ-45 Chipset: MIPSBE, QCA9533, 650 MHz Operating memory: 64MB DDR SDRAM Storage size: 16 MB Frequency range: 2.4 - 2.5GHz Antenna: build-in, 2 dBi Beam width: 360° Dimensions: 185 x 85 x 30 mm Mounting: mast or wall with the aid of antenna wall support Max. power consumption: 4 W Power: PoE 11 V - 57 V (Passive PoE and 802.3af/at with unshielded cable) Operating temperatures: -40°C ÷ 70°C Operating humidity: 5% ÷ 95%, non-condensing Certificates: FCC, IC Manufacturer: MikroTik</p>



#08461

Net Price:
64,40 EUR
Unit: pcs**Wireless access point 2.4GHz (MikroTik Routerboard SXT G-2HnD)**

Standards: IEEE 802.11b/g/n
Ports: 1x 10/100/1000 Mbps RJ-45, USB 2.0
Operating modes: Access Point, Bridge, Client, Router
Chipset: Atheros AR7241 400MHz CPU
Operating memory: 32MB DDR SDRAM
Frequency range: 2.4 - 2.5GHz
Max. output power: 802.11b/g - 32dBm @ 6Mbps do 29dBm @ 54 Mbps, 802.11n - 32dBm @ MCS0/8 do 25dBm @ MCS7/15
Receiver sensitivity: 802.11b/g - -96 dBm @ 6Mbps do -80 dBm @ 54 Mbps, 802.11n - -95 dBm @ MCS0 20MHz do -74 dBm @ MCS7 40MHz
Antenna: build-in, 10 dBi
Beam width: 60°/60°
Dimensions: 140x140x56mm
Weight: 265g
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 7 W
Power: PoE 8-30V
Operating temperatures: -30°C + 80°C
Operating humidity: 5% + 95%, non-condensing
Certificates: FCC, CE, ROHS
Manufacturer: MikroTik

Standard AC



#09009

Net Price:
27,10 EUR
Unit: pcs**1200Mbps Wireless Dual Band PCI-Express AC1200 (TP-Link Archer T4E)**

- Easy Installation - Plug the adapter into an available PCI-E slot to upgrade your desktop
- High Speed Wi-Fi - Up to 1200 Mbps Wi-Fi speeds (867 Mbps on 5 GHz band and 300 Mbps on 2.4 GHz band)
- 802.11ac Dual Band - 3 times faster than the 802.11n standard, perfect for high-intensity network usage
- Beamforming - Wi-Fi signals are strengthened towards certain direction where client exists
- Multiple-Size Brackets - Low profile and full height brackets are both provided, suitable for all PCs
- 2x2 MIMO - Users can easily access to high-speed wireless connection
- Broad Wireless Range - Two external antennas ensure greater Wi-Fi coverage and enhanced stability

HARDWARE FEATURES:

Interface: PCI Express x1

Antenna Type: Omni Directional, Detachable (RP-SMA)

WIRELESS FEATURES:

Wireless Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n

Frequency: 2.4-2.4835GHz, 5.180-5.240GHz, 5.745-5.825GHz

Signal Rate: 867Mbps at 5GHz, 300Mbps at 2.4GHz

EIRP: <20dBm (EIRP)

Reception Sensitivity: 5GHz- 11a -68dBm, 11n HT20 -64dBm, 11n HT40 -61dBm, 11ac HT20 -59dBm, 11ac HT40 -54dBm, 11ac HT80 -51dBm, 2.4GHz- 11b -76dBm, 11g -68dBm, 11n HT20 -64dBm, 11n HT40 -61dBm

Wireless Modes: Ad-Hoc / Infrastructure mode

Wireless Security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x

Modulation Technology: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM

OTHERS:

Certification: CE, FCC, RoHS, Wi-Fi

Package Contents: Wireless Adapter Archer T4E, Resource CD, Quick Installation Guide

System Requirements: Windows 7/8/8.1/10(32/64bits), Windows XP(32/64bits)

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing

Warranty: 2 years limited warranty. Advanced replacement service is available.



#09044

Net Price:
30,20 EUR
Unit: pcs**1200Mbps Wireless Dual Band PCI-Express AC1200, Bluetooth 4.2 (TP-Link Archer T5E)**

- Ultra-Fast Speed - Make full use of your network with Wi-Fi speeds up to 1167 Mbps (867 Mbps on the 5 GHz band and 300 Mbps on the 2.4 GHz band)
- Bluetooth 4.2 - Achieve 2.5x faster speed and 10x more packet capacity than Bluetooth 4.0
- Broad Wireless Range - Connect to your Wi-Fi in more parts of your home with two external high-gain antennas ensuring greater coverage and enhanced stability
- Easy Installation - Plug the adapter into an available PCI-E slot to upgrade your desktop

HARDWARE FEATURES:

Interface: PCI Express x1

Dimensions: 4.8 x 3.3 x 0.85 in (120.8 x 83.2 x 21.5 mm)

Antenna Type: 2 Detachable External Antennas

WIRELESS FEATURES:

Wireless Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n

Frequency: 2.4-2.4835GHz, 5.180-5.240GHz,

5.745-5.825GHz

Signal Rate: 867Mbps at 5GHz, 300Mbps at 2.4GHz

EIRP: 5 GHz- 21.5 dBm (FCC) / 23 dBm (CE) (EIRP), 2.4

GHz- 20.5 dBm (FCC) / 20 dBm (CE) (EIRP)

Wireless Modes: Ad-Hoc / Infrastructure mode

Wireless Security: Support 64/128 bit WEP,

WPA-PSK/WPA2-PSK, 802.1x

Modulation Technology: DBPSK, DQPSK, CCK, OFDM,

16-QAM, 64-QAM

OTHERS:

Certification: CE, FCC, RoHS, Wi-Fi

Package Contents: Wireless Adapter Archer T5E, Resource

CD, Quick Installation Guide, Low-Profile and Full Height

Brackets, Bluetooth USB Cable

System Requirements: Windows 7/8/8.1/10(32/64bits),

Windows XP(32/64bits)

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing



#04593

Net Price:
30,20 EUR
Unit: pcs**1300Mbps Wireless Dual Band PCI-Express AC1300 (TP-Link Archer T6E)**

- Easy Installation - Upgrade your desktop system easily by plugging the Archer T6E Wi-Fi adapter into an available PCI-E slot
- Hi-Speed Wi-Fi - Up to 1300Mbps Wi-Fi speeds (867Mbps on 5GHz band or 400Mbps on 2.4GHz band)
- 802.11ac Dual Band - 3 times faster than the 802.11n standard, perfect for hi-intensity network usage
- Backward Compatibility - With support for 802.11 a/b/g/n standards
- Broad Wireless Range - 2 external antennas ensure a greater range of Wi-Fi connection and stability

HARDWARE FEATURES:

Interface: PCI Express x1

Antenna Type: Omni Directional, Detachable (RP-SMA)

WIRELESS FEATURES:

Wireless Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n

Frequency: 2.4-2.4835GHz, 5.180-5.240GHz,

5.745-5.825GHz

Signal Rate: 867Mbps at 5GHz, 400Mbps at 2.4GHz

EIRP: <20dBm (EIRP)

Reception Sensitivity: 5GHz- 11a -68dBm, 11n HT20

-64dBm, 11n HT40 -61dBm, 11ac HT20 -59dBm, 11ac HT40

-54dBm, 11ac HT80 -51dBm, 2.4GHz- 11b -76dBm, 11g

-68dBm, 11n HT20 -64dBm, 11n HT40 -61dBm

Wireless Modes: Ad-Hoc / Infrastructure mode

Wireless Security: Support 64/128 bit WEP,

WPA-PSK/WPA2-PSK, 802.1x

Modulation Technology: DBPSK, DQPSK, CCK, OFDM,

16-QAM, 64-QAM

OTHERS:

Certification: CE, FCC, RoHS, Wi-Fi

Package Contents: Wireless Adapter Archer T6E, Resource

CD, Quick Installation Guide

System Requirements: Windows 7/8/8.1/10(32/64bits),

Windows XP(32/64bits)

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty: 2 years limited warranty. Advanced replacement service is available.



#09010

Net Price:
46,30 EUR
Unit: pcs

3000Mbps Wireless Dual Band PCI-Express AX3000, Wi-Fi 6, Bluetooth 5.0 (TP-Link Archer TX3000E)

- Unrivaled Wi-Fi 6 Speed-Breaks the gigabit barrier with speed up to 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
- Smoother Experience-75% lower latency ensures ultra-responsive real-time gaming
- Reliable Connections-IntelC Wi-Fi 6 chipset brings faster and clearer Wi-Fi to fully unlock the potential of your Wi-Fi 6 router
- Wider Signal Coverage-Two multi-directional antennas with magnetized base are designed for optimum signal reception
- Bluetooth 5.0-The latest Bluetooth technology achieves 2x Faster Speed and 4x Broader Coverage than BT 4.2
- Improved Security-The latest security enhancements WPA3 provides enhanced protection in personal password safety
- Fine Crafting-Specialized heatsink and gold plating is crafted to improve stability and reliability even in hot environments
- Backward Compatibility - Full support for 802.11ac/a/b/g/n standards

HARDWARE FEATURES:

Interface:PCI Express x1

Antenna Type: Two High-Gain Dual Band Antennas,

Magnetized Antenna Base

Chipset: Intel Wi-Fi 6 Chipset

WIRELESS FEATURES:

Wireless Standards:5 GHz@ IEEE 802.11ax/ac/n/a, 2,4 GHz@ IEEE 802.11ax/n/g/b, Bluetooth 5.0/4.2/4.0

Frequency: 2.4-2.4835GHz, 5.180-5.240GHz,

5.745-5.825GHz

Signal Rate: 2402Mbps at 5GHz, 574Mbps at 2.4GHz

EIRP:5 GHz @ 27 dBm (FCC) / 23 dBm (CE) (EIRP), 2,4 GHz @ 26 dBm (FCC) / 20 dBm (CE) (EIRP)

Wireless Modes: Infrastructure mode

Wireless Security:Support 64/128 bit WEP,

WPA/WAP2/WPA3, WPA-PSK/WPA2-PSK, 802.1x

Modulation Technology:DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM, 1024QAM

OTHERS:

Dimensions: 3.7 x 4.8 x 0.8 in (95.2 x 120.8 x 21.5 mm)

Certification:CE, FCC, RoHS, Wi-Fi

Package Contents:Archer TX3000E, Magnetized Antenna

Base with 1m RF Cable, Two 5 dBi High Gain Antennas,

Low-Profile Bracket, Bluetooth Header Cable, Quick

Installation Guide, Resource CD

System Requirements: Windows 7/8/8.1/10(32/64bits),

Windows XP(32/64bits)

Environment:Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty:2 years limited warranty. Advanced replacement service is available.



#09083

Net Price:
38,50 EUR
Unit: pcs

3000Mbps Wireless Dual Band PCI-Express AX3000, Wi-Fi 6, Bluetooth 5.0 (TP-Link Archer TX50E)

- Unrivaled Wi-Fi 6 Speed-Breaks the gigabit barrier with speed up to 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
- Smoother Experience-75% lower latency ensures ultra-responsive gaming, uninterrupted video chatting and seamless live streaming
- Reliable Connections-IntelC Wi-Fi 6 chipset brings faster and clearer Wi-Fi to fully unlock the potential of your Wi-Fi 6 router
- Wider Signal Coverage- Connect to your Wi-Fi in more parts of your home with two external high-gain antennas ensuring greater coverage and enhanced stability
- Bluetooth 5.0-The latest Bluetooth technology achieves 2x Faster Speed and 4x Broader Coverage than BT 4.2
- Improved Security-The latest security enhancements WPA3 provides enhanced protection in personal password safety
- Fine Crafting-Specialized heatsink and gold plating is crafted to improve stability and reliability even in hot environments
- Backward Compatibility - Full support for 802.11ac/a/b/g/n standards

HARDWARE FEATURES:

Interface:PCI Express x1

Antenna Type: Two High-Gain Dual Band Antennas

Chipset: Intel Wi-Fi 6 Chipset

WIRELESS FEATURES:

Wireless Standards:5 GHz@ IEEE 802.11ax/ac/n/a, 2,4

GHz@ IEEE 802.11ax/n/g/b, Bluetooth 5.0/4.2/4.0

Frequency: 2.4-2.4835GHz, 5.180-5.240GHz,

5.745-5.825GHz

Signal Rate: 2402Mbps at 5GHz, 574Mbps at 2.4GHz

EIRP:5 GHz @ 27 dBm (FCC) / 23 dBm (CE) (EIRP), 2,4

GHz @ 26 dBm (FCC) / 20 dBm (CE) (EIRP)

Wireless Modes: Infrastructure mode

Wireless Security:Support 64/128 bit WEP,

WPA/WAP2/WPA3, WPA-PSK/WPA2-PSK, 802.1x

Modulation Technology:DBPSK, DQPSK, CCK, OFDM,

16-QAM, 64-QAM, 256-QAM, 1024QAM

OTHERS:

Dimensions: 3.7 x 4.8 x 0.8 in (95.2 x 120.8 x 21.5 mm)

Certification:CE, FCC, RoHS, Wi-Fi

Package Contents:Archer TX50E, Two 5 dBi High Gain

Antennas, Low-Profile Bracket, Bluetooth Header Cable,

Quick Installation Guide, Resource CD

System Requirements: Windows 10(64-bit) only

Environment:Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty:2 years limited warranty. Advanced replacement service is available.



#07167

Net Price:
21,50 EUR
Unit: pcs

AC1200 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer T4U)

- Ultra-fast 1200 (867+300)Mbps wireless speed with 802.11ac
- Dual Band connections for lag-free HD video streaming and gaming
- SuperSpeed USB 3.0 port - Up to 10x faster than USB 2.0
- Easy wireless security encryption at a push of the WPS button
- Equipped with a USB Extension Cable for flexible deployment

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Interface: USB 3.0

Frequency range: 5GHz, 2.4GHz

Max. speed: up to 5GHz 867Mbps or 2.4GHz 300Mbps

Max. output power: 20 dBm

Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM,

64-QAM, 256-QAM

Operating modes: Ad-hoc, infrastructure

WLAN security: Support 64/128 bit WEP,

WPA-PSK/WPA2-PSK, 802.1x

Drivers: Windows 8 (32/64bits), Windows 7 (32/64bits),

Windows XP(32/64bits)

Dimensions: 92.2x29x14.6 mm

Operating temperatures: 0°C + 40°C

Operating humidity: 5% + 90%, non-condensing

Certificates: CE, FCC, RoHS

Manufacturer: TP-Link



#09008

Net Price:
16,60 EUR
Unit: pcs

AC1300 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer T3U)

- Ultimate Wi-Fi Speed - AC1300 (400 Mbps on 2.4GHz band and 867 Mbps on 5GHz band) wireless speed with the next generation Wi-Fi - 802.11ac
- Dual Band Wireless - 2.4GHz and 5GHz band for flexible connectivity
- Mini design - Mini-sized design for convenient portability with a reliable high performance
- Super Speed USB 3.0 Port - Up to 10x faster transfer speeds than USB 2.0
- MU-MIMO - Delivers highly efficient wireless connection
- Supported Operating System - Windows 10/8.1/8/7/XP, Mac OS X (Mac OS 10.15 will be supported soon.)

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Interface: USB 3.0
Antenna Type: Omni Directional
Frequency range: 5GHz, 2.4GHz
Max. speed: up to 5GHz 867Mbps or 2.4GHz 400Mbps
EIRP: <23dBm (EIRP)
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM
Operating modes: Ad-hoc, infrastructure
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)
Dimensions: 1.59 x 0.78 x 0.41in. (40.5 x 19.72 x 10.29mm)
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Certificates: CE, FCC, RoHS
Manufacturer: TP-Link



#09082

Net Price:
26,10 EUR
Unit: pcs

AC1300 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer T4U Plus)

- Ultra-Fast Wi-Fi - 1300Mbps wireless speeds (400Mbps on the 2.4GHz band and 867Mbps on the 5GHz band) with support for the next generation 802.11ac Wi-Fi standard
- Dual Band Wireless - 2.4GHz and 5GHz bands for flexible connectivity
- Dual High-Gain antennas - Improved range, signal quality and transmission performance
- MU-MIMO -Delivers highly efficient wireless connection
- Super Speed USB 3.0 Port - Up to 10x faster transfer speeds than USB 2.0
- Adjustable, Multi-Directional Antenna - Enable flexible deployment for the best reception

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Interface: USB 3.0
Frequency range: 5GHz, 2.4GHz
Antenna: 2x External 5 dBi High Gain Antennas
Max. speed: up to 5GHz 867Mbps or 2.4GHz 400Mbps
Max. output power: 20 dBm
Wireless Modes: Infrastructure mode
Wireless Security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Drivers: Supported operating systems include Windows 10/8.1/8/7, macOS
Dimensions: 84 x 156.3 x 19.2 mm (3.3 x 6.2 x 0.76 in)
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Certificates: CE, FCC, RoHS
Manufacturer: TP-Link



#09043

Net Price:
18,10 EUR
Unit: pcs

AC1300 Wireless High Gain Dual Band USB 3.0 Adapter (TP-Link Archer T3U Plus)

- AC1300 Lightning-Fast Speed - AC1300 (867 Mbps on the 5 GHz band or 400 Mbps on the 2.4 GHz band) dual-band Wi-Fi to ensure all your devices run at full speed
- MU-MIMO Technology - Improves the throughput and efficiency of the whole network with MU-MIMO technology
- Dual-Band Wireless - The 2.4 GHz and 5 GHz bands provide flexible connectivity, giving your devices access to the latest dual-band Wi-Fi router for faster speed and extended range
- High-Gain Antennas - Advanced external high-gain antennas greatly enhance the reception and transmission signal strength of the USB adapter
- Supports the Latest Operating Systems - Fully compatible with Windows 10/8.1/8/7/XP and macOS

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Interface: USB 3.0
LED: Status
Antenna Type: 2 External High Gain Antennas
Frequency range: 5GHz, 2.4GHz
Max. speed: up to 5GHz 867Mbps or 2.4GHz 400Mbps
EIRP: 5 GHz- 20 dBm (FCC) / 20 dBm (CE) (EIRP), 2.4 GHz- 18 dBm (FCC) / 18 dBm (CE) (EIRP)
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM
Operating modes: Ad-hoc, infrastructure
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)
Dimensions: 2.28 x 0.71 x 6.83 in (57.8 x 18 x 173.4 mm)
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Certificates: CE, FCC, RoHS
Manufacturer: TP-Link



#04688

Net Price:
44,50 EUR
Unit: pcs

AC1900 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer T9UH)

- Ultimate Wi-Fi Speed- AC1900 (600Mbps on 2.4GHz band or 1300Mbps on 5GHz band) wireless speed with the next generation Wi-Fi - 802.11ac
- Dual Band Wireless- 2.4GHz and 5GHz band for flexible connectivity
- Ultimate Range - High gain antennas ensure superior range and stability
- Beamforming Technology - Delivers a more targeted and highly efficient wireless connections
- Super Speed USB 3.0 Port - Up to 10x faster than USB 2.0
- Flexible Deployment - Equipped with a USB 3.0 Cradle for flexible deployment
- WPS Button - Easy wireless security encryption at a push of the WPS button
- Backward Compatibility - With support for 802.11 a/b/g/n standards

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Interface: USB 3.0
Frequency range: 5GHz, 2.4GHz
Max. speed: up to 5GHz 1300Mbps or 2.4GHz 600Mbps
Max. output power: 20 dBm
Modulation type: DBPSK, DQPSK, CCK, BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
Operating modes: Ad-hoc, infrastructure
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)
Dimensions: 3.96x1.44x0.56in. (100.53x36.6x14.3mm)
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Certificates: CE, FCC, RoHS
Manufacturer: TP-Link



#09006

Net Price:
11,00 EUR
Unit: pcs

AC600 Wireless Dual Band USB 2.0 Adapter (TP-Link Archer T2U Nano)

- High Speed WiFi- Up to 600Mbps speeds with 200Mbps on 2.4GHz and 433 Mbps on 5GHz, upgrades your devices to higher AC WiFi speeds.
- Dual Band Wireless - 2.4GHz and 5GHz band for flexible connectivity, upgrades your devices to work with the latest dual-band WiFi router for faster speed and extended range.
- Nano design - Small, unobtrusive design allows you to plug it in and forget it is even there
- Operating System - Supports Windows 10/8.1/8/7/XP, Mac OS X
- Advanced Security -Supports 64/128-bit WEP, WPA/WPA2, and WPA-PSK/WPA2-PSK encryption standards

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Interface: USB 2.0
Frequency range: 5GHz, 2.4GHz
Max. speed: up to 5GHz 433Mbps or 2.4GHz 200Mbps
Max. output power: 20 dBm
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM
Operating modes: Ad-hoc, infrastructure
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)
Dimensions: 15 x 7.1 x 18.6 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Certificates: CE, FCC, RoHS
Manufacturer: TP-Link



#09007

Net Price:
14,30 EUR
Unit: pcs

AC600 Wireless Dual Band USB 2.0 Adapter (TP-Link Archer T2U Plus)

- High-Speed Wi-Fi: 256QAM support increases the 2.4 GHz data rate from 150 Mbps to 200 Mbps, 200 Mbps on the 2.4 GHz band and 433 Mbps on the 5 GHz band, ensure you fully enjoy fast AC Wi-Fi.
- Dual Band Wireless: 2.4 GHz and 5 GHz band provide flexible connectivity, giving your devices access to the latest dual-band Wi-Fi router for faster speed and extended range
- High-Gain Antenna: A 5dBi high-gain antenna greatly enhances the reception and transmission signal strength of the USB adapter
- Supports the Latest Operating Systems: Fully compatible with Windows 10/8.1/8/7/XP and Mac OS X

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Interface: USB 2.0
LED: Status
Antena: 5dBi
Frequency range: 5GHz, 2.4GHz
Max. speed: up to 5GHz 433Mbps or 2.4GHz 200Mbps
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM
Operating modes: Ad-hoc, infrastructure
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)
Dimensions: 57,8 x 18 x 173,4 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Certificates: CE, FCC, RoHS
Manufacturer: TP-Link



#08939

Net Price:
13,30 EUR
Unit: pcs

AC600 Wireless Dual Band USB 2.0 Adapter (TP-Link Archer T2U)

- Ultra-fast 600 (433+150)Mbps wireless speed with 802.11ac
- Dual Band connections for lag-free HD video streaming and gaming

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Interface: USB 2.0

Frequency range: 5GHz, 2.4GHz

Max. speed: up to 5GHz 433Mbps or 2.4GHz 150Mbps

Max. output power: 20 dBm

Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM

Operating modes: Ad-hoc, infrastructure

WLAN security: Support 64/128 bit WEP,

WPA-PSK/WPA2-PSK, 802.1x

Drivers: Windows 8.1 (32/64bits), Windows 8 (32/64bits),

Windows 7 (32/64bits), Windows XP(32/64bits)

Dimensions: 1.6x0.7x0.3 in. (41x19.5x8.7mm)

Operating temperatures: 0°C + 40°C

Operating humidity: 5% + 90%, non-condensing

Certificates: CE, FCC, RoHS

Manufacturer: TP-Link



#09114

Net Price:
9,28 EUR
Unit: pcs

AC650 Wireless Dual Band USB 2.0 Adapter (TP-Link Mercusys MU6H)

- High-Speed Dual-Band Wi-Fi: 256-QAM support increases the 2.4 GHz data rate from 150 Mbps to 200 Mbps. Enjoy speeds of up to 200 Mbps on the 2.4 GHz band and 433 Mbps on the 5 GHz band, to take full advantage of your AC Wi-Fi.

- High-Gain Antenna: A 5dBi high-gain antenna greatly enhances the reception and transmission strength of the USB adapter

- Internal Driver: Smart easy-install for Windows operating system

- Supports the Latest Operating Systems: Fully compatible with Windows 10/8.1/8/7/XP

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Interface: USB 2.0

LED: Status

Antenna: 5dBi

Frequency range: 5GHz, 2.4GHz

Max. speed: up to 5GHz 433Mbps or 2.4GHz 200Mbps

Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM

Operating modes: Ad-hoc, infrastructure

WLAN security: WEP, WPA/WPA2, WPA-PSK/ WPA2-PS,

802.1X

Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits),

Windows 8 (32/64bits), Windows 7 (32/64bits), Windows

XP(32/64bits)

Dimensions: 57,8 x 16,8 x 173,4 mm

Manufacturer: TP-Link



#06260

Net Price:
69,10 EUR
Unit: pcs

1200Mbps Outdoor Wireless Access Point, AC1200 (TP-Link EAP225-Outdoor)

- Durable, weatherproof enclosure for outdoor Wi-Fi applications

- Up to 1200Mbps with 2x2 MIMO technology

- Omada Mesh Technology enables wireless connectivity between APs for extended range, making wireless deployments more flexible and convenient

- Supports Seamless Roaming so even video streams and voice calls are unaffected as users move between locations

- High transmission power and high gain antennas provide a long-range coverage area

- Free cloud centralized management and Omada app for ultra convenience and easy management

- Secure guest network along with multiple authentication options (SMS/Facebook Wi-Fi/ Voucher, etc.) and abundant wireless security technologies

- 802.3af/Passive PoE (PoE Adapter Included) compatible and simple mounting design allow for flexible deployment and convenient installation

Standards: IEEE 802.11ac/n/g/b/a

Ports: Gigabit Ethernet (RJ-45) Port *1 (ETH1 Support IEEE802.3af PoE)

Frequency range: 2.4GHz and 5GHz

Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps

EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm

Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client

Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation

Between Clients, SSID to VLAN Mapping, Rogue AP

Detection, 802.1X Support, 64/128/152-bit WEP / WPA /

WPA2-Enterprise, WPA-PSK / WPA2-PSK

EAP Controller Software: Yes

Email Alerts: Yes

LED ON/OFF Control: Yes

Management MAC Access Control: Yes

SNMP: v1,v2c

System Logging Local/Remote Syslog: Local/Remote Syslog

Telnet: Yes

Web-based Management: HTTP/HTTPS

L3 Management: Yes

Multi-site Management: Yes

Management VLAN: Yes

Antenna: 2.4GHz- 2 * 3dBi, 5GHz- 2 * 4dBi

Weatherproof Enclosure: IP65

Dimensions: 215.7*45*37.7mm (without antenna & mounting kit) , 403.8*90.7*55.2mm (with antenna & mounting kit)

Power: PoE or External 12VDC / 1.5A Power Supply

Power Consumption: 10.15 W

Mounting: Pole/Wall Mounting (Kits included)

Watch Dog: Yes

Operating Temperature: 0°C~40°C (-32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents: AC1200 Wireless Dual Band Gigabit

Access Point EAP225-Outdoor, Power Adapter, Mounting

Kits, Installation Guide

System Requirements: Microsoft Windows XP, Vista,

Windows 7, Windows 8, Windows 10

Certificates: CE, FCC, RoHS

Warranty: 5 years



#06263

Net Price:
51,20 EUR
Unit: pcs

1200Mbps Outdoor Wireless Access Point, AC1200 (TP-Link EAP225-Wall)

- Easy-mount construction allows installation into standard EU/US-type data wall-box
- Compact, low-profile design fits discreetly with any existing interior style
- Free cloud centralized management and Omada app supported for ultra convenience and easy management
- Power over Ethernet (802.3af/802.3at) support makes deployment effortless and flexible
- Provide secure guest network along with Facebook Wi-Fi/SMS authentication options and wireless isolation technology
- Enterprise class Wi-Fi security helps to decrease network security threats
- Supports management vlan for an enhanced network management

Standards: IEEE 802.11ac/n/g/b/a
Ports: 10/100Mbps (RJ-45) Port *1, Downlink- 10/100Mbps Ethernet Port*3 (One port supports PoE OUT. The PoE OUT feature requires 802.3at PoE+ input and the maximum output is 13W.)
Frequency range: 2.4GHz and 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
EAP Controller Software: Yes
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
Telnet: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: 2 Dual-Band Antennas, 2.4GHz- 2*3dBi, 5GHz- 2*4dBi
Dimensions: 143 × 86 × 19.7mm (5.6 × 3.4 × 0.8 in)
Power: 802.3af/802.3at PoE
Power Consumption: 9 watts /25.5 watts (PoE Out Included)
Mounting: Wall Plate Mounting
Physical Security Lock: Kensington Lock Slot
Watch Dog: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: AC1200 Wireless Dual Band Gigabit Access Point EAP225-Wall, Mounting Screw, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10
Certificates: CE, FCC, RoHS
Warranty: 5 years



#09088

Net Price:
52,70 EUR
Unit: pcs

1200Mbps Outdoor Wireless Access Point, AC1200 (TP-Link EAP230-Wall)

- Fast Dual-Band Wi-Fi: Simultaneous 300 Mbps on 2.4 GHz and 867 Mbps on 5 GHz totals 1,167 Mbps Wi-Fi speeds with MU-MIMO.
- Gigabit Ports: 2 Gigabit Ethernet ports (1× uplink + 1× downlink).
- Integrated into Omada SDN: Zero-Touch Provisioning (ZTP), Centralized Cloud Management, and Intelligent Monitoring.
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.
- Private Connection for Every Room: Designed to meet every network need in environments with numerous separated rooms, like hotels, offices, and dormitories.
- Elegant Appearance: Unprecedented thin design with just 11 mm, the same size and shape as a light switch or power outlet faceplate to fit perfectly in any room.
- Easy Installation and PoE Support: Easy-mount construction, compatible with 86 mm & EU standard junction box, and 802.3af/at PoE support.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ac/n/g/b/a
Ports: 10/100/1000Mbps (RJ-45) Port *1, Downlink- 10/100/1000Mbps Ethernet Port*1
Frequency range: 2.4GHz and 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
MANAGEMENT
Omada App: Yes
Centralized Management: Omada Cloud-Based Controller, Omada Hardware Controller (OC300), Omada Hardware Controller (OC200), Omada Software Controller
Cloud Access: Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
SSH: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: 2 Dual-Band Antennas, 2.4GHz- 2*4dBi, 5GHz- 2*3.6dBi
Dimensions: 3.4 × 3.4 × 1.2 in (86.8 × 86.8 × 30.2 mm)
Power: 802.3af/802.3at PoE
Power Consumption: 7 watts
Mounting: Wall Plate Mounting
Watch Dog: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: AC1200 Wireless Dual Band Gigabit Access Point EAP230-Wall, Mounting Screw, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10
Certificates: CE, FCC, RoHS



#09089

Net Price:
55,00 EUR
Unit: pcs

1200Mbps Outdoor Wireless Access Point, AC1200 (TP-Link EAP235-Wall)

- Fast Dual-Band Wi-Fi: Simultaneous 300 Mbps on 2.4 GHz and 867 Mbps on 5 GHz totals 1,167 Mbps Wi-Fi speeds with MU-MIMO.†
- Four Gigabit Ports: 4 Gigabit Ethernet ports (1× uplink + 3× downlink), with one downlink port supporting PoE pass-through to provide power for wired device.
- Integrated into Omada SDN: Zero-Touch Provisioning (ZTP)‡, Centralized Cloud Management, and Intelligent Monitoring.
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.
- Elegant Appearance: Ultra slimmest and conspicuous design blends into hotel rooms, hospitals, offices, dormitories and any other environments.
- Easy Installation and PoE Support: Easy-mount construction, compatible with 86 mm & EU & US standard junction box, and 802.3af/at PoE support.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.
- Advanced Wireless Tech: Optimize network performance with MU-MIMO, Band Steering, and Beamforming technologies.

Standards: IEEE 802.11ac/n/g/b/a
Ports: Uplink 1x 10/100/1000Mbps (RJ-45) Port, Downlink- 3x 10/100/1000 Mbps Ethernet Ports (One port supports PoE OUT. The PoE OUT feature requires 802.3at PoE+ input and the maximum output is 13 W.)
Frequency range: 2.4GHz and 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
MANAGEMENT
Omada App: Yes
Centralized Management: Omada Cloud-Based Controller, Omada Hardware Controller (OC300), Omada Hardware Controller (OC200), Omada Software Controller
Cloud Access: Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
SSH: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: 2 Dual-Band Antennas, 2.4GHz- 2*4dBi, 5GHz- 2*4dBi
Dimensions: 143 × 86 × 20 mm (5.6 × 3.4 × 0.8 in)
Power: 802.3af/802.3at PoE
Power Consumption: 9.8 watts /24.4 watts (PoE Out Included)
Mounting: Wall Plate Mounting
Watch Dog: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: AC1200 Wireless Dual Band Gigabit Access Point EAP235-Wall, Mounting Screw, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10
Certificates: CE, FCC, RoHS



#04658

Net Price:
64,40 EUR
Unit: pcs

1350Mbps Outdoor Wireless Access Point, AC1350 (TP-Link EAP225)

- Simultaneous 450Mbps on 2.4GHz and 867Mbps on 5GHz totals 1317Mbps Wi-Fi speeds
- Free EAP Controller Software lets administrators easily manage hundreds of EAPs
- Support Power over Ethernet(802.3af) for convenient and affordable installation
- Captive portal provides a convenient method for guest authentication
- Band Steering Automatically moves dual band devices onto the wider 5GHz band for faster connections

Standards: IEEE 802.11ac/n/g/b/a
Ports: Gigabit Ethernet (RJ-45) Port *1 (ETH1 Support IEEE802.3af PoE)
Frequency range: 2.4GHz and 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 450Mbps
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
EAP Controller Software: Yes
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
Telnet: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: 3 Internal Omni 2.4GHz- 4dBi, 5GHz- 5dBi
Dimensions: 8.1 x 7.1 x 1.5 in. (205.5 x 181.5 x 37.1 mm)
Power: PoE or External 12VDC / 1.5A Power Supply
Power Consumption: 10.5 W
Mounting: Ceiling /Wall Mounting (Kits included)
Physical Security Lock: Kensington Lock Slot
Watch Dog: Yes
Operating Temperature: 0°C~60°C (-32°F~144°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: AC1200 Wireless Dual Band Gigabit Access Point EAP225, Power Adapter, Mounting Kits, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10
Certificates: CE, FCC, RoHS
Warranty: 5 years



#04657

Net Price:
81,40 EUR
Unit: pcs

1750Mbps Outdoor Wireless Access Point, AC1750 (TP-Link EAP245)

- Simultaneous 450Mbps on 2.4GHz and 1300Mbps on 5GHz totals 1750Mbps Wi-Fi speeds
- Free EAP Controller Software lets administrators easily manage hundreds of EAPs
- Support Power over Ethernet(802.3at) for convenient and affordable installation
- Captive portal provides a convenient method for guest authentication
- Band Steering Automatically moves dual band devices onto the wider 5GHz band for faster connections
- Load balance ensures large numbers of users have smooth network experiences in high density business networks

Standards: IEEE 802.11ac/n/g/b/a
Ports: Gigabit Ethernet (RJ-45) Port *1 (ETH1 Support IEEE802.3at PoE)
Frequency range: 2.4GHz and 5GHz
Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 450Mbps
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
EAP Controller Software: Yes
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
Telnet: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: Internal Omni 2.4GHz 3* 6dBi4, 5GHz 3*4dBi
Dimensions: 7.1 x 7.1 x 1.9in. (180*180*47.5mm)
Power: PoE or External 12VDC / 1.5A Power Supply
Power Consumption: 12.7 W
Mounting: Ceiling /Wall Mounting (Kits included)
Physical Security Lock: Kensington Lock Slot
Watch Dog: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: AC1750 Wireless Dual Band Gigabit Access Point EAP245, Power Adapter, Mounting Kits, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10
Certificates: CE, FCC, RoHS
Warranty: 5 years



#09090

Net Price:
88,30 EUR
Unit: pcs

1750Mbps Outdoor Wireless Access Point, AC1750 (TP-Link EAP265 HD)

- Fast Dual-Band Wi-Fi: Simultaneous 450 Mbps on 2.4 GHz and 1300 Mbps on 5 GHz totals 1750 Mbps Wi-Fi speeds.
- High-Density Connectivity: MU-MIMO, Load Balance, and professional antennas improve capacity in high-density environments to connect more devices simultaneously.
- Integrated into Omada SDN: Supports Zero-Touch Provisioning (ZTP), Centralized Cloud Management, and Intelligent Monitoring.
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.
- Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.
- PoE Support: Supports both standard 802.3af/at and Passive PoE (PoE adapter included) for flexible installations.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ac/n/g/b/a
Ports: 2 x Gigabit Ethernet (RJ-45) Port (One port supports IEEE802.3af/at PoE and Passive PoE)
Button: Reset
Frequency range: 2.4GHz and 5GHz
Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 450Mbps
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
MANAGEMENT
Omada App: Yes
Centralized Management: Omada Cloud-Based Controller, Omada Hardware Controller (OC300), Omada Hardware Controller (OC200), Omada Software Controller
Cloud Access: Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
SSH: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: 2 Dual-Band Antennas, 2.4GHz- 2*3.5dBi, 5GHz- 2*4dBi
Dimensions: 8.1 x 7.1 x 1.5 in (205.5 x 181.5 x 37.1 mm)
Power: 802.3af/at PoE, 48V Passive PoE (+4,5pins; -7,8pins. PoE Adapter Included)
Power Consumption: 12.3 W
Mounting: Ceiling /Wall Mounting (Kits included)
Physical Security Lock: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: AC1750 Wireless MU-MIMO Gigabit Ceiling Mount Access Point EAP265 HD, Gigabit Passive PoE Adapter, Power Cord, Mounting Kits, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10, Linux
Certificates: CE, FCC, RoHS



NEW



#09189

Net Price:
87,10 EUR
Unit: pcs

1800Mbps Outdoor Wireless Access Point, AX1800 (TP-Link EAP610)

- Ultra-Fast WiFi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz totals 1775 Mbps Wi-Fi speeds.
- High-Efficiency WiFi 6: More connected devices can enjoy faster speeds.
- Centralized Cloud Management: Manage the whole network locally or from the cloud via web UI or Omada app.
- Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.
- Omada Mesh: Enables wireless connectivity between access points for extended range and flexible deployment.
- PoE+ Powered: Supports both Power over Ethernet (802.3at) and DC power supply for flexible installations.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ax/ac/n/g/b/a
Ports: 1x Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE)
Button: Reset

Frequency range: 2.4GHz and 5GHz
Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
MANAGEMENT
Omada App: Yes
Centralized Management: Omada Cloud-Based Controller, Omada Hardware Controller (OC300), Omada Hardware Controller (OC200), Omada Software Controller
Cloud Access: Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
SSH: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: 2 Dual-Band Antennas, 2.4GHz- 2*3.5dBi, 5GHz- 2*5dBi
Dimensions: 9.6 × 9.6 × 2.5 in (243 × 243 × 64 mm)
Power: 802.3at PoE, 12 V DC/1A
Power Consumption: EU 12.8 W (PoE); 10.8 W (DC)
Mounting: Ceiling /Wall Mounting (Kits included)
Physical Security Lock: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: EAP610, Power Adapter, Ceiling/Wall Mounting Kits, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10, Linux
Certificates: CE, FCC, RoHS

NEW



#09190

Net Price:
65,80 EUR
Unit: pcs

1800Mbps Outdoor Wireless Access Point, AX1800 (TP-Link EAP615-Wall)

- Superior WiFi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz totals 1775 Mbps Wi-Fi speeds.
- High-Performance Connectivity: Guarantee higher network efficiency and lower latency.
- Four Gigabit Ports: 4 Gigabit Ethernet ports (1x uplink + 3x downlink), with one downlink port supporting PoE pass-through to provide power for wired device.
- Centralized Management: Integrates into Omada SDN for cloud access and remote management.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.
- Easy Installation and PoE Support: Easy-to-install design, compatible with 86 mm & EU & US standard junction box, and 802.3af/at PoE support.

Standards: IEEE 802.11ax/ac/n/g/b/a
Ports: 10/100/1000Mbps (RJ-45) Port *1, Downlink-10/100/1000Mbps Ethernet Port*3 (One port supports PoE OUT. The PoE OUT feature requires 802.3at PoE+ input and the maximum output is 13W.)

Frequency range: 2.4GHz and 5GHz
Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
Omada App: Yes
Centralized Management: Omada Hardware Controller (OC300), Omada Hardware Controller (OC200), Omada Software Controller
Cloud Access: Yes (Through OC300, OC200, or Omada Software Controller)
EAP Controller Software: Yes
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
Telnet: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: 2 Dual-Band Antennas, 2.4GHz- 2*3dBi, 5GHz- 2*4dBi
Dimensions: 143 × 86 × 19.7mm (5.6 × 3.4 × 0.8 in)
Power: 802.3af/802.3at PoE
Power Consumption: EU 10W (802.3at PoE, PoE Out off), US 11.5W (802.3at PoE, PoE Out off)
Mounting: Wall Plate Mounting
Physical Security Lock: Kensington Lock Slot
Watch Dog: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: EAP615-Wall, Mounting Kits, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10
Certificates: CE, FCC, RoHS
Warranty: 5 years



#09091

Net Price:
111,00 EUR
Unit: pcs

1800Mbps Outdoor Wireless Access Point, AX1800 (TP-Link EAP620 HD)

- Ultra-Fast Wi-Fi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz totals 1775 Mbps Wi-Fi speeds.
- High-Density Connectivity: 4x increased capacity to connect more devices simultaneously.
- Integrated into Omada SDN: Zero-Touch Provisioning (ZTP), Centralized Cloud Management, and Intelligent Monitoring.
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.
- Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.
- PoE+ Support: Supports Power over Ethernet (802.3at) for convenient deployment and installation.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ax/ac/n/g/b/a
Ports: 1x Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE)
Button: Reset

Frequency range: 2.4GHz and 5GHz
Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
MANAGEMENT
Omada App: Yes
Centralized Management: Omada Cloud-Based Controller, Omada Hardware Controller (OC300), Omada Hardware Controller (OC200), Omada Software Controller
Cloud Access: Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
SSH: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: 2 Dual-Band Antennas, 2.4GHz- 2*3.5dBi, 5GHz- 2*5dBi
Dimensions: 9.6 × 9.6 × 2.5 in (243 × 243 × 64 mm)
Power: 802.3at PoE, 12 V DC
Power Consumption: 12 W
Mounting: Ceiling /Wall Mounting (Kits included)
Physical Security Lock: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: EAP620 HD, Power Adapter, Ceiling/Wall Mounting Kits, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10, Linux
Certificates: CE, FCC, RoHS



#09092

Net Price:
177,00 EUR
Unit: pcs

3600Mbps Outdoor Wireless Access Point, AX3600 (TP-Link EAP660 HD)

- Ultra-Fast Wi-Fi 6 Speeds: Simultaneous 1148 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz totals 3550 Mbps Wi-Fi speeds.
- High-Density Connectivity: 4x increased capacity to connect more devices simultaneously.
- Integrated into Omada SDN: Zero-Touch Provisioning (ZTP), Centralized Cloud Management, and Intelligent Monitoring.
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.
- 2.5G Port: A 2.5 Gbps Ethernet port boosts total internet throughput.
- Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.
- PoE+ Support: Supports Power over Ethernet (802.3at) for convenient deployment and installation.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ax/ac/n/g/b/a
Ports: 1x 2.5 Gbps Ethernet Port (supports IEEE802.3at PoE)
Button: Reset
Frequency range: 2.4GHz and 5GHz
Signal Rate: 5GHz Up to 2402Mbps, 2.4GHz Up to 1148Mbps
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
MANAGEMENT
Omada App: Yes
Centralized Management: Omada Cloud-Based Controller, Omada Hardware Controller (OC300), Omada Hardware Controller (OC200), Omada Software Controller
Cloud Access: Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
SSH: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: 2 Dual-Band Antennas, 2.4GHz- 2*3.5dBi, 5GHz- 2*5dBi
Dimensions: 9.6 x 9.6 x 2.5 in (243 x 243 x 64 mm)
Power: 802.3at PoE, 12 V DC
Power Consumption: 18.5 W
Mounting: Ceiling /Wall Mounting (Kits included)
Physical Security Lock: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: EAP660 HD, Power Adapter, Ceiling/Wall Mounting Kits, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10, Linux
Certificates: CE, FCC, RoHS



#07018

Net Price:
81,20 EUR
Unit: pcs

Wireless access point Ubiquiti NanoBeam M5 (Ubiquiti NBE-5AC-Gen2)

Standards: IEEE 802.11ac/n
Ports: 2x 10/100/1000 Mbps RJ-45
Chipset: Atheros MIPS 74Kc, 720 MHz
Operating memory: 128 MB DDR2
Flash memory: 8 MB
Antenna: build-in, 19 dBi
VSWR: 1.5
Dimensions: 189 x 189 x 125 mm
Weight: 0.530 kg
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 8.5 W
Power: PoE 24V 0.5A Gigabit PoE Adapter (Included)
Operating temperatures: -40°C + 80°C
Operating humidity: 5% + 95%, Non-condensing
Wind Loading: 45.4 N @ 200 km/h (10.2 lbf @ 125 mph)
Wind Survivability: 200 km/h (125 mph)
ESD/EMP Protection Air: +/- 24 kV, Contact +/- 24 kV
Certifications: CE, FCC, IC
RoHS Compliance: Yes
Salt Fog Test: IEC 68-2-11 (ASTM B117), Equivalent
MIL-STD-810 G Method 509.5
Vibration Test: IEC 68-2-6
Temperature Shock Test: IEC 68-2-14
UV Test: IEC 68-2-5 at 40° C (104° F), Equivalent ETS 300 019-1-4
Wind-Driven Rain Test: ETS 300 019-1-4, Equivalent
MIL-STD-810 G Method 506.5
Manufacturer: Ubiquiti



#07004

Net Price:
118,00 EUR
Unit: pcs

Wireless Access Point Ubiquiti NanoStation 5 AC (Ubiquiti NS-5AC)

Ports: 2x 10/100/1000 Mbps RJ-45
Chipset: Atheros MIPS 74Kc, 560 MHz
Operating memory: 64 MB DDR2
Frequency range: 5150 MHz + 5875 MHz
VSWR: 1.6
Beam width: 45°
Dimensions: 257 x 84 x 41 mm
Weight: 233 g
Mounting: Pole-Mount (Kit Included)
Max. power consumption: 8.5 W
Power: 802.3af Alternative A (Pairs 1, 2+; 3, 6 Return), 24V
Passive PoE (Pairs 4, 5+; 7, 8 Return)
Operating temperatures: -40°C + 70°C
Operating humidity: 5% + 95%, non-condensing
Certificates: CE, FCC, IC
Manufacturer: Ubiquiti



#07005

Net Price:
45,90 EUR
Unit: pcs**Wireless Access Point Ubiquiti NanoStation AC Loco (Ubiquiti NS-5ACL)**

Ports: 10/100/1000 Mbps RJ-45
Chipset: Atheros MIPS 74Kc, 560 MHz
Operating memory: 64 MB DDR2
Frequency range: 5150 MHz + 5875 MHz
VSWR: 1.8
Beam width: 45°
Dimensions: 179 x 77.5 x 59.1 mm
Weight: 180 g
Mounting: Pole-Mount (Kit Included)
Max. power consumption: 8,5 W
Power: 24V, 0.5A Gigabit PoE Supply (The product is delivered without a power adapter)
Operating temperatures: -40°C + 70°C
Operating humidity: 5% + 95%, non-condensing
Certifications: CE, FCC, IC
Manufacturer: Ubiquiti



#07039

Net Price:
212,00 EUR
Unit: pcs**Wireless Access Point Ubiquiti NanoStation AC Loco 5-pack (Ubiquiti NS-5ACL)**

Ports: 10/100/1000 Mbps RJ-45
Chipset: Atheros MIPS 74Kc, 560 MHz
Operating memory: 64 MB DDR2
Frequency range: 5150 MHz + 5875 MHz
VSWR: 1.8
Beam width: 45°
Dimensions: 179 x 77.5 x 59.1 mm
Weight: 180 g
Mounting: Pole-Mount (Kit Included)
Max. power consumption: 8,5 W
Power: 24V, 0.5A Gigabit PoE Supply (The product is delivered without a power adapter)
Operating temperatures: -40°C + 70°C
Operating humidity: 5% + 95%, non-condensing
Certifications: CE, FCC, IC
Manufacturer: Ubiquiti



#05349

Net Price:
180,00 EUR
Unit: pcs**Wireless Access Point Ubiquiti UniFi UAP AC M PRO, AC Mesh; (Ubiquiti UAP-AC-M-PRO)**

Networking Interface (Mbps): 2 x 10/100/1000 Ethernet Ports
Buttons: Reset
Antennas: 3x Internal Dual-Band Antennas (8 dBi)
Wi-Fi Standards: 802.11 a/b/g/n/ac
Power Method: 802.3af PoE (Supported Voltage Range- 44 to 57VDC)
Power Supply: 48V, 0.5A Gigabit PoE Adapter
Maximum Power Consumption: 9 W
Maximum TX Power: 22 dBm
BSSID: Up to 8 per Radio
Dimensions: 343.2 x 181.2 x 60.2 mm
Weight: 633 g
Power Save: Supported
Wireless Security: WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
Certifications: CE, FCC, IC
Mounting: Wall/Ceiling (Kits Included)
Operating Temperature: -40 + 70° C
Operating Humidity: 5 + 95% Condensing
Advanced Traffic Management
VLAN: 802.1Q
Advanced QoS: Per-User Rate Limiting
Guest traffic isolation: Supported
WMM: Voice, Video, Best Effort, and Background
Concurrent Clients: 250+
Supported Data Rates (Mbps)
802.11ac: 6.5 Mbps to 1300 Mbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80)
802.11n: 6.5 Mbps to 400 Mbps (MCS0 - MCS15, HT 20/40)
802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b: 1, 2, 5.5, 11 Mbps
Manufacturer: Ubiquiti



#05348

Net Price:
92,30 EUR
Unit: pcs**Wireless Access Point Ubiquiti UniFi UAP AC M, AC Mesh; (Ubiquiti UAP-AC-M)**

Networking Interface (Mbps): 1 x 10/100/1000 Ethernet Ports
Buttons: Reset
Antennas: 2x External Dual-Band Omni Antennas (3 dBi, 4 dBi)
Wi-Fi Standards: 802.11 a/b/g/n/ac
Power Method: 24V Passive PoE (Pairs 4, 5+; 7, 8 Return); 802.3af Alternative A (Pairs 1, 2+; 3, 6 Return), (Supported Voltage Range- 44 to 57VDC)
Power Supply: 24V, 0.5A Gigabit PoE Adapter
Maximum Power Consumption: 8,5 W
Maximum TX Power: 20 dBm
BSSID: Up to 8 per Radio
Dimensions: 353 x 46 x 34.4 mm
Weight: 152 g with Antennas
Power Save: Supported
Wireless Security: WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
Certifications: CE, FCC, IC
Mounting: Wall/Ceiling (Kits Included)
Operating Temperature: -30 + 70° C
Operating Humidity: 5 + 95% Condensing
Advanced Traffic Management
VLAN: 802.1Q
Advanced QoS: Per-User Rate Limiting
Guest traffic isolation: Supported
WMM: Voice, Video, Best Effort, and Background
Concurrent Clients: 250+
Supported Data Rates (Mbps)
802.11ac: 6.5 Mbps to 867 Mbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80)
802.11n: 6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b: 1, 2, 5.5, 11 Mbps
Manufacturer: Ubiquiti



#08353

Net Price:
359,00 EUR
Unit: pcs**Wireless Access Point UniFi UAP AC HD (Ubiquiti UAP-AC-HD)**

Ports: 2 x 10/100/1000 Ethernet Ports, , 1x USB 2.0 Port
Buttons: Reset
Antennas: (2) Dual-Port, Dual-Polarity, 2.4 GHz- 3 dBi, (2) Dual-Port, Dual-Polarity, 5 GHz- 4 dBi
Wi-Fi Standards: 802.11 a/b/g/n/ac-wave2
Power Method: Passive Power over Ethernet (44-57V), 802.3at Supported, PoE+
Maximum Power Consumption: 17 W
Maximum TX Power: 2.4 GHz - 6-25 dBm, 5 GHz - 6-25 dBm
BSSID: Up to 8 Per Radio
Dimensions: 220 x 220 x 48.1 mm (8.66 x 8.66 x 1.89")
Weight: 700 g (830 g with Mounting Kits)
Power Save: Supported
Wireless Security: WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
Certifications: CE, FCC, IC
Mounting: Wall/Ceiling (Kits Included)
Operating Temperature: -10 + 70° C
Operating Humidity: 5 + 95% Condensing
Advanced Traffic Management
VLAN: 802.1Q
Advanced QoS: Per-User Rate Limiting
Guest traffic isolation: Supported
WMM: Voice, Video, Best Effort, and Background
Concurrent Clients: 500+
Supported Data Rates (Mbps)
802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n: 6.5 Mbps to 450 Mbps (MCS0 - MCS23, HT 20/40)
802.11ac: 6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSS1/2/3/4, VHT 20/40/80)
802.11b: 1, 2, 5.5, 11 Mbps
802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
Manufacturer: Ubiquiti



#05352

Net Price:
80,60 EUR
Unit: pcs**Wireless Access Point UniFi UAP AC Lite (Ubiquiti UAP-AC-Lite)**

Networking Interface (Mbps): 1 x 10/100/1000 Ethernet Ports
Buttons: Reset
Antennas: (1) Dual-Band Antenna, Tri-Polarity, 2.4 GHz- 3 dBi, 5 GHz- 3 dBi
Wi-Fi Standards: 802.11 a/b/g/n/ac
Power Method: Passive Power over Ethernet (24V), 802.3af Supported
Power Supply: 24V, 0.5A PoE Adapter (Included)
Maximum Power Consumption: 6.5 W
Maximum TX Power: 2.4 GHz - 20 dBm, 5 GHz - 20 dBm
BSSID: Up to 8 Per Radio
Dimensions: 160 x 160 x 31.45 mm (6.30 x 6.30 x 1.24")
Weight: 170 g (185 g with Mounting Kits)
Power Save: Supported
Wireless Security: WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
Certifications: CE, FCC, IC
Mounting: Wall/Ceiling (Kits Included)
Operating Temperature: -10 + 70° C
Operating Humidity: 5 + 95% Condensing
Advanced Traffic Management
VLAN: 802.1Q
Advanced QoS: Per-User Rate Limiting
Guest traffic isolation: Supported
WMM: Voice, Video, Best Effort, and Background
Concurrent Clients: 250+
Supported Data Rates (Mbps)
802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n: 6.5 Mbps to 300 Mbps (MCS0 - MCS23, HT 20/40)
802.11ac: 6.5 Mbps to 867 Mbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80)
802.11b: 1, 2, 5.5, 11 Mbps
802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
Manufacturer: Ubiquiti



#08871

Net Price:
99,50 EUR
Unit: pcs**Wireless Access Point UniFi UAP AC LR
(Ubiquiti UAP-AC-LR)**

Ideal for long-range deployments, the UniFi AC LR AP offers simultaneous, dual-band operation with 3x3 MIMO in the 2.4 GHz band and 2x2 MIMO in the 5 GHz band.

The innovative antenna design provides a long-range, symmetrical-link coverage area, and the antenna gain of the UniFi AC LR AP performs better than one-way, high transmit power does for connecting distant clients.

Networking Interface (Mbps): 1 x 10/100/1000 Ethernet Ports
Buttons: Reset

Antennas: (1) Dual-Band Antenna, Tri-Polarity, 2.4 GHz- 3 dBi, 5 GHz- 3 dBi

Wi-Fi Standards: 802.11 a/b/g/n/ac

Power Method: Passive Power over Ethernet (24V), 802.3af Supported

Power Supply: 24V, 0.5A PoE Adapter (Included)

Maximum Power Consumption: 6.5 W

Maximum TX Power: 2.4 GHz - 30 dBm, 5 GHz - 22 dBm

BSSID: Up to Four Per Radio

Dimensions: 175.7 x 175.7 x 43.2 mm (6.92 x 6.92 x 1.70")

Weight: 240 g (315 g with Mounting Kits)

Power Save: Supported

Wireless Security: WEP, WPA-PSK, WPA-Enterprise

(WPA/WPA2, TKIP/AES)

Certifications: CE, FCC, IC

Mounting: Wall/Ceiling (Kits Included)

Operating Temperature: -10 ° 70° C

Operating Humidity: 5 + 95% Condensing

Advanced Traffic Management

VLAN: 802.1Q

Advanced QoS: Per-User Rate Limiting

Guest traffic isolation: Supported

WMM: Voice, Video, Best Effort, and Background

Concurrent Clients: 200+

Supported Data Rates (Mbps)

802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11n: 6.5 Mbps to 450 Mbps (MCS0 - MCS23, HT 20/40)

802.11ac: 6.5 Mbps to 867 Mbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80)

802.11b: 1, 2, 5.5, 11 Mbps

802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

Manufacturer: Ubiquiti



#08352

Net Price:
144,00 EUR
Unit: pcs**Wireless Access Point UniFi UAP AC PRO
(Ubiquiti UAP-AC-PRO)**

Ports: 2 x 10/100/1000 Ethernet Ports, , 1x USB 2.0 Port
Buttons: Reset

Antennas: (3) Dual-Band Antennas, 2.4 GHz- 3 dBi, 5 GHz- 3 dBi

Wi-Fi Standards: 802.11 a/b/g/n/ac

Power Method: Passive Power over Ethernet (48V),

802.3af/at Supported

Power Supply: 48V, 0.5A PoE Adapter (Included)

Maximum Power Consumption: 9 W

Maximum TX Power: 2.4 GHz - 22 dBm, 5 GHz - 22 dBm

BSSID: Up to 8 Per Radio

Dimensions: 196.7 x 196.7 x 35 mm (7.74 x 7.74 x 1.38")

Weight: 350 g (450 g with Mounting Kits)

Power Save: Supported

Wireless Security: WEP, WPA-PSK, WPA-Enterprise

(WPA/WPA2, TKIP/AES)

Certifications: CE, FCC, IC

Mounting: Wall/Ceiling (Kits Included)

Operating Temperature: -10 ° 70° C

Operating Humidity: 5 + 95% Condensing

Advanced Traffic Management

VLAN: 802.1Q

Advanced QoS: Per-User Rate Limiting

Guest traffic isolation: Supported

WMM: Voice, Video, Best Effort, and Background

Concurrent Clients: 250+

Supported Data Rates (Mbps)

802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11n: 6.5 Mbps to 450 Mbps (MCS0 - MCS23, HT 20/40)

802.11ac: 6.5 Mbps to 1300 Mbps (MCS0 - MCS9 NSS1/2/3, VHT 20/40/80)

802.11b: 1, 2, 5.5, 11 Mbps

802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

Manufacturer: Ubiquiti



#09069

Net Price:
47,70 EUR
Unit: pcs**Wireless N Access Point AC1200(TP-Link
TL-WA1201)**

- AC1200 Dual-Band Wi-Fi - 867 Mbps at 5 GHz and 300 Mbps at 2.4 GHz band.

- Flexible Deployment - Supports Passive PoE to carry electrical power and data simultaneously.

- Multiple Modes - Supports Access Point, Range Extender, Multi-SSID, and Client modes to meet any network needs.

- MU-MIMO Technology - Simultaneously transfers data to multiple devices for 2x faster performance.

- Boosted Coverage - Four fixed antennas equipped with Beamforming technology extend and concentrate the Wi-Fi signals.

- Captive Portal - Offers a designed portal page for heightened security and marketing.

Standards: IEEE 802.11n, IEEE 802.11b/g 2.4 GHz, IEEE 802.11ac/n/a 5 GHz

Ports: 1x 10/100/1000 Mbps RJ-45 PoE (LAN)

Frequency range: 2.4 GHz and 5 GHz

Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM

Operating modes: AP Mode, Multi-SSID Mode, AP Client

Mode, Repeater Mode (WDS / Universal), AP+ Bridge mode

Max. speed: 1200 Mbps (867 Mbps at 5 GHz, 300 Mbps at

2.4 GHz)

EIRP: CE <20 dBm (2.4 GHz), <23 dBm (5,15 GHz~5,25

GHz), FCC <30 dBm (2.4 GHz & 5 GHz)

Antenna: 4 Fixed High Performance Antennas

WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK,

WPA2,WPA2-PSK, TKIP, AES

WLAN features: 3T3R MIMO, CCA, QSS button, 4x SSIDs,

VLAN support

Auto MDI/MDIX: yes

Dimensions: 400x255x72 mm

Operating temperatures: 0°C + 40°C

Operating humidity:5% + 90%, non-condensing

Power: 12 V/1.5 A

Certificates: CE, FCC, RoHS

Manufacturer: TP-Link



#09001

Net Price:
412,00 EUR
Unit: pcs

11000Mbps Wireless Gigabit Router Tri-band AX11000, MU-MIMO (TP-Link Archer AX11000)

- Ultra-Fast Wi-Fi for Extreme Gaming - AX11000 speed machine that delivers 12-streams Wi-Fi Speeds Over 10 Gbps: 4804 Mbps (5 GHz Gaming) + 4804 Mbps (5 GHz) + 1148 Mbps (2.4 GHz)
- Game Accelerator - Detect and optimize gaming streams, to ensure your gaming stays immersive
- Game Protector - Keep your accounts and documents safe with HomecareTM security system powered by Trend MicroTM.
- Game Statistics - Real-time latency, game duration and network resource allocation in a glance with fine-tuned UI.
- Ultra Connectivity - 2.5 Gbps WAN port and eight Gigabit LAN ports, 2 USB 3.0 in Type A and Type C provide extensive connectivity.
- Powerful Processing - 1.8 GHz Quad-Core CPU and 3 coprocessors ensure your network performance always at peak run.
- Highly Efficient - OFDMA increases the avg. throughput and reduces the lag.
- Easy and Smart - Link to your router via Bluetooth and set it up in minutes with the powerful Tether app.

HARDWARE FEATURES:

Processor: 1.8 GHz 64 bit Quad-Core CPU
Memory: 1 GB RAM, 512 MB Flash
Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6
Interface: 8 10/100/1000Mbps LAN Ports, 1 2.5G/1G/100Mbps WAN Port, 1 USB-A 3.0 Port, 1 USB-C 3.0 Port
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off
Power Supply: 12V/5A
Dimensions (W X D X H): 11.3 x 11.3 x 7.2 in. (288 x 288 x 184mm)

Antenna: 8x High-Performance External Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5 GHz@ 4804 Mbps (802.11ax), 5 GHz@ 4804 Mbps (802.11ax), 2.4 GHz@ 1148 Mbps (802.11ax)
Wireless Functions: Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption
SOFTWARE FEATURES:
WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: Advanced Gaming Qos powered by TrendMicro
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comexe, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec Passthrough
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1

OTHERS:

Certification: CE, FCC, IC, RoHS
System Requirements: Microsoft Windows XP, VistaTM, Windows 7 or Windows 8/8.1/10, MAC OS, NetWareC, UNIX or Linux.
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#04566

Net Price:
47,70 EUR
Unit: pcs

1200Mbps Wireless Gigabit Router Dual-band AC1200 (TP-Link Archer C1200)

- Enjoy smooth online gaming and video streaming with dual band 1200Mbps Wi-Fi
- 3 External Antennas Greatly Expand Wireless Coverage
- Lightning-Fast wired connections using four Gigabit Ethernet Ports
- 2 USB Ports support storage and file sharing
- Easy setup and management with Tether App

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port, 1 USB 2.0 Port
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button
External Power Supply: 12VDC / 1A
Dimensions (W X D X H): 243x160,6x32,5mm (9,6x6,4x1,3 in.)

Antenna: 3 Detachable Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: <20dBm(EIRP)

Reception Sensitivity: 5GHz - 11a 54Mbps -76dBm, 11ac HT20 -68dBm, 11ac HT40 -65dBm, 11ac HT80 -62dBm, 11n HT20 -74dBm, 11n HT40 -71dBm, 2.4GHz - 11g 54M -75dBm, 11n HT20 -72dBm, 11n HT40 -69dBm

Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: WMM, Bandwidth Control
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comexe, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec Passthrough
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 2

OTHERS:

Certification: CE, FCC, IC, RoHS
Package Contents: Archer C1200, Power supply unit, Quick Installation Guide, Ethernet Cable
System Requirements: Microsoft Windows XP, VistaTM, Windows 7 or Windows 8, MAC OS, NetWareC, UNIX or Linux.
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.
Manufacturer: TP-Link



#09104

Net Price:
22,70 EUR
Unit: pcs

1200Mbps Wireless Gigabit Router Dual-band AC1200 (TP-Link Mercusys AC12G)

- AC1200 dual band Wi-Fi - speeds of up to 300 Mbps on the 2.4 GHz band and 867 Mbps on the 5 GHz band
- Full gigabit ports - lightning-fast connections for wired devices, including game consoles, STBs, smart TVs and more
- Share with up to 60 devices - internet access for multiple streaming simultaneously
- 4 high gain external antennas - powerful wireless coverage throughout your house
- Easy installation - intuitive webpage guides you through the setup process in minutes

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 3 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port
Button: WPS/Reset Button
External Power Supply: 9V/0.85A
Dimensions (W X D X H): 222 x 140 x 32 mm

Antenna: 4x 5 dBi

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: < 20 dBm
Reception Sensitivity: 5 GHz - 11a 6M -92 dBm, 11a 54M -75 dBm, 11ac 20M MCS8 -70 dBm, 11ac 40M MCS9 -64 dBm, 11ac 80M MCS9 -60 dBm, 2.4 GHz - 11g 6M -95 dBm, 11g 54M -77 dBm, 11n 20M MCS7 -74 dBm, 11n 40M MCS7 -71 dBm

Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics
Wireless Security: WPA-PSK / WPA2-PSK

SOFTWARE

WAN Type: Dynamic IP/Static IP/PPPoE/L2TP/PPTP
Management: Access Control, Local Management, Remote Management
DHCP: Server

Port Forwarding: Virtual Server, UPnP, DMZ

Dynamic DNS: NO-IP, DynDNS

Firewall Security: IP and MAC Address Binding

Guest Network: 2.4GHz Guest Network, 5GHz Guest Network

OTHERS:

Certifications: CE, ROHS
Package Contents: AC1200 Wireless Dual Band Router AC12G, Power Adapter, Quick Installation Guide, Ethernet Cable
Environment: Operating Temperature 0°~40° (32°~104°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing



#04610

Net Price:
66,60 EUR
Unit: pcs

1200Mbps Wireless Gigabit Router Dualband 1200AC, ADSL2+ (TP-Link Archer VR400)

- Speedy Wi-Fi - Superb wireless experience with 300Mbps (2.4GHz) + 867Mbps (5GHz) dual band Wi-Fi connections
- Superior Range - Three detachable antennas provide stable wireless connections and optimal coverage
- Versatile Connectivity - Fully compatible with the VDSL2/ADSL2+/ADSL2/ADSL standards, as well as fiber, cable and 3G/4G Internet services
- Beamforming Technology - Improves wireless range and performance at 5GHz band
- USB Port - Supports storage and print service sharing, FTP and media servers as well as 3G/4G dongle
- Tether App - TP-LINK Tether provides the easiest way to access and manage the router on your iOS and Android devices

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 1x10/100/1000Mbps RJ45 WAN/LAN Port, 3x10/100/1000Mbps RJ45 LAN Ports, 1xRJ11 Port, 1xUSB 2.0 Port

Button: 1 Power On/Off Button, 1 Wi-Fi On/Off Button, 1 WPS Button, 1 RESET Button

ADSL Standards: Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1 (G.DMT), ITU-T G.992.2 (G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1

ADSL2 Standards: ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis)

ADSL2+ Standards: ITU-T G.992.5

External Power Supply: 12VDC / 1.5A

Dimensions (W X D X H): 243.5 × 167.5 × 32.7mm

Antenna Type: 3 External detachable dual band antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz

Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: <20dBm (EIRP), 5GHz <23dBm (EIRP)

Wireless Functions: Enable/Disable Wireless Radio, WDS

Bridge, WMM, Wireless Statistics

Wireless Security: 64/128-bit WEP, WPA / WPA2, WPA-PSK /

WPA2-PSK encryption

SOFTWARE FEATURES:

Operating Modes: ADSL Modem Router, Wireless Router

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual

Access)/L2TP (Dual Access)/BigPond

DHCP: Server, Client, DHCP Client List, Address Reservation,

DHCP relay

Quality of Service: ATM QoS, Traffic Control (IP QoS)

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ,

ALG

Dynamic DNS: DynDns, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec

ATM Features: ATM Forum UNI3.1/4.0, PPP over ATM (RFC

2364), PPP over Ethernet (RFC2516), iPoA (RFC1577/2225),

MERIPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge),

PVC - Up to 8 PVCs

Security: NAT Firewall, Access Control, MAC / IP / URL

Filtering, Denial of Service (DoS), SYN Flooding, Ping of

Death, IP and MAC Address Binding

Advanced Functions: Parental Control, Network Address

Translation (NAT); Port Mapping (Grouping), Static Routing,

RIP v1/v2 (optional); DNS Relay, DDNS, IGMP v1/v2/v3

USB Sharing: Support Samba (Storage)/FTP Server/Media

Server/Printer Server

Management: Web Based Configuration (HTTP), Remote

management, Command Line Interface, SSL for TR-069,

SNMP v1/2c, Web Based Firmware Upgrade, Diagnostic

Tools

Guest Network: 2.4GHz guest network × 1, 5GHz guest

network × 1

IPSec VPN: Supports up to 10 IPSec VPN tunnels

IPv6: IPv6 and IPv4 dual stack

OTHERS:

Certification: CE, FCC, IC, RoHS

Package Contents: Archer VR400, External Splitter, RJ-11

Telephone Cable, RJ-45 Ethernet Cable, Power Adapter,

Quick Installation Guide

System Requirements: Windows 8/7/Vista/XP or Mac OS or

Linux-based operating system.

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty: 2 years limited warranty. Advanced replacement

service is available.

Manufacturer: TP-Link



#09084

Net Price:
50,50 EUR
Unit: pcs

1200Mbps Wireless Gigabit Router Dualband 1200AC, VDSL/ADSL+ (TP-Link Archer VR300)

- Parental Controls: manage responsible internet access for your children
- Guest Network: provides separate access for guests while securing the home network
- Firewall Security: supports DoS, SPI Firewall, IP Addressing/Domain Filter, IP/MAC Address Binding
- Quality of Service: prioritizes network traffic by device or application
- IPTV IGMP Proxy/Snooping: supports Bridge and Tag VLAN for smooth IPTV application
- IPv6: compatible with IPv6 (Internet Protocol version 6)
- Multilingual Interface: provides hassle-free configuration in six languages (EN/DE/IT/TR/RU/PO)

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz

Interface: 1x10/100Mbps RJ45 WAN/LAN Port,

3x10/100Mbps RJ45 LAN Ports, 1xRJ11 Port,

Button: 1 Power On/Off Button, 1 Wi-Fi On/Off Button, 1 WPS

Button, 1 RESET Button

ADSL Standards: Full-rate ANSI T1.413 Issue 2, ITU-T

G.992.1 (G.DMT), ITU-T G.992.2 (G.Lite), ITU-T G.994.1

(G.hs), ITU-T G.995.1

ADSL2 Standards: ITU-T G.992.3 (G.DMT.bis), ITU-T

G.992.4 (G.lite.bis)

ADSL2+ Standards: ITU-T G.992.5

External Power Supply: 12VDC / 1A

Dimensions (W X D X H): 385 × 290 × 76mm

Antenna Type: 4 fixed external antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz

Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps

EIRP: <20dBm (EIRP), 5GHz <23dBm (EIRP)

Wireless Functions: Enable/Disable Wireless Radio, WDS

Bridge, WMM, Wireless Statistics

Wireless Security: 64/128-bit WEP, WPA / WPA2, WPA-PSK /

WPA2-PSK encryption

SOFTWARE FEATURES:

Operating Modes: ADSL Modem Router, Wireless Router

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual

Access)/L2TP (Dual Access)/BigPond

DHCP: Server, Client, DHCP Client List, Address Reservation,

DHCP relay

Quality of Service: ATM QoS, Traffic Control (IP QoS)

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ,

ALG

Dynamic DNS: DynDns, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec

ATM Features: ATM Forum UNI3.1/4.0, PPP over ATM (RFC

2364), PPP over Ethernet (RFC2516), iPoA (RFC1577/2225),

MERIPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge),

PVC - Up to 8 PVCs

Security: NAT Firewall, Access Control, MAC / IP / URL

Filtering, Denial of Service (DoS), SYN Flooding, Ping of

Death, IP and MAC Address Binding

Advanced Functions: Parental Control, Network Address

Translation (NAT); Port Mapping (Grouping), Static Routing,

RIP v1/v2 (optional); DNS Relay, DDNS, IGMP v1/v2/v3

USB Sharing: Support Samba (Storage)/FTP Server/Media

Server/Printer Server

Management: Web Based Configuration (HTTP), Remote

management, Command Line Interface, SSL for TR-069,

SNMP v1/2c, Web Based Firmware Upgrade, Diagnostic

Tools

Guest Network: 2.4GHz guest network × 1, 5GHz guest

network × 1

IPSec VPN: Supports up to 10 IPSec VPN tunnels

IPv6: IPv6 and IPv4 dual stack

OTHERS:

Certification: CE, FCC, IC, RoHS

Package Contents: Archer VR300, External Splitter, RJ-11

Telephone Cable, RJ-45 Ethernet Cable, Power Adapter,

Quick Installation Guide

System Requirements: Microsoft Windows XP/7/8.1/10,

MAC OS, NetWare, UNIX or Linux, Internet Explorer, Firefox,

Chrome, Safari or other Java-enabled browser

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty: 2 years limited warranty. Advanced replacement

service is available.

Manufacturer: TP-Link



#06238

Net Price:
33,70 EUR
Unit: pcs

1200Mbps Wireless Gigabit Router Dualband AC1200 (TP-Link Archer C6)

- Supports 802.11ac standard
- Simultaneous 2.4GHz 300 Mbps and 5GHz 867 Mbps connections for 1200 Mbps of total available bandwidth
- 4 external antennas and one internal antenna provide stable wireless connections and optimal coverage
- Easy network management at your fingertips with TP-Link Tether
- MU-MIMO achieves 2X efficiency by communicating with up to 2 devices at once
- Supports Access Point mode to create a new Wi-Fi access point

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz

Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port

Button: WPS Button, Wireless On/Off Button, Reset Button,

On/Off Button

External Power Supply: 12V/1A

Dimensions (W X D X H): 230 × 144 × 35 mm (9.1 × 5.7 × 1.4

in.)

Antenna: 3 external detachable dual band antennas

(RP-SMA)

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz

Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps

EIRP: CE EIRP <20dBm (2.4GHz); <23dBm (5GHz)

Reception Sensitivity: 5GHz - 11a 6Mbps-93dBm, 11a

54Mbps -78dBm, 11ac HT20 -69dBm, 11ac HT40 -65dBm,

11ac HT80 -62dBm, 2.4GHz - 11g 54M -78dBm, 11n HT20

-74dBm, 11n HT40 -71dBm

Wireless Functions: Enable/Disable Wireless Radio, WDS

Bridge, WMM, Wireless Statistics

Wireless Security: 64/128-bit WEP, WPA / WPA2, WPA-PSK /

WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual

Access)/L2TP (Dual Access)/BigPond

DHCP: Server, Client, DHCP Client List, Address Reservation

Quality of Service: WMM, Bandwidth Control

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS: DynDns, Comex, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec

Access Control: Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC

Address Filter/Domain Filter, IP and MAC Address Binding

USB Sharing: Support Samba (Storage)/FTP Server/Media

Server/Printer Server

Management: Access Control, Local Management, Remote

Management

Guest Network: 2.4GHz guest network × 1, 5GHz guest

network × 1

OTHERS:

Certification: CE, FCC, IC, RoHS

Package Contents: Wireless Router Archer C6, Power

Adapter, RJ45 Ethernet Cable, Quick Installation Guide

System Requirements: Microsoft Windows 98SE, NT,

2000, XP, Vista TM, Windows 7 or Windows 8, MAC OS,

NetWare C, UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty: 2 years limited warranty. Advanced replacement

service is available.

Manufacturer: TP-Link



#09080

Net Price:
38,20 EUR
Unit: pcs

1200Mbps Wireless Gigabit Router Dualband AC1200 (TP-Link Archer C60)

- Supports 802.11ac standard
- Simultaneous 2.4GHz 300 Mbps and 5GHz 867 Mbps connections for 1200 Mbps of total available bandwidth
- 4 external antennas and one internal antenna provide stable wireless connections and optimal coverage
- Easy network management at your fingertips with TP-Link Tether
- MU-MIMO achieves 2X efficiency by communicating with up to 2 devices at once
- Beamforming technology delivers wider wireless coverage
- Supports Access Point mode to create a new Wi-Fi access point

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port, 1 USB 2.0 Port
Button: WPS Button, Wireless On/Off Button, Reset Button, On/Off Button
External Power Supply: 12V/1A
Dimensions (W X D X H): 8.5 x 4.6 x 1.2 in (215 x 117 x 32 mm)
Antenna: 3 external detachable dual band antennas (RP-SMA)

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: CE EIRP <20dBm(2.4GHz); <23dBm(5GHz)
Reception Sensitivity: 5GHz - 11a 6Mbps-93dBm, 11a 54Mbps -78dBm, 11ac HT20 -69dBm, 11ac HT40 -65dBm, 11ac HT80 -62dBm, 2.4GHz - 11g 54M -78dBm, 11n HT20 -74dBm, 11n HT40 -71dBm

Wireless Functions: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security: 64/128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation
Quality of Service: WMM, Bandwidth Control
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1

OTHERS:

Certification: CE, FCC, IC, RoHS
Package Contents: Wireless Router Archer C60, Power Adapter, RJ45 Ethernet Cable, Quick Installation Guide
System Requirements: Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.
Manufacturer: TP-Link



#04571

Net Price:
26,00 EUR
Unit: pcs

1200Mbps Wireless Router Dual-band AC1200 (TP-Link Archer C50)

- Supports 802.11ac standard - the next generation of Wi-Fi
- Simultaneous 2.4GHz 300Mbps and 5GHz 867Mbps connections for 1.2Gbps of total available bandwidth
- 2 dual band external antennas provide stable wireless connections and optimal coverage
- USB Port - easily share a printer locally and files & media with networked devices or remotely via FTP server
- Easy network management at your fingertips with TP-LINK Tether

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port, 1 USB 2.0 Port
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button
External Power Supply: 12VDC / 1.5A
Dimensions (W X D X H): 182.95 x 123.5 x 32.1mm (7.2 x 4.9 x 1.3 in.)
Antenna: 2 Detachable Antennas RP-SMA

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: <20dBm(EIRP)
Reception Sensitivity: 5GHz - 11a 54Mbps -76dBm, 11ac HT20 -70dBm, 11ac HT40 -65.5dBm, 11ac HT80 -61.5dBm, 2.4GHz - 11g 54M -76dBm, 11n HT20 -74dBm, 11n HT40 -71dBm

Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: WMM, Bandwidth Control
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comexe, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec Passthrough
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 2

OTHERS:

Certification: CE, FCC, IC, RoHS
Package Contents: Archer C50, 2 antennas, Power supply unit, Quick Installation Guide, Ethernet Cable
System Requirements: Microsoft Windows XP, Vista, Windows 7 or Windows 8, MAC OS, NetWare, UNIX or Linux
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.
Manufacturer: TP-Link



#09079

Net Price:
22,30 EUR
Unit: pcs

1200Mbps Wireless Router Dual-band AC1200 (TP-Link Archer C54)

- Faster AC Wi-Fi-AC1200 dual-band is ideal for 4K video streaming and high-speed downloading
- Far-Reaching Coverage-4x antennas and Beamforming delivers extensive Wi-Fi coverage and reliable connections.
- Multi-Mode 3-in-1-Supports Router, Access Point, and Range Extender modes for added flexibility.
- Parental Controls-Manages when and how connected devices can access the internet.
- Guest Network-Provides separate access for guests in order to secure the host network.
- Smooth HD Streaming-Supports IGMP Proxy/Snooping, Bridge, and Tag VLAN to optimize IPTV streaming.
- IPv6 Supported-Compatible with the IPv6 (the latest Internet Protocol version 6).
- Compact and Mountable-Designed to conserve space and complement any décor.

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port
Button: WPS/Reset Button
External Power Supply: 9VDC / 0.85A
Dimensions (W X D X H): 4.5 x 4.2 x 1.0 in (115 x 106.7 x 24.3 mm)
Antenna: 4 Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: CE <20dBm(2.4GHz), <23dBm(5GHz), FCC <30dB
Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: WMM, Bandwidth Control
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comexe, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec Passthrough
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 2

OTHERS:

Certification: CE, FCC, IC, RoHS
Package Contents: Archer C54, Power supply unit, Quick Installation Guide, Ethernet Cable
System Requirements: Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.
Manufacturer: TP-Link



#09102

Net Price:
17,90 EUR
Unit: pcs

**1200Mbps Wireless Router Dual-band AC1200
(TP-Link Mercusys AC10)**

- High-Speed Wi-Fi - Stream with fast and stable connections, reaching speeds up to 1167 Mbps (300 Mbps on the 2.4 GHz band and 867 Mbps on the 5 GHz band)
- 4 High-Gain External Antennas - Receive strong Wi-Fi signals in every corner of your home
- Easy Installation - Set up in minutes guided by an intuitive web UI
- Active Parental Controls - Protect your family by setting appropriate access policies for responsible, safe internet use
- Multi-Mode - Access Point Mode, Range Extender Mode, and Router Mode supported to satisfy all application scenarios
- IPTV and IPv6 Supported

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 2 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port
Button: WPS/Reset Button
External Power Supply: 9V/0.85A
Dimensions (W X D X H): 4.5 x 3.7 x 1.0 in (114 x 94 x 26 mm)
Antenna: 4 x 5 dBi Fixed Omni-Directional Antennas
WIRELESS FEATURES:
Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: 2.4 GHz < 20 dBm (EIRP), 5 GHz < 23 dBm (EIRP)
Reception Sensitivity: 11g 6 Mb/s -96 dBm, 11g 54 Mb/s -78 dBm, 11n HT40 MCS7 -74 dBm, 11n HT20 MCS7 -71 dBm, 11a 6 Mb/s -97 dBm, 11a 54 Mb/s -79 dBm, 11ac VHT20 MCS8 -74 dBm, 11ac VHT40 MCS9 -70 dBm, 11ac VHT80 MCS9 -65 dBm
Wireless Functions: Enable/Disable Wireless Radio, WMM
Wireless Security: WEP, WPA / WPA2, WPA-PSK / WPA2-PSK
OTHERS:
Package Contents: AC1200 Wireless Dual Band Router AC10, Power Adapter, Quick Installation Guide, Ethernet Cable
Environment: Operating Temperature 0°~40° (32°~104°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing



#09103

Net Price:
18,90 EUR
Unit: pcs

**1200Mbps Wireless Router Dual-band AC1200
(TP-Link Mercusys AC12)**

- Supports 802.11ac standard - the next generation of Wi-Fi
- Enjoy smooth online gaming and video streaming with dual band 1200Mbps Wi-Fi
- 4 External Antennas Greatly Expand Wireless Coverage
- Guest Network Access provides secure Wi-Fi access for guests sharing your home or office network
- Easy installation - intuitive webpage guides you through the setup process in minutes
- IPTV and IPv6 Supported

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 3 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port
Button: WPS/Reset Button
External Power Supply: 9V/0.85A
Dimensions (W X D X H): 222 x 140 x 32 mm
Antenna: 4 x 5 dBi
WIRELESS FEATURES:
Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: < 20 dBm
Reception Sensitivity: 5 GHz - 11a 6M -92 dBm, 11a 54M -75 dBm, 11ac 20M MCS8 -70 dBm, 11ac 40M MCS9 -64 dBm, 11ac 80M MCS9 -60 dBm, 2.4 GHz - 11g 6M -95 dBm, 11g 54M -77 dBm, 11n 20M MCS7 -74 dBm, 11n 40M MCS7 -71 dBm
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics
Wireless Security: WPA-PSK / WPA2-PSK
SOFTWARE
WAN Type: Dynamic IP/Static IP/PPPoE/L2TP/PPTP
Management: Access Control, Local Management, Remote Management
DHCP: Server
Port Forwarding: Virtual Server, UPnP, DMZ
Firewall Security: IP and MAC Address Binding
Guest Network: 2.4GHz Guest Network, 5GHz Guest Network
OTHERS:
Certifications: CE, ROHS
Package Contents: AC1200 Wireless Dual Band Router AC12, Power Adapter, Quick Installation Guide, Ethernet Cable
Environment: Operating Temperature 0°~40° (32°~104°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing

NEW



#09192

Net Price:
21,90 EUR
Unit: pcs

**1200Mbps Wireless Router Dual-band AC1200
(TP-Link Mercusys MR30G)**

- AC1200 Gigabit WiFi - Enjoy home entertainment without any lag, reaching speeds up to 1.2 Gbps (867 Mbps on the 5 GHz band and 300 Mbps on the 2.4 GHz band)
- Broader Coverage - 4x high-gain antennas with Beamforming boost stable connections throughout your home for strong WiFi signals in every corner
- Full Gigabit Ports - Make full use of your internet access and transfer data at dizzying speeds for peak performance
- Higher Network Efficiency - MU-MIMO technology allows MR30G to communicate with multiple devices at the same time, increasing WiFi throughput for each device
- Easily Manage Your Home Network - Varied software functions such as Parental Controls, QoS, and Guest Network for safety and effectiveness
- IPTV Supported - Supports IGMP Proxy/Snooping, Bridge, and Tag VLAN to optimize IPTV streaming
- IPv6 Supported - Allows you to both enjoy the IPv6 services provided by your ISP and visit IPv6 websites

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 2 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port
Button: WPS/Reset Button
Dimensions (W X D X H): 6.3 x 5.0 x 1.5 in (159.7 x 125.9 x 37.1 mm)
Antenna: 4 Fixed Omni Directional Antennas (5dBi)
WIRELESS FEATURES:
Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP: <20dBm(EIRP)
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics
Wireless Security: WPA-PSK / WPA2-PSK
SOFTWARE FEATURES:
WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)
Management: Access Control, Local Management, Remote Management
DHCP: Server
Port Forwarding: Virtual Server, UPnP, DMZ
Firewall Security: IP and MAC Address Binding
Protocols: IPv4, IPv6
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1
OTHERS:
Package Contents: MR30G, Power supply unit, Quick Installation Guide, Ethernet Cable



NEW



#09185

Net Price:
29,10 EUR
Unit: pcs

1200Mbps Wireless Router Dual-band AC1200, MU-MIMO (TP-Link Archer C64)

- 802.11ac Wave2 WiFi - 867 Mbps on the 5 GHz band and 400 Mbps on the 2.4 GHz band
- Boosted WiFi Coverage - 4 antennas provide stable wireless connections and optimal coverage
- MU-MIMO - Easy network management at your fingertips with TP-Link TetherMU-MIMO achieves 2X efficiency by communicating with up to 2 devices at once‡
- Beamforming - Beamforming technology delivers a highly efficient wireless connection
- AP Mode - Supports Access Point mode to create a new WiFi access point
- Intelligent Connection - Smart Connect directs clients to the less congested band and Airtime Fairness optimizes the time usage
- Easy Setup - Easy network management at your fingertips with TP-Link Tether

HARDWARE FEATURES:

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface:4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port
Button:WPS/Reset Button
External Power Supply: 12VDC / 1A
Dimensions (W X D X H): 4.7 × 4.7 × 1.1 in (120 × 120 × 27.9 mm)

Antenna: 4 Antennas

WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz
Signal Rate:5GHz Up to 867Mbps, 2.4GHz Up to 400Mbps
EIRP: CE <20dBm(2.4GHz), <23dBm(5GHz), FCC <30dB
Wireless Functions:Enable/Disable Wireless Radio, WMM, Wireless Statistics
Wireless Security:64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type:Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP:Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service:WMM, Bandwidth Control
Port Forwarding:Virtual Server,Port Triggering, UPnP, DMZ
Dynamic DNS:DynDns, Comexe, NO-IP
VPN Pass-Through:PPTP, L2TP, IPSec Passthrough
Access Control:Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security:DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing:Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management:Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network × 1, 5GHz guest network × 2

OTHERS:

Certification:CE, FCC,IC, RoHS
Package Contents:Archer C64, Power supply unit, Quick Installation Guide, Ethernet Cable
System Requirements:Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser
Environment:Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#09055

Net Price:
40,70 EUR
Unit: pcs

1350Mbps Wireless Gigabit Router Dualband AC1350, MU-MIMO (TP-Link EC230-G1)

- Upgrade to Fast AC Wi-Fi, 450Mbps + 867Mbps Dual Band Wi-Fi
- MU-MIMO for 2 x Faster Connections
- Beamforming for Better Coverage
- Gigabit Ethernet provides fast, reliable wired connections

HARDWARE FEATURES:

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface:4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port
Button:WPS Button, Wireless On/Off Button, Reset Button, On/Off Button
External Power Supply: 12V/1A
Dimensions (W X D X H):230 × 144 × 35 mm (9,1 × 5,7 × 1,4 in.)

Antenna: 4 external antennas, 1 internal antenna

WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz
Signal Rate:5GHz Up to 867Mbps, 2.4GHz Up to 450Mbps
Wireless Functions:Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security:64/128-bit WEP, WPA / WPA2, WPA-PSK/ WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type:Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP:Server, Client, DHCP Client List, Address Reservation
Quality of Service:WMM, Bandwidth Control
Port Forwarding:Virtual Server,Port Triggering, UPnP, DMZ
Dynamic DNS:DynDns, Comexe, NO-IP
VPN Pass-Through:PPTP, L2TP, IPSec
Access Control:Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security:DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing:Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management:Access Control, Local Management, Remote Management

OTHERS:

Certification:CE, RoHS
Package Contents:Wireless EC230-G1, Power Adapter, RJ45 Ethernet Cable, Quick Installation Guide
System Requirements:Microsoft WindowsC 98SE, NT, 2000, XP, VistaTM, Windows 7/8/10, MACC OS, NetWareC, UNIXC or Linux.
Environment:Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#09041

Net Price:
51,70 EUR
Unit: pcs

1500Mbps Wireless Gigabit Router Dual-band AX1500, MU-MIMO (TP-Link Archer AX10)

- Wi-Fi 6 Technology-Archer AX10 comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity, and reduced network congestion.
- Next-Gen 1.5 Gbps Speeds-Archer AX10 dual-band router reaches even faster speeds up to 1.5 Gbps (1201 Mbps on 5 GHz band and 300 Mbps on 2.4 GHz band).
- Connect Dozens of Devices-More simultaneous connections and reduced latency with OFDMA and MU-MIMO.
- Triple-Core CPU-Instant response to all your network activity with a 1.5 GHz triple-core CPU.
- Broader Coverage-4 Antennas and Beamforming technology focus signal towards individual clients for broader coverage.
- Full Gigabit Ports-Take full advantage of broadband speeds up to 1 Gbps.
- Easy Setup-Finish your network upgrade in minutes with Tether app.
- Compatible with Alexa-Control your router via voice commands and make your life smarter and easier with Amazon Alexa.

HARDWARE FEATURES:

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz, Wi-Fi 6
Interface:4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port
Button:WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off
Power Supply: 12V/1A
Dimensions (W X D X H): 10.2 × 5.3 × 1.5 in (260.2 × 135.0 × 38.6 mm)

Antenna: 4 × External Antennas

WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz
Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 300 Mbps (802.11n)
Wireless Functions:Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA
Wireless Security:64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type:Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP:Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service:Advanced Gaming Qos powered by TrendMicro
Port Forwarding:Virtual Server,Port Triggering, UPnP, DMZ
Dynamic DNS:DynDns, Comexe, NO-IP
VPN Pass-Through:PPTP, L2TP, IPSec Passthrough
Access Control:Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security:DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing:Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management:Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network × 1, 5GHz guest network × 1

OTHERS:

Certification:CE, FCC,IC, RoHS
System Requirements:Microsoft WindowsC XP, VistaTM, Windows 7 or Windows 8/8.1/10, MACC OS, NetWareC, UNIXC or Linux.
Environment:Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#07168

Net Price:
63,20 EUR
Unit: pcs

1750Mbps Wireless Gigabit Router Dualband AC1750 (TP-Link Archer C7)

- Supports 802.11ac standard - the next generation of Wi-Fi
- Simultaneous 2.4GHz 450Mbps and 5GHz 1300Mbps connections for 1.75Gbps of total available bandwidth
- 3*5dBi external antennas and 3 internal antennas provide maximum Omni-directional wireless coverage and reliability
- Dual USB Ports - easily share printers, files or media with your friends or family locally or over the internet
- Guest Network Access provides secure Wi-Fi access for guests sharing your home or office network

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port, 2 USB 2.0 Ports
Button: WPS Button, Wireless On/Off Button, Reset Button
External Power Supply: 12VDC / 2.5A
Dimensions (W X D X H): 9.6 x 6.4 x 1.3 in. (243 x 160.6 x 32.5mm)

Antenna: 3 external detachable dual band antennas (RP-SMA)

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 450Mbps
EIRP: <20dBm (EIRP)

Reception Sensitivity: 5GHz - 11a 6Mbps-96dBm, 11a 54Mbps -79dBm, 11ac HT20 -71dBm, 11ac HT40 -66dBm, 11ac HT80 -63dBm, 2.4GHz - 11g 54M -77dBm, 11n HT20 -74dBm, 11n HT40 -72dBm

Wireless Functions: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security: 64/128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation
Quality of Service: WMM, Bandwidth Control
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comex, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1

OTHERS:

Certification: CE, FCC, IC, RoHS
Package Contents: Archer C7, 3 detachable dual band antennas, Power supply unit, Resource CD, Quick Installation Guide
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM, Windows 7 or Windows 8, MAC OS, NetWareC, UNIX or Linux.
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.
Manufacturer: TP-Link



#09075

Net Price:
67,50 EUR
Unit: pcs

1800Mbps Wireless Gigabit Router Dual-band AX1800, MU-MIMO (TP-Link Archer AX20)

- Dual-Band Wi-Fi 6 - Equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity, and reduced network congestion.
- Next-Gen 1.8 Gbps Speeds - Enjoy smooth streaming, downloading, and gaming all without buffering with Wi-Fi speeds of 1.8 Gbps.
- Connect More Devices - Wi-Fi 6 technology communicates more data to more devices using revolutionary OFDMA technology while simultaneously reducing lag.
- Quad-Core Processing - The 1.5 GHz quad-core CPU ensures communications between your router and all connected devices are smooth.
- Extensive Coverage - Beamforming, independent FEM, and four antennas combine to deliver focused reception to devices far away.
- OneMesh Compatible - Use with OneMesh extenders to get whole-home coverage and enjoy smooth roaming between signals.
- Increased Battery Life - Target Wake Time technology reduces your devices' power consumption to extend their battery life. ‡
- USB Easy Sharing - A USB 2.0 Port enables easy file sharing within your network or building private Cloud Storage.
- Easy Setup - Set up your router in minutes with the powerful TP-Link Tether App.
- Backward Compatible - Supports all previous 802.11 standards and all Wi-Fi devices.

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6
Interface: 4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port, 1 USB 2.0 Port
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off
Power Supply: 12V/1.5A
Dimensions (W X D X H): 10.2 x 5.3 x 1.5 in (260.2 x 135.0 x 38.6 mm)

Antenna: 4 x External Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions: Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: Advanced Gaming Qos powered by TrendMicro
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comex, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec Passthrough
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1

OTHERS:

Certification: CE, FCC, IC, RoHS
System Requirements: Microsoft Windows XP, VistaTM, Windows 7 or Windows 8/8.1/10, MAC OS, NetWareC, UNIX or Linux.
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link

NEW



#09182

Net Price:
58,50 EUR
Unit: pcs

1800Mbps Wireless Gigabit Router Dual-band AX1800, MU-MIMO (TP-Link Archer AX23)

- Super-Fast 1.8 Gbps Wi-Fi - Enjoy smooth 4K streaming and downloading with super-fast Wi-Fi speeds of 1.8 Gbps.
- Connect More Devices - Communicates with more devices using OFDMA while simultaneously reducing lag.
- Broader Coverage - Improved algorithm, beamforming, and high-performance antennas enhance the Wi-Fi coverage performance.
- Next-Gen Platform - The Next-Gen High-Efficiency Chipset provides fast and stable Wi-Fi while saving power consumption.
- Parental Controls - Enjoy the most versatile yet free parental controls features among all routers, including URL blocking, profile management, pausing, and more.
- Works with Most ISPs - Compatible with most ISPs with extra L2TP/PPTP support. IPTV support works with your existing TV over the Internet contract.
- OneMesh - Use with OneMesh extenders to get whole-home coverage and enjoy smooth roaming between signals.
- Easy Setup - Set up your router in minutes with the powerful TP-Link Tether App.
- Backward Compatible - Supports all previous 802.11 standards Wi-Fi devices.

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6
Interface: 4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off
Power Supply: 12V/1A
Dimensions (W X D X H): 10.2 x 5.3 x 1.5 in (260.2 x 135.0 x 38.6 mm)

Antenna: 4 x External Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions: Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: Advanced Gaming Qos powered by TrendMicro
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comex, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec Passthrough
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1

OTHERS:

Certification: CE, FCC, IC, RoHS
System Requirements: Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#09109

Net Price:
34,20 EUR
Unit: pcs

1800Mbps Wireless Gigabit Router Dual-band AX1800, MU-MIMO (TP-Link Marcusys MR70X)

- Next-Gen WiFi 6 Speeds - Optimal WiFi 6 speeds reaching up to 1.8 Gbps (1201 Mbps on the 5 GHz band and 574 Mbps on the 2.4 GHz band)
- 4x More Capacity - OFDMA and MU-MIMO allow simultaneous data transmission to and from several devices, improving overall network efficiency
- Broader, Stronger Coverage - 4x multi-directional high-gain antennas with Beamforming boost stable connections throughout your home for strong WiFi signals in every corner
- Overall Security Protection - The latest WPA3 provides improved WiFi security
- Gigabit Wired Connections - Make full use of your internet access and transfer data at dizzying speeds for peak performance
- Eco-Friendly Power Saving - Target Wake Time (TWT) reduces power consumption for your mobile and IoT devices during data transmissions
- Less WiFi Interference - Minimizes the interference from neighboring signals to improve transmission efficiency with BSS color
- Smart Connect - Intelligently chooses the best available band for each device
- Access Point Mode - Extends a wired network and makes it wireless

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6

Interface: 3 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port

Button: WPS/Reset Button

Dimensions (W X D X H): 8.2 x 6.8 x 1.6 in (208.8 x 171.6 x 41.7 mm)

Antenna: 4x 5 dBi Fixed Omni-Directional Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz

Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions: Enable/Disable Wireless Radio, WMM

Wireless Security: WPA-PSK / WPA2-PSK/ WPA3

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/L2TP/PPTP

Management: Access Control, Local Management, Remote Management

DHCP: Server, DHCP Client List

NAT Forwarding: Port Forwarding, Port Triggering, UPnP, DMZ

Firewall Security: SPI Firewall, IP and MAC Address Binding

Guest Network: 2.4 GHz Guest Network, 5 GHz Guest Network

VPN Passthrough: OpenVPN, PPTP supported

OTHERS:

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing



#09042

Net Price:
44,90 EUR
Unit: pcs

1900Mbps Wireless Router Dual-band AC1900 (TP-Link Archer C80)

- 802.11ac Wave2 Wi-Fi - 1300 Mbps on the 5 GHz band and 600 Mbps on the 2.4 GHz band.
- 3x3 MIMO Technology - Transmitting and receiving data on three streams to pair flawlessly with your 3x3 clients.
- Boosted Wi-Fi Coverage - Beamforming technology delivers a highly efficient wireless connection.
- MU-MIMO - To help your devices achieve optimal performance by making communication more efficient.
- Personalized Management - Advanced features like Parental Controls, Guest Network, and Access Control provide individualized tools for network management.
- Intelligent Connection - Smart Connect directs clients to the less congested band and Airtime Fairness optimizes the time usage.

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE

802.11b/g/n 2.4GHz

Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port

Button: WPS/Reset Button, Wireless On/Off Button, Power On/off Button

External Power Supply: 12VDC / 1A

Dimensions (W X D X H): 8.5 x 4.6 x 1.26 in (215 x 117 x 32 mm)

Antenna: 4 Fixed Omni Directional Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz

Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 600Mbps

EIRP: <20dBm(EIRP)

Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics

Wireless Security: 64/128-bit WEP, WPA/WPA2,

WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual

Access)/L2TP (Dual Access)/BigPond

DHCP: Server, Client, DHCP Client List, Address Reservation,

DHCP relay

Quality of Service: WMM, Bandwidth Control

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS: DynDns, Comex, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec Passthrough

Access Control: Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC

Address Filter/Domain Filter, IP and MAC Address Binding

USB Sharing: Support Samba(Storage)/FTP Server/Media

Server/Printer Server

Management: Access Control, Local Management, Remote

Management

Guest Network: 2.4GHz guest network x 1, 5GHz guest

network x 2

OTHERS:

Certification: CE, FCC, IC, RoHS

Package Contents: Archer C80, 2 antennas, Power supply

unit, Quick Installation Guide, Ethernet Cable

System Requirements: Microsoft Windows XP, VistaTM,

Windows 7, 8, 10, MAC OS, NetWareC, UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty: 2 years limited warranty. Advanced replacement

service is available.

Manufacturer: TP-Link



#09108

Net Price:
29,90 EUR
Unit: pcs

1900Mbps Wireless Router Dual-band AC1900 (TP-Link Mercusys MR50G)

- AC1900 Dual Band Speeds - Enjoy home entertainment without any lag, reaching speeds up to 1900 Mbps (1300 Mbps on the 5 GHz band and 600 Mbps on the 2.4 GHz band)
- Far-Reaching Coverage - 6x high-gain antennas with Beamforming boost stable connections throughout your home for strong WiFi signals in every corner
- Full Gigabit Ports - Make full use of your internet access and transfer data at dizzying speeds for peak performance
- Higher Network Efficiency - MU-MIMO technology allows MR50G to communicate with multiple devices at the same time, increasing the overall network throughput
- Smart Connect- Intelligently chooses the best available band for each device

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE

802.11b/g/n 2.4GHz

Interface: 2 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port

Button: WPS/Reset Button

External Power Supply: 12VDC / 1A

Dimensions (W X D X H): 175.6 x 157.2 x 45 mm

Antenna: 6 Fixed Omni Directional Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz

Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 600Mbps

EIRP: <20dBm(EIRP)

Wireless Functions: Enable/Disable Wireless Radio, Wireless

Statistics

Wireless Security: WPA-PSK / WPA2-PSK

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual

Access)/L2TP (Dual Access)

Management: Access Control, Local Management, Remote

Management

DHCP: Server

Port Forwarding: Virtual Server, UPnP, DMZ

Firewall Security: IP and MAC Address Binding

Protocols: IPv4, IPv6

Guest Network: 2.4GHz guest network x 1, 5GHz guest

network x 1

OTHERS:

Package Contents: MR50G, Power supply unit, Quick

Installation Guide, Ethernet Cable



#09045

Net Price:
92,00 EUR
Unit: pcs

2100Mbps Wireless Gigabit Router Dualband 2100AC, ADSL, MU-MIMO (TP-Link Archer VR2100)

- Super VDSL - The Latest Super VDSL (VDSL2 Profile 35b) tech delivers internet speeds of up to 350 Mbps
- Ultra-Fast Speed - Surpasses the Wi-Fi speed limits of the previous generation, reaching up to 1733 Mbps on 5 GHz and 300 Mbps on 2.4 GHz
- 4x4 MU-MIMO - Simultaneously transfers data to multiple devices for 4x faster performance
- Whole-Home Coverage with OneMesh™ - Co-works with TP-Link OneMesh products to create a flexible and cost-efficient Mesh network
- Lightning-Fast Wired Connection - USB 3.0 port and four Gigabit Ethernet ports run up to 10x faster than the previous generation to unleash your home entertainment
- TP-Link Tether App - Easily access and manage your network, including remote control and automatic updates, using any iOS or Android mobile device.

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 4x10/100/1000Mbps RJ45 LAN Ports, 1xRJ11 Port, 2xUSB 2.0 Ports
Button: 1 Power On/Off Button, 1 Wi-Fi On/Off Button, 1 WPS Button, 1 RESET Button
ADSL Standards: Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite),
ADSL2 Standards: ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis)
ADSL2+ Standards: ITU-T G.992.5
External Power Supply: 12VDC / 1.5A
Dimensions (W X D X H): 8.5 x 6.5 x 1.4 in (216 x 164 x 36.8 mm)

Antenna Type: 3 External Dual Band Antennas + 1 Internal 5 GHz Antenna

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 1733Mbps, 2.4GHz Up to 300Mbps
EIRP: <20dBm(EIRP), 5GHz <23dBm(EIRP)
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security: 64/128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK encryption

SOFTWARE FEATURES:

Operating Modes: ADSL Modem Router, Wireless Router
WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: ATM QoS, Traffic Control (IP QoS)
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ, ALG
Dynamic DNS: DynDns, NO-IP
VPN Pass-Through: PPTP, L2TP, IPsec

ATM Features: ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364), PPP over Ethernet (RFC2516), iPoA (RFC1577/2225), MERIPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC - Up to 8 PVCs
Security: NAT Firewall, Access Control, MAC / IP / URL Filtering, Denial of Service (DoS), SYN Flooding, Ping of Death, IP and MAC Address Binding
Advanced Functions: Parental Control, Network Address Translation (NAT), Port Mapping (Grouping), Static Routing, RIP v1/v2 (optional), DNS Relay, DDNS, IGMP V1/V2/V3
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server

Management: Web Based Configuration (HTTP), Remote management, Command Line Interface, SSL for TR-069, SNMP v1/2c, Web Based Firmware Upgrade, Diagnostic Tools

Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1

IPSec VPN: Supports up to 10 IPSec VPN tunnels

IPv6: IPv6 and IPv4 dual stack

OTHERS:

Certification: CE, FCC, IC, RoHS
Package Contents: Archer VR2100, External Splitter, RJ-11 Telephone Cable, RJ-45 Ethernet Cable, Power Adapter, Quick Installation Guide

System Requirements: Windows 10/8/7/Vista/XP or Mac OS or Linux-based operating system.

Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#04691

Net Price:
99,60 EUR
Unit: pcs

2300Mbps Wireless Gigabit Router Dual-band AC2300, MU-MIMO (TP-Link Archer C2300)

- Watch 4K movies and game with high-speed AC2300 dual-band Wi-Fi
- Powerful 1.8GHz dual-core 64-bit CPU with two co-processors deliver smooth and speedy connections
- RangeBoost greatly improves Wi-Fi connection to devices located farther away
- MU-MIMO connects more Wi-Fi devices at once for faster performance
- Airtime Fairness equally divides attention between newer and older devices to improve Wi-Fi performance

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port, 1 USB 3.0 Port, 1 USB 2.0 Port
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button
External Power Supply: 12VDC / 4A
Dimensions (W X D X H): 8.5 x 6.5 x 1.4 in (216 x 164 x 36.8 mm)

Antenna: 3 Detachable Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 1625Mbps, 2.4GHz Up to 600Mbps
EIRP: <20dBm(EIRP)
Reception Sensitivity: 5GHz - 11a 6Mb/s -91dBm, 11a 54Mb/s -72dBm, 11ac HT20 -60dBm, 11ac HT40 -61dBm, 11ac HT80 -56dBm, 2.4GHz - 11g 54M -73dBm, 11n HT20 -70dBm, 11n HT40 -69dBm

Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics

Wireless Security: 64/128-bit WEP, WPA/WPA2,

WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: WMM, Bandwidth Control
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comex, NO-IP
VPN Pass-Through: PPTP, L2TP, IPsec Passthrough
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 2

OTHERS:

Certification: CE, FCC, IC, RoHS
Package Contents: Archer C2300, Power supply unit, Quick Installation Guide, Ethernet Cable
System Requirements: Microsoft Windows XP, Vista™, Windows 7, Windows 8, Windows 10, MAC OS, NetWareC, UNIX or Linux.
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.
Manufacturer: TP-Link



#09002

Net Price:
83,30 EUR
Unit: pcs

3000Mbps Wireless Gigabit Router Dual-band AX3000, MU-MIMO (TP-Link Archer AX50)

- Next-Gen Gigabit Wi-Fi 6 Speed-2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz band ensure smoother streaming and faster downloads.
- Connect More Devices-OFDMA technology increases capacity by 4 times to enable simultaneous transmission to more devices.
- Ultra-Low Latency-Up to 75% reduction in latency enables more responsive gaming and video chatting.
- Expanded Wi-Fi Coverage-Four high-gain external antennas and Beamforming technology combine to extend strong, reliable Wi-Fi throughout your home.
- Enhanced Security-More secure and trusted Wi-Fi with TP-Link HomeCare™.
- Reliable Connections-Intel® Home Wi-Fi Chipset greatly increases processing speed to deliver superior Wi-Fi 6 Giga+ performance.
- Improved Battery Life-Target Wake Time helps your devices to communicate more while consuming less power.
- Compatible with Alexa-Control your router via voice commands and make your life smarter and easier with Amazon Alexa.

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6
Interface: 4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port, 1 USB-A 3.0 Port
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off
Power Supply: 12V/2A
Dimensions (W X D X H): 10.2 x 5.3 x 1.5 in (260.2 x 135.0 x 38.6 mm)

Antenna: 4 x External Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5 GHz@ 2402 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)
Wireless Functions: Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: Advanced Gaming QoS powered by TrendMicro
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comex, NO-IP
VPN Pass-Through: PPTP, L2TP, IPsec Passthrough
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1

OTHERS:

Certification: CE, FCC, IC, RoHS
System Requirements: Microsoft Windows XP, Vista™, Windows 7 or Windows 8/8.1/10, MAC OS, NetWareC, UNIX or Linux.
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



NEW



#09183

Net Price:
83,30 EUR
Unit: pcs

3000Mbps Wireless Gigabit Router Dual-band AX3000, MU-MIMO (TP-Link Archer AX55)

- Next-Gen Gigabit Wi-Fi 6 Speed-2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz band ensure smoother streaming and faster downloads.
- Connect More Devices-OFDMA technology increases capacity by 4 times to enable simultaneous transmission to more devices.
- Ultra-Low Latency-Up to 75% reduction in latency enables more responsive gaming and video chatting.
- Expanded Wi-Fi Coverage-Four high-gain external antennas and Beamforming technology combine to extend strong, reliable Wi-Fi throughout your home.
- TP-Link HomeShield - Enhanced security defends against the latest cyber threats.
- Improved Battery Life-Target Wake Time helps your devices to communicate more while consuming less power.
- Compatible with Alexa-Control your router via voice commands and make your life smarter and easier with Amazon Alexa.

HARDWARE FEATURES:

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6
Interface:4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port, 1 USB-A 3.0 Port

Button:WPS/Reset Button, Wireless On/Off Button, Power On/Off Button

Power Supply: 12V/2A

Dimensions (W X D X H): 261.1 × 134.5 × 41.0 mm

Antenna: 4 × External Antennas

WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz

Signal Rate: 5 GHz@ 2402 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions:Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA

Wireless Security:WPA, WPA2, WPA3,

WPA/WPA2-Enterprise (802.1x) encryption

SOFTWARE FEATURES:

WAN Type:Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond

DHCP:Server, Client, DHCP Client List, Address Reservation,

DHCP relay

Quality of Service:Advanced Gaming Qos powered by TrendMicro

Port Forwarding:Virtual Server,Port Triggering, UPnP, DMZ

Dynamic DNS:DynDns, Comexe, NO-IP

VPN Pass-Through:PPTP, L2TP, IPSec Passthrough

Access Control:Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security:DoS, SPI Firewall, IP Address Filter/MAC

Address Filter/Domain Filter, IP and MAC Address Binding

USB Sharing:Support Samba(Storage)/FTP Server/Media

Server/Printer Server

Management:Access Control, Local Management, Remote

Management

Guest Network: 2.4GHz guest network × 1, 5GHz guest

network × 1

OTHERS:

Certification:CE, FCC,IC, RoHS

System Requirements:Internet Explorer 11+, Firefox 12.0+,

Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled

browser

Environment:Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Manufacturer: TP-Link



#04686

Net Price:
104,00 EUR
Unit: pcs

3G/4G Wireless AC1200 Router, 1200Mbps (TP-Link Archer MR400)

- Shares your 4G LTE network with multiple Wi-Fi devices and enjoy download speeds of up to 150Mbps
- Powerful, integrated antennas provide stable wireless connections and better coverage
- Requires no configuration, just insert a SIM card and turn it on to enjoy a fast wireless connection
- Creates simultaneous dual band Wi-Fi networks, with maximum speeds of up to 300Mbps on the 2.4GHz band and 867Mbps on the 5GHz band
- Offers options and flexibility with the LAN/WAN port, allowing you to choose your connection type

HARDWARE FEATURES:

Interface: 1 10/100Mbps LAN/WAN Port, 3 10/100Mbps LAN Ports, 1 SIM Card Slot

Button:WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button

External Power Supply:12VDC/1A

Dimensions (W x D x H):7.95 x 5.71 x 1.34 in. (202 x 145 x 34 mm)

Antenna Type: 3 Internal Wi-Fi Antennas, , 2 Detachable

External 4G LTE Antennas

WIRELESS FEATURES:

Wireless Standards:IEEE 802.11ac/n/a, IEEE 802.11g, IEEE 802.11b

Frequency:2.4GHz and 5GHz

EIRP:<20dBm, <23dBm(5GHz)

Signal Rate: 300Mbps at 2.4GHz, 867Mbps at 5GHz

Wireless Security:Support 64/128 bit WEP,

WPA-PSK/WPA2-PSK, Wireless MAC Filtering

SOFTWARE FEATURES:

Security:NAT Firewall, SPI Firewall, MAC / IP / Packet /

Application / URL Filtering, Denial of Service(DoS), SYN

Flooding, Ping of Death

Operating Modes: 3G/4G Router, Wireless Router

WAN Type: Dynamic IP/Static IP/PPPoE/PPTP(Dual

Access)/L2TP(Dual Access)

Management: Access Control, Local Management, Remote

Management

DHCP: Server, Client, DHCP Client List, Address Reservation

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS: DynDns, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec

Access Control: Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security: DoS, SPI Firewall, IP Address Filter/Domain

Filter, IP and MAC Address Binding

Protocols: Supports IPv4 and IPv6

Guest Network: 2.4GHz guest network x 1, 5GHz guest

network x 1

IPSec VPN: Supports up to 10 IPSec VPN tunnels

Network Type: 4G FDD-LTE Cat4

(800/900/1800/2100/2600MHz), TDD-LTE (2300/2600MHz),

3G DC-HSPA+/HSPA+/HSPA/UMTS (900/2100MHz), 2G

EDGE/GPRS/GSM (850/900/1800/1900MHz)

OTHERS:

Certification:CE, FCC, RoHS

Package Contents:3G/4G Wireless AC Router, 1 Antenna,

RJ45 Ethernet Cable, Power Adapter, Quick Installation

Guide, Micro to Standard SIM Card Adapter, Nano to

Standard SIM Card Adapter

System Requirements:Microsoft WindowsC 98SE, NT,

2000, XP, VistaTM or Windows 7/8/8.1, MACC OS,

NetWareC, UNIXC or Linux.

Environment:Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing



#04604

Net Price:
97,60 EUR
Unit: pcs

3G/4G Wireless AC750 Router, 750Mbps (TP-Link Archer MR200)

- Shares your 4G LTE network with multiple Wi-Fi devices and enjoy download speeds of up to 150Mbps
- Powerful, integrated antennas provide stable wireless connections and better coverage
- Requires no configuration, just insert a SIM card and turn it on to enjoy a fast wireless connection
- Creates simultaneous dual band Wi-Fi networks, with maximum speeds of up to 300Mbps on the 2.4GHz band and 433Mbps on the 5GHz band
- Offers options and flexibility with the LAN/WAN port, allowing you to choose your connection type

HARDWARE FEATURES:

Interface: 1 10/100Mbps LAN/WAN Port, 3 10/100Mbps LAN Ports, 1 SIM Card Slot

Button:WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button

External Power Supply:12VDC/1A

Dimensions (W x D x H):7.95 x 5.55 x 1.32 in. (202 x 141 x 33.6 mm)

Antenna Type: 3 Internal Wi-Fi Antennas, , 2 Detachable

External 4G LTE Antennas

WIRELESS FEATURES:

Wireless Standards:IEEE 802.11ac/n/a, IEEE 802.11g, IEEE 802.11b

Frequency:2.4GHz and 5GHz

EIRP:<20dBm, <23dBm(5GHz)

Signal Rate: 300Mbps at 2.4GHz, 433Mbps at 5GHz

Wireless Security:Support 64/128 bit WEP,

WPA-PSK/WPA2-PSK, Wireless MAC Filtering

SOFTWARE FEATURES:

Security:NAT Firewall, SPI Firewall, MAC / IP / Packet /

Application / URL Filtering, Denial of Service(DoS), SYN

Flooding, Ping of Death

Operating Modes: 3G/4G Router, Wireless Router

WAN Type: Dynamic IP/Static IP/PPPoE/PPTP(Dual

Access)/L2TP(Dual Access)

Management: Access Control, Local Management, Remote

Management

DHCP: Server, Client, DHCP Client List, Address Reservation

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS: DynDns, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec

Access Control: Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security: DoS, SPI Firewall, IP Address Filter/Domain

Filter, IP and MAC Address Binding

Protocols: Supports IPv4 and IPv6

Guest Network: 2.4GHz guest network x 1, 5GHz guest

network x 1

IPSec VPN: Supports up to 10 IPSec VPN tunnels

Network Type: 4G FDD-LTE Cat4

(800/900/1800/2100/2600MHz), TDD-LTE (2300/2600MHz),

3G DC-HSPA+/HSPA+/HSPA/UMTS (900/2100MHz), 2G

EDGE/GPRS/GSM (850/900/1800/1900MHz)

OTHERS:

Certification:CE, FCC, RoHS

Package Contents:3G/4G Wireless AC Router, RJ45 Ethernet

Cable, Power Adapter, Quick Installation Guide, Micro to

Standard SIM Card Adapter, Nano to Standard SIM Card

Adapter

System Requirements:Microsoft WindowsC 98SE, NT,

2000, XP, VistaTM or Windows 7/8/8.1, MACC OS,

NetWareC, UNIXC or Linux.

Environment:Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing



#09005

Net Price:
144,00 EUR
Unit: pcs

3G/4G+ Cat6 Wireless AC1200 Router, 1200Mbps (TP-Link Archer MR600)

- TP-Link's First 4G+ Router - supports 4G+ Cat6 to boost the data speeds of up to 300 Mbps
- Full Gigabit Ports - provides reliable wired connections for bandwidth-intensive devices such as game consoles and STB
- Plug a SIM card and play - no configurations needed, compatibility of SIM cards in 100+ countries are assured by years of field tests
- Better Signal for Connections Everywhere - enjoy stable and efficient connections to every device thanks to the two external LTE antennas
- Wi-Fi router mode - plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection
- Supports TP-Link OneMesh™ - co-works with TP-Link OneMesh products to create a flexible and cost-efficient Mesh network

HARDWARE FEATURES:

Interface: 1 10/100/1000Mbps LAN/WAN Port, 3 10/100/1000Mbps LAN Ports, 1 SIM Card Slot
Button: WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button
External Power Supply: 12VDC/1.5A
Dimensions (W x D x H): 9.0x6.3x1.5 in (229x160x37 mm)
Antenna Type: 3 Internal Wi-Fi Antennas, 2 Detachable External 4G LTE Antennas

WIRELESS FEATURES:

Wireless Standards: IEEE 802.11ac/n/a, IEEE 802.11g, IEEE 802.11b

Frequency: 2.4GHz and 5GHz

EIRP: <20dBm, <23dBm(5GHz)

Signal Rate: 300Mbps at 2.4GHz, 867Mbps at 5GHz

Wireless Security: Support 64/128 bit WEP,

WPA-PSK/WPA2-PSK, Wireless MAC Filtering

SOFTWARE FEATURES:

Security: NAT Firewall, SPI Firewall, MAC / IP / Packet /

Application / URL Filtering, Denial of Service(DoS), SYN

Flooding, Ping of Death

Operating Modes: 3G/4G Router, Wireless Router

WAN Type: Dynamic IP/Static IP/PPPoE/PTTP(Dual

Access)/L2TP(Dual Access)

Management: Access Control, Local Management, Remote

Management

DHCP: Server, Client, DHCP Client List, Address Reservation

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS: DynDns, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec

Access Control: Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security: DoS, SPI Firewall, IP Address Filter/Domain

Filter, IP and MAC Address Binding

Protocols: Supports IPv4 and IPv6

Guest Network: 2.4GHz guest network x 1, 5GHz guest

network x 1

IPSec VPN: Supports up to 10 IPSec VPN tunnels

Network Type: 4G FDD-LTE B1/B3/B5/B7/B8/B20/B28

(2100/1800/850/2600/900/800/700MHz), TDD-LTE

B38/B40/B41 (2600/2300/2500MHz), 3G

DC-HSPA+/HSPA/UMTS B1/B5/B8 (2100/850/900MHz)

OTHERS:

Certification: CE, FCC, RoHS

Package Contents: 4G Wireless AC Router, 1 Antenna, RJ45

Ethernet Cable, Power Adapter, Quick Installation Guide

System Requirements: Microsoft Windows 98SE, NT,

2000, XP, Vista™ or Windows 7/8/8.1/10, MAC OS,

NetWareC, UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing



#06237

Net Price:
238,00 EUR
Unit: pcs

4000Mbps Wireless Gigabit Router Tri-band AC4000, MU-MIMO (TP-Link Archer C4000)

- Run every connection at top speed with a powerful 1.8 GHz quad-core CPU
- AC4000 tri-band WiFi delivers up to 1625 Mbps on each 5 GHz band and 750 Mbps on the 2.4 GHz band
- Far-reaching coverage with RangeBoost and beamforming technology for maximum coverage and reliability
- Connect more devices and maximize performance with Multi-User MIMO, Airtime Fairness and Smart Connect
- Protect your network from intruders, viruses and malware with advanced WiFi encryption and comprehensive antivirus security
- Manage, limit and monitor internet use with rich controls that let you customize WiFi access for every person and device
- Double wired connection speeds from 1 Gbps to 2 Gbps with Link Aggregation
- Set up your WiFi in minutes and manage your network through the TP-Link Tether app

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE

802.11b/g/n 2.4GHz

Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps

WAN Port, 1 USB 3.0 Port, 1 USB 2.0 Port

Button: WPS/Reset Button, Wireless On/Off Button, Power

On/Off Button, LED On/Off

Power Supply: 100-240V 50/60Hz

Dimensions (W X D X H): 200 x 200 x 38mm (7.9 x 7.9 x 1.5 in.)

Antenna: 6

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz

Signal Rate: 750Mb/s @ 2.4GHz, 1625Mb/s @ 5GHz,

1625Mb/s @ 5GHz

Wireless Functions: Enable/Disable Wireless Radio, WMM,

Wireless Statistics

Wireless Security: 64/128-bit WEP, WPA/WPA2,

WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE, PPTP (Dual

Access)/L2TP (Dual Access)/BigPond

DHCP: Server, Client, DHCP Client List, Address Reservation,

DHCP relay

Quality of Service: WMM, Bandwidth Control

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS: DynDns, Comex, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec Passthrough

Access Control: Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC

Address Filter/Domain Filter, IP and MAC Address Binding

USB Sharing: Support Samba(Storage)/FTP Server/Media

Server/Printer Server

Management: Access Control, Local Management, Remote

Management

Guest Network: 2.4GHz guest network x 1, 5GHz guest

network x 2

OTHERS:

Certification: CE, FCC, IC, RoHS

System Requirements: Microsoft Windows XP, Vista™,

Windows 7 or Windows 8, MAC OS, NetWareC, UNIX or

Linux.

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Manufacturer: TP-Link

NEW



#09184

Net Price:
108,00 EUR
Unit: pcs

5400Mbps Wireless Gigabit Router Dual-band AX5400, MU-MIMO (TP-Link Archer AX72)

- Gigabit WiFi for 8K Streaming - 5400 Mbps WiFi for faster browsing, streamings, and downloading, all at the same time.
- Fully Featured Wi-Fi 6 - Equips with the top structure of 4T4R and HE160 on the 5 GHz band to enable 4.8 Gbps ultra-fast connection.
- Connect 100+ Devices - Supports MU-MIMO and OFDMA to reduce congestion and quadruple the average throughput.
- Extensive Coverage - 6x antennas and Beamforming ensure broad coverage.
- HomeShield - TP-Link's premium security services keep your home network safe with cutting-edge features for network and IoT protection.
- More Vents, Less Heat - Improved vents area unleash the full power of the whole machine.
- USB Sharing - 1x USB 3.0 port enables easy media sharing and private cloud building.
- Easy Setup - Set up the router in minutes with Tether app.

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE

802.11ax/b/g/n 2.4GHz, Wi-Fi 6

Interface: 4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps

WAN Port, 1 USB 3.0 Port

Button: WPS/Reset Button, Wireless On/Off Button, Power

On/off Button, LED On/Off

Power Supply: 12V/2.5A

Dimensions (W X D X H): 10.7 x 5.8 x 1.9 in (272.5 x 147.2 x 49.2 mm)

Antenna: 6 x External Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz

Signal Rate: 5 GHz@ 4804 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions: Enable/Disable Wireless Radio, Guest

Network, DFS, MU-MIMO, OFDMA

Wireless Security: 64/128-bit WEP, WPA/WPA2,

WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE, PPTP (Dual

Access)/L2TP (Dual Access)/BigPond

DHCP: Server, Client, DHCP Client List, Address Reservation,

DHCP relay

Quality of Service: Advanced Gaming Qos powered by

TrendMicro

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS: DynDns, Comex, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec Passthrough

Access Control: Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC

Address Filter/Domain Filter, IP and MAC Address Binding

USB Sharing: Support Samba(Storage)/FTP Server/Media

Server/Printer Server

Management: Access Control, Local Management, Remote

Management

Guest Network: 2.4GHz guest network x 1, 5GHz guest

network x 1

USB Support

Supported Partition Formats: NTFS, exFAT, HFS+, FAT32

Supported Functions: Apple Time Machine, FTP Server,

Media Server, Samba Server

OTHERS:

Certification: CE, FCC, IC, RoHS

System Requirements: Internet Explorer 11+, Firefox 12.0+,

Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled

browser

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Manufacturer: TP-Link



#09076

Net Price:
113,00 EUR
Unit: pcs

5400Mbps Wireless Gigabit Router Dual-band AX5400, MU-MIMO (TP-Link Archer AX73)

- Gigabit WiFi for 8K Streaming - 5400 Mbps WiFi for faster browsing, streamings, and downloading, all at the same time.
- Fully Featured Wi-Fi 6 - Equips with the top structure of 4T4R and HE160 on the 5 GHz band to enable 4.8 Gbps ultra-fast connection.
- Connect 200+ Devices - Supports MU-MIMO and OFDMA to reduce congestion and quadruple the average throughput.
- Extensive Coverage - 6x antennas and Beamforming ensure broad coverage.
- HomeShield - TP-Link's premium security services keep your home network safe with cutting-edge features for network and IoT protection.
- More Vents, Less Heat - Improved vents area unleash the full power of the whole machine.
- USB Sharing - 1x USB 3.0 port enables easy media sharing and private cloud building.
- Easy Setup - Set up the router in minutes with Tether app.

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6
Interface: 4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port, 1 USB 3.0 Port
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off
Power Supply: 12V/2.5A
Dimensions (W X D X H): 10.7 x 5.8 x 1.9 in (272.5 x 147.2 x 49.2 mm)

Antenna: 6 x External Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5 GHz@ 4804 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions: Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA

Wireless Security: 64/128-bit WEP, WPA/WPA2,

WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: Advanced Gaming QoS powered by TrendMicro

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comex, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec Passthrough

Access Control: Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC

Address Filter/Domain Filter, IP and MAC Address Binding

USB Sharing: Support Samba(Storage)/FTP Server/Media

Server/Printer Server

Management: Access Control, Local Management, Remote

Management

Guest Network: 2.4GHz guest network x 1, 5GHz guest

network x 1

USB Support

Supported Partition Formats: NTFS, exFAT, HFS+, FAT32

Supported Functions: Apple Time Machine, FTP Server,

Media Server, Samba Server

OTHERS:

Certification: CE, FCC, IC, RoHS

System Requirements: Microsoft Windows XP, Vista™,

Windows 7 or Windows 8/8.1/10, MAC OS, NetWareC,

UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Manufacturer: TP-Link



#09003

Net Price:
288,00 EUR
Unit: pcs

6000Mbps Wireless Gigabit Router Dual-band AX6000, MU-MIMO (TP-Link Archer AX6000)

- Blazing Speed - AX6000 Dual-Band Wi-Fi speed boosted by 1024QAM deliver astonishing wireless speed up to 5952 Mbps: 4804 Mbps (5 GHz) and 1148 Mbps (2.4 GHz)
- Ultra Connectivity - 1 x 2.5 Gbps WAN port, 8 x Gigabit LAN ports, and 2 x USB 3.0 in Type A and Type C
- Highly Efficient - OFDMA increases average throughput by 4x in high-density scenarios, compared with an 802.11ac standard router. Downlink and uplink MU-MIMO are both supported.
- Powerful Processing - 1.8 GHz Quad-Core CPU and 2 coprocessors eradicate latency and deliver stable performance
- Intelligent Connection - Band Steering directs clients to the less congested band and Airtime Fairness optimizes the time usage
- Security System Built-In - TP-Link HomeCare™ provides the whole network with advanced antimalware service powered by Trend Micro™, delivering Antivirus, Parental Controls and QoS
- Easy Setup - Link to your router via Bluetooth and set it up in minutes with the powerful Tether app

HARDWARE FEATURES:

Memory: 1 GB RAM and 128 MB Flash
Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz

Interface: 4 10/100/1000Mbps LAN Ports, 1 2.5 G/2G/1G/100Mbps WAN Port, 1 USB-A 3.0 Port + 1 USB-C 3.0 Port

Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off
Power Supply: 12V/4A

Dimensions (W X D X H): 10.3x10.3x2.4in

(261.2x261.2x60.2mm)

Antenna: 8 x External Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5 GHz@ 4804 Mbps (802.11ax), 2.4 GHz@ 1148 Mbps (802.11ax)

Wireless Functions: Enable/Disable Wireless Radio, Guest

Network, DFS, MU-MIMO, OFDMA

Wireless Security: 64/128-bit WEP, WPA/WPA2,

WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE, PPTP (Dual Access)/L2TP (Dual Access)/BigPond

DHCP: Server, Client, DHCP Client List, Address Reservation,

DHCP relay

Quality of Service: Advanced Gaming QoS powered by

TrendMicro

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS: DynDns, Comex, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec Passthrough

Access Control: Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC

Address Filter/Domain Filter, IP and MAC Address Binding

USB Sharing: Support Samba(Storage)/FTP Server/Media

Server/Printer Server

Management: Access Control, Local Management, Remote

Management

Guest Network: 2.4GHz guest network x 1, 5GHz guest

network x 1

OTHERS:

Certification: CE, FCC, IC, RoHS

System Requirements: Microsoft Windows XP, Vista™,

Windows 7 or Windows 8/8.1/10, MAC OS, NetWareC,

UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Manufacturer: TP-Link



#09077

Net Price:
248,00 EUR
Unit: pcs

6600Mbps Wireless Gigabit Router Tri-band AX6600, MU-MIMO (TP-Link Archer AX90)

- Faster AX6600 Tri-Band Wi-Fi - 4804 Mbps (5 GHz) + 1201 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Ultra Connectivity - 1 x 2.5 Gbps WAN/LAN port + 1 x 1 Gbps WAN/LAN port + 3 x Gigabit LAN ports and two USB ports ensure max flexibility and boosted throughput.
- Maximized Coverage - Eight high-gain antennas equipped with Beamforming ensure vast coverage.
- More Devices with Less Lag - OFDMA and MU-MIMO technology deliver data to multiple devices, simultaneously.
- TP-Link HomeShield - Enhanced security defends against the latest cyber threats.
- Powerful CPU - 1.5 GHz quad-core processor ensures fast transmission speeds and smooth operation of numerous devices and applications.
- Refined Security-WPA3 reinforces Wi-Fi encryption for improved security.

HARDWARE FEATURES:

Processor: 1.5 GHz 64 bit Quad-Core CPU
Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6

Interface: 3 10/100/1000Mbps LAN Ports, 1 2.5G/1G/100Mbps WAN Port, 1 USB 3.0 Port, 1 USB 2.0 Port

Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off
Power Supply: 12V/3.3A

Dimensions (W X D X H): 12.2 x 8.1 x 6.8 in (311 x 207 x 174 mm)

Antenna: 8x High-Performance External Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5 GHz@ 4804 Mbps (802.11ax), 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions: Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA

Wireless Security: 64/128-bit WEP, WPA/WPA2,

WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE, PPTP (Dual Access)/L2TP (Dual Access)/BigPond

DHCP: Server, Client, DHCP Client List, Address Reservation,

DHCP relay

Quality of Service: Advanced Gaming QoS powered by

TrendMicro

Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS: DynDns, Comex, NO-IP

VPN Pass-Through: PPTP, L2TP, IPSec Passthrough

Access Control: Parental Control, Local Management Control,

Host List, Access Schedule, Rule Management

Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC

Address Filter/Domain Filter, IP and MAC Address Binding

USB Sharing: Support Samba(Storage)/FTP Server/Media

Server/Printer Server

Management: Access Control, Local Management, Remote

Management

Guest Network: 2.4GHz guest network x 1, 5GHz guest

network x 1

OTHERS:

Certification: CE, FCC, IC, RoHS

System Requirements: Microsoft Windows XP, Vista™,

Windows 7 or Windows 8/8.1/10, MAC OS, NetWareC,

UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Manufacturer: TP-Link



#09081

Net Price:
271,00 EUR
Unit: pcs

6600Mbps Wireless Gigabit Router Tri-band AX6600, MU-MIMO (TP-Link Archer GX90)

- Game Band - Tri-Band structure provides a 4.8 Gbps Game Band exclusive for your gaming rigs and bings pure immersion.
- Game Accelerator - Detect and optimize gaming streams, to ensure your gaming stays immersive.
- Game Statistics - Real-time latency, game duration and network resource allocation in a glance with fine-tuned UI.
- Game Protector - Keep your accounts and documents safe with HomeCareTM security system.
- Expansive Coverage - 8 antennas, Beamforming, high-power FEM, 4T4R combine to deliver WiFi coverage up to a 4-bedroom house.
- 2.5 Gbps Wired Connection - Unleash the potential of your next-level bandwidth network with a 2.5 Gbps WAN/LAN port.
- Powerful Processing - 1.5 GHz Quad-Core CPU ensure your network performance always at peak run.
- Easy Setup - Sset it up in minutes with the powerful Tether app.

HARDWARE FEATURES:

Processor: 1.5 GHz 64 bit Quad-Core CPU
Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6
Interface: 3 10/100/1000Mbps LAN Ports, 1 2.5G/1G/100Mbps WAN Port, 1 USB 3.0 Port, 1 USB 2.0 Port
Button: WPS/Reset Button, Wireless On/Off Button, Power On/off Button, LED On/Off
Power Supply: 12V/5A
Dimensions (W X D X H): 8.3 x 8.3 x 2.0 in (212 x 212 x 51.8 mm)

Antenna: 8x High-Performance External Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5 GHz@ 4804 Mbps (802.11ax), 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)
Wireless Functions: Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: Advanced Gaming Qos powered by TrendMicro
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comexe, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec Passthrough
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1

Game Center: Game Accelerator - Detects and optimizes gaming streams to keep latency as low as possible, Game Statistics - Check real-time latency, system utilization, and game duration on a redesigned dashboard to tweak every detail, Game Protector - Keep your accounts and system safe with HomeCareTM antivirus protection

OTHERS:

Certification: CE, FCC, IC, RoHS
System Requirements: Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#06240

Net Price:
28,20 EUR
Unit: pcs

750Mbps Wireless AC Nano Router (TP-Link TL-WR902AC)

- Travel-Sized Design - Conveniently small and light to pack and take on the road, creating Wi-Fi network via Ethernet or WISP
- Dual Band AC750 Wi-Fi - Strong, fast connection for HD streaming on all your devices
- One Switch for Multiple Modes - Perfect for Wi-Fi at home, your hotel room or on the road
- Flexible Power - Micro USB port to an adapter, portable charger or laptop
- Versatile USB - For file sharing or providing power supply to mobile devices

HARDWARE FEATURES:

Interface: 1 10/100Mbps WAN/LAN Port, 1 USB Port, 1 Reset Button, 1 Mode Switch, 1 WPS Button
Wireless Standards: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Dimensions (W x D x H): 74x67x22mm (2,91x2,64x0,87 in.)
External Power Supply: 5V/2A
Antenna Type: On-Board

WIRELESS FEATURES:

Frequency: 2.4GHz and 5GHz
Signal Rate: 5GHz - Up to 433Mbps (Only with 11AC Wireless Adapter); Up to 150Mbps with 11N Wireless Adapter 2.4GHz - Up to 300Mbps
EIRP: <20dBm(2.4GHz), <23dBm(5GHz)
Reception Sensitivity: 11a 54M -76dBm; 11ac VHT20 MCS8 -70dBm; 11ac VHT40 MCS9 -65.5dBm; 11ac VHT80 MCS9 -61.5dBm; 2.4GHz 11g 54M -76dBm; 11n HT20 MCS7 -74dBm; 11n HT40 MCS7 -71dBm
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security: 64/128 WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP/L2TP
DHCP: Server, Client, DHCP Client List, Address Reservation
Quality of Service: WMM, Bandwidth Control
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comexe, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec (ESP Head)
Access Control: Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
Management: Access Control, Local Management, Remote Management
Protocols: Supports IPv4
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1

OTHERS:

Certification: CE, FCC, RoHS
Package Contents: TL-WR902AC, Power Adapter, USB Cable, Ethernet cable, Quick Installation Guide
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7/8/8.1/10, MAC OS, NetWare, UNIX or Linux
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing



#04572

Net Price:
22,30 EUR
Unit: pcs

750Mbps Wireless Router Dual-band AC750 (TP-Link Archer C20)

- Supports 802.11ac standard - the next generation of Wi-Fi
- Simultaneous 2.4GHz 300Mbps and 5GHz 433Mbps connections for 733Mbps of total available bandwidth
- 3 external antennas provide stable omnidirectional signal and superior wireless coverage

HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface: 4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button
External Power Supply: 9VDC / 0.6A
Dimensions (W X D X H): 230 x 144 x 35mm (9,1 x 5,7 x 1,4 in.)

Antenna: 3 Antennas

WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 433Mbps, 2.4GHz Up to 300Mbps
EIRP: CE <20dBm(2.4GHz), <23dBm(5GHz), FCC <30dB
Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption

SOFTWARE FEATURES:

WAN Type: Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service: WMM, Bandwidth Control
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, Comexe, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec Passthrough
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management: Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 2

OTHERS:

Certification: CE, FCC, IC, RoHS
Package Contents: Archer C20, Power supply unit, Quick Installation Guide, Ethernet Cable
System Requirements: Microsoft Windows XP, VistaTM, Windows 7 or Windows 8, MAC OS, NetWareC, UNIXC or Linux.
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.
Manufacturer: TP-Link



#09078

Net Price:
19,20 EUR
Unit: pcs

750Mbps Wireless Router Dual-band AC750 (TP-Link Archer C24)

- High-Speed Wi-Fi-AC750 dual-band is ideal for HD video streaming, high-speed downloading.
- Far-Reaching Coverage-4x antennas deliver far-reaching Wi-Fi and reliable connections.
- Multi-Mode 3 in 1-Supports Router, Access Point, and Range Extender to add flexibilities.
- Parental Controls-Manages when and how connected devices can access the internet.
- Guest Network-Provides separate access for guests while securing the host network.
- Smooth HD Streaming-Supports IGMP Proxy/Snooping, Bridge and Tag VLAN to optimize IPTV streaming.
- IPv6 Supported-Compatible with the IPv6 (the latest Internet Protocol version 6).
- Compact and Mountable-Designed to conserve space and complement any décor.

HARDWARE FEATURES:

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface:4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port
Button:WPS/Reset Button
External Power Supply: 9VDC / 0.6A
Dimensions (W X D X H): 4.5 x 4.2 x 1.0 in (115 x 106.7 x 24.3 mm)

Antenna: 4 Antennas

WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz
Signal Rate:5GHz Up to 433Mbps, 2.4GHz Up to 300Mbps
EIRP: CE <20dBm(2.4GHz), <23dBm(5GHz), FCC <30dB
Wireless Functions:Enable/Disable Wireless Radio, WMM, Wireless Statistics
Wireless Security:64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption
SOFTWARE FEATURES:
WAN Type:Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP:Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service:WMM, Bandwidth Control
Port Forwarding:Virtual Server,Port Triggering, UPnP, DMZ
Dynamic DNS:DynDns, Comexe, NO-IP
VPN Pass-Through:PPTP, L2TP, IPSec Passthrough
Access Control:Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security:DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing:Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management:Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 2

OTHERS:

Certification:CE, FCC,IC, RoHS
Package Contents:Archer C24, Power supply unit, Quick Installation Guide, Ethernet Cable
System Requirements:Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser
Environment:Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty:2 years limited warranty. Advanced replacement service is available.
Manufacturer: TP-Link



#09093

Net Price:
22,50 EUR
Unit: pcs

750Mbps Wireless Router Dual-band AC750 (TP-Link EC120-F5)

- Supports 802.11ac standard - the next generation of Wi-Fi
- Simultaneous 2.4GHz 300Mbps and 5GHz 433Mbps connections for 733Mbps of total available bandwidth
- 3 external antennas provide stable omnidirectional signal and superior wireless coverage

HARDWARE FEATURES:

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Interface:4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port
Button:WPS/Reset Button, Wireless On/Off Button, Power On/Off Button
External Power Supply: 9VDC / 0.6A
Dimensions (W X D X H): 230 x 144 x 35mm (9,1 x 5,7 x 1,4 in.)

Antenna: 3 Antennas

WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz
Signal Rate:5GHz Up to 433Mbps, 2.4GHz Up to 300Mbps
EIRP: CE <20dBm(2.4GHz), <23dBm(5GHz), FCC <30dB
Wireless Functions:Enable/Disable Wireless Radio, WMM, Wireless Statistics
Wireless Security:64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption
SOFTWARE FEATURES:

WAN Type:Dynamic IP/Static IP/PPPoE/, PPTP (Dual Access)/L2TP (Dual Access)/BigPond
DHCP:Server, Client, DHCP Client List, Address Reservation, DHCP relay
Quality of Service:WMM, Bandwidth Control
Port Forwarding:Virtual Server,Port Triggering, UPnP, DMZ
Dynamic DNS:DynDns, Comexe, NO-IP
VPN Pass-Through:PPTP, L2TP, IPSec Passthrough
Access Control:Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security:DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding
USB Sharing:Support Samba(Storage)/FTP Server/Media Server/Printer Server
Management:Access Control, Local Management, Remote Management
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 2
OTHERS:
Certification:CE, FCC,IC, RoHS
Package Contents:EC120-F5, Power supply unit, Quick Installation Guide, Ethernet Cable
System Requirements:Microsoft Windows XP, VistaTM, Windows 7/8/10, MAC OS, NetWareC, UNIX or Linux.
Environment:Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#09032

Net Price:
28,30 EUR
Unit: pcs

1200Mbps Wireless Range Extender Mesh, AC1200 (TP-Link RE300)

- Extends dual-band Wi-Fi across your home to eliminate Wi-Fi dead zones.
- Creates a Mesh network by connecting to a OneMesh router for seamless whole-home coverage.
- Operates over both the 2.4 GHz band (300 Mbps) and 5 GHz band (867 Mbps) for more stable wireless experience.
- Smart signal indicator helps to find the best location for optimal Wi-Fi coverage by showing the signal strength.
- Push the WPS button to easily set up a Mesh network you can uniformly manage from the Tether app or Web UI.
- Works with any Wi-Fi router or wireless access point.

HARDWARE FEATURES:

Plug Type: EU
Button:WPS Button, Reset Button
Power Consumption: About 7.3W
Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b, IEEE 802.11a
Dimensions (W x D x H): 4.9 x 2.7 x 2.0 in (124 x 69 x 52 mm)

WIRELESS FEATURES

Frequency:2.4GHz & 5GHz
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps
EIRP:<17dBm(2.4GHz) <17dBm(5GHz)
Reception Sensitivity:5GHz 11a 6Mbps -91dBm@10% PER, 11a 54Mbps -74dBm@10% PER, 11ac HT20 mcs8 -68dBm@10% PER, 11ac HT40 mcs9 -63dBm@10% PER, 11ac HT80 mcs9 -59dBm@10% PER, 2.4GHz 11g 54M -79dBm@10% PER, 11n HT20 mcs7 -77dBm@10% PER, 11n HT40 mcs7 -74dBm@10% PER
Wireless Modes:Range Extender
Wireless Functions: WMM (Wi-Fi Multimedia), Wireless Statistic, Domain Login Function
Wireless Security: 64/128-bit WEP, WPA-PSK / WPA2-PSK
OTHERS
Certification:CE, FCC, RoHS
Package Contents:RE300, Resource CD, Quick Installation Guide
System Requirements:Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7,8,10, MAC OS, NetWare, UNIX or Linux.
Environment:Operating Temperature 0°~30° (32°~86°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#09107

Net Price:
17,80 EUR
Unit: pcs

1200Mbps Wireless Range Extender, AC1200 (TP-Link Mercusys ME30)

- Eliminate WiFi Dead Zones - Boosts WiFi signals to previously unreachable or hard-to-wire areas flawlessly
- AC1200 Dual Band WiFi - Keep your whole home connected with strong WiFi expansion at a combined speed of up to 1.2 Gbps
- Easy One-Touch Setup - Simply press the WPS button to expand your WiFi coverage in seconds
- Signal Indicator - Multicolor LED helps you find the right location for your range extender for the best WiFi extension
- Fast 10/100 Mbps Port - Provides speedy wired connections for PCs, IPTVs, and game consoles
- Works with Any Router or Wireless Access Point

HARDWARE FEATURES:

Ports: 1 * 10/100M Ethernet Port (RJ45)
Plug Type: EU

Button: WPS Button, Reset Button

Power Consumption: About 9.2W

Wireless Standards: IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions (W x D x H): 112 x 84,7 x 39 mm

Antenna Type: 2 x external

WIRELESS FEATURES

Frequency: 2.4GHz & 5GHz

Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps

EIRP: < 20 dBm

Wireless Security: WPA-PSK/WPA2-PSK

OTHERS

Certification: CE, RoHS

Package Contents: ME30, Quick Installation Guide

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty: 2 years limited warranty. Advanced replacement service is available.



#04585

Net Price:
28,30 EUR
Unit: pcs

1200Mbps Wireless Range Extender, AC1200 (TP-Link RE305)

- Brings Wi-Fi dead zone to life with strong Wi-Fi expansion at combined speed of up to 1.2Gbps
- Operates over both the 2.4GHz band(300Mbps) and 5GHz band(867Mbps) for more stable wireless experience
- Intelligent signal light helps to find the best location for optimal Wi-Fi coverage by showing the signal strength
- Works with any Wi-Fi router or wireless access point

HARDWARE FEATURES:

Ports: 1 * 10/100M Ethernet Port (RJ45)

Plug Type: EU

Button: WPS Button, Reset Button

Power Consumption: About 7.3W

Wireless Standards: IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions (W x D x H): 3.1x3.0x3.0 in. (80x78x77mm)

Antenna Type: 2 x external

WIRELESS FEATURES

Frequency: 2.4GHz & 5GHz

Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps

EIRP: <17dBm(2.4GHz) <17dBm(5GHz)

Reception Sensitivity: 5GHz 11a 6Mbps -91dBm@10% PER,

11a 54Mbps -74dBm@10% PER, 11ac HT20 mcs8

-68dBm@10% PER, 11ac HT40 mcs9 -63dBm@10% PER,

11ac HT80 mcs9 -59dBm@10% PER, 2.4GHz 11g 54M

-79dBm@10% PER, 11n HT20 mcs7 -77dBm@10% PER,

11n HT40 mcs7 -74dBm@10% PER

Wireless Modes: Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless

Statistic, Domain Login Function

Wireless Security: 64/128-bit WEP, WPA-PSK / WPA2-PSK

OTHERS

Certification: CE, FCC, RoHS

Package Contents: RE305, Resource CD, Quick Installation

Guide, RJ-45 Ethernet Cable

System Requirements: Microsoft Windows 98SE, NT, 2000,

XP, VistaTM or Windows 7, 8, 10, MAC OS, NetWare, UNIX or

Linux.

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty: 2 years limited warranty. Advanced replacement service is available.

Manufacturer: TP-Link



#09063

Net Price:
75,20 EUR
Unit: pcs

1500Mbps Wireless Range Extender, AX1500 (TP-Link RE505X)

- RE505X comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity, and reduced network congestion.
- Creates a Mesh network by connecting to a OneMesh router for seamless whole-home coverage.
- Gigabit Ethernet Port - Provide faster-wired connections to smart TVs, computers and gaming consoles
- Intelligent Signal Light - Helps to determine the best location for optimal Wi-Fi coverage by indicating the signal strength in the current placement
- AP Mode - create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
- TP-LINK Tether App - Easily access and manage your network using any iOS or Android mobile device
- Ultimate Compatibility - Extend the range of any Wi-Fi router or wireless access point

HARDWARE FEATURES:

Ports: 1 Gigabit Ethernet Port

Plug Type: EU

Button: Reset Button, WPS Button

Power Consumption: About 10W

Wireless Standards: IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions (W x D x H): 74,0 x 46 x 124,8 mm

Antenna Type: 2 x External Antennas

WIRELESS FEATURES

Frequency: 2.4GHz & 5GHz

Signal Rate: 300 Mbps at 2.4GHz, 1200 Mbps at 5GHz

EIRP: CE 2.4 GHz <= 20 dBm, 5 GHz <= 30 dBm

Wireless Modes: Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless

Statistic, Domain Login Function

Wireless Security: 64/128/152-bit WEP, WPA-PSK /

WPA2-PSK

OTHERS

Certification: CE, FCC, RoHS

Package Contents: RE505X, Quick Installation Guide

System Requirements: Microsoft Windows 98SE, NT, 2000,

XP, VistaTM or Windows 7, 8, 10, MAC OS, NetWare, UNIX or

Linux.

Environment: Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty: 2 years limited warranty. Advanced replacement service is available.

Manufacturer: TP-Link



#04582

Net Price:
59,50 EUR
Unit: pcs

**1750Mbps Wireless Range Extender, AC1750
(TP-Link RE450)**

- Expand Wi-Fi Network for Ultimate Performance
- Expanded 450Mbps on 2.4GHz + 1300Mbps on 5GHz totals 1750Mbps Wi-Fi speeds
- Three adjustable external antennas provide optimal Wi-Fi coverage and reliable connections
- Gigabit Ethernet port acts as a wireless adapter to connect a wired device to your network at gigabit speed
- Intelligent signal light helps to find the best location for optimal Wi-Fi coverage by showing the signal strength
- Works with any Wi-Fi router or wireless access point

HARDWARE FEATURES:

Ports: 1 * 10/100/1000M Ethernet Port (RJ45)
Plug Type: EU
Button: RE (Range Extender) Button, Reset Button, LED Button, Power Button
Power Consumption: About 9W
Wireless Standards: IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensions (W x D x H): 6.4 x 3.0 x 2.6 in. (163 x 76.4 x 66.5mm)

Antenna Type: 3 x external

WIRELESS FEATURES

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 450Mbps
EIRP: <20dBm(2.4GHz) <23dBm(5GHz)
Reception Sensitivity: 5GHz 11a 6Mbps -93dBm@10% PER, 11a 54Mbps -76dBm@10% PER, 11ac HT20 mcs8 -68dBm@10% PER, 11ac HT40 mcs9 -64dBm@10% PER, 11ac HT80 mcs9 -61dBm@10% PER, 2.4GHz 11g 54M -77dBm@10% PER, 11n HT20 mcs7 -73dBm@10% PER, 11n HT40 mcs7 -70dBm@10% PER

Wireless Modes: Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless Statistic, Domain Login Function
Wireless Security: 64/128-bit WEP, WPA-PSK / WPA2-PSK
OTHERS

Certification: CE, FCC, RoHS

Package Contents: RE450, Resource CD, Quick Installation Guide, RJ-45 Ethernet Cable
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7, 8, MAC OS, NetWare, UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.
Manufacturer: TP-Link



#09128

Net Price:
86,00 EUR
Unit: pcs

**1800Mbps Wireless Range Extender, AX1800
(TP-Link RE605X)**

- RE605X comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity, and reduced network congestion.
- Creates a Mesh network by connecting to a OneMesh router for seamless whole-home coverage.
- Gigabit Ethernet Port - Provide faster-wired connections to smart TVs, computers and gaming consoles
- Intelligent Signal Light - Helps to determine the best location for optimal Wi-Fi coverage by indicating the signal strength in the current placement
- AP Mode - create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
- TP-LINK Tether App - Easily access and manage your network using any iOS or Android mobile device
- Ultimate Compatibility - Extend the range of any Wi-Fi router or wireless access point

HARDWARE FEATURES:

Ports: 1 Gigabit Ethernet Port
Plug Type: EU
Button: Reset Button, WPS Button
Power Consumption: About 10W
Wireless Standards: IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensions (W x D x H): 74.0 x 46 x 124.8 mm

Antenna Type: 2 x External Antennas

WIRELESS FEATURES

Frequency: 2.4GHz & 5GHz
Signal Rate: 574 Mbps at 2.4GHz, 1201 Mbps at 5GHz
EIRP: CE 2.4 GHz <= 15 dBm, 5 GHz <= 21 dBm
Wireless Modes: Range Extender
Wireless Functions: WMM (Wi-Fi Multimedia), Wireless Statistic, Domain Login Function
Wireless Security: 64/128/152-bit WEP, WPA-PSK / WPA2-PSK
OTHERS

Certification: CE, FCC, RoHS

Package Contents: RE605X, Quick Installation Guide
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7, 8, 10, MAC OS, NetWare, UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#09127

Net Price:
62,40 EUR
Unit: pcs

**1900Mbps Wireless Range Extender, AC1900
(TP-Link RE550)**

- Maximum Coverage - Extend Wi-Fi coverage by up to 1,115 m2 & #65288; 12,000sq. ft. & #65289;.
- AC1900 Dual Band Wi-Fi - Simultaneous 600Mbps on 2.4GHz + 1300Mbps on 5GHz
- Three Antennas - Three adjustable external antennas provide optimal Wi-Fi coverage and reliable connections
- Gigabit Ethernet port - Act as a wireless adapter to connect a wired device to your network at Gigabit speed
- Intelligent Signal Light - Help to find the best location for optimal Wi-Fi coverage by showing the signal strength
- AP Mode - Create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
- TP-LINK Tether App - Easily access and manage your network using any iOS or Android mobile device
- Ultimate Compatibility - Extend the range of any Wi-Fi router or wireless access point

HARDWARE FEATURES:

Ports: 1 * 10/100/1000M Ethernet Port (RJ45)
Plug Type: EU
Button: RE (Range Extender) Button, Reset Button, LED Button, Power Button
Power Consumption: About 10W
Wireless Standards: IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensions (W x D x H): 163 x 76.4 x 66.5 mm (6.4 x 3.0 x 2.6 in)

Antenna Type: 3 x external

WIRELESS FEATURES

Frequency: 2.4GHz & 5GHz
Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 600Mbps
EIRP: <20dBm(2.4GHz) <23dBm(5GHz)
Reception Sensitivity: 5GHz 11a 6Mbps -93dBm@10% PER, 11a 54Mbps -76dBm@10% PER, 11ac HT20 mcs8 -68dBm@10% PER, 11ac HT40 mcs9 -64dBm@10% PER, 11ac HT80 mcs9 -61dBm@10% PER, 2.4GHz 11g 54M -77dBm@10% PER, 11n HT20 mcs7 -73dBm@10% PER, 11n HT40 mcs7 -70dBm@10% PER
Wireless Modes: Range Extender
Wireless Functions: WMM (Wi-Fi Multimedia), Wireless Statistic, Domain Login Function
Wireless Security: 64/128-bit WEP, WPA-PSK / WPA2-PSK
OTHERS

Certification: CE, FCC, RoHS

Package Contents: RE550, Quick Installation Guide
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7, 8, 10, MAC OS, NetWare, UNIX or Linux.

Environment: Operating Temperature 0°~30° (32°~86°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Manufacturer: TP-Link



#04690

Net Price:
91,20 EUR
Unit: pcs

2533Mbps Wireless Range Extender, AC2600 (TP-Link RE650)

- Superior Extended Range - Four fixed external antennas extend Wi-Fi coverage by up to 14,000 sq. ft.
- 4-Stream for AC2600 Dual Band Wi-Fi - Simultaneous 800Mbps on 2.4GHz + 1733Mbps on 5GHz
- 4x4 MU-MIMO - Simultaneously transfers data to multiple devices for 4x faster performance
- Beamforming Technology - Send targeted Wi-Fi signal to individual devices for stronger connections
- Gigabit Ethernet Port - Provide faster wired connections to smart TVs, computers and gaming consoles
- Intelligent Signal Light - Helps to determine the best location for optimal Wi-Fi coverage by indicating the signal strength in the current placement
- AP Mode - create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
- TP-LINK Tether App - Easily access and manage your network using any iOS or Android mobile device
- Ultimate Compatibility - Extend the range of any Wi-Fi router or wireless access point

HARDWARE FEATURES:

Ports:1 * 10/100/1000M Ethernet Port (RJ45)

Plug Type: EU

Button:RE (Range Extender) Button, Reset Button, LED Button, Power Button

Power Consumption: About 12W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions (W x D x H): 6.4x 3.4 x 1.6 in. (163 x 86 x 40mm)

Antenna Type: 4 x external

WIRELESS FEATURES

Frequency:2.4GHz & 5GHz

Signal Rate: 5GHz Up to 1733Mbps, 2.4GHz Up to 800Mbps

EIRP:<20dBm(2.4GHz) <23dBm(5GHz)

Reception Sensitivity:5GHz 11a 6Mbps -96dBm@10% PER, 11a 54Mbps -78dBm@10% PER, 11ac HT20 mcs8

-69dBm@10% PER, 11ac HT40 mcs9 -66dBm@10% PER, 11ac HT80 mcs9 -63dBm@10% PER, 2.4GHz 11g 54M

-79dBm@10% PER, 11n HT20 mcs7 -77dBm@10% PER, 11n HT40 mcs7 -74dBm@10% PER

Wireless Modes:Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless

Statistic, Domain Login Function

Wireless Security: 64/128-bit WEP, WPA-PSK / WPA2-PSK

OTHERS

Certification:CE, FCC, RoHS

Package Contents:RE650, Quick Installation Guide

System Requirements:Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7,8,10, MAC OS, NetWare, UNIX or Linux.

Environment:Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty:2 years limited warranty. Advanced replacement

service is available.

Manufacturer: TP-Link



#09062

Net Price:
21,10 EUR
Unit: pcs

750Mbps Wireless Range Extender, AC750 (TP-Link RE190)

- Boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Compatible with 802.11 b/g/n and 802.11ac WiFi devices
- Dual band speeds up to 750Mbps
- Miniature size and wall-mounted design make it easy to deploy and move flexibly

HARDWARE FEATURES:

Plug Type: EU

Button:Reset Button, WPS Button

Power Consumption: About 7.0W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE

802.11g, IEEE 802.11b

Dimensions (W x D x H): 110,0 x 65,8 x 38,8 mm

Antenna Type: 3 x Omni-directional Antennas

WIRELESS FEATURES

Frequency:2.4GHz & 5GHz

Signal Rate:11n Up to 300Mbps(dynamic), 11g Up to

54Mbps(dynamic), 11b Up to 11Mbps(dynamic)

EIRP:<20dBm (EIRP)

Reception Sensitivity:270M -70dBm@10% PER, 130M

-70dBm@10% PER, 108M -73dBm@10% PER, 54M

-75dBm@10% PER, 11M -86dBm@8% PER, 6M

-92dBm@10% PER, 1M -94dBm@8% PER, 5G, 390M

-60dBm@10% PER, 29.3M -83dBm@10% PER, 180M

-64dBm@10% PER, 13.5M -87dBm@10% PER, 78M

-68dBm@10% PER, 6.5M -90dBm@10% PER, 54M

-75dBm@10% PER, 6M -90dBm@10% PER

Wireless Modes:Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless

Statistic, Domain Login Function

Wireless Security: 64/128/152-bit WEP, WPA-PSK /

WPA2-PSK

OTHERS

Certification:CE, FCC, RoHS

Package Contents:RE190, Quick Installation Guide

System Requirements:Microsoft Windows 98SE, NT, 2000,

XP, VistaTM or Windows 7,8, MAC OS, NetWare, UNIX or

Linux.

Environment:Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty:2 years limited warranty. Advanced replacement

service is available.

Manufacturer: TP-Link



#08935

Net Price:
24,40 EUR
Unit: pcs

750Mbps Wireless Range Extender, AC750 (TP-Link RE200)

- Boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Compatible with 802.11 b/g/n and 802.11ac WiFi devices
- Dual band speeds up to 750Mbps
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- Ethernet port allows the Extender to function as a wireless adapter to connect wired devices

HARDWARE FEATURES:

Ports:1 * 10/100M Ethernet Port (RJ45)

Plug Type: EU

Button:Reset Button, Range Extender Button

Power Consumption: About 6.5W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE

802.11g, IEEE 802.11b

Dimensions (W x D x H): 4.3x 2.6 x 3.0in. (110.0 x 65.8 x

75.2mm)

Antenna Type: 3 x internal

WIRELESS FEATURES

Frequency:2.4GHz & 5GHz

Signal Rate:11n Up to 300Mbps(dynamic), 11g Up to

54Mbps(dynamic), 11b Up to 11Mbps(dynamic)

EIRP:<20dBm (EIRP)

Reception Sensitivity:270M -70dBm@10% PER, 130M

-70dBm@10% PER, 108M -73dBm@10% PER, 54M

-75dBm@10% PER, 11M -86dBm@8% PER, 6M

-92dBm@10% PER, 1M -94dBm@8% PER, 5G, 390M

-60dBm@10% PER, 29.3M -83dBm@10% PER, 180M

-64dBm@10% PER, 13.5M -87dBm@10% PER, 78M

-68dBm@10% PER, 6.5M -90dBm@10% PER, 54M

-75dBm@10% PER, 6M -90dBm@10% PER

Wireless Modes:Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless

Statistic, Domain Login Function

Wireless Security: 64/128/152-bit WEP, WPA-PSK /

WPA2-PSK

OTHERS

Certification:CE, FCC, RoHS

Package Contents:RE200, Resource CD, Quick Installation

Guide, RJ-45 Ethernet Cable

System Requirements:Microsoft Windows 98SE, NT, 2000,

XP, VistaTM or Windows 7,8, MAC OS, NetWare, UNIX or

Linux.

Environment:Operating Temperature 0°~40° (32°~104°),

Storage Temperature -40°~70° (-40°~158°), Operating

Humidity 10%~90% non-condensing, Storage Humidity

5%~90% non-condensing

Warranty:2 years limited warranty. Advanced replacement

service is available.

Manufacturer: TP-Link

Standard N



#09047

Net Price:
57,60 EUR
Unit: pcs

867Mbps Wireless access point, 5GHz (TP-LINK CPE710)

- 802.11ac for up to 867Mbps on 5GHz wireless data rate
- 23dBi high-gain directional 2x2 MIMO, ideal for long-distance application
- Excellent beam directivity, improved latency and noise cancellation
- Innovative snap-lock parts make for fast assembly and a sturdy structural design keeps CPE710 stable even in strong winds
- Durable IP65 weatherproof enclosure along with 15kV ESD and 6kV lightning protection ensures all-weather suitability
- Pharos Control gives administrators a free, centralized management system
- Passive PoE supports to allow flexible deployment and convenient installation

Processor: Qualcomm 750 MHz, MIPS 74Kc
Memory: 128 MB DDR2 RAM, 16 MB Flash
Standards: IEEE 802.11a, IEEE 802.11n, IEEE 802.11ac
Ports: 1 10/100/1000Mbps Shielded Ethernet Port (LAN0, Passive PoE in), 1 Reset Button
Wireless Configurations: Pharos MAXstream TDMA Technology, 802.11a/n Modes, Selectable Channel Width 5/10/20/40MHz, Automatic Channel Selection, Transmission Power Control, Dynamic Frequency Selection (DFS), WDS Enable/Disable, SSID Broadcast Enable/Disable, Multi-SSID with VLAN Tagging (AP mode only), Distance/ACK Timeout Setting, Wireless MAC Address Filter
Security: WPA/WPA2, WPA-PSK/WPA2-PSK (AES/TKIP) Encryption, 64/128/152-bit WEP Encryption
Wireless Advanced: Beacon Interval/RTS Threshold/Fragmentation, Threshold/DTIM Interval/AP Isolation/Short GI/Wi-Fi Multimedia
Management: Discovery and Remote Management via Pharos Control application, HTTP/HTTPS Web-based management, System Log, SNMP Agent(v2c), Ping Watch Dog, Dynamic DDNS, SSH Server
System Tools: Wireless Signal Quality Indicators - Signal Strength/Noise/Transmit CQ/CPU/Memory, Monitors - Throughput/Stations/Interfaces/ARP/Routes/WAN/DHCP, Spectrum Analyzer, Speed Test, Ping, Traceroute
Signal Rate: Up to 300Mbps (40MHz, Dynamic), Up to 144.4Mbps (20MHz, Dynamic), Up to 72.2Mbps (10MHz, Dynamic), Up to 36.1Mbps (5MHz, Dynamic)
Receiver sensitivity: 802.11a 54M@ -75dBm 48M@ -76dBm 36M@ -83dBm 6-24M@ -95dBm, 802.11n MCS15 -73dBm, MCS14 -74dBm, MCS13 -76dBm, MCS12 -80dBm, MCS11 -83dBm, MCS10 -88dBm, MCS9 -90dBm, MCS8 -93dBm, MCS7 -73dBm, MCS6 -74dBm, MCS5 -76dBm, MCS4 -80dBm, MCS3 -83dBm, MCS2 -88dBm, MCS1 -90dBm, MCS0 -93dBm
Antenna: 23 dBi
Beam width: 9° (Azimuth)/7° (Elevation)
Dimensions: 366 x 280 x 207 mm (14.4 x 11.0 x 8.1 in.)
Power Supply: Passive Power over Ethernet via LAN0 (+4,5pins; -7,8pins), Voltage range 16-27VDC
Protection: 15KV ESD Protection, 6000V Lightning Protection
Enclosure: Outdoor ASA stabilized plastic material, IP65 water and dust proof design
Package Contents: Outdoor Wireless CPE, 24V 0.5A Passive PoE Adapter, Pole Mounting Straps, AC Power Cord, Installation Guide
Operating temperatures: -40°C + 70°C
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7/8/10, MAC OS, NetWare, UNIX or Linux.
Certificates: CE, FCC, RoHS, IP65, IC
Manufacturer: Tp-Link



#09013

Net Price:
31,70 EUR
Unit: pcs

AC1200 Whole Home Mesh Wi-Fi Add-On Unit (TP-Link DECO M3W)

- Only works with Deco Whole Home Mesh Wi-Fi router.
- Plug the add-on satellite into any outlets to easily expand mesh Wi-Fi coverage.
- Enjoy additional Wi-Fi coverage of up to 1,500 sq. ft. & #8224; to eliminate weak signal areas by plugging in every Deco M3W.
- Multiple Deco units form a whole-home network that auto-selects the best connection as you move around your home.
- Parental Controls limit online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
Button: 1 reset button on the right
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2 internal dual-band antennas per Deco unit
Dimensions: 4.9 x 2.7 x 1.4 in (124 x 69 x 35 mm) (without plug)
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 1 wall-plug add-on satellite (Deco M3W), 1 quick installation guide
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS



#09048

Net Price:
40,10 EUR
Unit: pcs

Router Mesh Deco E4 1-pack, AC1200 (TP-Link DECO E4(1-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco E4 three-pack delivers Wi-Fi to an area of up to 4,000 square feet (EU version). And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco E4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
Ports: 2 ports 10/100 Mb/s, 2 ports WAN/LAN, 1 Power Port
Button: 1 Reset button
Flash: 16 MB
SDRAM: 128 MB
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2 internal dual-band antennas per Deco unit
Dimensions: 7.5 x 3.6 x 3.6 in. (190.5 x 90.7 x 90.7 mm)
Power: 12 V/1 A
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 1 Deco unit, 1 Power Adapter, 1 RJ45 Ethernet Cable
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS



#09012

Net Price:
66,70 EUR
Unit: pcs

Router Mesh Deco E4 2-pack, AC1200 (TP-Link DECO E4(2-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco E4 three-pack delivers Wi-Fi to an area of up to 4,000 square feet (EU version). And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco E4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
Ports: 2 ports 10/100 Mb/s, 2 ports WAN/LAN, 1 Power Port
Button: 1 Reset button
Flash: 16 MB
SDRAM: 128 MB
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2 internal dual-band antennas per Deco unit
Dimensions: 7.5 × 3.6 × 3.6 in. (190.5 × 90.7 × 90.7 mm)
Power: 12 V/1 A
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 2 Deco units, 2 Power Adapters, 1 RJ45 Ethernet Cable
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS



#09049

Net Price:
98,90 EUR
Unit: pcs

Router Mesh Deco E4 3-pack, AC1200 (TP-Link DECO E4(3-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco E4 three-pack delivers Wi-Fi to an area of up to 4,000 square feet (EU version). And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco E4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
Ports: 2 ports 10/100 Mb/s, 2 ports WAN/LAN, 1 Power Port
Button: 1 Reset button
Flash: 16 MB
SDRAM: 128 MB
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2 internal dual-band antennas per Deco unit
Dimensions: 7.5 × 3.6 × 3.6 in. (190.5 × 90.7 × 90.7 mm)
Power: 12 V/1 A
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 3 Deco units, 3 Power Adapters, 1 RJ45 Ethernet Cable
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS



#09050

Net Price:
66,70 EUR
Unit: pcs

Router Mesh Deco M3 2-pack, AC1200 (TP-Link DECO M3(2-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- A Deco M3 two-pack (1 router-Deco M4R and 1 extender-Deco M3W) delivers Wi-Fi to an area of up to 2,400 square feet (EU version).
- Get further mesh Wi-Fi coverage by simply plugging in more Deco add-on extender Deco M3W into a wall outlet.
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between Decos as you move through your home for the fastest possible speeds.
- Deco M3 provides fast and stable connections with speeds of up to 1167 Mbps and works with a major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limit online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
Processor: Qualcomm CPU
Ports: Deco M4R- 2 Gigabit Ethernet Ports (WAN/LAN auto-sensing), 1 Power Port, Deco M3W - N/A
Button: 1 Reset button
Flash: Deco M4R- 16 MB; Deco M3W- 8 MB
SDRAM: 128 MB
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2 internal dual-band antennas per Deco unit
Dimensions: Deco M4R- 7.5 × 3.6 × 3.6 in. (190.5 × 90.7 × 90.7 mm), Deco M3W (without plug)- 4.9 × 2.7 × 1.4 in. (124 × 69 × 35 mm)
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: Deco M3 (2-pack) - 1 router Deco M4R, 1 wall-plug extender Deco M3W, 1 RJ45 Ethernet cable, 1 power adapter, 1 quick installation guide
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS



#09014

Net Price:
54,10 EUR
Unit: pcs

Router Mesh Deco M4 1-pack, AC1200 (TP-Link DECO M4(1-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco M4 delivers Wi-Fi to an area of up to 180 square metres. And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco M4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz

Processor: Qualcomm CPU

Ports: 2 ports 10/100/1000 Mb/s WAN/LAN

Button: 1 Reset button

Flash: 16 MB

SDRAM: 128 MB

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: FCC <30 dBm, CE <20 dBm (2,4 GHz) <23 dBm (5 GHz)

Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming

Wireless Security: WPA-PSK/WPA2-PSK

Software Features: Quality of Service - WMM, IPv6 Support,

WAN Type - Dynamic IP/Static IP/PPPoE, Local

Management, Remote Management, DHCP - Server, Client,

Port Forwarding Support, Access Control Blacklist, Firewall

Security SPI Firewall, Protocols Supports IPv4 and IPv6,

Homecare - Antivirus, Parental Controls, Quality of Service,

Speedtest, Monthly Usage Reports, Auto FW Update,

Expand for more deco, Guest Network 2.4 GHz guest

network * 1 - 5 GHz guest network * 1, Beamformig, Easy

setup by Deco App

Antenna: 2 internal dual-band antennas per Deco unit

Dimensions: Φ3,6 in. x 7.5 in. (Φ90,7 mm x 190 mm)

Power: 12 V/1,2 A

Operating Temperature: 0°C~40°C (-32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents: 1 Deco unit, 1 Power Adapter, 1 RJ45

Ethernet Cable, 1 quick installation guide

Smartphone/Tablet Requirements: iOS 9.0 or later, Android

4.4 or later

Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA,

VCCI, KC, RoHS



#09015

Net Price:
94,60 EUR
Unit: pcs

Router Mesh Deco M4 2-pack, AC1200 (TP-Link DECO M4(2-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco M4 delivers Wi-Fi to an area of up to 180 square metres. And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco M4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz

Processor: Qualcomm CPU

Ports: 2 ports 10/100/1000 Mb/s WAN/LAN

Button: 1 Reset button

Flash: 16 MB

SDRAM: 128 MB

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: FCC <30 dBm, CE <20 dBm (2,4 GHz) <23 dBm (5 GHz)

Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming

Wireless Security: WPA-PSK/WPA2-PSK

Software Features: Quality of Service - WMM, IPv6 Support,

WAN Type - Dynamic IP/Static IP/PPPoE, Local

Management, Remote Management, DHCP - Server, Client,

Port Forwarding Support, Access Control Blacklist, Firewall

Security SPI Firewall, Protocols Supports IPv4 and IPv6,

Homecare - Antivirus, Parental Controls, Quality of Service,

Speedtest, Monthly Usage Reports, Auto FW Update,

Expand for more deco, Guest Network 2.4 GHz guest

network * 1 - 5 GHz guest network * 1, Beamformig, Easy

setup by Deco App

Antenna: 2 internal dual-band antennas per Deco unit

Dimensions: Φ3,6 in. x 7.5 in. (Φ90,7 mm x 190 mm)

Power: 12 V/1,2 A

Operating Temperature: 0°C~40°C (-32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents: 2 Deco units, 2 Power Adapters, 1 RJ45

Ethernet Cable, 1 quick installation guide

Smartphone/Tablet Requirements: iOS 9.0 or later, Android

4.4 or later

Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA,

VCCI, KC, RoHS



#09016

Net Price:
135,00 EUR
Unit: pcs

Router Mesh Deco M4 3-pack, AC1200 (TP-Link DECO M4(3-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco M4 delivers Wi-Fi to an area of up to 180 square metres. And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco M4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz

Processor: Qualcomm CPU

Ports: 2 ports 10/100/1000 Mb/s WAN/LAN

Button: 1 Reset button

Flash: 16 MB

SDRAM: 128 MB

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: FCC <30 dBm, CE <20 dBm (2,4 GHz) <23 dBm (5 GHz)

Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming

Wireless Security: WPA-PSK/WPA2-PSK

Software Features: Quality of Service - WMM, IPv6 Support,

WAN Type - Dynamic IP/Static IP/PPPoE, Local

Management, Remote Management, DHCP - Server, Client,

Port Forwarding Support, Access Control Blacklist, Firewall

Security SPI Firewall, Protocols Supports IPv4 and IPv6,

Homecare - Antivirus, Parental Controls, Quality of Service,

Speedtest, Monthly Usage Reports, Auto FW Update,

Expand for more deco, Guest Network 2.4 GHz guest

network * 1 - 5 GHz guest network * 1, Beamformig, Easy

setup by Deco App

Antenna: 2 internal dual-band antennas per Deco unit

Dimensions: Φ3,6 in. x 7.5 in. (Φ90,7 mm x 190 mm)

Power: 12 V/1,2 A

Operating Temperature: 0°C~40°C (-32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents: 3 Deco units, 3 Power Adapters, 1 RJ45

Ethernet Cable, 1 quick installation guide

Smartphone/Tablet Requirements: iOS 9.0 or later, Android

4.4 or later

Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA,

VCCI, KC, RoHS



#09051

Net Price:
142,00 EUR
Unit: pcs

Router Mesh Deco M5 2-pack (TP-Link DECO M5(2-Pack))

- Covers up to 5,500 sq. ft.
- Fast dual band WiFi
- One WiFi name for the entire home
- Connects 100-plus devices
- Works with Amazon Alexa Voice Assistant

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
Ports: 2 LAN/WAN Gigabit Ethernet Ports
Processor: Quad-core CPU
Button: 1 Reset button on the underside
Flash: 32 MB
SDRAM: 256 MB
Bluetooth version: 4.2 and above
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 400 Mbps on 2.4 GHz, 867 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 4 internal antennas per Deco unit
Dimensions: Φ4.7 in. x 1.3 in. (Φ120 mm x 38 mm)
Power: 12 V/1.2 A
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 2 Deco units, 1 RJ45 Ethernet Cable, 2 Power Adapters
Smartphone/Tablet Requirements: iOS 8.0 or later, Android 4.3 or later, Bluetooth 4.0 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA



#09017

Net Price:
256,00 EUR
Unit: pcs

Router Mesh Deco M9 Plus 2-pack, AC2200 (TP-Link DECO M9 Plus(2-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form one unified whole-home network with the same network name. Devices automatically switch between Decos as you move through your home for the fastest possible speeds.
- A Deco M9 Plus two-pack delivers Wi-Fi to an area of up to 420 square metres. If that's not enough, simply add more Deco units to the network anytime to increase coverage.
- Three separate wireless bands provide a fast and stable connection with speeds of up to 2134Mbps, which is ideal for your gigabit fibre.
- Deco M9 Plus acts as a hub for your smart home devices. Adjust settings and create interactions from one platform - there's no need to buy an additional smart hub.
- Deco can handle traffic from even the busiest of networks, providing lag-free Wi-Fi connections for over 100 devices.
- TP-Link HomeCare™ provides a suite of personalised and security features, including Parental Controls, built-in Antivirus and Quality of Service (QoS).
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz, Bluetooth 4.2, ZigBee HA1.2
Ports: 2 * 10/100/1000 Mb/s WAN/LAN, 1 * USB 2.0 Port (reserved), 1 * Power Port
Button: 1 Reset button
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 400 Mbps on 2.4 GHz, 867 Mbps on 5 GHz, 867 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App, 3-Year Free Built-In Antivirus, Works with Alexa & IFTTT
Antenna: 8 internal antennas per Deco unit
Dimensions: Φ5.7 in. x 1.8 in. (Φ144 mm x 46 mm)
Power: 12 V/2 A
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 2 Deco units, 2 Power Adapters, 1 RJ45 Ethernet Cable
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS



#09074

Net Price:
376,00 EUR
Unit: pcs

Router Mesh Deco M9 Plus 3-pack (TP-Link DECO M9 Plus(3-Pack))

- Seamless Coverage: Achieve seamless whole-home coverage with a mesh Wi-Fi system and eliminate weak signal areas once and for all.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Broad Coverage: Enjoy Wi-Fi coverage up to 4,500 square feet with just 2 Deco M9 Plus units and expand it by just adding more Decos.
- Fast Connections: Three separate wireless bands up to 2134 Mbps with a dynamic backhaul up to 1.5 Gbps ensure stable, high-speed connections wherever you are in your home.
- Seamless Management: Deco M9 Plus acts as a hub for your wireless and smart home devices.
- Connect Multiple Devices: Deco handles traffic from even the busiest networks, providing lag-free connection for over 100 devices.
- Total Security: HomeCare™ provides personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS)* to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through setup-step by step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
Ports: 2 * LAN/WAN Gigabit Ethernet Ports, 1 * USB 2.0 Port (reserved), 1 * Power Port
Button: 1 Reset button on the underside
Flash: 32 MB
SDRAM: 256 MB
Bluetooth version: 4.2 and above
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 400 Mbps on 2.4 GHz, 867 Mbps on 5 GHz (1), 867 Mbps on 5 GHz (2)
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 8 internal antennas per Deco unit
Dimensions: Φ5.7 in. x 1.8 in. (Φ144 mm x 46 mm)
Power: 12 V/2.0 A
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 3 Deco units, 1 RJ45 Ethernet Cable, 3 Power Adapters
Smartphone/Tablet Requirements: iOS 8.0 or later, Android 4.3 or later, Bluetooth 4.0 or later



#09018

Net Price:
158,00 EUR
Unit: pcs

Router Mesh Deco P9 2-pack, AC1200 (TP-Link DECO P9(2-Pack))

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
Processor: Qualcomm CPU
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN
Button: 1 Reset button
Signal Rate: 1000 Mb/s
Standard: HomePlug AV2
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2 internal dual-band antennas per Deco unit
Dimensions: 190 mm x 90,7 mm x 90,7 mm (7,5 in. x 3,6 in. x 3,6 in.)
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 2 Deco units, 2 Power Adapters, 1 RJ45 Ethernet Cable, 1 quick installation guide
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS



#09019

Net Price:
226,00 EUR
Unit: pcs

Router Mesh Deco P9 3-pack, AC1200 (TP-Link DECO P9(3-Pack))

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
Processor: Qualcomm CPU
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN
Button: 1 Reset button
Signal Rate: 1000 Mb/s
Standard: HomePlug AV2
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2 internal dual-band antennas per Deco unit
Dimensions: 190 mm x 90,7 mm x 90,7 mm (7,5 in. x 3,6 in. x 3,6 in.)
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 3 Deco units, 3 Power Adapters, 1 RJ45 Ethernet Cable, 1 quick installation guide
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS



#09085

Net Price:
226,00 EUR
Unit: pcs

Router Mesh Deco X20 2-pack, AX1800 (TP-Link DECO X20(2-Pack))

- Faster Connections: Wi-Fi 6 speeds up to 1,800 Mbps-1,201 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger whole home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCare™ provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through setup step-by-step.
Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz
Processor: Qualcomm 1 GHz Quad-core CPU
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN
Button: 1 Reset button
Flash: 16 MB
SDRAM: 128 MB
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 4 internal antennas per Deco unit
Dimensions: 93,433 in. x 4.49 in. (x 934,110 mm x 114 mm)
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 2 Deco units, 2 Power Adapters, 1 RJ45 Ethernet Cable, 1 quick installation guide
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS



#09053

Net Price:
316,00 EUR
Unit: pcs

Router Mesh Deco X20 3-pack, AX1800 (TP-Link DECO X20(3-Pack))

- Faster Connections: Wi-Fi 6 speeds up to 1,800 Mbps-1,201 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger whole home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCare™ provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz
Processor: Qualcomm 1 GHz Quad-core CPU
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN
Button: 1 Reset button
Flash: 16 MB
SDRAM: 128 MB
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 4 internal antennas per Deco unit
Dimensions: 89.34x4.33 in. x 4.49 in. (89.34x110 mm x 114 mm)
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 3 Deco units, 3 Power Adapters, 1 RJ45 Ethernet Cable, 1 quick installation guide
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS

NEW



#09186

Net Price:
226,00 EUR
Unit: pcs

Router Mesh Deco X20-4G, AX1800, LTE (TP-Link DECO X20-4G)

- Internet Everywhere with 4G+ Speed - Provides WiFi 6 Mesh coverage through 4G+ CAT6 access
 - Superior WiFi 6 speeds up to 1.8 Gbps - 1201 Mbps (5 GHz) and 574 Mbps (2.4 GHz) dual band WiFi with WiFi 6 technology
 - Fully Gigabit Ethernet - 3x Gigabit WAN/LAN Ethernet ports provide flexible internet access at warp speed**
 - TP-Link HomeShield - Real-time IoT and network protection, robust Parental Controls, and comprehensive reports
 - 3G/4G Failover - Flexible access from Ethernet to 3G/4G to prevent data loss
- Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz
Processor: 1.5 GHz Quad-Core CPU
Ports: 3 ports 10/100/1000 Mb/s WAN/LAN
Button: 1 Reset button
USB Support: 12 V / 1.5 A
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: 3G/4G, Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2 LTE antennas, 2 Wi-Fi antennas (Internal)
Compatibility: 4G-FDD-LTE-B1/B3/B5/B7/B8/B20/B28(2100/1800/850/2600/900 /800 /700 MHz), TDD-LTE- B38/B40/B41(2600/2300/2500 MHz), 3G- DC-HSPA+/HSPA/UMTS B1/B5/B8 (2100/850/900 MHz)
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: Deco unit, Power Adapter, 1 RJ45 Ethernet Cable, 1 quick installation guide
Certificates: CE, RoHS

NEW



#09187

Net Price:
135,00 EUR
Unit: pcs

Router Mesh Deco X20-DSL, AX1800, VDSL/ADSL (TP-Link DECO X20-DSL)

- VDSL Modem Router + Mesh WiFi - Save a modem, and gaining a better WiFi experience
 - Super VDSL2 Speed - Supports Profile 35b tech to deliver downstream up to 350 Mbps
 - Superior WiFi 6 speeds up to 1.8 Gbps - 1201 Mbps (5 GHz) and 574 Mbps (2.4 GHz) dual-band WiFi with WiFi 6 technology
 - Fully Gigabit Ethernet - 4x Gigabit WAN/LAN Ethernet ports provide flexible internet access at warp speed
 - TP-Link HomeShield - Real-time IoT and network protection, robust Parental Controls, and comprehensive reports
 - True Seamless Roaming Mesh WiFi - Walk through your home and stay connected with the fastest possible speeds
- Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz
Processor: 1.5 GHz Quad-Core CPU
Ports: 4 ports 10/100/1000 Mb/s WAN/LAN, 1 DSL Port
Button: 1 Reset button
USB Support: 12 V / 1.2 A
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz
EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: DSL, Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2x Antennas (Internal)
Compatibility: VDSL2 / ADSL2+ / ADSL2 / ADSL
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: Deco unit, Power Adapter, 1 RJ45 Ethernet Cable, 2 RJ11 DSL Cables, 1 External DSL Splitter, 1 quick installation guide
Certificates: CE, EAC, RoHS, RCM



#09086

Net Price:
301,00 EUR
Unit: pcs

Router Mesh Deco X60 2-pack, AX3000 (TP-Link DECO X60(2-Pack))

- Faster Connections: Wi-Fi 6 speeds up to 3,000 Mbps-2,402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole-home coverage with a clearer and stronger whole-home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCare™ provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through the setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz
Processor: Qualcomm 1 GHz Quad-core CPU
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN
Button: 1 Reset button
Flash: 16 MB
SDRAM: 128 MB
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2 internal antennas per Deco unit
Dimensions: Φ4.33 in. × 4.49 in. (Φ110 mm × 114 mm)
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 2 Deco units, 2 Power Adapters, 1 RJ45 Ethernet Cable, 1 quick installation guide
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS



#09054

Net Price:
437,00 EUR
Unit: pcs

Router Mesh Deco X60 3-pack, AX3000 (TP-Link DECO X60(3-Pack))

- Faster Connections: Wi-Fi 6 speeds up to 3,000 Mbps-2,402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole-home coverage with a clearer and stronger whole-home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCare™ provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through the setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz
Processor: Qualcomm 1 GHz Quad-core CPU
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN
Button: 1 Reset button
Flash: 16 MB
SDRAM: 128 MB
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 2 internal antennas per Deco unit
Dimensions: Φ4.33 in. × 4.49 in. (Φ110 mm × 114 mm)
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 3 Deco units, 3 Power Adapters, 1 RJ45 Ethernet Cable, 1 quick installation guide
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, VCCI, KC, RoHS

NEW



#09188

Net Price:
338,00 EUR
Unit: pcs

Router Mesh Deco X68 2-pack, AX3600 (TP-Link DECO X68(2-Pack))

- AX3600 Tri-Band WiFi: Boosts overall speeds up to an incredible 3600 Mbps
- AI-Driven Mesh: Intelligently learns the network environment to provide ideal WiFi unique to your home
- Connect More Devices: Connect over 150 devices without dragging down performance
- Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger whole home WiFi signal generated by WiFi 6
- TP-Link HomeShield: Keeps your home network safe with cutting-edge features for network and IoT protection
- Setup Made Easier Than Ever: The Deco app walks you through setup step-by-step

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz
Processor: 1.5 GHz Quad-Core CPU
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN
Button: 1 Reset button
Power: 12V / 2.5 A
Frequency range: 2.4 GHz and 5 GHz
Signal Rate: 5 GHz 1802 Mb/s (802.11ax), 5 GHz 1201 Mb/s (802.11ax), 2.4 GHz 574 Mb/s (802.11ax)
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming
Wireless Security: WPA-PSK/WPA2-PSK
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network * 1 - 5 GHz guest network * 1, Beamformig, Easy setup by Deco App
Antenna: 5× High-Gain Antennas
Dimensions: 4.1 × 4.1 × 6.7 in (105 × 105 × 168 mm)
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 2 Deco units, 2 Power Adapters, 1 RJ45 Ethernet Cable, 1 quick installation guide
Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later
Certificates: CE, FCC, IC, RoHS, RCM, JPA, JRF, VCCI



#09087

Net Price:
550,00 EUR
Unit: pcs

Router Mesh Deco X90 2-pack, AX6600 (TP-Link DECO X90(2-Pack))

- AX6600 Tri-Band WiFi: Boosts overall speeds up to an incredible 6600 Mbps
- AI-Driven Mesh: Intelligently learns the network environment to provide ideal Wi-Fi unique to your home
- Smart Antennas: Establish a stronger backhaul to boost coverage and improve wireless connections
- Connect More Devices: Connect up to 200 devices without dragging down performance
- Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger whole home Wi-Fi signal generated by Wi-Fi 6
- TP-Link HomeShield: Keeps your home network safe with cutting-edge features for network and IoT protection
- Setup Made Easier Than Ever: The Deco app walks you through setup step-by-step

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz

Processor: Qualcomm 1,5 GHz Quad-core CPU

Ports: 2 ports 10/100/1000 Mb/s WAN/LAN

Button: 1 Reset button

Power: 12 V & #9107; 2,5 A

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz,

4804 Mbps on 5 GHz (802.11ax, HE160)

EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming

Wireless Security: WPA-PSK/WPA2-PSK

Software Features: Quality of Service - WMM, IPv6 Support,

WAN Type - Dynamic IP/Static IP/PPPoE, Local

Management, Remote Management, DHCP - Server, Client,

Port Forwarding Support, Access Control Blacklist, Firewall

Security SPI Firewall, Protocols Supports IPv4 and IPv6,

Homecare - Antivirus, Parental Controls, Quality of Service,

Speedtest, Monthly Usage Reports, Auto FW Update,

Expand for more deco, Guest Network 2.4 GHz guest

network * 1 - 5 GHz guest network * 1, Beamformig, Easy

setup by Deco App

Antenna: 4x High-Gain Antennas (Internal) - Multiple

antennas form a signal-boosting array to cover more

directions and large areas, 2x Smart Antennas (Internal) -

Smart antennas auto-detect other Deco units to establish a

stronger backhaul between one another to boost WiFi

coverage

Dimensions: 5.1 x 4.8 x 8.3 in (130 x 123 x 210 mm)

Operating Temperature: 0°C~40°C (-32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents: 2 Deco units, 2 Power Adapters, 1 RJ45

Ethernet Cable, 1 quick installation guide

Smartphone/Tablet Requirements: iOS 9.0 or later, Android

4.4 or later

Certificates: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA,

VCCI, KC, RoHS

NEW



#09191

Net Price:
88,60 EUR
Unit: pcs

Router Mesh Halo H50G 3-pack, AC1900 (TP-Link Mercusys Halo H50G(3-pack))

- One Unified Network - With advanced Mesh Technology, Halo units work together to form a single unified whole home network with one WiFi name and password.
- Seamless Roaming - Automatically switch between Halos as you move around your home, always getting the best signal to enjoy the fastest connections for all your devices.
- Whole Home Coverage - Blanket up to 6,000 ft2 (550 m2) with high-speed WiFi, eliminating WiFi dead zones at your home.
- 1.9 Gbps Dual Band WiFi - Halo H50G provides fast and stable connections for over 100 devices with speeds of up to 1,900 Mbps and works with major internet service providers (ISPs) and modems.
- Easy App Control - Use the MERCUSYS App to quickly set up and manage your WiFi.
- Full Gigabit Ports - 3x Gigabit ports per Halo unit for lightning-fast wired connections

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Ports: 3 x 10/100/1000 Mb/s ports per Halo unit (WAN/LAN auto-sensing)

Button: 1 Reset button

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 600 Mbps on 2.4 GHz, 1300 Mbps on 5 GHz

EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Wireless Security: WPA2-PSK + AES

Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics

Mesh protocol: 802.11k/v

WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP

Management: Access Control, Local Management, Remote

Management

DHCP: Server, Address Reservation, DHCP Client List

Port Forwarding: Virtual Server, UPnP, DMZ, Port Triggering

Protocols: IPv4, IPv6

Guest Network: 2.4 GHz Guest Network, 5 GHz Guest

Network

Dimensions: 3.5 x 3.5 x 3.5 in (88 x 88 x 88 mm)

Operating Temperature: 0°C~40°C (-32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents: 3 Halo H50G units, 3 Power Adapters, 1

RJ45 Ethernet Cable, 1 Quick Installation Guide



#09105

Net Price:
42,20 EUR
Unit: pcs

Router Mesh Halo S12 2-pack, AC1200 (TP-Link Mercusys Halo S12(2-pack))

- One Unified Network - With advanced Mesh Technology, Halo S12 units work together to form a single unified whole-home network with one Wi-Fi name and password.
- Seamless Roaming - Automatically switch between Halos as you move around your home, always getting the best signal to enjoy the fastest connections for all your devices.
- Whole-Home Coverage - Blanket up to 2,800 ft2 (260 m2) with high-speed Wi-Fi.
- Hi-Speed Wi-Fi - Halo S12 provides fast and stable connections with speeds of up to 1,167 Mbps and works with major internet service providers (ISP) and modems.
- Ultra-High Performance - Enjoy lag-free connection and non-stop entertainment on all your devices, at the same time.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz

Ports: 2 x 10/100 Mb/s ports per Halo unit (WAN/LAN auto-sensing)

Button: 1 Reset button, 1 Pair button

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Wireless Security: WPA2-PSK + AES

Wireless Functions: Enable/Disable Wireless Radio, Wireless

Statistics

Mesh protocol: 802.11k/v

WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP

Management: Access Control, Local Management, Remote

Management

DHCP: Server, Address Reservation, DHCP Client List

Port Forwarding: Virtual Server, UPnP, DMZ, Port Triggering

Protocols: IPv4, IPv6

Guest Network: 2.4 GHz Guest Network, 5 GHz Guest

Network

Dimensions: 3.5 x 3.5 x 3.5 in (88 x 88 x 88 mm)

Power: 9 V/0.85 A

Operating Temperature: 0°C~40°C (-32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents: 2 Halo S12 units, 2 Power Adapters, 1

RJ45 Ethernet Cable, 1 Quick Installation Guide



#09106

Net Price:
60,20 EUR
Unit: pcs

Router Mesh Halo S12 3-pack, AC1200 (TP-Link Mercusys Halo S12(3-pack))

- One Unified Network - With advanced Mesh Technology, Halo S12 units work together to form a single unified whole-home network with one Wi-Fi name and password.
- Seamless Roaming - Automatically switch between Halos as you move around your home, always getting the best signal to enjoy the fastest connections for all your devices.
- Ultra-High Performance - Enjoy lag-free connection and non-stop entertainment on all your devices, at the same time.
- Whole-Home Coverage - Blanket up to 2,800 ft² (260 m²) with high-speed Wi-Fi.

- Hi-Speed Wi-Fi - Halo S12 provides fast and stable connections with speeds of up to 1,167 Mbps and works with major internet service providers (ISP) and modems.
- Ultra-High Performance - Enjoy lag-free connection and non-stop entertainment on all your devices, at the same time.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz

Ports: 2 x 10/100 Mb/s ports per Halo unit (WAN/LAN auto-sensing)

Button: 1 Reset button, 1 Pair button

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Wireless Security: WPA2-PSK + AES

Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics

Mesh protocol: 802.11k/v

WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP

Management: Access Control, Local Management, Remote Management

DHCP: Server, Address Reservation, DHCP Client List

Port Forwarding: Virtual Server, UPnP, DMZ, Port Triggering

Protocols: IPv4, IPv6

Guest Network: 2.4 GHz Guest Network, 5 GHz Guest Network

Dimensions: 3.5 x 3.5 x 3.5 in (88 x 88 x 88 mm)

Power: 9 V/0.85 A

Operating Temperature: 0°C~40°C (-32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents: 3 Halo S12 units, 3 Power Adapters, 1 RJ45 Ethernet Cable, 1 Quick Installation Guide



#08843

Net Price:
80,60 EUR
Unit: pcs

Wireless access point Ubiquiti NanoBeam M2 MIMO (Ubiquiti NBE-M2-13)

Standards: IEEE 802.11n

Ports: 1x 10/100 Mbps RJ-45

Chipset: Atheros MIPS 74KC, 560 MHz

Operating memory: 64 MB DDR2

Flash memory: 8 MB

Antenna: build-in, 18 dBi

VSWR: 1.5

Diameter: 189mm

Weight: 1.795 kg

Mounting: mast or wall with the aid of antenna wall support

Max. power consumption: 6 W

Power: PoE 24V

Operating temperatures: -40°C + 70°C

Operating humidity: 5% + 95%, Non-condensing

Manufacturer: Ubiquiti



#08141

Net Price:
44,80 EUR
Unit: pcs

Wireless access point Ubiquiti NanoStation Loco M2 (Ubiquiti LOCOM2)

Standards: IEEE 802.11b/g/n, IEEE 802.3u

Ports: 1x 10/100 Mbps RJ-45

Operating modes: Access Point, Bridge, Client, WDS

Chipset: Atheros MIPS 24KC, 400MHz

Operating memory: 32MB SDRAM

Flash memory: 8MB

Frequency range: 2400 MHz + 2483,5 MHz

Max. output power: 20 dBm

Antenna: build-in, 8 dBi, detachable RSMA

Dimensions: 163x80x31 mm

Weight: 0.18 kg

Mounting: mast or wall with the aid of antenna wall support

Max. power consumption: 5.5 W

Power: PoE 24V

Operating temperatures: -30°C + 80°C

Operating humidity: 5% + 90%, non-condensing

Certificates: CE, FCC, IC RS210



#08928

Net Price:
80,60 EUR
Unit: pcs

Wireless access point Ubiquiti NanoStation M2 (Ubiquiti NSM2)

Standards: IEEE 802.11b/g/n, IEEE 802.3u

Ports: 2x 10/100 Mbps RJ-45

Operating modes: Access Point, Bridge, Client, WDS

Chipset: Atheros MIPS 24KC, 400MHz

Operating memory: 32MB SDRAM

Flash memory: 8MB

Frequency range: 2400 MHz + 2483,5 MHz

Gain: 10.4-11.2 dBi

Max. output power: 23 dBm

Dimensions: 294 x 31 x 80 mm (11.57 x 1.22 x 3.15")

Weight: 400 g

Mounting: mast or wall with the aid of antenna wall support

Max. power consumption: 5.5 W

Power: PoE 24V, 0.5A

Operating temperatures: -30°C + 75°C

Operating humidity: 5% + 95%, non-condensing

Certificates: FCC Part 15.247, IC RS210, CE

Shock & Vibration: ETSI300-019-1.4



#08394

Net Price:
205,00 EUR
Unit: pcs

Wireless Access Point UniFi UAP PRO (Ubiquiti UAP-PRO)

The UniFi Enterprise Wi-Fi System is a scalable enterprise access point solution designed to be easily deployed and managed. UniFi Access Point (AP) indoor models have a sleek design and can be easily mounted to a ceiling tile or wall using the included mounting hardware. UniFi AP (UAP) outdoor models have a form factor built to last outdoors.

The UniFi Enterprise Wi-Fi System includes the UniFi Controller software. The software installs on any PC, Mac, or Linux machine within the network and is easily accessible through any standard web browser. Using the UniFi Controller software, an Enterprise Wi-Fi network can be quickly configured and administered without any special training. Real-time status, automatic UAP device detection, map loading, and advanced security options are all seamlessly integrated.

Networking Interface (Mbps): 2 x 10/100/1000 Ethernet Ports
Buttons: Reset
Antennas: 2.4 GHz - 3 Integrated (Supports 3x3 MIMO with Spatial Diversity), 5 GHz - 2 Integrated (Supports 2x2 MIMO with Spatial Diversity)
Wi-Fi Standards: 802.11 a/b/g/n
Power Method: Passive Power over Ethernet (48V), 802.3af Supported
Power Supply: 48V, 0.5A PoE Adapter (Included)
Maximum Power Consumption: 12 W
Maximum TX Power: 2.4 GHz - 30 dBm, 5 GHz - 22 dBm
BSSID: Up to Four Per Radio
Dimensions: 200 x 200 x 36.5 mm
Weight: 298 g (358 g with Mounting Kits)
Power Save: Supported
Wireless Security: WEP, WPA-PSK, WPA-TKIP, WPA2 AES, 802.11i
Certifications: CE, FCC, IC
Mounting: Wall/Ceiling (Kits Included)
Operating Temperature: -10 ° 70 ° C
Operating Humidity: 5 + 80% Condensing
Advanced Traffic Management
VLAN: 802.1Q
Advanced QoS: Per-User Rate Limiting
Guest traffic isolation: Supported
WMM: Voice, Video, Best Effort, and Background
Concurrent Clients: 200+
Supported Data Rates (Mbps)
802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n: 6.5 Mbps to 450 Mbps (MCS0 - MCS23, HT 20/40)
802.11b: 1, 2, 5.5, 11 Mbps
802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps



Wireless Base Station Airmax TDMA (Ubiquiti Rocket M2)

Standards: IEEE 802.11a, IEEE 802.11n, IEEE 802.3u
Ports: 1x 10/100 Mbps RJ-45
Operating modes: Access Point, Bridge, Client, WDS
Chipset: Atheros MIPS 24KC 400MHz
Operating memory: 128 MB SDRAM
Flash memory: 8 MB
Frequency range: 2402 - 2462 MHz
Max. output power: 28 dBm
Antenna: detachable, 2x SMA-RP(F)
Dimensions: 160x80x30 mm
Weight: 0.5 kg
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 6.5 W
Power: PoE 24V, 1A
Operating temperatures: -30°C + 75°C
Operating humidity: 5% + 95%, non-condensing
Certificates: CE, FCC, IC RS210
Manufacturer: Ubiquiti

#07895

Net Price:
80,60 EUR
Unit: pcs



3G Mobile Hotspot Wi-Fi (TP-Link M5350)

- Equipped with a built-in 3G modem - No additional bulky devices required
- HSPA+ supported with up to 21.6Mbps download and 5.76Mbps upload speeds
- Powerful 2000mAh battery is ideal for extended hours of outdoor use
- Supports up to 10 users simultaneously

HARDWARE FEATURES

Interface: 1 micro USB port for power supply, SIM Card Slot, Micro SD card Slot
Button: Power On/Off Button, Reset Button
OLED Display: Signal strength, Network type, Wi-Fi status, Message, Internet connection status, Battery meter, connection mode and Traffic Statistics
Wireless Standards: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Network Type: HSPA+/HSPA/UMTS/EDGE/GRPS/GSM
Data Rates: DL- 21.6Mbps, UL- 5.76Mbps
Antenna: Internal Antenna
Power Supply: Internal 2000mAh Rechargeable Battery, 5VDC/1.0A
Dimensions (W x D x H): 3.7x2.2x0.8in.(94x56.7x19.8mm)
Micro SD Card Reader: up to 32G
Band: WCDMA 2100/900MHz, GSM 850/900/1800/1900MHz
WIRELESS FEATURES
Frequency: 2.4-2.4835GHz
EIRP: <20dBm
Wireless Security: Support WPA-PSK/WPA2-PSK, Wireless MAC Filtering, Enable/Disable SSID Broadcast
DHCP: DHCP server, DHCP Client List
OTHERS
Certification: CE, FCC, RoHS
Package Contents: 3G Mobile Wi-Fi M5350, Battery, Power Adapter, Micro USB Cable, Micro to Standard SIM Card Adapter, Nano to Standard SIM Card Adapter, Quick Installation Guide
System Requirements: Windows 8/7/vista/XP, Mac OS, Android, iOS, Windows phone
Weight: 92.5g (battery included)



#09101

Net Price:
49,50 EUR
Unit: pcs

LTE Mobile Hotspot Wi-Fi (TP-Link M7000)

- Share with friends internet access for up to 10 devices simultaneously
- 2000mAh battery for 8 hours of usage
- Supports the latest generation 4G FDD/TDD-LTE, compatible with the network of most countries and regions
- Easy management with the tpMiFi App

HARDWARE FEATURES

Interface: 1 micro USB port for power supply, SIM Card Slot
Button: Power On/Off Button, Reset
Display: Wi-Fi status, Internet connection status, Battery status
Wireless Standards: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Network Type: 4G FDD-LTE B1/B3/B7/B8/B20 (2100/1800/2600/900/800MHz), TDD-LTE B38/B40/B41 (2600/2300/2500MHz), 3G DC-HSPA+/HSPA+/HSPA/UMTS B1/B8 (2100/850/900MHz)
Data Rates: DL- up to 150Mbps, UL- up to 50Mbps
Antenna: Internal Antenna
Power Supply: Internal 2000mAh Rechargeable Battery
Dimensions (W x D x H): 3.7x2.2x0.8 in. (94x56.7x19.8mm)
WIRELESS FEATURES
Frequency: 2.4GHz
EIRP: <20dBm
Wireless Security: Support WPA-PSK/WPA2-PSK, Wireless MAC Filtering
DHCP: DHCP server, DHCP Client List
OTHERS
Operating Temperature: 0°C~35°C (32°F ~95°F)
Storage Temperature: -20°C~60°C (-4°F ~140°F)
Operating Humidity: 10%~90% non-condensing
Certification: CE, FCC, RoHS
Package Contents: 4G LTE Mobile Wi-Fi M7000, Micro USB Cable, 2000mAh Battery, Quick Installation Guide
System Requirements: Windows 10/8/7/vista/XP, Mac OS, Android, iOS, Windows phone



#06243

Net Price:
52,20 EUR
Unit: pcs

LTE Mobile Hotspot Wi-Fi (TP-Link M7200)

- Share with friends internet access for up to 10 devices simultaneously
- 2000mAh battery for 8 hours of usage
- Supports the latest generation 4G FDD/TDD-LTE, compatible with the network of most countries and regions
- Easy management with the tpMiFi App

HARDWARE FEATURES

Interface: 1 micro USB port for power supply, SIM Card Slot
Button: Power On/Off Button
Display: Wi-Fi status, Internet connection status, Battery status
Wireless Standards: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Network Type: 4G FDD-LTE B1/B3/B7/B8/B20 (2100/1800/2600/900/800MHz), TDD-LTE B38/B40/B41 (2600/2300/2500MHz), 3G DC-HSPA+/HSPA+/HSPA/UMTS B1/B8 (2100/900MHz)
Data Rates: DL- up to 150Mbps, UL- up to 50Mbps
Antenna: Internal Antenna
Power Supply: Internal 2000mAh Rechargeable Battery
Dimensions (W x D x H): 3.7x2.2x0.8 in. (94x56.7x19.8mm)
WIRELESS FEATURES
Frequency: 2.4GHz
EIRP: <20dBm
Wireless Security: Support WPA-PSK/WPA2-PSK, Wireless MAC Filtering
DHCP: DHCP server, DHCP Client List
OTHERS
Certification: CE, FCC, RoHS
Package Contents: 4G LTE Mobile Wi-Fi M7200, Micro USB Cable, 2000mAh Battery, Quick Installation Guide
System Requirements: Windows 10/8/7/vista/XP, Mac OS, Android, iOS, Windows phone



#08942

Net Price:
79,50 EUR
Unit: pcs

LTE Mobile Hotspot Wi-Fi (TP-Link M7350)

- 4G LTE supported with up to 150Mbps download and 50Mbps upload speeds
- Supports up to 15 devices simultaneously
- All useful information at a glance with screen display
- 2550mAh battery for up to 10 hours of working
- Selectable 2.4GHz or 5GHz dual band WiFi
- Equipped with a micro SD card slot for up to 32GB of optional storage

HARDWARE FEATURES

Interface: 1 micro USB port for power supply, SIM Card Slot, Micro SD card Slot
Button: Power On/Off Button, Menu Button
OLED Display: Traffic statistics, Wi-Fi status, user numbers, network type (2G/3G/4G), signal strength, Internet connection status, messages, battery meter

Wireless Standards: IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Network Type: FDD-LTE Cat4 (800/900/1800/2100/2600MHz), DC-HSPA+/HSPA/UMTS (900/2100MHz), EDGE/GPRS/GSM (850/900/1800/1900MHz)

Data Rates: DL- up to 150Mbps, UL- up to 50Mbps

Antenna: Internal Antenna

Power Supply: Internal 2550mAh Rechargeable Battery
Dimensions (W x D x H): 4.2 x 2.6 x 0.6 in. (106 x 66 x 16mm)

Micro SD Card Reader: up to 32G

WIRELESS FEATURES

Frequency: 2.4GHz & 5GHz

EIRP: <20dBm

Wireless Security: Support WPA-PSK/WPA2-PSK, Wireless

MAC Filtering, Enable/Disable SSID Broadcast

DHCP: DHCP server, DHCP Client List

OTHERS

Certification: CE, FCC, RoHS

Package Contents: LTE-Advanced Mobile WiFi M7350, Micro

USB Cable, Micro to Standard SIM Card Adapter, Nano to

Standard SIM Card Adapter, Power Adapter, Quick

Installation Guide

System Requirements: Windows 8/7/vista/XP, Mac OS,

Android, iOS, Windows phone

Weight: 92.5g (battery included)



#04687

Net Price:
168,00 EUR
Unit: pcs

LTE Mobile Hotspot Wi-Fi, 600Mbps (TP-Link M7650)

- LTE-Advanced cat11 supported with up to 600Mbps download and 50Mbps upload speeds
- Supports up to 32 devices simultaneously
- Selectable 300Mbps at 2.4GHz or 867Mbps at 5GHz dual band Wi-Fi
- All useful information at a glance with screen display
- 3000mAh battery for up to 15 hours of working
- Equipped with a micro SD card slot for up to 32GB of optional storage
- Easy management with the tpMiFi App

HARDWARE FEATURES

Interface: 1 micro USB port for power supply, SIM Card Slot, Micro SD card Slot

Button: Power On/Off Button, Reset Button

OLED Display: Traffic statistics, Wi-Fi status, user numbers, network type (2G/3G/4G), signal strength, Internet connection status, messages, battery meter

Wireless Standards: IEEE 802.11a/b/g/n/ac 300Mbps at

2.4GHz or 867Mbps at 5GHz

Network Type: FDD-LTE-

B1/B3/B7/B8/B20(2100/1800/2600/900/800MHz), TDD-LTE-

B38/B40/B41 (2600/2300/2500MHz),

DC-HSPA+/HSPA/UMTS- B1/B8(2100/900MHz),

EDGE/GPRS/GSM- 850/900/1800/1900MHz

Data Rates: DL- up to 600Mbps, UL- up to 50Mbps

Antenna: Internal Antenna

Power Supply: Internal 3000mAh Rechargeable Battery
Dimensions (W x D x H): 4.2 x 2.6 x 0.6 in. (106 x 66 x 16mm)

Micro SD Card Reader: up to 32G

WIRELESS FEATURES

Frequency: 2.4GHz & 5GHz

EIRP: 2.4G <20dbm, 5G <23dbm

Wireless Security: Support WPA-PSK/WPA2-PSK, Wireless

MAC Filtering, Enable/Disable SSID Broadcast

DHCP: DHCP server, DHCP Client List

OTHERS

Certification: CE, FCC, RoHS

Package Contents: 600Mbps LTE-Advanced Mobile Wi-Fi

M7650, Micro USB Cable, Nano to Micro SIM Card Adapter,

3000mAh Battery, Quick Installation Guide

System Requirements: Windows 10/8/7/vista/XP, Mac OS,

Android, iOS, Windows phone



#06242

Net Price:
137,00 EUR
Unit: pcs

LTE-Advanced Mobile Hotspot Wi-Fi (TP-Link M7450)

- LTE-Advanced cat6 supported with up to 300Mbps download and 50Mbps upload speeds
- Supports up to 32 devices simultaneously
- Selectable 300Mbps at 2.4GHz or 867Mbps at 5GHz dual band Wi-Fi
- All useful information at a glance with screen display
- 3000mAh battery for up to 15 hours of working
- Equipped with a micro SD card slot for up to 32GB of optional storage
- Easy management with the tpMiFi App

HARDWARE FEATURES

Interface: 1 micro USB port for power supply, SIM Card Slot, Micro SD card Slot

Button: Power On/Off Button, Menu Button

Display: 1.44", TFT

Wireless Standards: IEEE 802.11a/b/g/n/ac 300Mbps at 2.4GHz or 867Mbps at 5GHz

Network Type: FDD-LTE-

B1/B3/B7/B8/B20(2100/1800/2600/900/800MHz), TDD-LTE-

B38/B40/B41 (2600/2300/2500MHz),

DC-HSPA+/HSPA/UMTS B1/B8(2100/900MHz),

EDGE/GPRS/GSM 850/900/1800/1900MHz

Data Rates: DL- 300Mbps, UL- 50Mbps

Antenna: Internal Antenna

Power Supply: Internal 3000mAh Rechargeable Battery

Dimensions (W x D x H): 112,5x66,5x16mm

Micro SD Card Reader: up to 32G

WIRELESS FEATURES

Frequency: 2.4GHz & 5GHz

EIRP: 2.4G <20dbm, 5G <23dbm

Wireless Security: Support WPA-PSK/WPA2-PSK, Wireless

MAC Filtering,

DHCP: DHCP server, DHCP Client List

OTHERS

Certification: CE, RoHS

Package Contents: 300Mbps LTE-Advanced Mobile Wi-Fi

M7450, Micro USB Cable, Nano to Micro SIM Card Adapter,

3000mAh Battery, Quick Installation Guide

System Requirements: Windows 10/8/7/vista/XP, Mac OS,

Android, iOS, Windows phone



#09011

Net Price:
40,50 EUR
Unit: pcs

150Mbps Wireless access point, 5GHz, PoE (TP-Link CPE605)

- Up to 150Mbps on 5GHz wireless data rates
- 23dBi high-gain directional antenna and a dedicated metal reflector, ideal for long-distance application
- Excellent beam directivity, improved latency and noise cancellation
- Innovative snap-lock parts make for fast assembly and a sturdy structural design keeps CPE605 stable even in strong winds
- Durable IP65 weatherproof enclosure along with 15 kV ESD and 6 kV lightning protection ensures all-weather suitability
- TP-Link Pharos MAXstream TDMA technology improves throughput, capacity and latency performance
- Pharos Control gives administrators a free, centralized management system
- Passive PoE supports to allow flexible deployment and convenient installation

Processor: Qualcomm 560MHz CPU, MIPS 74Kc
Memory: 64MB DDR2 RAM, 8MB Flash
Standards: IEEE 802.11a, IEEE 802.11n
Ports: 1 10/100Mbps Shielded Ethernet Port (LAN0, Passive PoE in), 1 Reset Button
Antenna Gain: 23dBi
Antenna Beamwidth: 7°(Azimuth), 10°(Elevation)
Wireless Configurations: Pharos MAXstream TDMA Technology, 802.11a/n Modes, Selectable Channel Width 5/10/20/40MHz, Automatic Channel Selection, Transmission Power Control, Dynamic Frequency Selection (DFS), WDS Enable/Disable, SSID Broadcast Enable/Disable, Multi-SSID with VLAN Tagging (AP mode only), Distance/ACK Timeout Setting, Wireless MAC Address Filter, Long Range PIP Security: WPA/WPA2, WPA-PSK/WPA2-PSK (AES/TKIP) Encryption, 64/128/152-bit WEP Encryption
Wireless Advanced: Beacon Interval/RTS Threshold/Fragmentation, Threshold/DTIM Interval/AP Isolation/Short GI/Wi-Fi Multimedia
Management: Discovery and Remote Management via Pharos Control application, HTTP/HTTPS Web-based management, System Log, SNMP Agent(v2c), Ping Watch Dog, Dynamic DDNS, SSH Server
System Tools: Wireless Signal Quality Indicators - Signal Strength/Noise/Transmit CCQ/CPU/Memory, Monitors - Throughput/Stations/Interfaces/ARP/Routes/WAN/DHCP, Spectrum Analyzer, Speed Test, Ping, Traceroute
Signal Rate: Up to 150Mbps (40MHz, Dynamic), Up to 72.2Mbps (20MHz, Dynamic), Up to 36.1Mbps (10MHz, Dynamic), Up to 18.05Mbps (5MHz, Dynamic)
Dimensions: 350 x 255 x 207 mm (13.8 x 10.0 x 8.1 in.)
Power Supply: Passive Power over Ethernet via LAN (+4,5pins; -7,8pins), Voltage range- 16-27VDC
Protection: 15KV ESD Protection, 6000V Lightning Protection
Enclosure: Outdoor PC stabilized plastic, Weatherproof IP65 water and dust proof design
Package Contents: Outdoor Wireless CPE, 24V 0.25A Passive PoE Adapter, Pole Mounting Kits, AC Power Cord, Installation Guide
Operating temperatures: -40°C + 70°C
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~95% non-condensing
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, Vista™ lub Windows 10, Windows 8, Windows 7, MAC OS, NetWare, UNIX lub Linux. We recommend you to use one of following Web browsers for an improved user experience Google Chrome, Safari, and Firefox. IE browsers are not recommended.
Certificates: CE, FCC, RoHS, IPX5
Warranty: 5 years
Manufacturer: Tp-Link



#04680

Net Price:
41,00 EUR
Unit: pcs

300Mbps Outdoor Wireless Access Point, N300 (TP-Link EAP110-Outdoor)

- Built for outdoor Wi-Fi applications
- Up to 300Mbps Wi-Fi with 2x2 MIMO technology
- High transmission power and high gain antennas provide a long-range coverage area
- Durable, weatherproof enclosure to withstand fair and foul weather
- Passive PoE(Power over Ethernet) support and simple mounting design allow for flexible deployment and convenient installation
- Free Auranet Controller Software lets administrators easily manage hundreds of EAPs
- Captive portal provides a convenient method for guest authentication

Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Ports: Fast Ethernet (RJ-45) Port *1（Support Passive PoE）
Frequency range: 2,4GHz
Wireless Functions: Multiple SSIDs (Up to 8 SSIDs), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Load Balance, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
Antenna: 2*5dBi External Omni waterproof
Dimensions: 95 x 42,6 x 209 mm
Power: 24VDC / 0.6A Passive PoE Supply
Power Consumption: 6.3W
Mounting: Pole / Wall Mounting (Kits included)
Watch Dog: Yes
Operating Temperature: -30°C~65°C (-22°F~149°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: 300Mbps Wireless N Outdoor Access Point, EAP110-Outdoor, Passive PoE Adapter, Power Cord, Mounting Kits, Waterproof Rubber Insert, Waterproof Antennas, Installation Guide
System Requirements: Microsoft Windows 10/8/7/Vista/XP
Certificates: CE, FCC, RoHS
Warranty: 5 years



#04679

Net Price:
24,60 EUR
Unit: pcs

300Mbps Outdoor Wireless Access Point, N300 (TP-Link EAP115-Wall)

- Easy-mount construction allows installation into any standard EU-type data wall-box
- Compact, low-profile design fits discreetly with any existing interior style
- Free Auranet Controller Software enables administrators to easily manage hundreds of EAPs
- Support Power over Ethernet (802.3af) for convenient and affordable installation
- Enterprise class Wi-Fi security helps to decrease network security threats
- Captive portal provides one convenient method of authentication for Wi-Fi guests
- Supports management vlan for an enhanced network management

Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Ports: Fast Ethernet (RJ-45) Port *2
Frequency range: 2,4GHz
Wireless Functions: Multiple SSIDs (Up to 8 SSIDs), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Load Balance, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
Antenna: Internal 2*1.8dBi Omni
Dimensions: 86,8*86,8*30,2 mm (3,4*3,4*1,2 in)
Power: PoE (IEEE 802.3af)
Power Consumption: 2.8W
Mounting: Wall Mounting
Watch Dog: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: EAP115-Wall, Power Adapter, Mounting Kits, Installation Guide
System Requirements: Microsoft Windows 10/8/7/Vista/XP
Certificates: CE, FCC, RoHS
Warranty: 5 years



#08941

Net Price:
34,00 EUR
Unit: pcs

300Mbps Wireless access point, 2.4GHz (TP-LINK CPE210)

Processor: Qualcomm Atheros 560MHz CPU, MIPS 74Kc
Memory: 64MB DDR2 RAM, 8MB Flash
Standards: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Ports: 1 10/100Mbps Shielded Ethernet Port (LAN0, Passive PoE in), 1 10/100Mbps Shielded Ethernet Port (LAN1, Passive PoE Passthrough), 1 Grounding Terminal, 1 Reset Button
Wireless Configurations: Pharos MAXstream TDMA Technology, 802.11b/g/n Modes, Selectable Channel Width 5/10/20/40MHz, Automatic Channel Selection, Transmission Power Control, Dynamic Frequency Selection (DFS), WDS Enable/Disable, SSID Broadcast Enable/Disable, Multi-SSID with VLAN Tagging (AP mode only), Distance/ACK Timeout Setting, Wireless MAC Address Filter
Security: WPA/WPA2, WPA-PSK/WPA2-PSK (AES/TKIP) Encryption, 64/128/152-bit WEP Encryption
Wireless Advanced: Beacon Interval/RTS Threshold/Fragmentation, Threshold/DTIM Interval/AP Isolation/Short GI/Wi-Fi Multimedia
Management: Discovery and Remote Management via Pharos Control application, HTTP/HTTPS Web-based management, System Log, SNMP Agent(v2c), Ping Watch Dog, Dynamic DDNS, SSH Server
System Tools: Wireless Signal Quality Indicators - Signal Strength/Noise/Transmit CCQ/CPU/Memory, Monitors - Throughput/Stations/Interfaces/ARP/Routes/WAN/DHCP, Spectrum Analyzer, Speed Test, Ping, Traceroute
Signal Rate: Up to 300Mbps (40MHz, Dynamic), Up to 144.4Mbps (20MHz, Dynamic), Up to 72.2Mbps (10MHz, Dynamic), Up to 36.1Mbps (5MHz, Dynamic)
Receiver sensitivity: 802.11b 11M@ -95dBm, 5.5M@ -96dBm, 2M@ -96dBm, 1M@ -96dBm 802.11g 54M@ -79dBm 48M@ -80dBm 36M@ -84dBm 6-24M@ -88dBm, 802.11n MCS15 -76dBm, MCS14 -78dBm, MCS13 -80dBm, MCS12 -84dBm, MCS11 -87dBm, MCS10 -91dBm, MCS9 -93dBm, MCS8 -96dBm, MCS7 -76dBm, MCS6 -78dBm, MCS5 -80dBm, MCS4 -84dBm, MCS3 -87dBm, MCS2 -91dBm, MCS1 -93dBm, MCS0 -96dBm
Antenna: Built-in 9dBi 2x2 Dual-polarized Directional Antenna
Beam width: 65° (H-Plane) / 35° (E-Plane)
Dimensions: 224 x 79 x 60 mm
Power Consumption: 10.5 Watts Max (When deployed using Passive PoE, the power drawn from the power source will be higher by some amount depending on the length of the connecting cable)
Power Supply: Passive Power over Ethernet via LAN0 (+4,5pins; -7,8pins), Voltage range 16-27VDC
Protection: 15KV ESD Protection, 6000V Lightning Protection
Enclosure: Outdoor ASA stabilized plastic material, IPX5 waterproof Certification
Package Contents: Outdoor Wireless CPE, 24V 1A Passive PoE Adapter, Pole Mounting Straps, AC Power Cord, Installation Guide
Operating temperatures: -30°C + 70°C
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7, MAC OS, NetWare, UNIX or Linux.
Certificates: CE, FCC, RoHS, IPX5
Warranty: 5 years
Manufacturer: Tp-Link



#08940

Net Price:
46,40 EUR
Unit: pcs

300Mbps Wireless access point, 5GHz (TP-LINK CPE510)

Processor: Qualcomm Atheros Enterprise AR9350B 560MHz CPU, MIPS 74Kc
Memory: 64MB DDR2 RAM, 8MB Flash
Standards: IEEE 802.11a, IEEE 802.11n
Ports: 1 10/100Mbps Shielded Ethernet Port (LAN0, Passive PoE in), 1 10/100Mbps Shielded Ethernet Port (LAN1, Passive PoE Passthrough), 1 Grounding Terminal, 1 Reset Button
Wireless Configurations: Pharos MAXstream TDMA Technology, 802.11a/n Modes, Selectable Channel Width 5/10/20/40MHz, Automatic Channel Selection, Transmission Power Control, Dynamic Frequency Selection (DFS), WDS Enable/Disable, SSID Broadcast Enable/Disable, Multi-SSID with VLAN Tagging (AP mode only), Distance/ACK Timeout Setting, Wireless MAC Address Filter
Security: WPA/WPA2, WPA-PSK/WPA2-PSK (AES/TKIP) Encryption, 64/128/152-bit WEP Encryption
Wireless Advanced: Beacon Interval/RTS Threshold/Fragmentation, Threshold/DTIM Interval/AP Isolation/Short GI/Wi-Fi Multimedia
Management: Discovery and Remote Management via Pharos Control application, HTTP/HTTPS Web-based management, System Log, SNMP Agent(v2c), Ping Watch Dog, Dynamic DDNS, SSH Server
System Tools: Wireless Signal Quality Indicators - Signal Strength/Noise/Transmit CCQ/CPU/Memory, Monitors - Throughput/Stations/Interfaces/ARP/Routes/WAN/DHCP, Spectrum Analyzer, Speed Test, Ping, Traceroute
Signal Rate: Up to 300Mbps (40MHz, Dynamic), Up to 144.4Mbps (20MHz, Dynamic), Up to 72.2Mbps (10MHz, Dynamic), Up to 36.1Mbps (5MHz, Dynamic)
Receiver sensitivity: 802.11a 54M@ -75dBm 48M@ -76dBm 36M@ -83dBm 6-24M@ -95dBm, 802.11n MCS15 -73dBm, MCS14 -74dBm, MCS13 -76dBm, MCS12 -80dBm, MCS11 -83dBm, MCS10 -88dBm, MCS9 -90dBm, MCS8 -93dBm, MCS7 -73dBm, MCS6 -74dBm, MCS5 -76dBm, MCS4 -80dBm, MCS3 -83dBm, MCS2 -88dBm, MCS1 -90dBm, MCS0 -93dBm
Antenna: Built-in 13dBi 2x2 Dual-polarized Directional Antenna
Beam width: 45° (H-Plane) / 30° (E-Plane)
Dimensions: 224 x 79 x 60 mm
Power Consumption: 13 Watts Max (When deployed using Passive PoE, the power drawn from the power source will be higher by some amount depending on the length of the connecting cable)
Power Supply: Passive Power over Ethernet via LAN0 (+4,5pins; -7,8pins), Voltage range 16-27VDC
Protection: 15KV ESD Protection, 6000V Lightning Protection
Enclosure: Outdoor ASA stabilized plastic material, IPX5 waterproof Certification
Package Contents: Outdoor Wireless CPE, 24V 1A Passive PoE Adapter, Pole Mounting Straps, AC Power Cord, Installation Guide
Operating temperatures: -30°C + 70°C
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7, MAC OS, NetWare, UNIX or Linux.
Certificates: CE, FCC, RoHS, IPX5
Warranty: 5 years
Manufacturer: Tp-Link



#04661

Net Price:
24,70 EUR
Unit: pcs

300Mbps Wireless Access Point, N (TP-Link EAP110)

- EAP Controller Software enables administrators to easily manage hundreds of EAPs
- Supports passive PoE for convenient installation up to 100meters
- Ceiling mounting design with chassis make it easy to deploy on a wall or ceiling
- Captive portal provides one convenient method of authentication for Wi-Fi guests
- Multi-SSID divides multiple wireless networks for different users
- Enterprise class Wi-Fi security help to decrease network security threats

Standards: IEEE 802.11n/g/b
Ports: Fast Ethernet (RJ-45) Port *1 (Support Passive PoE)
Frequency range: 2.4-2.4835GHz
Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)
EIRP: FCC <26dBm(2.4GHz), CE <20dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
EAP Controller Software: Yes
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
Telnet: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: Internal 2* 3dBi Omni
Dimensions: 7.1 x 7.1 x 1.9in. (180*180*47.5mm)
Power: 24VDC / 1A Passive PoE Supply
Power Consumption: 7.7 W
Mounting: Ceiling /Wall Mounting (Kits included)
Physical Security Lock: Kensington Lock Slot
Watch Dog: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: Wireless Access Point EAP110, Passive PoE Adapter, Power Adapter, Mounting Kits, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10
Certificates: CE, FCC, RoHS
Warranty: 5 years



#04660

Net Price:
28,90 EUR
Unit: pcs

300Mbps Wireless Access Point, N (TP-Link EAP115)

- Free Auranet Controller Software enables administrators to easily manage hundreds of EAPs
- The user-friendly Cluster Mode allows manage up to 24 (EAP115) without requiring any extra hardware or software
- Supports Power over Ethernet (802.3af) for convenient and affordable installation
- Simple mounting design for easy attachment to a wall or ceiling
- Captive portal provides one convenient method of authentication for Wi-Fi guests
- Enterprise class Wi-Fi security help to decrease network security threats
- Multi-SSID divides multiple wireless networks for different user types

Standards: IEEE 802.11n/g/b
Ports: Fast Ethernet (RJ-45) Port *1 (ETH1 Support IEEE802.3af PoE)
Frequency range: 2.4-2.4835GHz
Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)
EIRP: FCC <26dBm(2.4GHz), CE <20dBm
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
EAP Controller Software: Yes
Email Alerts: Yes
LED ON/OFF Control: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
System Logging Local/Remote Syslog: Local/Remote Syslog
Telnet: Yes
Web-based Management: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes
Antenna: Internal 2* 3dBi Omni
Dimensions: 7.1 x 7.1 x 1.9in. (180*180*47.5mm)
Power: PoE or External 12VDC / 1A Power Supply
Power Consumption: 5 W
Mounting: Ceiling /Wall Mounting (Kits included)
Physical Security Lock: Kensington Lock Slot
Watch Dog: Yes
Operating Temperature: 0°C~40°C (-32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
Package Contents: Wireless Access Point EAP115, Power Adapter, Mounting Kits, Installation Guide
System Requirements: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10
Certificates: CE, FCC, RoHS
Warranty: 5 years



Wireless Access Point UniFi UAP 2.4GHz (Ubiquiti UAP)

The UniFiC Enterprise Wi-Fi System is a scalable enterprise access point solution designed to be easily deployed and managed. UniFi Access Point (AP) indoor models have a sleek design and can be easily mounted to a ceiling tile or wall using the included mounting hardware. UniFi AP (UAP) outdoor models have a form factor built to last outdoors.

The UniFi Enterprise Wi-Fi System includes the UniFi Controller software. The software installs on any PC, Mac, or Linux machine within the network and is easily accessible through any standard web browser. Using the UniFi Controller software, an Enterprise Wi-Fi network can be quickly configured and administered without any special training. Real-time status, automatic UAP device detection, map loading, and advanced security options are all seamlessly integrated.

Networking Interface (Mbps): 1 x 10/100 Ethernet Ports
Buttons: Reset
Antennas: 2 Integrated (Supports 2x2 MIMO with Spatial Diversity)
Wi-Fi Standards: 802.11 b/g/n
Power Method: Passive Power over Ethernet (12-24V)
Power Supply: 24V, 0.5A PoE Adapter (Included)
Maximum Power Consumption: 4 W
Maximum TX Power: 20 dBm
BSSID: Up to Four Per Radio
Dimensions: 200 x 200 x 36.5 mm
Weight: 290 g (430 g with Mounting Kits)
Power Save: Supported
Wireless Security: WEP, WPA-PSK, WPA-TKIP, WPA2 AES, 802.11i
Certifications: CE, FCC, IC
Mounting: Wall/Ceiling (Kits Included)
Operating Temperature: -10 + 70° C
Operating Humidity: 5 + 80% Condensing
Advanced Traffic Management
VLAN: 802.1Q
Advanced QoS: Per-User Rate Limiting
Guest traffic isolation: Supported
WMM: Voice, Video, Best Effort, and Background
Concurrent Clients: 200+
Supported Data Rates (Mbps)
802.11n: 6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11b: 1, 2, 5.5, 11 Mbps
802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
Manufacturer: Ubiquiti



#08911

Net Price:
117,00 EUR
Unit: pcs

Wireless Access Point UniFi UAP Outdoor-5 (Ubiquiti UAP-Outdoor5)

The UniFiC Enterprise Wi-Fi System is a scalable enterprise access point solution designed to be easily deployed and managed. UniFi Access Point (AP) indoor models have a sleek design and can be easily mounted to a ceiling tile or wall using the included mounting hardware. UniFi AP (UAP) outdoor models have a form factor built to last outdoors.

The UniFi Enterprise Wi-Fi System includes the UniFi Controller software. The software installs on any PC, Mac, or Linux machine within the network and is easily accessible through any standard web browser. Using the UniFi Controller software, an Enterprise Wi-Fi network can be quickly configured and administered without any special training. Real-time status, automatic UAP device detection, map loading, and advanced security options are all seamlessly integrated.

Networking Interface (Mbps): 2 x 10/100 Ethernet Ports
Buttons: Reset
Antennas: 2 External 6 dBi Omni Antennas Included, 191 mm (Length), 13mm (Diameter)
Wi-Fi Standards: 802.11 a/n
Power Method: Passive Power over Ethernet (12-24V), 802.3af Supported
Power Supply: 24V, 1A PoE Adapter (Included)
Maximum Power Consumption: 6,5 W
Maximum TX Power: 27 dBm
BSSID: Up to Four Per Radio
Dimensions: 170 x 80 x 30 mm
Weight: 230 g (274 g with Antennas)
Power Save: Supported
Wireless Security: WEP, WPA-PSK, WPA-TKIP, WPA2 AES, 802.11i
Certifications: CE, FCC, IC
Mounting: Wall/Ceiling (Kits Included)
Operating Temperature: -30 + 75° C
Operating Humidity: 5 + 95% Condensing
Advanced Traffic Management
VLAN: 802.1Q
Advanced QoS: Per-User Rate Limiting
Guest traffic isolation: Supported
WMM: Voice, Video, Best Effort, and Background
Concurrent Clients: 100+
Supported Data Rates (Mbps)
802.11n: 6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
Manufacturer: Ubiquiti



#07019

Net Price:
20,50 EUR
Unit: pcs

Wireless N Access Point (TP-Link TL-WA801ND)

Standards: IEEE 802.11n, IEEE 802.11b/g
Ports: 1x 10/100 Mbps RJ-45 PoE (LAN)
Frequency range: 2400 MHz + 2483,5 MHz
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Operating modes: AP Mode, Multi-SSID Mode, AP Client Mode, Repeater Mode (WDS / Universal), AP+ Bridge mode
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 2x 4 dBi
WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK, WPA2, WPA2-PSK, TKIP, AES
WLAN features: 2T2R MIMO, CCA, QSS button, 4x SSIDs, VLAN support
Auto MDI/MDIX: yes
Dimensions: 174x120x28,8 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Power: 9V AC 0.8A, ~230V 50Hz
Certificates: CE, FCC
Warranty period: 24 months
Manufacturer: TP-Link



#07032

Net Price:
31,50 EUR
Unit: pcs

Wireless N Access Point (TP-Link TL-WA901N)

Standards: IEEE 802.11n, IEEE 802.11b/g
Ports: 1x 10/100 Mbps RJ-45 PoE (LAN)
Frequency range: 2400 MHz + 2483,5 MHz
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Operating modes: AP Mode, Multi-SSID Mode, AP Client Mode, Repeater Mode (WDS / Universal), AP+ Bridge mode
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 3x Fixed Omni-Directional Antennas
WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK, WPA2, WPA2-PSK, TKIP, AES
WLAN features: 3T3R MIMO, CCA, QSS button, 4x SSIDs, VLAN support
Auto MDI/MDIX: yes
Dimensions: 174x120x28 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Power: 9V AC 1A, ~230V 50Hz
Certificates: CE, FCC
Warranty period: 24 months
Manufacturer: TP-Link



#09118

Net Price:
5,51 EUR
Unit: pcs

Mini Wireless adapter N USB 2.0, 300Mbps (TP-Link Mercusys MW300UM)

- Provides fast 300Mbps Wi-Fi connections for wired devices
- Ideal for online gaming, HD streaming, web browsing, and more
- Supports Windows 10/8.1/8/7/XP (32/64bit)

Standards: IEEE 802.11 b/g, IEEE 802.11n
Interface: USB 2.0 typ A
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 300 Mbps when connected to 11n device
Max. output power: 20 dBm
WLAN security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Drivers: Windows 10/8.1/8/7/XP (32/64bit)
Dimensions: 42.9 x 17.2 x 8.5 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Manufacturer: TP-Link


#08549

Net Price:
8,42 EUR
Unit: pcs

Mini Wireless adapter N USB 2.0, 300Mbps (TP-Link TL-WN823N)

- 300Mbps wireless speed ideal for smooth HD video, voice streaming and online gaming
- Mini-sized design for convenient portability with a reliable high performance
- SoftAP Mode - Turn a wired internet connection to a PC or Laptop into a Wi-Fi hotspot
- Easily setup a secure wireless connection with one-touch WPS button

Standards: IEEE 802.11 b/g, IEEE 802.11n
Interface: USB 2.0 typ A
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 300 Mbps when connected to 11n device
Max. output power: 20 dBm
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Operating modes: Soft AP Mode, Client Mode (support Ad-hoc/Infrastructure network)
WLAN security: 64/128 bits WEP, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES)
Roaming support: yes
WLAN features: MIMO, CCA
Drivers: Windows Windows XP/Vista/7
Dimensions: 39 x 18.35 x 7.87mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, FCC, RoHS
Manufacturer: TP-Link


#09117

Net Price:
7,63 EUR
Unit: pcs

Wireless adapter Lite N USB 2.0 High Gain (TP-Link Mercusys MW300UH)

- Provides fast 300Mbps Wi-Fi connections for wired devices
- Two 5dBi high gain antennas deliver enhanced reception and transmission performance
- With 2x2 MIMO, users can easily access to high-speed wireless connection
- Supports Windows 10/8.1/8/7/XP (32/64bit)

Standards: IEEE 802.11 b/g, IEEE 802.11n
Interface: micro USB 2.0
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 300 Mbps when connected to 11n device
Max. output power: 20 dBm
WLAN security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Drivers: Windows Windows 10/8.1/8/7/XP (32/64 bit)
Dimensions: 113.2 x 63.8 x 21.7 mm (without antennas), 113.2 x 100.5 x 201.1 mm (with vertical antennas)
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, RoHS
Manufacturer: TP-Link


#07054

Net Price:
8,42 EUR
Unit: pcs

Wireless adapter Lite N USB 2.0 High Gain (TP-Link TL-WN722N)

Standards: IEEE 802.11 b/g, IEEE 802.11n
Interface: USB 2.0 typ A
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 150 Mbps when connected to 11n device
Max. output power: 20 dBm
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Operating modes: Ad-hoc, infrastructure
Antenna: detachable, RP-SMA
WLAN security: 64/128 bits WEP, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES)
Roaming support: yes
Drivers: Windows Windows 2k/XP/Vista
Dimensions: 93,5x26x11 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, FCC
Manufacturer: TP-Link


#08424

Net Price:
11,00 EUR
Unit: pcs

Wireless adapter Lite N USB 2.0 High Gain (TP-Link TL-WN822N)

- 11N speed allows for the best HD video streaming and internet calling experience
- Dual external antennas deliver enhanced reception and transmission performance
- Easy one-touch wireless security encryption with the Quick Security Setup button
- 1.5 meter USB extension cable enables convenient, flexible deployment
- Supports Windows XP / Vista / 7

Standards: IEEE 802.11 b/g, IEEE 802.11n
Interface: mini USB 2.0
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 300 Mbps when connected to 11n device
Max. output power: 20 dBm
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Operating modes: Ad-hoc, infrastructure
Antenna: detachable, RP-SMA
WLAN security: 64/128 bits WEP, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES)
Roaming support: yes
Drivers: Windows Windows 2k/XP/Vista/7
Dimensions: 90 x 68 x 16,8mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, FCC
Manufacturer: TP-Link


#06433

Net Price:
8,24 EUR
Unit: pcs

Wireless adapter N USB 2.0 (TP-Link TL-WN821N)

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11 b/g
Interface: USB 2.0 typ A
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 300 Mbps
Max. output power: 20 dBm
Operating modes: Ad-hoc, infrastructure
WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK, TKIP, AES
Roaming support: yes
WLAN features: MIMO, CCA
Drivers: Windows Windows 2k/XP/Vista
Dimensions: 94x26x11 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, FCC
Warranty period: 24 months
Manufacturer: TP-Link


#08463

Net Price:
5,88 EUR
Unit: pcs

Wireless adapter N USB NANO 2.0 (TP-Link TL-WN725N)

Standards: IEEE 802.11b/g/n
Interface: USB 2.0 typ A
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 150 Mbps
Max. output power: 20 dBm
Operating modes: Ad-hoc, infrastructure
WLAN security: WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES), IEEE 802.1X support
Drivers: Windows Windows XP/Vista/7
Dimensions: 18.6x15x7.1mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, FCC, IC, RoHS
Warranty period: 24 months
Manufacturer: TP-Link


#06431

Net Price:
7,56 EUR
Unit: pcs

Wireless N PCMCIA adaptor (TP-Link TL-WN811N)

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g
Interface: Cardbus 32-bit Type II
Frequency range: 2400MHz - 2483,5MHz
Max. speed: 300 Mbps
Max. output power: 20 dBm
Operating modes: Ad-Hoc, Infrastructure
WLAN security: 64/128/152-bit WEP, WPA, WPA2, TKIP/AES
Drivers: Windows 2000/XP/Vista
Roaming support: yes
Dimensions: 124x54x11.3 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, FCC
Warranty: 2 years
Manufacturer: TP-Link


#06427

Net Price:
7,80 EUR
Unit: pcs

Wireless N PCMCIA adaptor (TP-Link TL-WN910N)

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g
Interface: Cardbus 32-bit
Frequency range: 2400MHz - 2483,5MHz
Max. speed: 300 Mbps
Max. output power: 20 dBm
Operating modes: Ad-Hoc, Infrastructure
WLAN security: 64/128/152-bit WEP, WPA, WPA2, TKIP/AES
Drivers: Windows 2000/XP/Vista
Dimensions: 124x54x11.3 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, FCC
Warranty: 2 years
Manufacturer: TP-Link



#08464

Net Price:
9,47 EUR
Unit: pcs

Wireless PCI Express N adaptor (TP-Link TL-WN781ND)

Standards: IEEE 802.11b/g/n
Interface: PCI Express
Frequency range: 2400 MHz ± 2483,5 MHz
Max. speed: 150 Mbps
Max. output power: 20 dBm
Operating modes: Ad-Hoc, Infrastructure
WLAN security: 64/128-bit WEP, WPA, WPA2, WPA-PSK/WPA2-PSK (TKIP/AES), Wireless MAC Filtering
Antenna: detachable, SMA RP
Roaming support: yes
Drivers: Windows XP/Vista/7/8
Dimensions: 120.8x78.5x21.5 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, FCC, RoHS
Warranty period: 24 months
Manufacturer: TP-Link



#08552

Net Price:
13,20 EUR
Unit: pcs

Wireless PCI-Express N adaptor, 300Mbps (TP-Link TL-WN881ND)

- Wireless N speed up to 300Mbps makes it ideal for video streaming, online gaming and Internet calls
- MIMO technology with stronger signal penetration strength, wider wireless coverage, providing better performance and stability
- Easily setup a highly secured wireless link with WPSTN (Wi-Fi Protected Setup)
Standards: IEEE 802.11n, IEEE 802.11b/g
Interface: PCI Express
Frequency range: 2400 MHz ± 2483,5 MHz
Max. speed: 300 Mbps
Max. output power: <20 dBm
Operating modes: Ad-Hoc, Infrastructure
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK
Antenna: Omni Directional, Detachable (RP-SMA)
Antenna Gain: 2x2dBi
Roaming support: yes
Drivers: Windows XP/Vista/7
Dimensions: 120.8 x 78.5 x 21.5mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, FCC, RoHS
Warranty period: 24 months
Manufacturer: TP-Link



#06257

Net Price:
59,70 EUR
Unit: pcs

Omada Cloud Controller (TP-Link OC200)

- Professional centralized management for Wi-Fi network
- Free cloud access to manage from anywhere, anytime
- PoE (802.3af/802.3at) supported for easy installation
- Industry leading hardware design with powerful chipset, durable metal casing, and USB port for auto backup
- Omada App for a convenient management
- Secure guest network with multiple login options(Facebook Wi-Fi, SMS login, Voucher)
Ports: 2*10/100Mbps Ethernet Port, 1*USB 2.0 Port, 1*Micro USB Port
Features:
Wireless Function: L3 Management, Multi-SSID, Load Balance, Band Steering, Airtime Fairness, Beamforming, Rate Limit, Wireless Schedule, QoS
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection
AP Management: Automatic Discovery, Unified Configuration, Reboot Schedule, Batch Firmware Upgrade, LED ON/OFF
Authentication: Captive Portal
Dimensions: 3.9x3.9x1.0in. (100x98x25mm)
Operating temperature: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Power: 802.3af/at PoE or Micro USB（DC 5V/Minimum 1A）
Certificates:CE, FCC, RoHS



#09124

Net Price:
144,00 EUR
Unit: pcs

Omada Cloud Controller (TP-Link OC300)

- Centralized management for up to 500 Omada access points, JetStream switches, and SafeStream routers.
- Cloud access to manage from anywhere, anytime.
- Locally monitor and manage devices with the ultimate security and stability.
- The Omada app for convenient management.
- Industry-leading hardware design with a powerful chipset, durable metal casing, and USB 3.0 port for auto backup.
- Batch management, multi-site management, and remote firmware updates benefit network maintenance.
- The easy-to-use dashboard makes it easy to see your real-time network status and check network usage and traffic distribution.
- Network topology helps IT admins quickly see and troubleshoot connections at a glance.
Ports: 2*10/100/1000Mbps Ethernet Port, 1*USB 3.0 Port
Features:
Omada App: Yes
Centralized Management: Up to 500 Omada access points, JetStream switches, and SafeStream routers*, Up to 15,000 clients
*Only some JetStream switches and Safestream gateways can be centrally managed by OC300, please refer to www.tp-link.com/business-networking/all-omada/ to find all the models supported by OC300
Cloud Access: Yes
L3 Management: Yes
Multi-site Management: Yes
Management Features: Automatic Device Discovery, Batch Configuration, Batch Firmware Upgrading, Intelligent Network Monitoring, Abnormal Event Warnings, Unified Configuration, Reboot Schedule, Captive Portal Configuration
Dimensions: 11.6 x 7.1 x 1.7 in (294 x 180 x 44 mm)
Power: 100-240 V~50/60 Hz, 0.6 A
Package Contents: Omada Hardware Controller OC300, Quick Installation Guide, Ethernet Cable, Power Cord, Rackmount Kit
System Requirements: Microsoft Windows C10, 8, 7, Vista™, XP or MAC OS, NetWareC, UNIXC or Linux
Environment: Operating Temperature 0-50 °C (32-122 °F), Storage Temperature -40-70 °C (-40-158 °F), Operating Humidity 10-90% RH non-condensing, Storage Humidity 5-90% RH non-condensing
Certificates:CE, FCC, RoHS



#09116

Net Price:
10,60 EUR
Unit: pcs

300Mbps Wireless Range Extender (TP-Link Mercusys MW300RE)

- Range Extender mode boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Three external antennas with MIMO technology help set the MW300RE apart from ordinary range extenders
- Easily expand wireless coverage at easy two-touch setup or a push of WPS button
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- The multicolor LED helps you to find the right location to deliver the best Wi-Fi extension
HARDWARE FEATURES:
Interface: 1x10/100Mbps Auto-Sensing RJ45 Port
Plug Type: EU
Button: Reset Button, WPS Button
Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensions (W x D x H): 101 x 74.8 x 75.8 mm
Antenna Type: 3 x external
WIRELESS FEATURES
Frequency: 2.4-2.4835GHz
EIRP: <20dBm (EIRP)
Wireless Security: WPA-PSK/WPA2-PSK
OTHERS
Certification: CE, RoHS
Package Contents: MW300RE, Quick Installation Guide
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.



#08541

Net Price:
15,60 EUR
Unit: pcs

300Mbps Wireless Range Extender (TP-Link TL-WA850RE)

- Range Extender mode boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- Easily expand wireless coverage at a push of Range Extender button
- Ethernet port allows the Extender to function as a wireless adapter to connect wired devices
HARDWARE FEATURES:
Interface: 1x10/100Mbps Auto-Sensing RJ45 Port
Plug Type: EU
Button: Reset Button, Range Extender Button
Power Consumption: About 3W
Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensions (W x D x H): 4.3x 2.6 x 3.0in. (110.0 x 65.8 x 75.2mm)
Antenna Type: 2 x internal
WIRELESS FEATURES
Frequency: 2.4-2.4835GHz
Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)
EIRP: <20dBm (EIRP)
Reception Sensitivity: 270M -68dBm@10% PER, 130M -68dBm@10% PER, 108M -68dBm@10% PER, 54M -73dBm@10% PER, 11M -85dBm@8% PER, 6M -88dBm@10% PER, 1M -90dBm@8% PER
Wireless Modes: Range Extender
Wireless Functions: WMM (Wi-Fi Multimedia), Wireless MAC Address Filtering, Wireless Statistic, Domain Login Function
Wireless Security: 64/128/152-bit WEP, WPA-PSK / WPA2-PSK
OTHERS
Certification: CE, FCC, RoHS
Package Contents: TL-WA850RE, RJ-45 Patchcord, Power supply unit, Resource CD, Quick Installation Guide
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC OS, NetWare, UNIX or Linux.
Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.



#08542

Net Price:
13,50 EUR
Unit: pcs

300Mbps Wireless Range Extender (TP-Link TL-WA854RE)

- Range Extender mode boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- Easily expand wireless coverage at a push of Range Extender button

HARDWARE FEATURES:

Plug Type: EU
Button: Reset Button, Range Extender Button
Power Consumption: About 3W
Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensions (W x D x H): 4.3x 2.6 x 3.0in. (110.0 x 65.8 x 75.2mm)

Antenna Type: 2 x internal

WIRELESS FEATURES

Frequency: 2.4-2.4835GHz
Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)
EIRP: <20dBm (EIRP)

Reception Sensitivity: 270M -68dBm@10% PER, 130M -68dBm@10% PER, 108M -68dBm@10% PER, 54M -73dBm@10% PER, 11M -85dBm@8% PER, 6M -88dBm@10% PER, 1M -90dBm@8% PER

Wireless Modes: Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless MAC

Address Filtering, Wireless Statistic, Domain Login Function

Wireless Security: 64/128/152-bit WEP, WPA-PSK /

WPA2-PSK

OTHERS

Certification: CE, FCC, RoHS

Package Contents: TL-WA854RE, Resource CD, Quick Installation Guide

System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7,8, MAC OS, NetWare, UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.



#04587

Net Price:
16,50 EUR
Unit: pcs

300Mbps Wireless Range Extender (TP-Link TL-WA855RE)

- Boosts your existing Wi-Fi coverage to deliver fast and reliable wired and wireless connectivity
- External antennas for faster and more reliable Wi-Fi
- Supports AP mode which creates a new Wi-Fi Access point
- Easily expand wireless coverage at a push of the Range Extender button
- Set the Power Schedule for the range extender for power-saving
- Tether App allows easy access and management with your mobile devices remotely
- Works with Any Wi-Fi Router

HARDWARE FEATURES:

Interface: 1x10/100Mbps Auto-Sensing RJ45 Port

Plug Type: EU

Button: Reset Button, Range Extender Button

Power Consumption: About 3W

Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE

802.11b

Dimensions (W x D x H): 2.0x 1.3 x 2.6in. (52 x 34 x 65mm)

Antenna Type: 2 x external

WIRELESS FEATURES

Frequency: 2.4-2.4835GHz

Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)

EIRP: <20dBm (EIRP)

Reception Sensitivity: 270M -68dBm@10% PER, 130M

-68dBm@10% PER, 108M -68dBm@10% PER, 54M

-68dBm@10% PER, 11M -68dBm@8% PER, 6M

-68dBm@10% PER, 1M -68dBm@8% PER

Wireless Modes: Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless MAC

Address Filtering, Wireless Statistic, Domain Login Function

Wireless Security: 64/128/152-bit WEP, WPA-PSK /

WPA2-PSK

OTHERS

Certification: CE, FCC, RoHS

Package Contents: TL-WA855RE, RJ-45 Patchcord, Quick Installation Guide

System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7,8, MAC OS, NetWare, UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.



#08936

Net Price:
22,10 EUR
Unit: pcs

300Mbps Wireless Range Extender (TP-Link TL-WA860RE)

- Range Extender mode boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- Extra power socket making sure that no power outlet is going to waste
- 2 fixed external antennas provide excellent WiFi coverage and reliability
- Easily expand wireless coverage at a push of Range Extender button

HARDWARE FEATURES:

Interface: 1x10/100Mbps Auto-Sensing RJ45 Port

Plug Type: EU

Button: Reset Button, Range Extender Button

Power Consumption: About 3W

Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions (W x D x H): 4.3x 2.6 x 3.0in. (110.0 x 65.8 x 75.2mm)

Antenna Type: 2 x external

WIRELESS FEATURES

Frequency: 2.4-2.4835GHz

Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)

EIRP: <20dBm (EIRP)

Reception Sensitivity: 270M -69dBm@10% PER, 130M

-69dBm@10% PER, 108M -69dBm@10% PER, 54M

-69dBm@10% PER, 11M -86dBm@8% PER, 6M

-89dBm@10% PER, 1M -91dBm@8% PER

Wireless Modes: Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless MAC

Address Filtering, Wireless Statistic, Domain Login Function

Wireless Security: 64/128/152-bit WEP, WPA-PSK /

WPA2-PSK

OTHERS

Certification: CE, FCC, RoHS

Package Contents: TL-WA860RE, RJ-45 Patchcord, Power supply unit, Resource CD, Quick Installation Guide

System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7,8, MAC OS, NetWare, UNIX or Linux.

Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.



#04579

Net Price:
20,50 EUR
Unit: pcs

300Mbps Wireless N Nano Router (TP-Link TL-WR802N)

- 300Mbps wireless data rates is ideal for video streaming, online gaming and Internet calling
- Pocket-size - Ideal for home and travel use
- Supports Router, Repeater, Client, AP and hotspot operation modes
- Powered through a micro USB port by an external power adapter or USB connection to a computer provides flexibility for any situation
- Easy installation in minutes



#09161

Net Price:
28,80 EUR
Unit: pcs

300Mbps Wireless N VDSL/ADSL Modem Router, (TP-Link TD-W9960)

- Versatile Connectivity - With DSL and LAN/WAN ports, TD-W9960 is fully compatible with the VDSL2/ADSL2+/ADSL2/ADSL standards and also works with fiber/cable access.
- Boosted Speeds - Superfast VDSL broadband speeds of up to 100Mbps together with 300Mbps Wi-Fi.
- Maximized Range - Powerful external antennas provide far-reaching wireless coverage in every direction.
- Effortless Management - Set up in minutes with the powerful Tether app or intuitive web interface and manage the network from anywhere.



#06248

Net Price:
33,60 EUR
Unit: pcs

300Mbps Wireless N VDSL/ADSL Modem Router, USB port (TP-Link TD-W9970)

- Featuring dual WAN ports, compatible with VDSL/ADSL/Fiber/Cable services
- Providing broadband speeds up to 100Mbps over VDSL2 and backward compatible with ADSL
- Share files, media and printers with your friends or family using the multi-functional USB port



#09122

Net Price:
65,00 EUR
Unit: pcs

3G/4G Wireless N Router, 300Mbps (TP-Link TL-MR100)

- Cutting-edge 4G network - Share internet access with up to 32 Wi-Fi devices and enjoy download speeds of up to 150 Mbps
- Plug a SIM card and play - No configurations needed, compatibility of SIM cards in 100+ countries are assured by years of field tests
- Two detachable advanced LTE antennas - Enjoy stable and efficient connections to every device thanks to the two external antennas
- Wi-Fi router mode - Plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection

HARDWARE FEATURES:

Interface: 1 10/100Mbps LAN/WAN Port, 1 10/100Mbps LAN Ports, 1 SIM Card Slot
Button:WPS/Reset Button
External Power Supply:9VDC/0.85A
Dimensions (W x D x H):6.06×4.49×1.42 in (154×114×36 mm)

Antenna Type: 2 Detachable External 4G LTE Antennas

WIRELESS FEATURES:

Wireless Standards:IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency:2.4GHz
EIRP:<20dBm
Signal Rate: 300Mbps at 2.4GHz
Wireless Security:64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
Network Type: 4G- FDD-LTE- B1/B3/B5/B7/B8/B20 (2100/1800/850/2600/900/800 MHz), TDD-LTE- B38/B40/B41 (2600/2300/2500 MHz), 3G- HSPA/UMTS- B1/B5/B8 (2100/850/900 MHz)
SOFTWARE FEATURES:
Security: IPv4 SPI Firewall, IP and MAC Address Binding
Operating Modes: 3G/4G Router, Wireless Router
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
Management: Local Management, Remote Management
DHCP: Server, DHCP Client List, Address Reservation
Port Forwarding: ALG, Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, NO-IP
Protocols: IPv4, IPv6
Guest Network: 2.4 GHz Guest Network
Administration: Upgrade Firmware, Factory Default, System Log, Diagnostic Tools
OTHERS:
Certification:CE, RoHS
Package Contents:3G/4G Wireless AC Router, RJ45 Ethernet Cable, Power Adapter, Quick Installation Guide
Requirements: Microsoft Windows
98SE/NT/2000/XP/VistaTM/7/8/10, MAC OS, NetWare, UNIX or Linux, Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other, Java-enabled browser, Micro SIM Card
Environment:Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing



#04605

Net Price:
73,00 EUR
Unit: pcs

3G/4G Wireless N Router, 300Mbps (TP-Link TL-MR6400)

- Share your 4G LTE network with multiple Wi-Fi devices and enjoy download speeds of up to 150Mbps
- Wireless N speeds of up to 300Mbps
- Integrated antennas provide stable wireless connections
- Requires no configuration - just insert a SIM card and turn it on to enjoy high speed internet access
- LAN/WAN port provides options and flexibility, allowing you to choose your connection type

HARDWARE FEATURES:

Interface: 1 10/100Mbps LAN/WAN Port, 3 10/100Mbps LAN Ports, 1 SIM Card Slot
Button:WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button
External Power Supply:12VDC/1A
Dimensions (W x D x H):7.95 x 5.55 x 1.32 in. (202 x 141 x 33.6 mm)

Antenna Type: 2 Internal Wi-Fi Antennas, , 2 Detachable External 4G LTE Antennas

WIRELESS FEATURES:

Wireless Standards:IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency:2.4GHz
EIRP:<20dBm
Signal Rate: 300Mbps at 2.4GHz
Wireless Security:Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, Wireless MAC Filtering
SOFTWARE FEATURES:
Security:NAT Firewall, SPI Firewall, MAC / IP / Packet / Application / URL Filtering, Denial of Service(DoS), SYN Flooding, Ping of Death
Operating Modes: 3G/4G Router, Wireless Router
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
Management: Access Control, Local Management, Remote Management
DHCP: Server, Client, DHCP Client List, Address Reservation
Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, NO-IP
VPN Pass-Through: PPTP, L2TP, IPSec
Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall, IP Address Filter/Domain Filter, IP and MAC Address Binding
Protocols: Supports IPv4 and IPv6
Guest Network: 2.4GHz guest network x 1, 5GHz guest network x 1
IPSec VPN: Supports up to 10 IPSec VPN tunnels
Network Type: 4G FDD-LTE Cat4 (800/900/1800/2100/2600MHz), TDD-LTE (2300/2600MHz), 3G DC-HSPA+/HSPA+/HSPA/UMTS (900/2100MHz), 2G EDGE/GPRS/GSM (850/900/1800/1900MHz)
OTHERS:
Certification:CE, FCC, RoHS
Package Contents:3G/4G Wireless AC Router, 1 Antenna, RJ45 Ethernet Cable, Power Adapter, Quick Installation Guide, Micro to Standard SIM Card Adapter, Nano to Standard SIM Card Adapter
System Requirements:Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7/8/8.1, MAC OS, NetWareC, UNIXC or Linux.
Environment:Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing



#09123

Net Price:
87,00 EUR
Unit: pcs

3G/4G Wireless N Telephony Router, 300Mbps (TP-Link TL-MR6500v)

- Cutting-edge 4G network - share internet access with up to 32 Wi-Fi devices and enjoy download speeds of up to 150 Mbps*
- Plug a SIM card and play - no configurations needed, compatibility for SIM cards in 100+ countries are assured by years of field tests
- WiFi speeds up to 300 Mbps - enjoy uninterrupted HD movies, rapid file downloads, seamless video chats, and more at the same time*
- Professional voice functions - supports VoLTE/CSFB/VoIP functions and provides 50 MB of internal storage for 100 minutes of voicemail
- Two detachable advanced LTE antennas - enjoy stable and efficient connections to every device thanks to the two external antennas
- Wi-Fi router mode - plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection

HARDWARE FEATURES:

Interface: 1 10/100Mbps LAN/WAN Port, 2 10/100Mbps LAN Ports, 1 SIM Card Slot, 1 Phone Port
Button:WPS/Reset Button, Wi-Fi ON/OFF Button
External Power Supply:12VDC/1A
Dimensions (W x D x H):7.95 × 5.55 × 1.32 in (202 × 141 × 33.6 mm)

Antenna Type: 2 Detachable External 4G LTE Antennas

WIRELESS FEATURES:

Wireless Standards:IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency:2.4GHz
EIRP:<20dBm
Signal Rate: 300Mbps at 2.4GHz
Wireless Security:64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
Network Type: 4G- FDD-LTE- B1/B3/B5/B7/B8/B20 (2100/1800/850/2600/900/800 MHz), TDD-LTE- B38/B40/B41 (2600/2300/2500 MHz), 3G- HSPA/UMTS- B1/B5/B8 (2100/850/900 MHz)

SOFTWARE FEATURES:

Security: IPv4 SPI Firewall, IP and MAC Address Binding
Operating Modes: 3G/4G Router, Wireless Router
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
Management: Local Management, Remote Management
DHCP: Server, DHCP Client List, Address Reservation
Port Forwarding: ALG, Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS: DynDns, NO-IP
Protocols: IPv4, IPv6
Guest Network: 2.4 GHz Guest Network
Administration: Upgrade Firmware, Factory Default, System Log, Diagnostic Tools
TELEPHONY:
VoIP Standards: SIP(RFC3261)/RTP(RFC1889/3550), G.711A/u, G.729AB, G.726
Integrated Answering Machine: Stores 100 minutes long voice messages internally on the modem router
Advanced Telephone Functions: Call Blocking, Anonymous Call Blocks, Speed Dial, Emergency Number
OTHERS:
Certification:CE, RoHS
Package Contents:3G/4G Wireless AC Router, RJ45 Ethernet Cable, Power Adapter, Quick Installation Guide
Requirements: Microsoft Windows
98SE/NT/2000/XP/VistaTM/7/8/10, MAC OS, NetWare, UNIX or Linux, Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other, Java-enabled browser, Micro SIM Card
Environment:Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing



#08365

Net Price:
19,20 EUR
Unit: pcs

Portable 3G/4G Wireless N Router (TP-Link TL-MR3020)

Share a 3G/4G* mobile connection, compatible with 120+ LTE/HSPA+/UMTS/EVDO 3G/4G USB modems, tested in the field

Travel-size Design, small and light enough to take on the road, enables users to share a 3G/4G* mobile connection wherever 3G/4G* coverage is available

Wireless speed is up to 150Mbps

Three modes available for different situations: 3G/4G* Router, WISP Client Router and Travel Router Mode (AP Mode)

With 3G/4G* and WAN failover back-up strategy, TL-MR3020 can provide a sustained internet connection.

HARDWARE FEATURES:

Interface: 1 10/100Mbps WAN/LAN Port, USB 2.0 Port for 3G/4G modem, a mini USB Port for power supply.
Button: Quick Setup Security Button, Reset Button, Mode Switch

External Power Supply: 5VDC/1.0A
Dimensions (W x D x H): 2.9 x 2.6 x 0.9 in. (74 x 67 x 22 mm)
Antenna Type: Internal Antenna

WIRELESS FEATURES:

Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Frequency: 2.4-2.4835GHz

EIRP: <20dBm

Wireless Modes: 3G Router, Travel Router (AP), WISP Client Router

Wireless Security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, Wireless MAC Filtering

SOFTWARE FEATURES:

DHCP: Server, DHCP Client List, Address Reservation
Port Forwarding: Virtual Server, Port Triggering, DMZ, UPnP
Access Control: Parental Control, Host List, Access Schedule, Rule Management

Security: Firewall, MAC filtering, Denial of Service (DoS)

OTHERS:

Certification: CE, FCC, RoHS
Package Contents: TL-MR3020 router, QIG, Power Adapter, USB Cable, Resource CD, Ethernet Cable
System Requirements: Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7, MAC OS, NetWareC, UNIXC or Linux.

Environment: Operating temperature -10°~60°, Storage Temperature -40°~80°, Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing
Warranty: 2 years limited warranty. Advanced replacement service is available.



#06236

Net Price:
86,50 EUR
Unit: pcs

Router Mesh Deco M5 1-pack (TP-Link DECO M5)

- Standalone coverage up to 2,000 sq. ft.
- Fast dual band WiFi
- Can be added to any TP-Link WiFi System
- Works with Amazon Alexa Voice Assistant

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz

Ports: 2 LAN/WAN Gigabit Ethernet Ports

Processor: Quad-core CPU

Button: 1 Reset button on the underside

Flash: 32 MB

SDRAM: 256 MB

Bluetooth version: 4.2 and above

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 400 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: TP-Link Mesh Technology - MU-MIMO,

Auto Path Selection, AP Steering, Band Steering,

Beamforming

Wireless Security: WPA-PSK/WPA2-PSK

Software Features: Quality of Service - WMM, IPv6 Support,

WAN Type - Dynamic IP/Static IP/PPPoE, Local

Management, Remote Management, DHCP - Server, Client,

Port Forwarding Support, Access Control Blacklist, Firewall

Security SPI Firewall, Protocols Supports IPv4 and IPv6,

Homecare - Antivirus, Parental Controls, Quality of Service,

Speedtest, Monthly Usage Reports, Auto FW Update,

Expand for more deco, Guest Network 2.4 GHz guest

network * 1 - 5 GHz guest network * 1, Beamformig, Easy

setup by Deco App

Antenna: 4 internal antennas per Deco unit

Dimensions: 8#934;4.7 in. x 1.3 in. (8#934;120 mm x 38 mm)

Power: 12 V/1.2 A

Operating Temperature: 0°C~40°C (-32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents: Deco unit, 1 RJ45 Ethernet Cable, Power

Adapter

Smartphone/Tablet Requirements: iOS 8.0 or later, Android

4.3 or later, Bluetooth 4.0 or later

Certificates: CE, FCC, IC, NCC, BSMI, IDA



#06235

Net Price:
200,00 EUR
Unit: pcs

Router Mesh Deco M5 3-pack (TP-Link DECO M5)

- Covers up to 5,500 sq. ft.
- Fast dual band WiFi
- One WiFi name for the entire home
- Connects 100-plus devices
- Works with Amazon Alexa Voice Assistant

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz

Ports: 2 LAN/WAN Gigabit Ethernet Ports

Processor: Quad-core CPU

Button: 1 Reset button on the underside

Flash: 32 MB

SDRAM: 256 MB

Bluetooth version: 4.2 and above

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 400 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: TP-Link Mesh Technology - MU-MIMO,

Auto Path Selection, AP Steering, Band Steering,

Beamforming

Wireless Security: WPA-PSK/WPA2-PSK

Software Features: Quality of Service - WMM, IPv6 Support,

WAN Type - Dynamic IP/Static IP/PPPoE, Local

Management, Remote Management, DHCP - Server, Client,

Port Forwarding Support, Access Control Blacklist, Firewall

Security SPI Firewall, Protocols Supports IPv4 and IPv6,

Homecare - Antivirus, Parental Controls, Quality of Service,

Speedtest, Monthly Usage Reports, Auto FW Update,

Expand for more deco, Guest Network 2.4 GHz guest

network * 1 - 5 GHz guest network * 1, Beamformig, Easy

setup by Deco App

Antenna: 4 internal antennas per Deco unit

Dimensions: 8#934;4.7 in. x 1.3 in. (8#934;120 mm x 38 mm)

Power: 12 V/1.2 A

Operating Temperature: 0°C~40°C (-32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents: 3 Deco units, 1 RJ45 Ethernet Cable, 3

Power Adapters

Smartphone/Tablet Requirements: iOS 8.0 or later, Android

4.3 or later, Bluetooth 4.0 or later

Certificates: CE, FCC, IC, NCC, BSMI, IDA



#09115

Net Price:
13,90 EUR
Unit: pcs

Wireless N broadband ADSL2+ router, 3x LAN (TP-Link Mercusys MW300D)

- High Speed Wi-Fi - 300 Mbps wireless speed for multi-user HD video streaming
- Great Coverage - Two fixed high performance antennas provide maximum omni-directional wireless coverage
- Compatibility - Fully compatible with ADSL2+/ADSL2/ADSL standards
- Effortless Management - Set up in minutes and manage the network with the powerful intuitive web interface.

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g

Ports: 3x 10/100 Mbps RJ-45 (LAN), 1x RJ-11

Button: WPS/Reset Button

Transmission Power: <20dBm (EIRP)

Antenna Type: 2x External Antennas

Wireless Security: WPA-PSK / WPA2-PSK

Wireless Functions: Enable/Disable Wireless Radio

DHCP: Server

External Power Supply : 9V/0.6A

Dimensions: 114 x 94 x 26 mm

Operating temperatures: 0°C + 40°C

Operating humidity: 5% + 90%, non-condensing

Manufacturer: TP-Link



#06247

Net Price:
21,60 EUR
Unit: pcs

Wireless N broadband ADSL2+ router, 4x LAN (TP-Link TD-W8961N)

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g

Ports: 4x 10/100 Mbps RJ-45 (LAN), 1x RJ-11

ADSL Feature: Full-rate ANSI T1.413 Issue 2, ITU-T

G.992.1 (G.dmt), ITU-T G.992.2 (G.lite) ITU-T G.994.1

(G.hs), ITU-T G.992.3 (G.dmt.bis), ITU-T G.992.4 (G.lite.bis),

Supports Annex A/L/M

Frequency range: 2400 MHz + 2483.5 MHz

Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM,

64-QAM

Operating modes: AP Router

Max. speed: 300 Mbps

Max. output power: 20 dBm

Antenna: Omni directional, Detachable, Reverse SMA

WLAN security: Support 64/128 bit WEP,

WPA-PSK/WPA2-PSK, Wireless MAC Filtering

LAN security: ACL, firewall, ICMP-FLOOD, UDP-FLOOD,

TCP-SYN-FLOOD filtering, domain filtering, MAC address

filtering, 802.1x, parental control

Network features: VPN pass-through, DDNS, UPnP

Router features: virtual servers, NAT, DMZ host, static routes

WLAN features: 2x2 MIMO, CCA

Auto MDI/MDIX: yes

Addressing: DHCP client, DHCP server

Dimensions: 7.7 * 5.1 * 1.4 in. (195 * 130 * 35 mm)

Operating temperatures: 0°C + 40°C

Operating humidity: 5% + 90%, non-condensing

Certificates: CE, FCC

Manufacturer: TP-Link



#09119

Net Price:
8,28 EUR
Unit: pcs

Wireless N router (TP-Link Mercusys MW302R)

- Fast Wi-Fi for Daily Life - MW302R provides fast and stable connections to meet all your network needs with speeds of up to 300 Mbps
- Broader Coverage - Equipped with high gain external antennas to deliver strong Wi-Fi signals to every corner of your home
- Multi-Mode - Four modes in one device to satisfy all application scenarios
- Easy installation - Intuitive webpage guides you through the setup process in minutes
- Active Parental Controls - Establish appropriate access policies to protect children with responsible, safe internet access
- Compatible with IPv6 (Internet Protocol version 6)

Standards: IEEE 802.11n, IEEE 802.11b/g
Ports: 2x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 2x Omni-Directional Antennas
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridging
WLAN security: WPA-PSK / WPA2-PSK
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP
Management: Access Control, Local Management, Remote Management
DHCP: Server
Port Forwarding: Virtual Server, UPnP, DMZ
Access Control: Parental Controls, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: SPI firewall, IP and MAC Address Binding
Protocols: IPv4, IPv6
Guest Network: 1x 2.4 GHz Guest Network
Dimensions: 114 mm x 94 mm x 26 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Power: 5 V DC / 0,6 A
Manufacturer: TP-Link



#09120

Net Price:
8,97 EUR
Unit: pcs

Wireless N router (TP-Link Mercusys MW305R)

- 300Mbps wireless speed is ideal for HD streaming, online gaming, and large file downloads
 - Three 5dBi antennas greatly increase wireless signal strength, size and stability
 - Intuitive webpage guides you through the setup process in minutes
- Standards: IEEE 802.11n, IEEE 802.11b/g
Ports: 3x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 3x Omni-Directional Antennas 5dBi
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridging
WLAN security: WPA-PSK / WPA2-PSK
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP
Management: Access Control, Local Management, Remote Management
DHCP: Server
Port Forwarding: Virtual Server, UPnP, DMZ
Access Control: Parental Controls, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: SPI firewall, IP and MAC Address Binding
Protocols: IPv4, IPv6
Guest Network: 1x 2.4 GHz Guest Network
Dimensions: 147 mm x 115 mm x 34 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Power: 5 V DC / 0,6 A
Manufacturer: TP-Link



#09121

Net Price:
10,50 EUR
Unit: pcs

Wireless N router (TP-Link Mercusys MW325R)

- Great Coverage - four 5dBi antennas provide wide wireless coverage
 - Enhanced Signal - high gain antennas dramatically increase wireless signal strength, size and stability
 - 300Mbps Wireless Speed - ideal for HD streaming, online gaming, and large file downloads
 - Easy Installation - intuitive webpage guides you through the setup process in minutes
- Standards: IEEE 802.11n, IEEE 802.11b/g
Ports: 3x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 4x Omni-Directional Antennas 5dBi
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridging
WLAN security: WPA-PSK / WPA2-PSK
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP
Management: Access Control, Local Management, Remote Management
DHCP: Server
Port Forwarding: Virtual Server, UPnP, DMZ
Access Control: Parental Controls, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: SPI firewall, IP and MAC Address Binding
Protocols: IPv4, IPv6
Guest Network: 1x 2.4 GHz Guest Network
Dimensions: 167 x 118 x 33 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Power: 5 V DC / 0,6 A
Manufacturer: TP-Link



#07114

Net Price:
24,50 EUR
Unit: pcs

Wireless N router (TP-Link TL-MR3420)

Standards: IEEE 802.11n/g/b, IEEE 802.3/3u, USB 2.0
Ports: 4x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)
Frequency range: 2400 MHz + 2483,5 MHz
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Operating modes: AP Router
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 3x detachable SMA RP, 2 dBi
WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK, WPA2, WPA2-PSK, TKIP, AES
LAN security: ACL, firewall, ICMP-FLOOD, UDP-FLOOD, TCP-SYN-FLOOD filtering, domain filtering, MAC address filtering, 802.1x, parental control
Network features: VPN pass-through, DDNS, UPnP
Router features: virtual servers, NAT, DMZ host, static routes
WLAN features: 2x2 MIMO, CCA
Auto MDI/MDIX: yes
Addressing: DHCP client, DHCP server
Dimensions: 174 x 111 x 30 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Power: 9V AC 0.8A, ~230V 50Hz
Certificates: CE, FCC
Warranty period: 24 months
Manufacturer: TP-Link



#09071

Net Price:
10,90 EUR
Unit: pcs

Wireless N router (TP-Link TL-WR820N)

- 300 Mbps Wi-Fi speed is ideal for daily tasks including browsing, emailing, and video streaming
 - IPTV supports IGMP Proxy/Snooping, Bridge and Tag VLAN to optimize IPTV streaming
 - Guest Network provides separate access for guests while securing the host network
 - Parental Controls manage when and how connected devices can access the internet
 - SPI firewall and wireless encryption protect your home network
 - Compatible with IPv6 (Internet Protocol version 6)
- Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g, IEEE 802.3/u, 802.1x
Ports: 2x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 2x Omni-Directional Antennas
Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics
WLAN security: WEP, WPA / WPA2, WPA / WPA2-PSK
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP
Management: Access Control, Local Management, Remote Management
DHCP: Server, DHCP Client List
Port Forwarding: Virtual Server, UPnP, DMZ
Dynamic DNS: DynDns, NO-IP
Access Control: Parental Controls, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: SPI firewall, IP and MAC Address Binding
Protocols: IPv4, IPv6
Guest Network: 1x 2.4 GHz Guest Network
Working Modes: Router Mode
Dimensions: 6.1 x 4.5 x 1.4 in. (154 x 114 x 36 mm)
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Power: 5 V DC / 0,6 A
Certificates: CE, RoHS
Manufacturer: TP-Link



#07058

Net Price:
16,20 EUR
Unit: pcs

Wireless N router (TP-Link TL-WR841N)

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g, IEEE 802.3/u, 802.1x
Ports: 4x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)
Frequency range: 2400 MHz + 2483,5 MHz
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Operating modes: AP Router
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 3dBi fixed Omni Directional Antenna X 2
WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK, WPA2, WPA2-PSK, TKIP, AES
LAN security: ACL, firewall, ICMP-FLOOD, UDP-FLOOD, TCP-SYN-FLOOD filtering, domain filtering, MAC address filtering, 802.1x, parental control
Network features: VPN pass-through, DDNS, UPnP
Router features: virtual servers, NAT, DMZ host, static routes
WLAN features: 2x2 MIMO, CCA
Auto MDI/MDIX: yes
Addressing: DHCP client, DHCP server
Dimensions: 174 x 111 x 30 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Power: 12VDC / 1A, ~230V 50Hz
Certificates: CE, FCC
Warranty period: 24 months
Manufacturer: TP-Link



#09072

Net Price:
12,40 EUR
Unit: pcs

Wireless N router (TP-Link TL-WR844N)

- High-Speed Wi-Fi - 300 Mbps wireless transmission rate is ideal for both bandwidth sensitive tasks and basic work.
- Boosted Coverage - Two omnidirectional antennas and 2x2 MIMO deliver strong Wi-Fi signal and reliable connections.
- Multi-Mode 4 in 1 - Supports Router, Access Point, Range Extender, and WISP modes to meet any network need.
- Parental Controls - Manages when and how connected devices can access the internet.
- Guest Network - Provides separate access for guests while securing the host network.
- Smooth HD Streaming - Supports IGMP Proxy/Snooping, Bridge and Tag VLAN to optimize IPTV streaming.
- IPv6 Supported - Compatible with the IPv6 (the latest Internet Protocol version 6).

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g, IEEE 802.3u, 802.1x
Ports: 4x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)
Frequency range: 2400 MHz ± 2483,5 MHz
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 2x Omni-Directional Antennas
Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics
WLAN security: WEP, WPA / WPA2, WPA / WPA2-PSK
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP
Management: Access Control, Local Management, Remote Management
DHCP: Server, DHCP Client List
Port Forwarding: Virtual Server, UPnP, DMZ
Dynamic DNS: DynDns, NO-IP
Access Control: Parental Controls, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: SPI firewall, IP and MAC Address Binding
Protocols: IPv4, IPv6
Guest Network: 1x 2.4 GHz Guest Network
Working Modes: Wireless Router, Range Extender, Access Point, WISP
Dimensions: 4.5 x 4.2 x 1.0 in (115 x 106.7 x 24.3 mm)
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Power: 5 V DC / 0.6 A
Certificates: CE, RoHS
Manufacturer: TP-Link



#09073

Net Price:
17,60 EUR
Unit: pcs

Wireless N router (TP-Link TL-WR850N)

- 300Mbps wireless transmission rate ideal for both bandwidth sensitive tasks and basic work
- Supports Agile Config- Enable ISPs to customize default configurations by themselves
- Parental Controls manage when and how connected devices can access the internet
- IPTV supports IGMP Proxy/Snooping to optimize IPTV streaming
- Compatible with IPv6 (Internet Protocol version 6)
- Guest Network provides separate access for guests while securing the home network

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g, IEEE 802.3u, 802.1x
Ports: 4x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)
Frequency range: 2400 MHz ± 2483,5 MHz
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Operating modes: AP Router
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 2x Omni-Directional Antennas
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
WLAN security: 64/128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP
Management: Access Control, Local Management, Remote Management
DHCP: Server, DHCP Client List
Port Forwarding: Virtual Server, UPnP, DMZ
Dynamic DNS: DynDns, NO-IP
Access Control: Parental Controls, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security: DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
Protocols: IPv4, IPv6
Guest Network: 1x 2.4 GHz Guest Network
Dimensions: 7.2 x 5.0 x 1.4in.(182 x 128 x 35 mm)
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Power: 5 V DC / 0.6 A
Certificates: CE, RoHS
Manufacturer: TP-Link



#08143

Net Price:
19,20 EUR
Unit: pcs

Wireless N router (TP-Link TL-WR940N)

Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Ports: 4x 10/100Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)
Frequency range: 2400 MHz ± 2483,5 MHz
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
Operating modes: AP Router
Max. speed: 300 Mbps
Max. output power: 20 dBm
Antenna: 3dBi fixed Omni directional antenna x 3
WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK, WPA2, WPA2-PSK, TKIP, AES
LAN security: ACL, firewall, ICMP-FLOOD, UDP-FLOOD, TCP-SYN-FLOOD filtering, domain filtering, MAC address filtering, 802.1x, parental control
Network features: VPN pass-through, DDNS, UPnP
Router features: virtual servers, NAT, DMZ host, static routes
WLAN features: 3x3 MIMO, CCA
Auto MDI/MDIX: yes
Addressing: DHCP client, DHCP server
Dimensions: 200x140x28 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 90%, non-condensing
Power: 9V AC 0.85A, ~230V 50Hz
Certificates: CE, FCC
Warranty period: 24 months
Manufacturer: TP-Link

Wireless active devices 2.4GHz



#05375

Net Price:
35,20 EUR
Unit: pcs

Wireless Access Point (AT8-4)

Standard: IEEE 802.11a/b/g
Chipset: Atheros AR5112 i AR2312
Frequency band: 2400 MHz ± 2483,5 MHz, 5150 MHz ± 5350 MHz, 5470 MHz ± 5725 MHz
Max. speed: 108 Mbps
Radio modes: 11b/g, 11g, 11a, SuperA
Max. TX power: 20 dBm
Operational modes: Bridge, Access Point, Client Infrastructure, Client Ad-hoc
Modulation: 802.11a - OFDM, 802.11b - DSSS, 802.11g - OFDM
Antenna: detachable, SMA-RP
WDS: 8x
Access Control: SSID, MAC Address Control, max. clients
WLAN Security: WEP 64/128/152-bit, WPA-PSK, WPA-TKIP/AES, RADIUS
Addressing: fixed IP, DHCP client
Management: WWW, telnet, UPnP
Log: system log, Syslog
Dimensions: 124,3x154,4x41,0 mm
Operational temperature: 0°C + 40°C
Operational humidity: 10% + 90%, non-condensing
Certificates: CE, FCC, TELECOM
Manufacturer: Wistron



#05445

Net Price:
69,00 EUR
Unit: pcs

Wireless Access Point (Comex WP18)

Standards: IEEE 802.11a/b/g, IEEE 802.3u
Frequency range: 2412 MHz ± 2462 MHz, 2412 MHz ± 2484 MHz, 5150 MHz ± 5350 MHz, 5470 MHz ± 5725 MHz
Max. speed: 108 Mbps
Max. TX power: 18 dBm (IEEE 802.11a), 19 dBm (IEEE 802.11g), 20 dBm (IEEE 802.11b)
Operational modes: Access Point, Client, RootAP / Transparent Client, Wireless Routing Client
WLAN Security: 64/128-bit WEP, WPA, WPA2, IEEE 802.1x
Network features: Dynamic DNS, Wireless Multimedia QoS, Bandwidth Control, Spanning Tree Protocol, Wireless Pseudo VLAN, Firewall SPI
Additional features: PoE support, Long Range Parameter Settings, UPnP, Multiple SSID, Antenna Alignment
WAN interface: static IP, dynamic IP, PPPoE, PPTP, L2TP
VPN: IPSec
Monitoring features: syslog, detailed statistics per client
Management: WWW, SNMP, uConfig, telnet, SSH, SSL
Dimensions: 170x160x31 mm
Weight: 0,26 kg
Power: 5V DC 4A, ~230 V AC
Operational temperature: 0°C + 55°C
Operational humidity: 10% + 80%, non-condensing
Certificates: CE, FCC
Manufacturer: Comex



#05327

Net Price:
47,60 EUR
Unit: pcs

Wireless Access Point ADV (Interepoch IWE2100)

Standards: IEEE 802.11a/b/g, IEEE 802.3u, IEEE 802.1Q/x
Ports: 1x 10/100 Mbps RJ-45
Frequency range: 2400 MHz ± 2483,5 MHz, 5150 MHz ± 5350 MHz, 5470 MHz ± 5825 MHz
Operating modes: AP, Bridge, AP Client
Max. speed: 11 Mbps
Max. output power: 17 dBm
Receiver sensitivity: > -85 dBm
Antenna: detachable SMA-RP, 2 dBi
WLAN security: WEP 64/128-bit, WPA, TKIP, 802.1x
Addressing: DHCP client/server
Additional features: Association control, packet filtering, VPN Pass Through, VLAN support, WLAN Client Isolation
Management: WWW
Housing: indoor
Dimensions: 175x145x50 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 5% + 95%, non-condensing
Power: 5V DC 2A ~230V AC 50Hz
Certificates: CE
Manufacturer: InterEpoch



#05425

Net Price:
100,00 EUR
Unit: pcs

Wireless client device airClient Nexus PRO TOTAL (smartBridges sB3412)

Standard: IEEE 802.11a/b/g, IEEE 802.3u
Ports: 2x 10/100 Mbps RJ-45, 1x N(F) 2.4 GHz, 1x N(F) 5.x GHz
Operating modes: AP Client, Router, Bridge
Frequency range: 2.400 - 2.485 GHz, 5.150 - 5.350 GHz, 5.470 - 5.875 GHz
Modulation: COFDM with BPSK, QPSK, 16 QAM, 64QAM, DSSS with CCK, BPSK, QPSK
Max. output power: 26dBm @ 1Mbps (2.4 GHz), 23dBm @ 54 Mbps (2.4 GHz), 21dBm @ 6 Mbps (5.x GHz), 18dBm @ 54 Mbps (5.x GHz)
Max. output power with build-in antenna: 39dBm @ 1 Mbps (2.4 GHz), 36dBm @ 54 Mbps (2.4 GHz), 38dBm @ 6 Mbps (5.x GHz), 35dBm @ 54 Mbps (5.x GHz)
Receiver sensitivity: -97dBm @ 1Mbps (2.4 GHz), -73dBm @ 54 Mbps (2.4 GHz), -91dBm @ 6 Mbps (5.x GHz), -69dBm @ 54 Mbps (5.x GHz)
Receiver sensitivity with integrated antenna: -112dBm @ 1 Mbps (2.4 GHz), -88dBm @ 54 Mbps (2.4 GHz), -108dBm @ 6 Mbps (5.x GHz), -86dBm @ 54 Mbps (5.x GHz)
Non-overlapping channels: 27
Interference mitigation: TPC/DFS (IEEE 802.11d/h), Tight Spectral Mask, Multi-band, Squelch control
Management: WWW, SNMP
Data throughput: Packet Bursting and Compression
Access protocol: CSMA/CA
WLAN security: 128-bit AES, WPA / WPA2, 64/128 bit WEP
VLAN support: yes
Routing protocols: RIPv2
Spanning Tree support: yes
Bandwidth management: QoS (8 levels)
Additional features: Link Test, Link Budget, Site Survey, Watch Guard, Radio and Ethernet Traffic Statistics, Audio Tone Antenna Alignment, RSSI graph
Antenna: 2x N(F), integrated 17 dBi (5GHz), 15 dBi (2.4GHz)
Housing: outdoor
Dimensions: 305x305x152 mm
Weight: 3,5 kg
Operating temperature: -45°C + 60°C
Operating humidity: 5% + 95%, non-condensing
Mounting: pole or wall
Power: PoE 48V
Power consumption: 200 mA @ 48V
Certificates: CE, FCC, ETSI, RSS 139
Warranty period: 12 months
Manufacturer: smartBridges



#06495

Net Price:
12,20 EUR
Unit: pcs

Wireless mini-PCI adapter (NMP8602)

Standard: IEEE 802.11a/b/g
Interface: mini-PCI typ III
Chipset: Atheros 5006X
Frequency range: 2400 MHz + 2484 MHz, 5150 MHz + 5850 MHz
Max. speed: 54 Mbps
Modulation: CCK, DQPSK, DBPSK (802.11b), 64 QAM, 16 QAM, QPSK, BPSK (802.11a/g)
Receiver sensitivity: -90 dBm @ 6Mbps (802.11a), -74 dBm @ 54 Mbps (802.11a), -92 dBm @ 6Mbps (802.11g), -76 dBm @ 54 Mbps (802.11g), -96 dBm @ 1 Mbps (802.11b), -92 dBm @ 11 Mbps (802.11b)
Max. output power: 20 dBm (802.11b), 20 dBm (802.11g), 19 dBm (802.11a)
Operational modes: infrastructure
Antenna: 2x U.FL (I-PEX)
Supported protocols: TCP/IP, IPX, NDIS4, NDIS5, NDIS 5.1
Drivers: Windows 98SE/ME/2000/XP, Linux
Operating temperatures: 0°C + 55°C
Operating humidity: 10% + 85%, non-condensing
Dimensions: 60x45 mm
Weight: 0.02 kg



#05344

Net Price:
9,52 EUR
Unit: pcs

Wireless PCI card (VZA-81)

Standard: IEEE 802.11a/b/g
Interface: PCI ver. 2.2
Frequency band: 2400 MHz + 2483,5 MHz, 2412 MHz + 2483,5 MHz, 5150 MHz + 5350 MHz, 5470 MHz + 5725 MHz
Max speed: 108 Mbps
Max. TX power: 20 dBm
Operational modes: Ad-hoc, infrastructure
Modulation: 802.11a - OFDM, 802.11b/g - DSSS, OFDM
Channels: 13 (802.11b/g), 19 non-overlapping (802.11a)
WLAN Security: WEP 64/128/152-bit, AES, TKIP, RADIUS
Antenna: SMA-RP connector
Drivers: Windows 98SE/Me/2k/XP
Operational temperature: 0°C + 70°C
Certificates: CE, FCC
Manufacturer: Wistron



#05284

Net Price:
28,60 EUR
Unit: pcs

Wireless router PRO (Interepoch WIE1100-R8S17P)

Standard: IEEE 802.3/u, 802.11b
Operational modes: AP/Bridge, Router w/PPPoE, Router w/DHCP, Router w/Static-IP, Router w/Dial-up
WDS links: 6x
Max. TX power [dBm]: 17
Antenna / connector type: detachable, omnidirectional 3 dBi / SMA-RP(F)
TX power control: yes
Ports: 1x 10/100 Mbps RJ-45 LAN, 1x 10/100 Mbps RJ-45 WAN
Access control: DHCP Server, MAC Address Filtering, Packet Type Filtering, TCP/UDP Port Filtering, NAT, Virtual Server, DMZ, UPnP, UPnP for NAT, SPI Firewall
WLAN Security: WPA (802.1x/TKIP), WEP 64/128-bit, ESSID Disable, RADIUS
Management: Status Monitoring, WWW, telnet, Windows-based Management, UPnP, SNMP, Antenna Alignment Assistance
Housing / case type: indoor
Dimensions: 175x140x40 mm
Operating temperature: 0°C + 55°C
Operating humidity: 5% + 95%, non-condensing
Power: external 5V DC 2A, ~230V AC 50Hz
Certificates: CE, FCC Class B
Warranty period: 1 year
Manufacturer: InterEpoch



#06272

Net Price:
9,52 EUR
Unit: pcs

Wireless mini-PCI adapter (Compex WLM54AGP26 400W)

Standard: IEEE 802.11b/g
Interface: mini-PCI
Chipset: AR5414
Frequency range: 2412 MHz + 2472 MHz
Max. speed: 54 Mbps
Modulation: OFDM (BPSK, QPSK, 16 QAM, 64QAM), DSSS (DBPSK, DQPSK, CCK)
Receiver sensitivity: -92 dBm @ 1Mbps (IEEE 802.11b), -87 dBm @ 11Mbps (IEEE 802.11b), -90 dBm @ 6Mbps (IEEE 802.11g), -70 dBm @ 54Mbps (IEEE 802.11g)
Max. TX power: 26 dBm (IEEE 802.11b), 26 dBm (IEEE 802.11g)
Operational modes: Ad-hoc, infrastructure
WLAN security: WEP 64/128-bit, WPA, WPA2, IEEE 802.1X
Antenna: antenna's socket 1x U.FL (I-PEX), 1x MCX (Main)
Operational temperature: -20°C + 70°C
Operational humidity: 5% + 95%, non-condensing
Dimensions: 60x45 mm
Weight: 0,02 Kg
Manufacturer: Compex



#07051

Net Price:
2,44 EUR
Unit: pcs

Wireless PCI adaptor (TP-Link TL-WN350G)

Standards: IEEE 802.11b/g
Chipset: Atheros
Interface: PCI 32-bit
Frequency range: 2400 MHz + 2483,5 MHz
Max. speed: 54 Mbps
Max. output power: 18 dBm
Operating modes: Ad-Hoc, Infrastructure
WLAN security: 64/128/152-bit WEP, WPA, WPA2, TKIP/AES
Antenna: fixed
Roaming support: yes
Drivers: Windows 98SE/ME/2000/XP/Vista
Dimensions: 133x121x22 mm
Operating temperatures: 0°C + 40°C
Operating humidity: 10% + 90%, non-condensing
Certificates: CE, FCC
Warranty period: 24 months
Manufacturer: TP-Link


#06258

Net Price:
2,44 EUR
Unit: pcs

Wireless PCI adaptor (TP-Link TL-WN353G)

Standards: IEEE 802.11b/g
Chipset: Realtek
Interface: PCI 32-bit
Frequency range: 2400 MHz \pm 2483,5 MHz
Max. speed: 54 Mbps
Max. output power: 15 dBm
Operating modes: Ad-Hoc, Infrastructure
WLAN security: 64/128/152-bit WEP, WPA, WPA2, TKIP/AES
Antenna: fixed
Roaming support: yes
Drivers: Windows 98SE/ME/2000/XP/Vista
Dimensions: 133x121x22 mm
Operating temperatures: 0°C \pm 40°C
Operating humidity: 10% \pm 90%, non-condensing
Certificates: CE, FCC
Warranty period: 24 months
Manufacturer: TP-Link


#05470

Net Price:
3,41 EUR
Unit: pcs

Wireless PCI adaptor (TP-Link TL-WN551G)

Standards: IEEE 802.11b/g
Interface: PCI 32-bit
Frequency range: 2400 MHz \pm 2483,5 MHz
Max. speed: 54 Mbps
Max. output power: 17 dBm
Operating modes: Ad-Hoc, Infrastructure
WLAN security: 64/128/152-bit WEP, WPA, WPA2, TKIP/AES
Antenna: detachable, SMA
WLAN features: Extended Range
Roaming support: yes
Drivers: Windows 98SE/ME/2000/XP
Dimensions: 133x121x22 mm
Operating temperatures: 0°C \pm 40°C
Operating humidity: 10% \pm 90%, non-condensing
Certificates: CE, FCC
Warranty period: 24 months
Manufacturer: TP-Link


#06847

Net Price:
2,44 EUR
Unit: pcs

Wireless PCMCIA adaptor (TP-Link TL-WN310G)

Standards: IEEE 802.11b/g
Interface: Cardbus 32-bit
Frequency range: 2400MHz - 2483,5MHz
Max. speed: 54 Mbps
Max. output power: 17 dBm
Operating modes: Ad-Hoc, Infrastructure
WLAN security: 64/128/152-bit WEP, WPA, WPA2, TKIP/AES
Roaming support: yes
Receiver Sensitivity: 54M -68dBm@10% PER, 11M -85dBm@8% PER, 6M -88dBm@10% PER, 1M -90dBm@8% PER, 256K -105dBm@8% PER
WLAN Features: eXtended Range
Drivers: Windows 2000/XP/Vista
Dimensions: 115x54x5 mm
Operating temperatures: 0°C \pm 40°C
Operating humidity: 10% \pm 90%, non-condensing
Certificates: CE, FCC
Warranty: 2 years
Manufacturer: TP-Link


#05324

Net Price:
92,90 EUR
Unit: pcs

Wireless Access Point ADV MAX OUTDOOR. (Interepoch IWE1700-AAS11XM)

Standard: IEEE 802.3/u, 802.11b
Operational modes: AP/Bridge, AP Client
WDS links: 6x
Max. TX power [dBm]: 20
Antenna / connector type: external / N(F)
TX power control: yes
Ports: 1x 10/100 Mbps MIL-C-5015 LAN
Access control: DHCP Server, MAC Address Filtering, Packet Type Filtering, TCP/UDP Port Filtering
WLAN Security: WPA (802.1x/TKIP), WEP 64/128-bit, ESSID Disable, RADIUS
Management: Status Monitoring, WWW, telnet, Windows-based Management, UPnP, SNMP, Antenna Alignment Assistance
Additional functionality: RSSI (for AP Client), Wireless Client Isolation, AP Load Balancing, Link Integrity, Association Control
PoE support: yes
Housing / case type: outdoor IP68
Net weight: 1480g
Dimensions: 234x170x63 mm
Operating temperature: -20°C \pm 70°C
Power: external PoE 48V DC 1A
Certificates: CE, FCC Class B
Warranty period: 1 year
Manufacturer: InterEpoch

Kit contains: outdoor AP, PoE injector, shielded water resistant 20m transmission cable, UTP 1m cable, power cable


#05323

Net Price:
90,50 EUR
Unit: pcs

Wireless Access Point PRO MAX OUTDOOR. (Interepoch IWE1700-AAS11PM)

Standard: IEEE 802.3/u, 802.11b
Operational modes: AP/Bridge, AP Client
WDS links: 6x
Max. TX power [dBm]: 20
Antenna / connector type: external / N(F)
TX power control: yes
Ports: 1x 10/100 Mbps MIL-C-5015 LAN
Access control: DHCP Server, MAC Address Filtering, Packet Type Filtering, TCP/UDP Port Filtering
WLAN Security: WEP 64/128-bit, ESSID Disable
Management: Status Monitoring, WWW, telnet, Windows-based Management, UPnP, SNMP, Antenna Alignment Assistance
Additional functionality: RSSI (for AP Client), Link Integrity
PoE support: yes
Housing / case type: outdoor IP68
Net weight: 1480g
Dimensions: 234x170x63 mm
Operating temperature: -20°C \pm 70°C
Power: external PoE 48V DC 1A
Certificates: CE, FCC Class B
Warranty period: 1 year
Manufacturer: InterEpoch


#06019

Net Price:
57,10 EUR
Unit: pcs

Wireless client device airClient Nexus TOTAL 241 (smartBridges sB3415-03)

Standards: IEEE 802.11b/g, IEEE 802.3u
Ports: 1x 10/100 Mbps RJ-45
Operating modes: AP Client, Router, NAT, Bridge
Frequency range: 2400 MHz - 2485 MHz
Modulation: QPSK, 16QAM, 64QAM, DBPSK, DQPSK, CCK
Max output power (inbuild antenna): 33dBm
Max output power (external antenna): 18dBm
Receiver sensitivity (inbuild antenna): -109dBm @ 1Mbps, -87dBm @ 54 Mbps
Receiver sensitivity (external antenna): -94dBm @ 1Mbps, -71dBm @ 54 Mbps
Typical useful throughput: 3 Mbps
Management: WWW, SNMP
WLAN security: WPA, 64/128 bit WEP, AES
Bandwidth management: MAC-based
VLAN support: yes
QoS: 8 hardware queues
Addressing: DHCP client, DHCP server
Diagnostic tools: link loopback test, Link Budget, Device Discovery Tool, Radio/Ethernet Traffic Statistics, RSSI Graph
Antenna: integrated 15 dBi, external N(F) connector
Housing: outdoor
Dimensions: 305x305x152 mm
Weight: 3,3 kg
Operating temperatures: -30°C \pm 60°C
Operating humidity: 20% \pm 95%, non-condensing
Mounting: mast or pole
Power: PoE 48V
Power consumption: 200 mA @ 48V
Certificates: CE, FCC
Manufacturer: smartBridges



#05325

Net Price:
71,40 EUR
Unit: pcs

Wireless dual-radio repeater ADV MAX OUTDOOR. (Interepoch IWE1700-TAS12XM)

Standard: IEEE 802.3/u, 802.11b
Operational modes: Bridge Repeater, Static AP Repeater, Dynamic AP Repeater, Dual AP
WDS links: 6x
Max. TX power [dBm]: 20
Antenna / connector type: 2x external / N(F)
TX power control: yes
Ports: 1x 10/100 Mbps MIL-C-5015 LAN
Access control: DHCP Server, MAC Address Filtering, Packet Type Filtering, TCP/UDP Port Filtering
WLAN Security: WPA (802.1x/TKIP), WEP 64/128-bit, ESSID Disable, RADIUS
Management: Status Monitoring, WWW, Windows-based Management, UPnP, SNMP, Antenna Alignment Assistance
Additional functionality: Wireless Client Isolation, AP Load Balancing, Link Integrity, Association Control
PoE support: yes
Housing / case type: outdoor IP68
Net weight: 1580g
Dimensions: 234x170x63 mm
Operating temperature: -20°C ÷ 70°C
Operating humidity: 5% ÷ 95%, non-condensing
Power: external PoE 48V DC 1A
Certificates: CE, FCC Class B
Warranty period: 1 year
Manufacturer: InterEpoch

Wireless active devices 5GHz



#08912

Net Price:
13,20 EUR
Unit: pcs

Protective radome Ubiquiti NanoBeam (Ubiquiti NBE-RAD-300)

A protective radome is available as an optional accessory for the
NBE-M5-300 (#08844)



#07008

Net Price:
60,90 EUR
Unit: pcs

Wireless access point Airmax NanoStation Loco M5 TDMA (Ubiquiti LOCOM5)

Standards: IEEE 802.11a, IEEE 802.11n, IEEE 802.3u
Ports: 1x 10/100 Mbps RJ-45
Operating modes: Access Point, Bridge, Client, WDS
Chipset: Atheros MIPS 24KC 400MHz
Operating memory: 32 MB SDRAM
Flash memory: 8 MB
Frequency range: 5470 MHz ÷ 5825 MHz
Max. output power: 27 dBm @ 6-24 Mbps, 25 dBm @ 36 Mbps, 23 dBm @ 48 Mbps, 22 dBm @ 54 Mbps, 27 dBm @ MSC0, 27 dBm @ MSC1, 27 dBm @ MSC2, 27 dBm @ MSC3, 26 dBm @ MSC4, 24 dBm @ MSC5, 22 dBm @ MSC6, 21 dBm @ MSC7, 27 dBm @ MSC8, 27 dBm @ MSC9, 27 dBm @ MSC10, 27 dBm @ MSC11, 26 dBm @ MSC12, 24 dBm @ MSC13, 22 dBm @ MSC14, 21 dBm @ MSC15
Receiver sensitivity: -94 dBm @ 6-24 Mbps, -80 dBm @ 36 Mbps, -77 dBm @ 48 Mbps, -75 dBm @ 54 Mbps, -96 dBm @ MSC0, -95 dBm @ MSC1, -92 dBm @ MSC2, -90 dBm @ MSC3, -86 dBm @ MSC4, -83 dBm @ MSC5, -77 dBm @ MSC6, -74 dBm @ MSC7, -95 dBm @ MSC8, -93 dBm @ MSC9, -90 dBm @ MSC10, -87 dBm @ MSC11, -84 dBm @ MSC12, -79 dBm @ MSC13, -78 dBm @ MSC14, -75 dBm @ MSC15
Antenna: build-in, 2x2 MIMO 13 dBi
VSWR: 1.6
Beam width: 15°
Dimensions: 163x80x30 mm
Weight: 0.2 kg
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 8 W
Power: PoE 24V
Operating temperatures: -30°C ÷ 80°C
Operating humidity: 5% ÷ 95%, non-condensing
Certificates: CE, FCC, IC RS210
Manufacturer: Ubiquiti



#07006

Net Price:
80,60 EUR
Unit: pcs

Wireless access point Airmax NanoStation M5 TDMA (Ubiquiti NSM5)

Standards: IEEE 802.11a, IEEE 802.11n, IEEE 802.3u
Ports: 2x 10/100 Mbps RJ-45
Operating modes: Access Point, Bridge, Client, WDS
Chipset: Atheros MIPS 24KC 400MHz
Operating memory: 32 MB SDRAM
Flash memory: 8 MB
Frequency range: 5470 MHz ÷ 5825 MHz
Max. output power: 27 dBm @ 6-24 Mbps, 25 dBm @ 36 Mbps, 23 dBm @ 48 Mbps, 22 dBm @ 54 Mbps, 27 dBm @ MSC0, 27 dBm @ MSC1, 27 dBm @ MSC2, 27 dBm @ MSC3, 26 dBm @ MSC4, 24 dBm @ MSC5, 22 dBm @ MSC6, 21 dBm @ MSC7, 27 dBm @ MSC8, 27 dBm @ MSC9, 27 dBm @ MSC10, 27 dBm @ MSC11, 26 dBm @ MSC12, 24 dBm @ MSC13, 22 dBm @ MSC14, 21 dBm @ MSC15
Receiver sensitivity: -94 dBm @ 6-24 Mbps, -80 dBm @ 36 Mbps, -77 dBm @ 48 Mbps, -75 dBm @ 54 Mbps, -96 dBm @ MSC0, -95 dBm @ MSC1, -92 dBm @ MSC2, -90 dBm @ MSC3, -86 dBm @ MSC4, -83 dBm @ MSC5, -77 dBm @ MSC6, -74 dBm @ MSC7, -95 dBm @ MSC8, -93 dBm @ MSC9, -90 dBm @ MSC10, -87 dBm @ MSC11, -84 dBm @ MSC12, -79 dBm @ MSC13, -78 dBm @ MSC14, -75 dBm @ MSC15
Antenna: build-in, 2x2 MIMO 14 dBi
VSWR: 1.6
Beam width: 15°
Dimensions: 294x80x30 mm
Weight: 0.4 kg
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 8 W
Power: PoE 15V
Operating temperatures: -30°C ÷ 80°C
Operating humidity: 5% ÷ 95%, non-condensing
Certificates: CE, FCC, IC RS210
Manufacturer: Ubiquiti



#08180

Net Price:
53,40 EUR
Unit: pcs

Wireless access point Ubiquiti AirGrid M5 23dBi 1x1 MIMO HP (Ubiquiti AirGrid M5)

Utilizing InnerFeed technology, the new AirGrid M Series represents the evolution of outdoor broadband wireless devices. Complete antenna and radio system integration provides revolutionary cost/performance solutions to the Worldwide Broadband Industry.

Standards: IEEE 802.11a, IEEE 802.3u
Ports: 1x 10/100 Mbps RJ-45
Operating modes: Access Point, Bridge, Client, WDS, Router
Chipset: Atheros MIPS 24KC, 400MHz
Operating memory: 32 MB SDRAM
Flash memory: 8 MB
Frequency range: 5475MHz - 5825MHz
Antenna: build-in, 23 dBi
Weight: 1.65 kg
Grid dimensions: 279.4 x 355.6 mm
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 3 W
Power: PoE 24V
Operating temperatures: -30°C + 75°C
Operating humidity: 5% + 95%, condensing
Manufacturer: Ubiquiti



#08181

Net Price:
62,00 EUR
Unit: pcs

Wireless access point Ubiquiti AirGrid M5 27dBi 1x1 MIMO HP (AirGrid M5)

Utilizing InnerFeed technology, the new AirGrid M Series represents the evolution of outdoor broadband wireless devices. Complete antenna and radio system integration provides revolutionary cost/performance solutions to the Worldwide Broadband Industry.

Standards: IEEE 802.11a, IEEE 802.3u
Ports: 1x 10/100 Mbps RJ-45
Operating modes: Access Point, Bridge, Client, WDS, Router
Chipset: Atheros MIPS 24KC, 400MHz
Operating memory: 32 MB SDRAM
Flash memory: 8 MB
Frequency range: 5475MHz - 5825MHz
Antenna: build-in, 27 dBi
Weight: 2.75 kg
Grid dimensions: 431.8 x 609.6 mm
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 3 W
Power: PoE 24V
Operating temperatures: -30°C + 75°C
Operating humidity: 5% + 95%, condensing
Manufacturer: Ubiquiti



#08846

Net Price:
60,90 EUR
Unit: pcs

Wireless access point Ubiquiti NanoBeam M5 MIMO (Ubiquiti NBE-M5-16)

Standards: IEEE 802.11a/n
Ports: 1x 10/100 Mbps RJ-45
Chipset: Atheros MIPS 74KC, 560 MHz
Operating memory: 64 MB DDR2
Flash memory: 8 MB
Antenna: build-in, 16 dBi
VSWR: 1.5
Diameter: 190mm
Weight: 0.320 kg
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 6 W
Power: PoE 24V
Operating temperatures: -40°C + 70°C
Operating humidity: 5% + 95%, Non-condensing
Manufacturer: Ubiquiti



#08874

Net Price:
72,00 EUR
Unit: pcs

Wireless access point Ubiquiti PowerBeam M5 MIMO 5GHz (Ubiquiti PBE-M5-300)

Standards: IEEE 802.11a/n
Ports: 1x 10/100 Mbps RJ-45
Chipset: Atheros MIPS 74KC, 560 MHz
Operating memory: 64 MB DDR2
Flash memory: 8 MB
Antenna: build-in, 22 dBi
Range: 20+ km
VSWR: 1.5
Diameter: 300mm
Weight: 1.203 kg
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 6 W
Power: PoE 24V
Operating temperatures: -40°C + 70°C
Operating humidity: 5% + 95%, Non-condensing
Manufacturer: Ubiquiti



#06285

Net Price:
87,80 EUR
Unit: pcs

Wireless access point Ubiquiti PowerBeam M5 MIMO 5GHz (Ubiquiti PBE-M5-300-ISO-EU)

Standards: IEEE 802.11a/n
Ports: 1x 10/100 Mbps RJ-45
Chipset: Atheros MIPS 74KC, 560 MHz
Operating memory: 64 MB DDR2
Flash memory: 8 MB
Antenna: build-in, 22 dBi
Range: 20+ km
VSWR: 1.5
Dimensions: 364 x 364 x 276 mm (14.33 x 14.33 x 10.87")
Weight: 2.55 kg (5.62 lb)
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 6 W
Power: 24V, 0.5A PoE, Passive PoE (Pairs 4, 5+; 7, 8 Return)
Operating temperatures: -40°C + 70°C
Operating humidity: 5% + 95%, Non-condensing
Salt Fog Test: IEC 68-2-11 (ASTM B117), Equivalent
MIL-STD-810 G Method 509.5
Vibration Test: IEC 68-2-6
Temperature Shock Test: IEC 68-2-14
UV Test: IEC 68-2-5 at 40° C (104° F), Equivalent ETS 300 019-1-4
Wind-Driven Rain Test: ETS 300 019-1-4, Equivalent
MIL-STD-810 G Method 506.5
Manufacturer: Ubiquiti



#08875

Net Price:
84,50 EUR
Unit: pcs

Wireless access point Ubiquiti PowerBeam M5 MIMO 5GHz (Ubiquiti PBE-M5-400)

Standards: IEEE 802.11a/n
Ports: 1x 10/100/1000 Mbps RJ-45
Chipset: Atheros MIPS 74KC, 560 MHz
Operating memory: 64 MB DDR2
Flash memory: 8 MB
Antenna: build-in, 25 dBi
Range: 25+ km
VSWR: 1.5
Diameter: 400mm
Weight: 1.753 kg
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 8 W
Power: PoE 24V
Operating temperatures: -40°C + 70°C
Operating humidity: 5% + 95%, Non-condensing
Manufacturer: Ubiquiti



#06286

Net Price:
101,00 EUR
Unit: pcs

Wireless access point Ubiquiti PowerBeam M5 MIMO 5GHz (Ubiquiti PBE-M5-400-ISO-EU)

Standards: IEEE 802.11a/n
Ports: 1x 10/100/1000 Mbps RJ-45
Chipset: Atheros MIPS 74KC, 560 MHz
Operating memory: 64 MB DDR2
Flash memory: 8 MB
Antenna: build-in, 25 dBi
Range: 25+ km
VSWR: 1.5
Dimensions: 459 x 459 x 261 mm (18.07 x 18.07 x 10.28")
Weight: 3.22 kg (7.10 lb)
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 8 W
Power: PoE 24V
Operating temperatures: -40°C + 70°C
Operating humidity: 5% + 95%, Non-condensing
Salt Fog Test: IEC 68-2-11 (ASTM B117), Equivalent
MIL-STD-810 G Method 509.5
Vibration Test: IEC 68-2-6
Temperature Shock Test: IEC 68-2-14
UV Test: IEC 68-2-5 at 40° C (104° F), Equivalent ETS 300 019-1-4
Wind-Driven Rain Test: ETS 300 019-1-4, Equivalent
MIL-STD-810 G Method 506.5
Manufacturer: Ubiquiti



#08876

Net Price:
180,00 EUR
Unit: pcs

Wireless access point Ubiquiti PowerBeam M5 MIMO 5GHz (Ubiquiti PBE-M5-620)

Standards: IEEE 802.11a/n
Ports: 1x 10/100/1000 Mbps RJ-45
Chipset: Atheros MIPS 74KC, 560 MHz
Operating memory: 64 MB DDR2
Flash memory: 8 MB
Antenna: build-in, 29 dBi
Range: 30+ km
VSWR: 1.5
Diameter: 600mm
Weight: 6.4 kg
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 8.5 W
Power: PoE 24V
Operating temperatures: -40°C + 70°C
Operating humidity: 5% + 95%, Non-condensing
Manufacturer: Ubiquiti



#07007

Net Price:
80,60 EUR
Unit: pcs

Wireless Base Station Airmax TDMA (Ubiquiti Rocket M5)

Standards: IEEE 802.11a, IEEE 802.11n, IEEE 802.3u
Ports: 1x 10/100 Mbps RJ-45
Operating modes: Access Point, Bridge, Client, WDS
Chipset: Atheros MIPS 24KC 400MHz
Operating memory: 64 MB SDRAM
Flash memory: 8 MB
Frequency range: 5470 MHz + 5825 MHz
Max. output power: 27 dBm @ 6-24 Mbps, 25 dBm @ 36 Mbps, 23 dBm @ 48 Mbps, 22 dBm @ 54 Mbps, 27 dBm @ MSC0, 27 dBm @ MSC1, 27 dBm @ MSC2, 27 dBm @ MSC3, 26 dBm @ MSC4, 24 dBm @ MSC5, 22 dBm @ MSC6, 21 dBm @ MSC7, 27 dBm @ MSC8, 27 dBm @ MSC9, 27 dBm @ MSC10, 27 dBm @ MSC11, 26 dBm @ MSC12, 24 dBm @ MSC13, 22 dBm @ MSC14, 21 dBm @ MSC15
Receiver sensitivity: -94 dBm @ 6-24 Mbps, -80 dBm @ 36 Mbps, -77 dBm @ 48 Mbps, -75 dBm @ 54 Mbps, -96 dBm @ MSC0, -95 dBm @ MSC1, -92 dBm @ MSC2, -90 dBm @ MSC3, -86 dBm @ MSC4, -83 dBm @ MSC5, -77 dBm @ MSC6, -74 dBm @ MSC7, -95 dBm @ MSC8, -93 dBm @ MSC9, -90 dBm @ MSC10, -87 dBm @ MSC11, -84 dBm @ MSC12, -79 dBm @ MSC13, -78 dBm @ MSC14, -75 dBm @ MSC15
Antenna: detachable, 2x SMA-RP(F)
Dimensions: 160x80x30 mm
Weight: 0.5 kg
Mounting: mast or wall with the aid of antenna wall support
Max. power consumption: 8 W
Power: PoE 24V
Operating temperatures: -30°C + 75°C
Operating humidity: 5% + 95%, non-condensing
Certificates: CE, FCC, IC RS210
Manufacturer: Ubiquiti

Antennas 2.4 GHz



#07042

Net Price:
11,20 EUR
Unit: pcs

Directional panel antenna 9dBi (TP-Link TL-ANT2409B)

Frequency range: 2.4GHz~2.4835GHz
Gain: 9 dBi
Impedance: 50 Ω
Polarization: Linear Vertical
Beamwidth (HPBW): Horizontal 60°, Vertical 76°
VSWR: 1.92
Connector: N Female
Cable length: 100cm CFD-200
Dimensions (LxWxH mm): 120x120x40 mm
Safety, Emission and others: CE FCC Compliant with RoHS
Manufacturer: TP-Link



#05428

Net Price:
9,59 EUR
Unit: pcs

Directional panel antenna PANEL 13 dBi, 3 m cable with connector

Gain: 13 dBi (without cable)
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 38 degree
Horizontal beam width: 37 degree
Polarization: H or V
Impedance: 50 Ohm
Connector: RP-SMA
Cable: 3 m H155
VSWR: 1,5
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0,3 kg



#05429

Net Price:
10,70 EUR
Unit: pcs

Directional panel antenna PANEL 13 dBi, 5 m cable with connector

Gain: 13 dBi (without cable)
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 38 degree
Horizontal beam width: 37 degree
Polarization: H or V
Impedance: 50 Ohm
Connector: RP-SMA
Cable: 5 m H155
VSWR: 1,5
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0,3 kg



#05430

Net Price:
11,50 EUR
Unit: pcs

Directional panel antenna PANEL 13 dBi, 7 m cable with connector

Gain: 13 dBi (without cable)
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 38 degree
Horizontal beam width: 37 degree
Polarization: H or V
Impedance: 50 Ohm
Connector: RP-SMA
Cable: 7 m H155
VSWR: 1,5
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0,3 kg



#05427

Net Price:
8,80 EUR
Unit: pcs

Directional panel antenna PANEL 13 dBi, 0.5 m cable with connector

Gain: 13 dBi (without cable)
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 38 degree
Horizontal beam width: 37 degree
Polarization: H or V
Impedance: 50 Ohm
Connector: RP-SMA
Cable: 0.5m H155
VSWR: 1,5
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0,3 kg



#05431

Net Price:
12,50 EUR
Unit: pcs

Directional panel antenna PANEL 13 dBi, 10 m cable with connector

Gain: 13 dBi (without cable)
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 38 degree
Horizontal beam width: 37 degree
Polarization: H or V
Impedance: 50 Ohm
Connector: RP-SMA
Cable: 10 m H155
VSWR: 1,5
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0,3 kg



#05417
Net Price:
14,40 EUR
Unit: pcs

Directional panel antenna PANEL 15dBi

Gain: 15 dBi
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 34 degree
Horizontal beam width: 36 degree
Polarization: H or V
Impedance: 50 Ohm
Connector: N(F)
VSWR: 1,4
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0,4 kg



#05314
Net Price:
24,90 EUR
Unit: pcs

Directional panel antenna PANEL MAX 18 dBi

Gain: 18 dBi
Vertical beam width: 11 degree
Horizontal beam width: 12 degree
Polarization: H or V
VSWR: 1,4
Connector: N(F)
Height: 304,8 mm
Width: 304,8 mm
Thickness: 38,1 mm
Weight: 1,89 kg



#05453
Net Price:
48,80 EUR
Unit: pcs

Directional panel antenna PANEL XP 22 dBi

Gain: 22 dBi
Frequency range: 2400MHz - 2485 MHz
Vertical beam width: 12 degree
Horizontal beam width: 12 degree
Polarization: H, V or inclined
Impedance: 50 Ohm
Connector: N(F)
VSWR: 1,4
Height: 510 mm
Width: 510 mm
Thickness: 38,1 mm
Weight: 3,17 kg



#07061
Net Price:
40,00 EUR
Unit: pcs

Directional sector antenna VECTOR H-PRO-120 17 dBi

Gain: 17 dBi
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 6 degree
Horizontal beam width: 120 degree
Polarization: H
Impedance: 50 Ohm
Connector: N(F)
VSWR: 1,4
Height: 740 mm
Width: 120 mm
Thickness: 60 mm
Weight: 1,8 kg



#05456
Net Price:
40,00 EUR
Unit: pcs

Directional sector antenna VECTOR H-PRO-90 18 dBi

Gain: 18 dBi
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 6 degree
Horizontal beam width: 90 degree
Polarization: H
Impedance: 50 Ohm
Connector: N(F)
VSWR: 1,4
Height: 740 mm
Width: 120 mm
Thickness: 60 mm
Weight: 1,8 kg



#08055
Net Price:
41,70 EUR
Unit: pcs

Directional sector antenna VECTOR MIMO-120 17 dBi

Gain: 17 dBi
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 8 degree
Horizontal beam width: 120 degree
Polarization: Horizontal / vertical (both)
Impedance: 50 Ohm
Connector: 2 x N(F)
VSWR: 1,4
Height: 740 mm
Width: 180 mm
Thickness: 60 mm
Weight: 2,19 kg



#08053
Net Price:
39,80 EUR
Unit: pcs

Directional sector antenna VECTOR MIMO-60 19 dBi

Gain: 19 dBi
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 8 degree
Horizontal beam width: 60 degree
Polarization: Horizontal / vertical (both)
Impedance: 50 Ohm
Connector: 2 x N(F)
VSWR: 1,4
Height: 740 mm
Width: 180 mm
Thickness: 60 mm
Weight: 2,31 kg



#08054
Net Price:
37,30 EUR
Unit: pcs

Directional sector antenna VECTOR MIMO-90 18 dBi

Gain: 18 dBi
Frequency range: 2400MHz - 2500 MHz
Vertical beam width: 8 degree
Horizontal beam width: 90 degree
Polarization: Horizontal / vertical (both)
Impedance: 50 Ohm
Connector: 2 x N(F)
VSWR: 1,4
Height: 740 mm
Width: 180 mm
Thickness: 60 mm
Weight: 2,22 kg



#02618
Net Price:
30,20 EUR
Unit: pcs

Directional Yagi antenna YAGI XP 16 dBi

Gain: 16 dBi
Vertical beam width: 26 degree
Horizontal beam width: 23 degree
Polarization: H and V
Reverse radiation: -20 dBi
VSWR: 1,4
Connector: N(M)
Cable: 30 cm H155
Length: 600 mm
Width: 80 mm
Weight: 0,9 kg



#03028
Net Price:
40,00 EUR
Unit: pcs

Directional Yagi antenna YAGI XP 16 dBi 10 m cable with connector

Gain: 16 dBi
Vertical beam width: 26 degree
Horizontal beam width: 23 degree
Polarization: H and V
Reverse radiation: -20 dBi
VSWR: 1,4
Connector: SMA RP(M)
Cable: 10 m H155
Length: 600 mm
Width: 80 mm
Weight: 0,9 kg



#08202
Net Price:
155,00 EUR
Unit: pcs

Omni-directional antenna AIRMAX MIMO 10dBi (Ubiquiti AMO-2G10)

Directional gain: 10 dBi
Frequency range: 2,35 - 2,55 GHz
Vertical beam width: 12 degree
Horizontal beam width: 360 degree
VSWR: 1,7
Connector: 2xRSMA
Weight: 2,1 kg



#08203
Net Price:
224,00 EUR
Unit: pcs

Omni-directional antenna AIRMAX MIMO 10dBi (Ubiquiti AMO-2G13)

Directional gain: 13 dBi
Frequency range: 2,35 - 2,55 GHz
Vertical beam width: 7 degree
Horizontal beam width: 360 degree
VSWR: 1,7
Connector: 2xRSMA
Weight: 2,4 kg



#02572
Net Price:
18,50 EUR
Unit: pcs

Omni-directional antenna PATRIA 10 dBi

Omnidirectional gain: 10 dBi
Vertical beam width: 5 degree
Horizontal beam width: 360 degree
Reverse radiation: -
VSWR: 1.5
Connector: N(F)
Length: 600 mm
Diameter: 50 mm
Weight: 0.9 kg



#08961
Net Price:
123,00 EUR
Unit: pcs

Omni-directional sector antenna AIRMAX 120 15dBi (Ubiquiti AM-2G15-120)

Gain: 15.0 - 16.0 dBi
Frequency: 2.3 - 2.7 GHz
Vertical beam width: 118° (6 dB)
Horizontal beam width: 123° (6 dB)
Polarization: Dual Linear
VSWR: 1.5
Wind Survivability: 200 km/h (125 mph)
Wind Loading: 169 N @ 200 km/h (38 lbf @ 125 mph)
Height: 700 mm
Width: 145 mm
Thickness: 93 mm
Weight: 4.0 kg
Cross-Pol Isolation: 28 dB Min.
ETSI Specification: EN 302 326 DN2
Mounting: Universal Pole Mount, Rocket Bracket, and Weatherproof RF Jumpers Included



#08960
Net Price:
123,00 EUR
Unit: pcs

Omni-directional sector antenna AIRMAX 90 16dBi (Ubiquiti AM-2G16-90)

Gain: 16.0 - 17.0 dBi
Frequency: 2.3 - 2.7 GHz
Vertical beam width: 90° (6 dB)
Horizontal beam width: 91° (6 dB)
Polarization: Dual Linear
VSWR: 1.5
Wind Survivability: 200 km/h (125 mph)
Wind Loading: 169 N @ 200 km/h (38 lbf @ 125 mph)
Height: 700 mm
Width: 145 mm
Thickness: 79 mm
Weight: 3.9 kg
Cross-Pol Isolation: 28 dB Min.
ETSI Specification: EN 302 326 DN2
Mounting: Universal Pole Mount, Rocket Bracket, and Weatherproof RF Jumpers Included



#02690
Net Price:
21,70 EUR
Unit: pcs

Omni-directional sector antenna RADIUS 17 dBi

Designed to mount to round mast with 1/2" to 7/4" diameter. Antenna is made of lightweight Al alloy. Antenna is hermetic, weatherproof. Additional powder paint and heat treating ensures correct operation under any weather conditions.

Gain: 17 dBi
Vertical beam width: 6 degree
Horizontal beam width: 90 degree
Polarization: H
VSWR: 1.2
Connector: N(F)
Height: 420 mm
Width: 95 mm
Thickness: 40 mm
Weight: 0.33 kg



#06790
Net Price:
21,70 EUR
Unit: pcs

Omni-directional sector antenna RADIUS V-PRO 17 dBi

Designed to mount to round mast with 3/4" to 7/4" diameter. Antenna is made of lightweight Al alloy. Antenna is hermetic, weatherproof. Additional powder paint and heat treating ensures correct operation under any weather conditions.

Frequency range: 2.4 - 2.5 GHz
Gain: 17 dBi
Vertical beam width: 6 degree
Horizontal beam width: 90 degree
Polarization: V
VSWR: 1.2
Connector: N(F)
Height: 420 mm
Width: 95 mm
Thickness: 40 mm
Weight: 0.33 kg



#08067
Net Price:
32,40 EUR
Unit: pcs

Omni-directional sector antenna RADIUS XP 17 dBi MIMO

Designed to mount to round mast with 1/2" to 7/4" diameter. Antenna is made of lightweight Al alloy. Antenna is hermetic, weatherproof. Additional powder paint and heat treating ensures correct operation under any weather conditions.

Gain: 17 dBi
Vertical beam width: 6 degree
Horizontal beam width: 90 degree
Polarization: H
VSWR: 1.2
Connector: 2x N(F)
Height: 420 mm
Width: 95 mm
Thickness: 40 mm
Weight: 0.33 kg



#02628
Net Price:
45,60 EUR
Unit: pcs

Omni-directional sector antenna VECTOR MINI 19 dBi

Designed to mount to round mast with 1/2" to 7/4" diameter. Antenna is made of lightweight Al alloy. Antenna is hermetic, weatherproof. Additional powder paint and heat treating ensures correct operation under any weather conditions.

Gain: 19 dBi
Vertical beam width: 9 degree
Horizontal beam width: 150 degree
Polarization: H
Reverse radiation: -
VSWR: 1.2
Connector: N(F)
Height: 920 mm
Width: 100 mm
Thickness: 25 mm
Weight: 1.7 kg



#06199
Net Price:
42,00 EUR
Unit: pcs

Omni-directional sector antenna VECTOR V-PRO 17 dBi - 120

Gain: 17 dBi
Vertical beam width: 6 degree
Horizontal beam width: 120 degree
Polarization: V
Reverse radiation: -28 dBi
VSWR: 1.4
Connector: N(F)
Height: 740 mm
Width: 120 mm
Thickness: 60 mm
Weight: 1.8 kg



#05264
Net Price:
42,00 EUR
Unit: pcs

Omni-directional sector antenna VECTOR V-PRO 18 dBi

Gain: 18 dBi
Vertical beam width: 6 degree
Horizontal beam width: 90 degree
Polarization: V
Reverse radiation: -28 dBi
VSWR: 1.4
Connector: N(F)
Height: 740 mm
Width: 120 mm
Thickness: 60 mm
Weight: 1.8 kg












#02621
Net Price:
60,20 EUR
Unit: pcs

Omni-directional sector antenna VECTOR XP 22 dBi

Designed to mount to round mast with 3/4" to 7/4" diameter. Antenna is made of lightweight Al alloy. Antenna is hermetic, weatherproof. Additional powder paint and heat treating ensures correct operation under any weather conditions.

Gain: 22 dBi
Vertical beam width: 3 degree
Horizontal beam width: 120 degree
Polarization: H
Reverse radiation: -30 dBi
VSWR: 1.2
Connector: N(F)
Height: 1450 mm
Width: 100 mm
Thickness: 50 mm
Weight: 3.5 kg

Antennas 5 GHz					
	<p>#05252</p> <p>Net Price: 45,10 EUR Unit: pcs</p>		<p>#07016</p> <p>Net Price: 123,00 EUR Unit: pcs</p>		<p>#07071</p> <p>Net Price: 273,00 EUR Unit: pcs</p>
<p>5GHz Directional panel antenna MIMO PANEL MAX 21 dBi</p> <p>Gain: 21 dBi Frequency range: 5.1 - 6.0 GHz Vertical beam width: 11 degree Horizontal beam width: 11 degree Polarization: H or V VSWR: 1.5 Connector: 2xN(F) Height: 304.8 mm Width: 304.8 mm Depth: 38.1 mm Weight: 2.27 kg</p>		<p>Airmax dish antenna 5 GHz, 30 dBi (Ubiquiti RocketDish 5G-30)</p> <p>Directional gain: 30 dBi Frequency range: 5.1 - 5.9 GHz Vertical beam width: 5 degree Horizontal beam width: 5 degree Polarization: dual linear Cross-pol isolation: 35 db min. F/B Ratio: -34 dB VSWR: 1.4 Windloading: 120 mph Connector: SMA-RP(F) Diameter: Ø 648 mm Weight: 9.8 kg Manufacturer: Ubiquiti</p>		<p>Airmax dish antenna 5 GHz, 34 dBi (Ubiquiti RocketDish 5G-34)</p> <p>Directional gain: 34 dBi Frequency range: 5.1 - 5.9 GHz Vertical beam width: 3 degree Horizontal beam width: 3 degree Polarization: dual linear Cross-pol izolation: 35 db min. F/B Ratio: -42 dB VSWR: 1.4 Wind Survivability: 125 mph Connector: SMA-RP(F) Diameter: Ø 1050 mm Weight: 13.5 kg Manufacturer: Ubiquiti</p>	
	<p>#07013</p> <p>Net Price: 72,00 EUR Unit: pcs</p>		<p>#07012</p> <p>Net Price: 72,00 EUR Unit: pcs</p>		<p>#07011</p> <p>Net Price: 123,00 EUR Unit: pcs</p>
<p>Airmax sector antenna 5 GHz, 16 dBi - 120 deg. (Ubiquiti 5G-120-16)</p> <p>Patent-pending next-generation technology achieves gain, cross-pol isolation, and beamshaping characteristics rivaling the highest quality cellular carrier basestation antennas in the world. Instantly pair with Rocket M5 to create a powerful AirMax 2x2 MIMO PtMP BaseStation. Rocket mount and weatherproof RF jumpers included.</p> <p>Directional gain: 16 dBi Frequency range: 5.1 - 5.9 GHz Vertical beam width: 8 degree Horizontal beam width: 118 degree Polarization: dual linear Cross-pol izolation: 22 db min. Electrical downtilt: 4 degree VSWR: 1.5 Windloading: 120 mph Connector: SMA-RP(F) Height: 367 mm Width: 63 mm Thickness: 41 mm Weight: 1.1 kg Manufacturer: Ubiquiti</p>		<p>Airmax sector antenna 5 GHz, 17 dBi - 90 deg. (Ubiquiti 5G-90-17)</p> <p>Patent-pending next-generation technology achieves gain, cross-pol isolation, and beamshaping characteristics rivaling the highest quality cellular carrier basestation antennas in the world. Instantly pair with Rocket M5 to create a powerful AirMax 2x2 MIMO PtMP BaseStation. Rocket mount and weatherproof RF jumpers included.</p> <p>Directional gain: 17 dBi Frequency range: 4.9 - 5.9 GHz Vertical beam width: 8 degree Horizontal beam width: 93 degree Polarization: dual linear Cross-pol izolation: 22 db min. Electrical downtilt: 4 degree VSWR: 1.5 Windloading: 120 mph Connector: SMA-RP(F) Height: 367 mm Width: 63 mm Thickness: 41 mm Weight: 1.1 kg Manufacturer: Ubiquiti</p>		<p>Airmax sector antenna 5 GHz, 19 dBi - 120 deg. (Ubiquiti 5G-120-19)</p> <p>Patent-pending next-generation technology achieves gain, cross-pol isolation, and beamshaping characteristics rivaling the highest quality cellular carrier basestation antennas in the world. Instantly pair with Rocket M5 to create a powerful AirMax 2x2 MIMO PtMP BaseStation. Rocket mount and weatherproof RF jumpers included.</p> <p>Directional gain: 19 dBi Frequency range: 5.15 - 5.85 GHz Vertical beam width: 4 degree Horizontal beam width: 123 degree Polarization: dual linear Cross-pol izolation: 28 db min. Electrical downtilt: 2 degree VSWR: 1.5 Windloading: 160 mph Connector: SMA-RP(F) Height: 700 mm Width: 145 mm Thickness: 93 mm Weight: 5.9 kg Manufacturer: Ubiquiti</p>	
	<p>#07010</p> <p>Net Price: 123,00 EUR Unit: pcs</p>		<p>#05320</p> <p>Net Price: 28,80 EUR Unit: pcs</p>		<p>#05418</p> <p>Net Price: 20,50 EUR Unit: pcs</p>
<p>Airmax sector antenna 5 GHz, 20 dBi - 90 deg. (Ubiquiti 5G-90-20)</p> <p>Patent-pending next-generation technology achieves gain, cross-pol isolation, and beamshaping characteristics rivaling the highest quality cellular carrier basestation antennas in the world. Instantly pair with Rocket M5 to create a powerful AirMax 2x2 MIMO PtMP BaseStation. Rocket mount and weatherproof RF jumpers included.</p> <p>Directional gain: 20 dBi Frequency range: 5.15 - 5.85 GHz Vertical beam width: 4 degree Horizontal beam width: 91 degree Polarization: dual linear Cross-pol izolation: 28 db min. Electrical downtilt: 2 degree VSWR: 1.5 Windloading: 160 mph Connector: SMA-RP(F) Height: 700 mm Width: 145 mm Thickness: 93 mm Weight: 5.9 kg Manufacturer: Ubiquiti</p>		<p>Directional panel antenna PANEL 16 dBi</p> <p>Gain: 16 dBi Frequency range: 5.15 - 5.875 GHz (channels 36 - 165) Vertical beam width: 6 degree Horizontal beam width: 120 degree Polarization: H or V VSWR: 1.5 Connector: N(F) Height: 95 mm Width: 420 mm Depth: 40 mm Weight: 0.32 kg</p>		<p>Directional panel antenna PANEL 19dBi</p> <p>Gain: 19 dBi Frequency range: 5250 MHz - 5875 MHz Vertical beam width: 17 degree Horizontal beam width: 16 degree Polarization: H or V Impedancia: 50 Ohm Connector: N(F) VSWR: 1.4 Height: 190 mm Width: 190 mm Thickness: 40 mm Weight: 0.4 kg</p>	


#05251

Net Price:
29,00 EUR
Unit: pcs

Directional panel antenna PANEL MAX 23 dBi

Gain: 23 dBi
Frequency range: 5,25 - 5,875 GHz (channels 50 - 165)
Vertical beam width: 11 degree
Horizontal beam width: 12 degree
Polarization: H or V
VSWR: 1.5
Connector: N(F)
Height: 304.8 mm
Width: 304.8 mm
Depth: 38.1 mm
Weight: 2.27 kg


#06782

Net Price:
11,70 EUR
Unit: pcs

Directional panel antenna PANEL MIDI 18 dBi, 1 m

Frequency range: 5.25 - 5.875 GHz
Gain: 18 dBi
Vertical beam width: 17 degree
Horizontal beam width: 16 degree
Polarization: H, V
Impedance: 50 Ohm
VSWR: 1.5
Connector: RSMA (m)
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0.40 kg
Cable: 1 m


#06787

Net Price:
16,00 EUR
Unit: pcs

Directional panel antenna PANEL MIDI 18 dBi, 11 m

Frequency range: 5.25 - 5.875 GHz
Gain: 18 dBi
Vertical beam width: 17 degree
Horizontal beam width: 16 degree
Polarization: H, V
Impedance: 50 Ohm
VSWR: 1.5
Connector: RSMA (m)
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0.40 kg
Cable: 11 m


#06788

Net Price:
17,30 EUR
Unit: pcs

Directional panel antenna PANEL MIDI 18 dBi, 13 m

Frequency range: 5.25 - 5.875 GHz
Gain: 18 dBi
Vertical beam width: 17 degree
Horizontal beam width: 16 degree
Polarization: H, V
Impedance: 50 Ohm
VSWR: 1.5
Connector: RSMA (m)
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0.40 kg
Cable: 13 m


#06789

Net Price:
18,10 EUR
Unit: pcs

Directional panel antenna PANEL MIDI 18 dBi, 15 m

Frequency range: 5.25 - 5.875 GHz
Gain: 18 dBi
Vertical beam width: 17 degree
Horizontal beam width: 16 degree
Polarization: H, V
Impedance: 50 Ohm
VSWR: 1.5
Connector: RSMA (m)
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0.40 kg
Cable: 15 m


#06783

Net Price:
12,30 EUR
Unit: pcs

Directional panel antenna PANEL MIDI 18 dBi, 3 m

Frequency range: 5.25 - 5.875 GHz
Gain: 18 dBi
Vertical beam width: 17 degree
Horizontal beam width: 16 degree
Polarization: H, V
Impedance: 50 Ohm
VSWR: 1.5
Connector: RSMA (m)
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0.40 kg
Cable: 3 m


#06784

Net Price:
13,90 EUR
Unit: pcs

Directional panel antenna PANEL MIDI 18 dBi, 5 m

Frequency range: 5.25 - 5.875 GHz
Gain: 18 dBi
Vertical beam width: 17 degree
Horizontal beam width: 16 degree
Polarization: H, V
Impedance: 50 Ohm
VSWR: 1.5
Connector: RSMA (m)
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0.40 kg
Cable: 5 m


#06785

Net Price:
14,70 EUR
Unit: pcs

Directional panel antenna PANEL MIDI 18 dBi, 7 m

Frequency range: 5.25 - 5.875 GHz
Gain: 18 dBi
Vertical beam width: 17 degree
Horizontal beam width: 16 degree
Polarization: H, V
Impedance: 50 Ohm
VSWR: 1.5
Connector: RSMA (m)
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0.40 kg
Cable: 7 m


#06786

Net Price:
15,70 EUR
Unit: pcs

Directional panel antenna PANEL MIDI 18 dBi, 9 m

Frequency range: 5.25 - 5.875 GHz
Gain: 18 dBi
Vertical beam width: 17 degree
Horizontal beam width: 16 degree
Polarization: H, V
Impedance: 50 Ohm
VSWR: 1.5
Connector: RSMA (m)
Height: 190 mm
Width: 190 mm
Thickness: 40 mm
Weight: 0.40 kg
Cable: 9 m


#05452

Net Price:
67,30 EUR
Unit: pcs

Directional panel antenna PANEL XP 28 dBi

Gain: 28 dBi
Frequency range: 5470 MHz - 5825 MHz
Vertical beam width: 7 degree
Horizontal beam width: 7 degree
Polarization: H, V or inclined
Impedance: 50 Ohm
Connector: N(F)
VSWR: 1.4
Height: 510 mm
Width: 510 mm
Thickness: 38,1 mm
Weight: 3,6 kg


#08200

Net Price:
112,00 EUR
Unit: pcs

Omni-directional antenna AIRMAX MIMO 10dBi (Ubiquiti AMO-5G10)

Directional gain: 10 dBi
Frequency range: 5.15 - 5.875 GHz
Vertical beam width: 12 degree
Horizontal beam width: 360 degree
VSWR: 1,6
Connector: 2xRSMA
Weight: 0,68 kg


#05372

Net Price:
25,60 EUR
Unit: pcs

Omni-directional antenna PATRIA MAX 12dBi

Directional gain: 12 dBi
Frequency range: 5.15 - 5.875 GHz
Vertical beam width: 5 degree
Horizontal beam width: 360 degree
Polarization: V
VSWR: 1,5
Impedance: 50 Ohm
Connector: N(F)
Diameter: 50 mm
Width: 600 mm
Weight: 0,8 kg


#05406

Net Price:
68,00 EUR
Unit: pcs

Omni-directional antenna PATRIA MAX 12dBi MIMO

Directional gain: 16 dBi
Frequency range: 5.1 - 5.8 GHz
Vertical beam width: 5 degree
Horizontal beam width: 360 degree
Polarization: V + H
VSWR: 1.5
Impedance: 50 Ohm
Connector: 2xN(F)
Standards: IEEE 802.11x
Diameter: 80 mm
Width: 600 mm
Weight: 2.27 kg


#08050

Net Price:
48,30 EUR
Unit: pcs

Omni-directional sector antenna VECTOR MIMO-120 17dBi

Directional gain: 17 dBi
Frequency range: 5.10 - 6.0 GHz
Vertical beam width: 8 degree
Horizontal beam width: 120 degree
Polarization: Horizontal / vertical (both)
VSWR: 1,4
Impedance: 50 Ohm
Connector: 2 x N(F)
Height: 740mm
Width: 180 mm
Thickness: 60 mm
Weight: 2.19 kg


#08048

Net Price:
48,30 EUR
Unit: pcs

Omni-directional sector antenna VECTOR MIMO-60 19dBi

Directional gain: 19 dBi
Frequency range: 5100 MHz - 5875 MHz
Vertical beam width: 8 degree
Horizontal beam width: 60 degree
Polarization: Horizontal / vertical (both)
VSWR: 1,4
Impedance: 50 Ohm
Connector: 2 x N(F)
Height: 740mm
Width: 180 mm
Thickness: 60 mm
Weight: 2.31 kg


#08049

Net Price:
47,10 EUR
Unit: pcs

Omni-directional sector antenna VECTOR MIMO-90 18dBi

Directional gain: 18 dBi
Frequency range: 5.10 - 6.0 GHz
Vertical beam width: 8 degree
Horizontal beam width: 90 degree
Polarization: Horizontal / vertical (both)
VSWR: 1,4
Impedance: 50 Ohm
Connector: 2 x N(F)
Height: 740mm
Width: 180 mm
Thickness: 60 mm
Weight: 2.22 kg


#05463

Net Price:
39,50 EUR
Unit: pcs

Omni-directional sector antenna VECTOR H-PRO 18dBi - 90 degree

Directional gain: 18 dBi
Frequency range: 5100 MHz - 5875 MHz
Vertical beam width: 7 degree
Horizontal beam width: 90 degree
Polarization: H
VSWR: 1,4
Impedance: 50 Ohm
Connector: N(F)
Height: 740 mm
Width: 120 mm
Thickness: 60 mm
Weight: 1,14 kg


#06781

Net Price:
42,00 EUR
Unit: pcs

Omni-directional sector antenna VECTOR H-PRO 19dBi - 60 degree

Directional gain: 19 dBi
Frequency range: 5.10 - 5.875 GHz
Vertical beam width: 7 degree
Horizontal beam width: 60 degree
Polarization: H
VSWR: 1,4
Impedance: 50 Ohm
Connector: N(F)
Height: 740 mm
Width: 120 mm
Thickness: 60 mm
Weight: 1,14 kg


#05461

Net Price:
34,40 EUR
Unit: pcs

Omni-directional sector antenna VECTOR MINI H-PRO 17dBi

Directional gain: 17 dBi
Frequency range: 5100 MHz - 5875 MHz
Vertical beam width: 10 degree
Horizontal beam width: 90 degree
Polarization: H
VSWR: 1,4
Impedance: 50 Ohm
Connector: N(F)
Height: 420 mm
Width: 95 mm
Thickness: 40 mm
Weight: 0,33 kg


#08051

Net Price:
40,00 EUR
Unit: pcs

Omni-directional sector antenna VECTOR MINI MIMO-90 17dBi

Directional gain: 17 dBi
Frequency range: 5.10 - 6.0 GHz
Vertical beam width: 8 degree
Horizontal beam width: 90 degree
Polarization: Horizontal / vertical (both)
VSWR: 1,4
Impedance: 50 Ohm
Connector: 2 x N(F)
Height: 420 mm
Width: 95 mm
Thickness: 40 mm
Weight: 0.36 kg


#05462

Net Price:
34,40 EUR
Unit: pcs

Omni-directional sector antenna VECTOR MINI V-PRO 17dBi

Directional gain: 17 dBi
Frequency range: 5100 MHz - 5875 MHz
Vertical beam width: 10 degree
Horizontal beam width: 90 degree
Polarization: V
VSWR: 1,4
Impedance: 50 Ohm
Connector: N(F)
Height: 420 mm
Width: 95 mm
Thickness: 40 mm
Weight: 0,33 kg


#05436

Net Price:
44,90 EUR
Unit: pcs

Omni-directional sector antenna VECTOR V-PRO 17dBi

Directional gain: 17 dBi
Frequency range: 5.10 - 5.875 GHz
Vertical beam width: 6 degree
Horizontal beam width: 120 degree
Polarization: V
VSWR: 1,4
Impedance: 50 Ohm
Connector: N(F)
Height: 740 mm
Width: 120 mm
Thickness: 60 mm
Weight: 1,9 kg


#05435

Net Price:
45,60 EUR
Unit: pcs

Omni-directional sector antenna VECTOR V-PRO 18dBi












Directional gain: 18 dBi
Frequency range: 5.10 - 5.875 GHz
Vertical beam width: 6 degree
Horizontal beam width: 90 degree
Polarization: V
VSWR: 1,4
Impedance: 50 Ohm
Connector: N(F)
Height: 740 mm
Width: 120 mm
Thickness: 60 mm
Weight: 1,9 kg


#05434

Net Price:
46,30 EUR
Unit: pcs

Omni-directional sector antenna VECTOR V-PRO 19dBi

Directional gain: 19 dBi
Frequency range: 5.10 - 5.875 GHz
Vertical beam width: 6 degree
Horizontal beam width: 60 degree
Polarization: V
VSWR: 1,4
Impedance: 50 Ohm
Connector: N(F)
Height: 740 mm
Width: 120 mm
Thickness: 60 mm
Weight: 1,9 kg

 <p>#05230 Net Price: 43,90 EUR Unit: pcs</p> <p>Omni-directional sector antenna VECTOR 18 dBi Gain: 18 dBi Frequency range: 5.15 - 5.875 GHz (channels 112 - 165) Vertical beam width: 5 degree Horizontal beam width: 120 degree Polarization: H VSWR: 1.5 Connector: N(F) Height: 686 mm Width: 50 mm Thickness: 20 mm Weight: 1.2 kg</p>	 <p>#05228 Net Price: 46,60 EUR Unit: pcs</p> <p>Omni-directional sector antenna VECTOR DUAL 16 dBi Gain: 16 dBi Frequency range: 5.15 - 5.875 GHz (channels 112 - 165) Vertical beam width: 4 degree Horizontal beam width: 2 x 110 degree Polarization: H VSWR: 1.5 Connector: N(F) Height: 686 mm Width: 50 mm Thickness: 20 mm Weight: 1.1 kg</p>	 <p>#06920 Net Price: 39,50 EUR Unit: pcs</p> <p>Omni-directional sector antenna VECTOR V-PRO 17 dBi - 120 degree Gain: 17 dBi Range: 5.10 - 5.875 GHz Vertical beam width: 7 degree Horizontal beam width: 120 degree Polarization: H Reverse radiation: -28 dBi VSWR: 1.4 Connector: N(F) Height: 740 mm Width: 120 mm Thickness: 60 mm Weight: 1.14 kg</p>
 <p>#05491 Net Price: 22,90 EUR Unit: pcs</p> <p>Outdoor Grid Parabolic antenna 27dBi, 5 Ghz (AP-F5G27) Dimension: 400x600 mm Frequency: 5.15~5.85GHz Impedance: 50 Ohms Gain: 27 dBi VSWR: < 1.5 (Typ.), 2.0 (Max.) HPBW/H(°): 6° HPBW/V(°): 9° Polarization: Vertical or Horizontal Connector Type: N Female Mounting: Pole Mount Application: Outdoor Lightning Protection: DC Ground Operating Temp.: -40°C~70°C(-40°F~149°F) Maximum Input Power: 100W Weight: 2.4 kg Rated Wind Velocity: 60 m/s</p>	 <p>#08519 Net Price: 31,20 EUR Unit: pcs</p> <p>Outdoor Panel antenna 23dBi (TP-Link TL-ANT5823B) Dimension: 320x320x20 mm Frequency: 5.15~5.85GHz Impedance: 50 Ohms Gain: 23 dBi VSWR(MAX.): < 1.5 HPBW/H(°): 12° HPBW/V(°): 12° Polarization: Vertical or Horizontal Connector Type: N Female Mounting: Pole Mount / Wall Mount Application: Outdoor Lightning Protection: DC Ground Operating Temp.: -40°C~65°C(-40°F~149°F) Storage Temp.: -40°C~80°C(-40°F~176°F) Maximum Input Power: 100W Safety, Emission and Others: RoHS, WEEE Manufacturer: TP-Link</p>	 <p>#06921 Net Price: 32,20 EUR Unit: pcs</p> <p>Panel antenna RooTenna 19 dBi 5GHz Antenna type: panel Frequency range: 4940-5850 MHz Gain: 19 dBi Beam width: 15° Polarization: H or V VSWR: 1.5 Impedance: 50 Ω Connector: SMA Diam of holder: 38 - 51 mm Dimensions: 267 x 267 x 89 mm Weight: 0.8 kg</p>
 <p>#05399 Net Price: 45,20 EUR Unit: pcs</p> <p>Parabolic dish antenna 18 dBi (smartBridges sB3801-5518) Frequency range: 4.9 - 5.85 GHz Dish diameter: 241 mm Gain: 18 dBi Beam width: 16 degree Polarization: horizontal or vertical VSWR: 1.4 Impedance: 50 Ohm Cable: 60 cm LMR40 Connector: N(M) Weight: 4,9 kg</p>	 <p>#05476 Net Price: 37,30 EUR Unit: pcs</p> <p>Parabolic dish antenna PARABOLA XP 29 dBi, 5 GHz Dish diameter: 500 mm Frequency range: 5,2 GHz + 5,9 GHz Gain: 29 dBi Vertical beam width: 4,5 degree Horizontal beam width: 4,5 degree Polarization: h, v VSWR: 1.4 Connector: SMA-RP(M) Weight: 1,4 kg Cable: MRC 240, 1m</p>	
Antennas LTE, 3G, GSM		
 <p>#08957 Net Price: 11,00 EUR Unit: pcs</p> <p>Mini omni-directional antenna AS1-LTE Frequency range: 790-960 MHz, 1710-2700MHz Gain: up to 5 dBi Impedance: 50 Ohm Connector: interchangeable TS9 / CRC9 Standard: LTE To use with: Huawei B593s; B593u; E5373; E398</p>	 <p>#08958 Net Price: 12,70 EUR Unit: pcs</p> <p>Mini omni-directional outdoor antenna AZ4/LTE Frequency range: 790-960 MHz, 1710-2700MHz Gain: 3 dBi Impedance: 50 Ohm Connector: SMA + interchangeable TS9 / CRC9 Standard: LTE To use with: Huawei B593s; B593u; E5373; E398</p>	 <p>#08959 Net Price: 25,90 EUR Unit: pcs</p> <p>Mini omni-directional outdoor antenna set AZ4/LTE x2 2x AZ4/LTE antenna with mounting kit. Frequency range: 790-960 MHz, 1710-2700MHz Gain: 3 dBi Impedance: 50 Ohm Connector: SMA + interchangeable TS9 / CRC9 Standard: LTE To use with: Huawei B593s; B593u; E5373; E398</p>

Antenna patch cables		
 <p>#02627 Net Price: 13,20 EUR Unit: pcs</p> <p>Patch cable, H155 N(F) - SMA RP(M), 1 m</p>	 <p>#02633 Net Price: 14,60 EUR Unit: pcs</p> <p>Patch cable, H155 N(F) - SMA RP(M), 2 m</p>	 <p>#05232 Net Price: 16,10 EUR Unit: pcs</p> <p>Patch cable, H155 N(F) - SMA RP(M), 3 m</p>
 <p>#02634 Net Price: 19,00 EUR Unit: pcs</p> <p>Patch cable, H155 N(F) - SMA RP(M), 5 m</p>	 <p>#02626 Net Price: 33,70 EUR Unit: pcs</p> <p>Patch cable, H155 N(F) - SMA RP(M), 15 m</p>	 <p>#02614 Net Price: 26,30 EUR Unit: pcs</p> <p>Patch cable, H155 N(F) - SMA RP(M), 10 m</p>
 <p>#02631 Net Price: 13,20 EUR Unit: pcs</p> <p>Patch cable, H155 N(M) - SMA RP(M), 1 m</p>	 <p>#02629 Net Price: 14,60 EUR Unit: pcs</p> <p>Patch cable, H155 N(M) - SMA RP(M), 2 m</p>	 <p>#05231 Net Price: 16,10 EUR Unit: pcs</p> <p>Patch cable, H155 N(M) - SMA RP(M), 3 m</p>
 <p>#02635 Net Price: 19,00 EUR Unit: pcs</p> <p>Patch cable, H155 N(M) - SMA RP(M), 5 m</p>	 <p>#02696 Net Price: 26,30 EUR Unit: pcs</p> <p>Patch cable, H155 N(M) - SMA RP(M), 10 m</p>	 <p>#02632 Net Price: 33,70 EUR Unit: pcs</p> <p>Patch cable, H155 N(M) - SMA RP(M), 15 m</p>
 <p>#05201 Net Price: 13,20 EUR Unit: pcs</p> <p>Patch cable, H155 SMA RP(M) - SMA RP(F), 1 m</p>	 <p>#05202 Net Price: 14,60 EUR Unit: pcs</p> <p>Patch cable, H155 SMA RP(M) - SMA RP(F), 2 m</p>	 <p>#05203 Net Price: 19,00 EUR Unit: pcs</p> <p>Patch cable, H155 SMA RP(M) - SMA RP(F), 5 m</p>
 <p>#05204 Net Price: 26,30 EUR Unit: pcs</p> <p>Patch cable, H155 SMA RP(M) - SMA RP(F) 10 m</p>	 <p>#05310 Net Price: 14,60 EUR Unit: pcs</p> <p>Patch cable, H155 TNC RP(M) - N(M), 2 m</p>	 <p>#05311 Net Price: 16,10 EUR Unit: pcs</p> <p>Patch cable, H155 TNC RP(M) - N(M), 3 m</p>
 <p>#05357 Net Price: 13,20 EUR Unit: pcs</p> <p>Patch cable CNT200 N(M) - SMA RP(M), 1 m</p>	 <p>#05358 Net Price: 14,60 EUR Unit: pcs</p> <p>Patch cable CNT200 N(M) - SMA RP(M), 2 m</p>	 <p>#05361 Net Price: 16,10 EUR Unit: pcs</p> <p>Patch cable CNT200 N(M) - SMA RP(M), 3 m</p>
 <p>#05347 Net Price: 19,00 EUR Unit: pcs</p> <p>Patch cable CNT200 N(M) - SMA RP(M), 5 m</p>	 <p>#05272 Net Price: 22,00 EUR Unit: pcs</p> <p>Patch cable CNT200 N(M) - SMA RP(M), 7 m</p>	 <p>#05346 Net Price: 26,30 EUR Unit: pcs</p> <p>Patch cable CNT200 N(M) - SMA RP(M), 10 m</p>
 <p>#06874 Net Price: 13,20 EUR Unit: pcs</p> <p>Patch cable CNT200 SMA(M) - N(M), 1 m</p>	 <p>#05273 Net Price: 14,60 EUR Unit: pcs</p> <p>Patch cable CNT400 N(M) - N(F), 1 m</p>	 <p>#05362 Net Price: 20,50 EUR Unit: pcs</p> <p>Patch cable CNT400 N(M) - N(F), 3 m</p>



#05301
Net Price:
14,60 EUR
Unit: pcs

Patch cable CNT400 N(M) - N(F), 5 m



#05359
Net Price:
32,20 EUR
Unit: pcs

Patch cable CNT400 N(M) - N(F), 7 m



#06044
Net Price:
14,60 EUR
Unit: pcs

Patch cable CNT400 N(M) - N(M), 1 m



#05478
Net Price:
17,60 EUR
Unit: pcs

Patch cable CNT400 N(M) - N(M), 2 m



#05477
Net Price:
41,00 EUR
Unit: pcs

Patch cable CNT400 N(M) - N(M), 10 m

Wireless accessories



#06933
Net Price:
15,90 EUR
Unit: set

(E8514) Tower clamp, OK-43T13

Distance from the mast of the chimney: 130 mm
Mast diameter max.: 50 mm



#06932
Net Price:
14,50 EUR
Unit: set

(E8516) Tower clamp, OK-50W13

Distance from the mast of the chimney: 130 mm
Mast diameter max.: 50 mm



#05381
Net Price:
6,39 EUR
Unit: pcs

(E8533) Wall bracket, 0 MM-50L13

Distance from a wall: 130 mm
Mount holes diameter: 12 mm



#06562
Net Price:
14,10 EUR
Unit: pcs

(E8533) Wall bracket, OMP-50L40

Distance from a wall: 387 mm
Mount hole diameter: 53 mm



#05382
Net Price:
3,44 EUR
Unit: pcs

(E8681) Antenna wall support, UML-38L10

Diameter: 38 mm
Distance from a wall: 130 mm
Height: 100 mm
Mount holes diameter: 9 mm



#05383
Net Price:
4,76 EUR
Unit: pcs

(E8682) Wall bracket, UML-38L30

Diameter: 38 mm
Distance from a wall: 300 mm
Height: 300 mm
Mount holes diameter: 9 mm
Weight: 0.97 kg



#06729
Net Price:
7,59 EUR
Unit: pcs

(E8686) Wall bracket, UML-38L30x60

Diameter: 38 mm
Distance from a wall: 340 mm
Height: 580 mm
Mount holes diameter: 10 mm
Weight: 1.44 kg
colour: white or silver



#05385
Net Price:
3,76 EUR
Unit: pcs

(E8728) Antenna mount, TV-SAT, US-32*200, painted

Diameter: 32 mm
Distance from a wall: 200 mm



#08806
Net Price:
15,20 EUR
Unit: pcs

(E8735Y) Antenna support, WG-5, 50 cm x 110 cm

Diameter: 38 mm
Distance from a wall: 500 mm
Height: 1100 mm



#05390
Net Price:
7,42 EUR
Unit: pcs

(E903815) Antenna mast, 38 mm/1.5

Diameter: 38 mm
Width: 1500 mm



#05394
Net Price:
4,33 EUR
Unit: pcs

(E9228) Antenna support, WG-25/800

Diameter: 25 mm
Width: 800 mm



#08182
Net Price:
7,51 EUR
Unit: pcs

Mikrotik Power Adapter, 24V, 1A, PoE


#09040

Net Price:
6,99 EUR
Unit: pcs

Nano adapter Bluetooth 4.0 (TP-Link UB400)

- Bluetooth 4.0 - Applies the latest Bluetooth 4.0 with low energy (BLE) technology and it is backward compatible with Bluetooth V3.0/2.1/2.0/1.1
- Driver Free - Plug and Play for Win 8, Win 8.1, and Win 10
- Nano-Sized - Ultra-small for convenient portability with reliable high performance
- Supported Operating System - Supports Windows 10/8.1/8/7/XP

HARDWARE FEATURES

Standards and Protocols: Bluetooth 4.0

Interface: USB 2.0

Dimensions (W x D x H): 0.58 x 0.27 x 0.74 in (14.8 x 6.8 x 18.9 mm)

OTHERS

Certification: FCC, CE, RoHS

Package Contents: Bluetooth 4.0 Nano USB Adapter UB400,

Quick Installation Guide

System Requirements: Windows 10/8.1/8/7/XP

Environment

Operating Temperature: 0°C~40°C (32°F ~104°F)

Storage Temperature: -40°C~70°C (-40°F ~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Manufacturer: TP-Link

NEW


#09196

Net Price:
8,81 EUR
Unit: pcs

Nano adapter Bluetooth 5.0 (TP-Link UB500)

- Bluetooth 5.0 - Applies the latest Bluetooth 5.0 technology, backward compatible with Bluetooth V4.0/3.0/2.1/2.0/1.1
- Wireless Connectivity - Provides stable and convenient communication between Bluetooth devices and your PC or laptop
- Nano-Sized - Ultra-small for convenient portability with reliable high performance
- Supported Operating System - Windows 10/8.1/7

HARDWARE FEATURES

Standards and Protocols: Bluetooth 5.0

Interface: USB 2.0

Dimensions (W x D x H): 0.58 x 0.27 x 0.74 in (14.8 x 6.8 x 18.9 mm)

OTHERS

Package Contents: Bluetooth 5.0 Nano USB Adapter UB500,

Quick Installation Guide

System Requirements: Windows 10/8.1/8/7/XP

Environment

Operating Temperature: 0°C~40°C (32°F ~104°F)

Storage Temperature: -40°C~70°C (-40°F ~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Manufacturer: TP-Link


#06379

Net Price:
3,15 EUR
Unit: pcs

Pigtail U.FL - N(F), 20cm, RG316

#06380

Net Price:
3,90 EUR
Unit: pcs

Pigtail U.FL-SMA RP(F), 20cm, RG316

#05408

Net Price:
6,67 EUR
Unit: pcs

PoE Injector 48V, 30W. (smartBridges sB2840)

#08847

Net Price:
11,80 EUR
Unit: pcs

Protective radome Ubiquiti NanoBeam (Ubiquiti NBE-RAD-400)

A protective radome is available as an optional accessory for the NBE-M2-400 (#08843) and NBE-M5-400 (#08842).


#05227

Net Price:
14,10 EUR
Unit: pcs

Two-way antenna signal splitter

Splitter makes possible connecting two identical WiFi antennas to single AP. It ensures full electrical compatibility of attached antenna system. After installing the splitter one must turn off connected AP and turn it back again after about 10 seconds. The use of electrocitic copper secures best working conditions.

Impedance: 50 Ω

Connectors: 1x N(F) (input), 2x N(F) (output)

Signal loss: 3 dBm

Index

Mikrotik Routerboard	1
Standard AC	3
Standard N	29
Wireless active devices 2.4GHz	50
Wireless active devices 5GHz	53
Antennas 2.4 GHz	55
Antennas 5 GHz	58
Antennas LTE, 3G, GSM	61
Antenna patch cables	62
Wireless accessories	63