



FCC CFR47 PART 15 SUBPART C

Bluetooth

CERTIFICATION TEST REPORT

FOR

AIRWAY CLEARANCE SYSTEM

PRODUCT NAME: PMACS1WI

FCC ID: 2AJKO-PMACS1WI

REPORT NUMBER: 4787592605-E3V2

ISSUE DATE: DEC 26, 2016

Prepared for

Hill-Rom Services Private Limited
1 Yishun Avenue 7, 768923, Singapore

Prepared by

UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



ACCREDITED

TL-637

Revision History

Rev.	Issue Date	Revisions	Revised By
V1	12/21/16	Initial issue	Junwhan Lee
V2	12/26/16	Addressed TCB's questions	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>6</i>
4.2. <i>SAMPLE CALCULATION.....</i>	<i>6</i>
4.3. <i>MEASUREMENT UNCERTAINTY</i>	<i>6</i>
5. EQUIPMENT UNDER TEST	7
5.1. <i>DESCRIPTION OF EUT.....</i>	<i>7</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>7</i>
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>7</i>
5.4. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	<i>7</i>
5.5. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>8</i>
6. TEST AND MEASUREMENT EQUIPMENT	10
7. SUMMARY TABLE	11
8. ANTENNA PORT TEST RESULTS	12
8.1. <i>20 dB AND 99% BANDWIDTH.....</i>	<i>12</i>
8.1.1. <i>BASIC DATA RATE GFSK MODULATION.....</i>	<i>12</i>
8.1.2. <i>ENHANCED DATA RATE Pi/4-DQPSK MODULATION</i>	<i>12</i>
8.1.3. <i>ENHANCED DATA RATE 8PSK MODULATION.....</i>	<i>12</i>
8.1.4. <i>20 dB AND 99% BANDWIDTH PLOTS.....</i>	<i>13</i>
8.2. <i>HOPPING FREQUENCY SEPARATION</i>	<i>16</i>
8.3. <i>NUMBER OF HOPPING CHANNELS.....</i>	<i>17</i>
8.4. <i>AVERAGE TIME OF OCCUPANCY.....</i>	<i>19</i>
8.5. <i>OUTPUT POWER</i>	<i>23</i>
8.5.1. <i>BASIC DATA RATE GFSK MODULATION.....</i>	<i>23</i>
8.5.2. <i>ENHANCED DATA RATE Pi/4-DPSK MODULATION</i>	<i>23</i>
8.5.3. <i>ENHANCED DATA RATE 8PSK MODULATION.....</i>	<i>23</i>
8.5.4. <i>OUTPUT POWER PLOTS</i>	<i>24</i>
8.6. <i>AVERAGE POWER.....</i>	<i>27</i>
8.6.1. <i>BASIC DATA RATE GFSK MODULATION.....</i>	<i>27</i>
8.6.2. <i>DATA RATE Pi/4-DQPSK MODULATION</i>	<i>27</i>
8.6.3. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	<i>27</i>
8.7. <i>CONDUCTED SPURIOUS EMISSIONS.....</i>	<i>28</i>
8.7.1. <i>BASIC DATA RATE GFSK MODULATION</i>	<i>29</i>

9. RADIATED TEST RESULTS	41
<i>9.1. LIMITS AND PROCEDURE</i>	<i>41</i>
<i>9.2. TRANSMITTER ABOVE 1 GHz</i>	<i>43</i>
<i>9.2.1. BASIC DATA RATE GFSK MODULATION.....</i>	<i>43</i>
<i>9.2.2. ENHANCED DATA RATE 8PSK MODULATION</i>	<i>53</i>
<i>9.3. WORST-CASE BELOW 1 GHz</i>	<i>63</i>
10. AC POWER LINE CONDUCTED EMISSIONS	65
11. SETUP PHOTOS	70

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Hill-Rom Services Private Limited
EUT DESCRIPTION: Airway Clearance System
PRODUCT NAME: PMACS1WI
SERIAL NUMBER: PREDVM0036 (RADIATED & CONDUCTED)
DATE TESTED: OCT 07, 2016 - DEC 21, 2016

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro
<input checked="" type="checkbox"/> Chamber 1
<input type="checkbox"/> Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a Airway Clearance System with DTS/UNII a/b/g/n and BT/BLE features. This test report addresses the DSS (BT) operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2402 - 2480	Basic GFSK	Average	7.998	6.307
		Peak	8.255	6.691
	Enhanced Pi/4-DPSK	Average	5.155	3.277
		Peak	7.093	5.120
	Enhanced 8PSK	Average	5.176	3.293
		Peak	7.464	5.577

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an Chip antenna, with a maximum gain of 0.5 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

Note: GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance. For average power data please refer to section 8.6.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Adapter	SHENZHEN MEGMEET ELECTRICAL CO., LTD	MANGO120-24CK	8801631000045	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-DIN	Shielded	1.2m	N/A

TEST SETUP

The EUT is a stand-alone unit during the tests.
Test software exercised the EUT to enable BT mode.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-25-17
Antenna, Horn, 18 GHz	ETS	3115	00161451	05-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168724	06-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168717	06-17-17
Antenna, Horn, 40 GHz	ETS	3116C	00166155	11-30-17
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	12-15-17
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-17-17
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-16-17
Preamplifier	ETS	3115-PA	00167475	08-17-17
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-16-17
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-17-17
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-16-17
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	08-18-17
Average Power Sensor	R&S	NRZ-Z91	102681	08-16-17
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-17-17
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-17-17
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-16-17
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-16-17
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-17-17
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-16-17
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-17-17
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-16-17
High Pass Filter 6GHz	Micro-Tronics	HPM17542	009	08-17-17
High Pass Filter 6GHz	Micro-Tronics	HPM17542	016	08-16-17
LISN	R&S	ENV-216	101836	08-16-17
LISN	R&S	ENV-216	101837	08-16-17
Attenuator	PASTERNACK	PE7087-10	A009	08-16-17
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	11-25-17

7. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
2.1049	Occupied Band width (99%)	N/A	Conducted	Pass	1.163 MHz
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-38.41 dBm
15.247 (b)(1)	TX conducted output power	<21dBm		Pass	8.255 dBm (Peak)
15.247 (a)(1)	Hopping frequency separation	> 25KHz		Pass	1 MHz
15.247 (a)(1)(iii)	Number of Hopping channels	More than 15 non-overlapping channels		Pass	79
15.247 (a)(1)(iii)	Avg Time of Occupancy	< 0.4sec		Pass	0.31669 sec
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass	48.56 dBuV (Qp)
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m	Radiated	Pass	45.02 dBuV/m (Av)

8. ANTENNA PORT TEST RESULTS

8.1. 20 dB AND 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to \geq 1% of the 20 dB bandwidth. The VBW is set to \geq RBW. The sweep time is coupled.

RESULTS

8.1.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [kHz]	99% Bandwidth [KHz]
Low	2402	905.900	860.200
Mid	2441	885.900	862.600
High	2480	888.200	861.130
Worst		905.900	862.600

8.1.2. ENHANCED DATA RATE Pi/4-DQPSK MODULATION


Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [MHz]
Low	2402	1.256	1.161
Mid	2441	1.228	1.161
High	2480	1.230	1.162
Worst		1.256	1.162

8.1.3. ENHANCED DATA RATE 8PSK MODULATION


Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [MHz]
Low	2402	1.218	1.163
Mid	2441	1.236	1.160
High	2480	1.236	1.161
Worst		1.236	1.163

8.1.4. 20 dB AND 99% BANDWIDTH PLOTS


GFSK BANDWIDTH



Pi/4-DQPSK BANDWIDTH



8PSK BANDWIDTH



8.2. HOPPING FREQUENCY SEPARATION

LIMIT

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hoping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

HOPPING FREQUENCY SEPARATION PLOT



8.3. NUMBER OF HOPPING CHANNELS

LIMIT

FCC §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.

TEST PROCEDURE


DA 00-705: The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


RESULTS

Normal Mode: 79 Channels observed.

NUMBER OF HOPPING CHANNELS PLOTS

NUMBER OF HOPPING CHANNELS (100 MHZ SPAN)





8.4. AVERAGE TIME OF OCCUPANCY

LIMIT

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 31.6 second period (79 channels * 0.4 s) is equal to $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{pulse width}$.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{pulse width}$.


RESULTS

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Normal					
DH1	0.377	32	0.120480	0.4	-0.2795
DH3	1.632	16	0.261120	0.4	-0.1389
DH5	2.879	11	0.316690	0.4	-0.0833
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK AFH					
DH1	0.377	8	0.030120	0.4	-0.36988
DH3	1.632	4	0.065280	0.4	-0.33472
DH5	2.879	2.75	0.079173	0.4	-0.32083


DH1



DH3



DH5



8.5. OUTPUT POWER

LIMIT

§15.247 (b) (1)

The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

8.5.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2402	5.083	21	-15.917
Middle	2441	7.343	21	-13.657
High	2480	8.255	21	-12.745
Worst		8.255	21	-12.745

8.5.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION


Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2402	3.202	21	-17.798
Middle	2441	5.911	21	-15.089
High	2480	7.093	21	-13.907
Worst		7.093	21	-13.907

8.5.3. ENHANCED DATA RATE 8PSK MODULATION


Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2402	3.613	21	-17.387
Middle	2441	6.177	21	-14.823
High	2480	7.464	21	-13.536
Worst		7.464	21	-13.536

8.5.4. OUTPUT POWER PLOTS


GFSK OUTPUT POWER



Pi/4-DPSK OUTPUT POWER



8PSK OUTPUT POWER



8.6. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.1 dB (including 10 dB pad and 0.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

8.6.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	4.652	2.92
Middle	2441	7.003	5.01
High	2480	7.998	6.31

8.6.2. DATA RATE PI/4-DQPSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	0.910	1.23
Middle	2441	3.789	2.39
High	2480	5.155	3.28

8.6.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	0.920	1.24
Middle	2441	3.823	2.41
High	2480	5.176	3.29

8.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.

RESULTS

8.7.1. BASIC DATA RATE GFSK MODULATION

GFSK Mode







BandEdge Emission at GFSK Hopping Mode

[GFSK Hopping Mode] Low Channel BandEdge



[GFSK Hopping Mode] High Channel BandEdge



PI/4-DQPSK Mode








BandEdge Emission at PI/4-DQPSK Hopping Mode

[PI/4-DQPSK Hopping Mode] Low Channel BandEdge



[PI/4-DQPSK Hopping Mode] High Channel BandEdge




8PSK Mode



[8PSK] Mid Channel BandEdge



[8PSK] Mid Channel Spurious





BandEdge Emission at 8PSK Hopping Mode

[8PSK Hopping Mode] Low Channel BandEdge



[8PSK Hopping Mode] High Channel BandEdge



9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (μ V/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements.(Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.)

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1/T (on time) for average measurement.

$$\text{GFSK} = 1/T = 1 / 0.0029S = 350\text{Hz.}$$

The minimum VBW was 350Hz, but test receiver(ESU40) couldn't set value 350Hz. Due to this reason, testing VBW was set to 500Hz(Worst cases).

The spectrum from 1GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Note : Emission was pre-scanned from 9KHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.


Formula for converting the filed strength from uV/m to dBuV/m is:
Limit (dBuV/m) = 20 log limit (uV/m)

9.2. TRANSMITTER ABOVE 1 GHz

9.2.1. BASIC DATA RATE GFSK MODULATION

RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	47.34	Pk	31.8	-29	50.14	-	-	74	-23.86	127	150	H
2	* 2.349	49.21	Pk	31.7	-29	51.91	-	-	74	-22.09	127	150	H
3	* 2.39	35.88	VA1T	31.8	-29	38.68	54	-15.32	-	-	127	150	H
4	* 2.389	35.94	VA1T	31.8	-29	38.74	54	-15.26	-	-	127	150	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	46.01	Pk	31.8	-29	48.81	-	-	74	-25.19	156	150	V
2	* 2.326	48.99	Pk	31.7	-29	51.69	-	-	74	-22.31	156	150	V
3	* 2.39	35.87	VA1T	31.8	-29	38.67	54	-15.33	-	-	156	150	V
4	* 2.376	35.94	VA1T	31.8	-29	38.74	54	-15.26	-	-	156	150	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	49.58	Pk	32	-28.9	52.68	-	-	74	-21.32	89	149	H
2	* 2.484	49.69	Pk	32	-28.9	52.79	-	-	74	-21.21	89	149	H
3	* 2.484	38.52	VA1T	32	-28.9	41.62	54	-12.38	-	-	89	149	H
4	2.506	36.09	VA1T	32	-28.9	39.19	54	-14.81	-	-	89	149	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	49.83	Pk	32	-28.9	52.93	-	-	74	-21.07	156	144	V
2	* 2.484	50.74	Pk	32	-28.9	53.84	-	-	74	-20.16	156	144	V
3	* 2.484	39.04	VA1T	32	-28.9	42.14	54	-11.86	-	-	156	144	V
4	2.558	36.17	VA1T	32	-28.8	39.37	54	-14.63	-	-	156	144	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.804	46.31	PK	34	-33.8	46.51	-	-	74	-27.49	0-360	150	H
3	7.206	44.22	PK	35.7	-30.8	49.12	-	-	74	-24.88	0-360	250	H
5	9.608	30.44	PK	37	-27.3	40.14	-	-	74	-33.86	0-360	150	H
2	* 4.804	48.13	PK	34	-33.8	48.33	-	-	74	-25.67	0-360	150	V
4	7.206	37.98	PK	35.7	-30.8	42.88	-	-	74	-31.12	0-360	250	V
6	9.61	30.6	PK	37	-27.3	40.3	-	-	74	-33.7	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.804	53.53	PK2	34	-33.8	53.73	-	-	74	-20.27	212	128	H
* 4.804	39.36	VA1T	34	-33.8	39.56	54	-14.44	-	-	212	128	H
7.205	47.45	PK2	35.7	-30.8	52.35	-	-	74	-21.65	105	400	H
* 4.804	55.08	PK2	34	-33.8	55.28	-	-	74	-18.72	187	142	V
* 4.804	40.44	VA1T	34	-33.8	40.64	54	-13.36	-	-	187	142	V
7.206	47.32	PK2	35.7	-30.8	52.22	-	-	74	-21.78	103	158	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.882	45.38	PK	34	-34	45.38	-	-	74	-28.62	0-360	250	H
3	* 7.323	51.49	PK	35.8	-30.9	56.39	-	-	74	-17.61	0-360	250	H
5	9.765	30.68	PK	37.2	-26.6	41.28	-	-	74	-32.72	0-360	250	H
2	* 4.881	48.88	PK	34	-34	48.88	-	-	74	-25.12	0-360	150	V
4	* 7.323	45.24	PK	35.8	-30.9	50.14	-	-	74	-23.86	0-360	150	V
6	9.767	30.59	PK	37.2	-26.5	41.29	-	-	74	-32.71	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.881	52.18	PK2	34	-34	52.18	-	-	74	-21.82	89	145	H
* 4.882	38.2	VA1T	34	-34	38.2	54	-15.8	-	-	89	145	H
* 7.323	55.95	PK2	35.8	-30.9	60.85	-	-	74	-13.15	126	238	H
* 7.323	39.4	VA1T	35.8	-30.9	44.3	54	-9.7	-	-	126	238	H
* 4.882	53.97	PK2	34	-34	53.97	-	-	74	-20.03	89	148	V
* 4.882	39.79	VA1T	34	-34	39.79	54	-14.21	-	-	89	148	V
* 7.322	52.05	PK2	35.8	-30.9	56.95	-	-	74	-17.05	94	155	V
* 7.323	37.21	VA1T	35.8	-30.9	42.11	54	-11.89	-	-	94	155	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.959	48.75	PK	34	-34	48.75	-	-	74	-25.25	0-360	150	H
3	* 7.441	53.43	PK	35.8	-30.7	58.53	-	-	74	-15.47	0-360	250	H
5	9.92	32.21	PK	37.4	-27.2	42.41	-	-	74	-31.59	0-360	150	H
2	* 4.959	48.45	PK	34	-34	48.45	-	-	74	-25.55	0-360	150	V
4	* 7.441	45.63	PK	35.8	-30.7	50.73	-	-	74	-23.27	0-360	150	V
6	9.92	29.6	PK	37.4	-27.2	39.8	-	-	74	-34.2	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.96	53.53	PK2	34	-34	53.53	-	-	74	-20.47	189	149	H
* 4.96	39.55	VA1T	34	-34	39.55	54	-14.45	-	-	189	149	H
* 7.44	56.29	PK2	35.8	-30.7	61.39	-	-	74	-12.61	130	212	H
* 7.44	39.92	VA1T	35.8	-30.7	45.02	54	-8.98	-	-	130	212	H
* 4.96	54.54	PK2	34	-34	54.54	-	-	74	-19.46	78	168	V
* 4.96	40.15	VA1T	34	-34	40.15	54	-13.85	-	-	78	168	V
* 7.441	49.93	PK2	35.8	-30.7	55.03	-	-	74	-18.97	101	153	V
* 7.44	36.72	VA1T	35.8	-30.7	41.82	54	-12.18	-	-	101	153	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

9.2.2. ENHANCED DATA RATE 8PSK MODULATION RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dB _U)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dB _U /m)	Average Limit (dB _U /m)	Margin (dB)	Peak Limit (dB _U /m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	47.59	Pk	31.8	-29	50.39	-	-	74	-23.61	137	105	H
2	* 2.371	49	Pk	31.8	-29	51.8	-	-	74	-22.2	137	105	H
3	* 2.39	36	VA1T	31.8	-29	38.8	54	-15.2	-	-	137	105	H
4	* 2.389	36.35	VA1T	31.8	-29	39.15	54	-14.85	-	-	137	105	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBm)	Average Limit (dBm/m)	Margin (dB)	Peak Limit (dBm/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	45.3	Pk	31.8	-29	48.1	-	-	74	-25.9	158	136	V
2	* 2.363	49.01	Pk	31.8	-29	51.81	-	-	74	-22.19	158	136	V
3	* 2.39	35.51	VA1T	31.8	-29	38.31	54	-15.69	-	-	158	136	V
4	* 2.337	36.43	VA1T	31.7	-29	39.13	54	-14.87	-	-	158	136	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	45.86	Pk	32	-28.9	48.96	-	-	74	-25.04	89	148	H
2	2.505	49.25	Pk	32	-28.9	52.35	-	-	74	-21.65	89	148	H
3	* 2.484	36.08	VA1T	32	-28.9	39.18	54	-14.82	-	-	89	148	H
4	* 2.484	36.08	VA1T	32	-28.9	39.18	54	-14.82	-	-	89	148	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_2	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	47.27	Pk	32	-28.9	50.37	-	-	74	-23.63	155	144	V
2	2.533	49.45	Pk	32	-28.8	52.65	-	-	74	-21.35	155	144	V
3	* 2.484	36.1	VA1T	32	-28.9	39.2	54	-14.8	-	-	155	144	V
4	* 2.484	36.09	VA1T	32	-28.9	39.19	54	-14.81	-	-	155	144	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

HARMONICS AND SPURIOUS EMISSIONS



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.804	40.5	Pk	34	-33.8	40.7	-	-	74	-33.3	0-360	250	H
4	7.206	34.77	Pk	35.7	-30.8	39.67	-	-	74	-34.33	0-360	150	H
5	9.61	31.41	Pk	37	-27.3	41.11	-	-	74	-32.89	0-360	250	H
2	* 4.804	39.76	Pk	34	-33.8	39.96	-	-	74	-34.04	0-360	250	V
3	7.206	34.63	Pk	35.7	-30.8	39.53	-	-	74	-34.47	0-360	150	V
6	9.61	31.24	Pk	37	-27.3	40.94	-	-	74	-33.06	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.805	49.95	PK2	34	-33.8	50.15	-	-	74	-23.85	220	109	H
* 4.804	39.32	VA1T	34	-33.8	39.52	54	-14.48	-	-	220	109	H
* 4.804	49.71	PK2	34	-33.8	49.91	-	-	74	-24.09	178	117	V
* 4.804	39.22	VA1T	34	-33.8	39.42	54	-14.58	-	-	178	117	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.881	41.41	Pk	34	-34	41.41	-	-	74	-32.59	0-360	150	H
4	* 7.323	40.33	Pk	35.8	-30.9	45.23	-	-	74	-28.77	0-360	250	H
5	9.752	30.86	Pk	37.2	-26.7	41.36	-	-	74	-32.64	0-360	150	H
2	* 4.881	43.61	Pk	34	-34	43.61	-	-	74	-30.39	0-360	150	V
3	* 7.323	33.99	Pk	35.8	-30.9	38.89	-	-	74	-35.11	0-360	150	V
6	9.749	30.19	Pk	37.2	-26.8	40.59	-	-	74	-33.41	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.882	50.1	PK2	34	-34	50.1	-	-	74	-23.9	241	322	H
* 4.882	35.21	VA1T	34	-34	35.21	54	-18.79	-	-	241	322	H
* 4.882	51.75	PK2	34	-34	51.75	-	-	74	-22.25	204	246	V
* 4.882	36.34	VA1T	34	-34	36.34	54	-17.66	-	-	204	246	V
* 7.322	48.39	PK2	35.8	-30.9	53.29	-	-	74	-20.71	76	105	H
* 7.323	32.13	VA1T	35.8	-30.9	37.03	54	-16.97	-	-	76	105	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.96	47.33	PK	34	-34	47.33	-	-	74	-26.67	0-360	150	H
3	* 7.44	43.58	PK	35.8	-30.7	48.68	-	-	74	-25.32	0-360	250	H
5	9.918	30.39	PK	37.4	-27.3	40.49	-	-	74	-33.51	0-360	250	H
2	* 4.959	45.01	PK	34	-34	45.01	-	-	74	-28.99	0-360	150	V
4	* 7.44	36.6	PK	35.8	-30.7	41.7	-	-	74	-32.3	0-360	150	V
6	9.923	29.94	PK	37.4	-27.1	40.24	-	-	74	-33.76	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.96	51.68	PK2	34	-34	51.68	-	-	74	-22.32	189	171	H
* 4.96	36.98	VA1T	34	-34	36.98	54	-17.02	-	-	189	171	H
* 7.44	51.9	PK2	35.8	-30.7	57	-	-	74	-17	129	208	H
* 7.44	34.8	VA1T	35.8	-30.7	39.9	54	-14.1	-	-	129	208	H
* 4.96	51.76	PK2	34	-34	51.76	-	-	74	-22.24	88	144	V
* 4.96	36.78	VA1T	34	-34	36.78	54	-17.22	-	-	88	144	V
* 7.44	47.55	PK2	35.8	-30.7	52.65	-	-	74	-21.35	104	147	V
* 7.44	32.06	VA1T	35.8	-30.7	37.16	54	-16.84	-	-	104	147	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak


V1TV - U-NII: VB=1/Ton, Linear Voltage Average where: Ton is packet duration

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration


9.3. WORST-CASE BELOW 1 GHz

GFSK SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)

HORIZONTAL PLOT



VERTICAL PLOT



BELow 1 GHz TABLE

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163-750	Bi-Log	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	57.4125	45.26	Pk	13	-30	28.26	40	-11.74	0-360	400	H
2	179.26	49.2	Pk	9.4	-28.3	30.3	43.52	-13.22	0-360	100	H
3	35.3125	48.85	Pk	10.6	-30.4	29.05	40	-10.95	0-360	100	V
4	* 171.8225	49.4	Pk	9	-28.4	30	43.52	-13.52	0-360	100	V
5	186.74	46.44	Pk	10.1	-28.3	28.24	43.52	-15.28	0-360	200	V
6	207.9	41.66	Pk	11.5	-28.1	25.06	43.52	-18.46	0-360	100	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

10. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers

Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_with ex-cord_L1	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
1	.366	41.43	Pk	9.9	0	51.33	58.59	-7.26	-	-
2	.375	29.63	Av	9.9	0	39.53	-	-	48.39	-8.86
3	.501	35.52	Pk	9.9	0	45.42	56	-10.58	-	-
4	.501	24.98	Av	9.9	0	34.88	-	-	46	-11.12
5	.735	38.73	Pk	9.9	0	48.63	56	-7.37	-	-
6	.735	24.77	Av	9.9	0	34.67	-	-	46	-11.33
7	1.023	34.5	Pk	9.8	0	44.3	56	-11.7	-	-
8	1.023	21.75	Av	9.8	0	31.55	-	-	46	-14.45
9	1.608	37.92	Pk	9.7	.1	47.72	56	-8.28	-	-
10	1.626	19.96	Av	9.7	.1	29.76	-	-	46	-16.24
11	1.752	36.2	Pk	9.7	.1	46	56	-10	-	-
12	1.752	16.78	Av	9.7	.1	26.58	-	-	46	-19.42

Pk - Peak detector

Av - Average detection


Quasi-Peak Emissions

Phase L1 .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_with ex-cord_L1	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
.3696	38.66	Qp	9.9	0	48.56	58.51	-9.95	-	-
.7314	32.73	Qp	9.9	0	42.63	56	-13.37	-	-
1.6035	32.74	Qp	9.7	.1	42.54	56	-13.46	-	-
1.7475	31.16	Qp	9.7	.1	40.96	56	-15.04	-	-

Qp – Quasi-Peak detector

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_w ith ex- cord_N	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22	Margin (dB)	CISPR 22	Margin (dB)
							Class B ITE QP		Class B ITE AV	
13	.339	39.04	Pk	9.8	0	48.84	59.23	-10.39	-	-
14	.375	26.63	Av	9.9	0	36.53	-	-	48.39	-11.86
15	.438	35.42	Pk	9.9	0	45.32	57.1	-11.78	-	-
16	.438	26.16	Av	9.9	0	36.06	-	-	47.1	-11.04
17	.735	37.97	Pk	9.9	0	47.87	56	-8.13	-	-
18	.735	24.76	Av	9.9	0	34.66	-	-	46	-11.34
19	1.032	34.27	Pk	9.8	0	44.07	56	-11.93	-	-
20	1.032	21.85	Av	9.8	0	31.65	-	-	46	-14.35
21	1.608	36.63	Pk	9.7	.1	46.43	56	-9.57	-	-
22	1.626	20.03	Av	9.7	.1	29.83	-	-	46	-16.17
23	1.752	36.48	Pk	9.7	.1	46.28	56	-9.72	-	-
24	1.752	16.77	Av	9.7	.1	26.57	-	-	46	-19.43

Pk - Peak detector

Quasi-Peak Emissions

Av - Average detection

Phase N .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_wit h ex-cord_N	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22	Margin (dB)	CISPR 22	Margin (dB)
						Class B ITE QP		Class B ITE AV	
.7386	32.73	Qp	9.9	0	42.63	56	-13.37	-	-
1.6044	31.76	Qp	9.7	.1	41.56	56	-14.44	-	-

Qp – Quasi-Peak detector