



INDUSTRIAL MODEL

THE PINNACLE OF RELIABILITY, DURABILITY, AND VERSATILITY



INDUSTRIAL GRADE

Strong and sturdy to withstand the demands of everyday industrial use



FLAT-FREE

No flats, no inflating, no punctures, no worries



LOW-MAINTENANCE

Prevent downtime, reduce cost, minimize hassle

DURABLE Dual legged kickstand, forged Al cranks, tamper proof axle bolts • **SAFE** Fully enclosed belt guard, reflectors, and courtesy bell

VALUE Designed to maximize quality and performance

CONTACT

NORTH AMERICA

Northamerica@mobiabikes.com

Phone: 310-884-7756

EUROPE & MIDDLE EAST

Europe@mobiabikes.com

Middle-East@mobiabikes.com

Phone: +49 7771 9185910

ASIA-PACIFIC

Apac@mobiabikes.com

Phone: +6421337276

LATIN AMERICA

Latam@mobiabikes.com

Phone: +54 9 11 60260108

MOBIABIKES.COM

SPECIFICATIONS

FRAMESET

FRAME

6061 Custom Industrial-grade Aluminum frame, hydro formed tubes, belt drive compatible, integrated rack & fender mounts

FORK

Industrial-grade strength Aluminum fork, oversized fork blades, double eyelet dropout

WHEELSETS

WHEELS

Alloy front/rear hubs, 12g spokes, 42mm wide double walled rims, flat-free tires

FRONT HUB

Alloy front hub, 36 hole, 12g compatible, double sealed bearings, rust proof coated axle

REAR HUB

Alloy rear hub, 36 hole, 12g compatible, double sealed bearings, coaster brake, rust proof coated axle

RIMS

Industrial-grade, 42mm wide dual wall alloy, 36 hole, 12 gauge spoke compatible

TIRES

Titec flat-free tires, 26" X 1.95", 45 p.s.i. equivalent

COMPONENTS

SADDLE

Custom design, durable top cover, internal gel, formed edge to prevent tearing

SEATPOST

Alloy, 400mm, 31.6mm, integrated security cable

HANDLEBAR

Heavy duty alloy handlebar with integrated alloy front basket, 660mm width, 60mm sweep back

FRONT BASKET

Industrial grade, tubular aluminum front basket, 400mm width X 300mm deep X 100mm height, max load 25kg

STEM

Alloy, 28.6 rear clamp, 4-bolt 25.4 front clamp, 25 degree rise

BRAKES

Coaster brake, rear hub

HEADSET

1-1/8" double sealed bearings, threadless

GRIPS

Dual Density comfort grips

FENDERS

Poly Carbonite, stainless steel fender supports

PEDALS

Industrial grade Aluminum w/integrated reflectors

DRIVETRAIN

CRANK

Gates Alloy, 5-arm, 170mm length

BOTTOM BRACKET

Sealed cartridge bearings, rust proof coated axle

BELT

118T Gates Center Track™ belt

FRONT SPROCKET

Gates 46T Stainless steel, Center Track™ belt drive

REAR SPROCKET

Gates 24T Stainless steel, Center Track™ belt drive

BELT GUARD

Rigid alloy guard, fully covers belt for safety

WEIGHT

18.5 kg (including front basket)

We reserve the right to make changes to the product information contained in this document any time without notice, including with respect to equipment, specifications, models, colors, and materials. Bike and frame weights are based off pre-production painted frames at time of publication. Weights may vary in final production.

SIZING AND FIT

Proper bike fit is essential for best performance and comfort. Any size and measurements showing are for general comparison purposes only.

GEOMETRY

Wheel size	26in
A: Seat tube	41.5cm
B: Seat tube angle	67°
C: Head tube Length	18cm
D: Head angle	69°
E: Effective top tube	62.5cm
F: Bottom bracket height	27.5cm
G: Chainstay length	45cm
H: Offset	5cm
I: Trail	5.8cm
J: Wheelbase	109.8cm

