## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Rac
------------------------------------

Supplier's address: Radium Customer Service, Dr. Eugen Kersting Str. 6, 51688 Wipperfürth, DE

**Model identifier:** 4008597198311

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	GY6.35		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

## **Product parameters**

Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
	nption in on- 00 h), rounded st integer	5	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), iners to the flux in , in a wide cone arrow cone (90º)	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	4,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	50	Spectral power dis-	See image
sions without	Width	18	tribution in the	in last page
separate con- trol gear, light-	Depth	18	range 250 nm to 800 nm, at full-load	

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	40
		Chromaticity coordi-	0,458
		nates (x and y)	0,410
Parameters for LED and OLED light sources:			
R9 colour rendering index value 0 Survi		Survival factor	0,90
the lumen maintenance factor	0,70		

(a)'-': not applicable; (b)'-': not applicable;

