

# BENEFITS OF INDUCTION



**FASTER** Rapid heat delivery with quicker recovery than gas or electric.



**COST EFFECTIVE** 90% less expensive than canned fuel and helps save on air conditioning costs.



**PRECISE** Even heating, no hot spots. Adjusts automatically as food is added or subtracted.



**SAFER** No open flame or hot coils; surface cool to the touch when pan is removed.



**MORE EFFICIENT** 50% more efficient than gas; heats pans directly without losing energy into the air.



**COOLER** Low radiant heat keeps room cool. Heat stops when pan is removed.



**CLEANER** Sealed glass surface wipes easy. No stocking, spilling or disposing of canned fuel.



# SPRING USA INDUCTION

COUNTERTOP | RECONFIGURABLE | DROP-IN | HIDDEN

**ONE-YEAR OVERNIGHT EXCHANGE WARRANTY** on all Spring USA ranges in the continental United States

**PROVEN RELIABILITY** with a less than 1% failure rating

**SMART SCAN® TECHNOLOGY** safety features adjusts electrical output for pan size and construction, adjusts instantly to voltage fluctuations and auto shuts off after two minutes of non-use

**AUTOMATIC PAN RECOVERY** seamlessly adjusts and recognizes pans as you lift or tilt from the surface - similar to a gas range but with no flash point and better cost savings than conventional gas

**GLASS TOP IS 25% THICKER THAN COMPETITION.**  
5mm tempered glass is reinforced for durability

**EASY TO USE AND MAINTAIN.**

Includes easy to read LED controls, self-leveling, slip-proof legs that prevent scratched surfaces, and dials are heavy duty knurled knobs\*





LoPRO™

**NEW!**

The LoPRO™ slimline induction range is a new series of lightweight, compact induction ranges designed for durability and performance backed by Spring USA's industry-leading induction technology.

- Sleek, low-profile housing less than 2.4" high
- LED touch controls accessible via an easy to clean, tempered glass top
- Exclusive SmartScan® technology and Automatic Pan Recovery
- Available in low watt hold-only, cook/ hold, and double hob models
- FCC, ETL listed to: UL 197, CSA C22.2 #109 (cETL), NSF-4



**HOLD-ONLY INDUCTION RANGE**

**SM-300LP**

300 W | 110-120 V | 2.5 amps | 60 Hz  
4 Settings | 145-185°F/62-85°C  
NEMA 5-15P



**COOK/HOLD INDUCTION RANGE**

**SM-1800LP**

1800 W | 110-120 V | 15 amps | 60 Hz  
Cook Power Levels 1-20  
Temp Mode, Temp 110°F - 400°F  
NEMA 5-15P



**HOLD ONLY INDUCTION RANGE**

**SM-1800LP-D**

900x2 W | 110-120 V | 7.5x2 amps | 60 Hz  
Cook Power Levels 1-20  
Temp Mode, Temp 110°F - 400°F  
NEMA 5-15P



**MAX INDUCTION®**

The first induction ranges to debut in the United States - MAX Induction offers optimal durability and performance with greater efficiency, precision, and safety over gas or flame.

- Reaches max temperature in just 60 seconds
- Exclusive SmartScan® technology assures correct temperature for optimal performance and energy-efficiency
- No flash points and better cost savings than conventional gas ranges
- 5mm glass top, the thickest glass surface in its class
- Automatic Pan Recovery seamlessly adjusts and recognizes pans as you lift or tilt from the surface during cooking, sauteing, or flipping
- Available in stainless steel and titanium for countertop models, as well as reconfigurable, drop-in, and hidden models



**PLUG-IN TWO IN ONE  
15-AMP CIRCUIT**

**HOLD-ONLY 650 WATT RANGE  
SM-651C-T**

Countertop  
650 W | 110-120 V | 5.4 amps | 60 Hz  
4 Settings | 145-185°F/62-85°C  
NEMA 5-15P  
9.8 lbs  
12.5"W x 16.0"D x 3.1"H  
FCC, ETL, ETL-Sanitation to NSF-4,  
CETL, UL 197  
7 ft. cord

INDUCTION RANGES



**COOK & HOLD 1800 WATT RANGE  
SM-181C**

Countertop  
1800 W | 110-120 V | 15 amps | 60 Hz  
20 Settings | 110-400°F/43-204°C  
NEMA 5-15P  
11.8 lbs  
12.5"W x 16.0"D x 3.1"H  
FCC, ETL, ETL-Sanitation to NSF-4,  
CETL, UL 197  
7 ft. cord




**COOK & HOLD 1800 WATT RANGE  
SM-181C-T**

Countertop  
1800 W | 110-120 V | 15 amps | 60 Hz  
20 Settings | 110-400°F/43-204°C  
NEMA 5-15P  
11.8 lbs  
12.5"W x 16.0"D x 3.1"H  
FCC, ETL, ETL-Sanitation to NSF-4,  
CETL, UL 197  
7 ft. cord



**COOK & HOLD 2600 WATT RANGE  
SM-261C**

Countertop  
2600 W | 208-240 V | 10.8 amps | 60 Hz  
20 Settings | 110-400°F/43-204°C  
NEMA 6-20P  
11.8 lbs  
12.9"W x 16.5"D x 4.0"H  
FCC, ETL, ETL-Sanitation to NSF-4,  
CETL, UL 197  
7 ft. cord

SM-263C   
2600 W | 220-240 V | 10.8 amp | 50-60 Hz  
CEE 7/7 Schuko Plu

SM-263CU UK  
2600 W | 220-240 V | 10.8 amps | 50-60 Hz  
BS 1363 (13A) U.K. Plug




COUNTERTOP



**COOK & HOLD 3500 WATT RANGE  
SM-351C**

Countertop  
3500 W | 208-240 V | 14.6 amps | 60 Hz  
20 Settings | 110-400°F/43-204°C  
NEMA 6-20P  
18.0 lbs  
15.0"W x 20.2"D x 5.8"H  
FCC, ETL, ETL-Sanitation to NSF-4,  
CETL, UL 197  
7 ft. cord

SM-353C   
3500 W | 220-240 V | 14.6 amps | 50-60 Hz  
CEE 7/7 Schuko Plug

SM-353CU UK  
3000 W | 220-240 V | 12.5 amp | 50-60 Hz  
BS 1363 (13A) U.K. Plug



**COOK & HOLD 3500 WATT RANGE  
SM-351C-FT**

Countertop  
3500 W | 208-240 V | 14.6 amps | 60 Hz  
4 Time Settings | 110-400°F/43-204°C  
NEMA 6-20P  
18.0 lbs  
15.0"W x 20.2"D x 5.8"H  
FCC, ETL, ETL-Sanitation to NSF-4,  
CETL, UL 197  
30, 45, 70 or 80 sec countdown timer  
7 ft. cord

SM-353C-FTU UK  
3000 W | 220-240 V  
12.5 amps | 50-60 Hz  
BS 1363 (13A) U.K. Plug



## RECONFIGURABLE INDUCTION

**REMOVABLE CONTROLS** for countertop or drop-in application!



### HOLD-ONLY ROUND INDUCTION RANGE

**SM-360R**  
Countertop, Drop-in, Flushmount  
360 W | 110-120 V | 3 amps | 60 Hz  
4 Settings | 145-185°F/62-85°C  
NEMA 5-15P



### WYNWOOD BY SKYRA™ INDUCTION DOT DISPLAY STAND

**SK-145360R**  
13.5" Diameter  
Food-safe, nonporous, easy to clean

The Spring USA Induction DOT round induction range is the perfect solution for powerful induction in tight spaces. Compact in size with just a 9.1" diameter, these ranges take up minimal countertop space for either drop-in, flush-mount, or countertop induction.

- Low profile design, only 9.1" in diameter
- 3 different configurations: countertop, drop-in, or flush-mount
- Daisy-chain up to 4 units on a single 15-amp circuit
- Removable control box with touch controls & indicator lights
- Sleek, round housing with stainless-steel rim
- NSF-Certified, UL Rated NSF-4

## UNLIMITED INDUCTION™

- Edge-to-Edge technology can read one or more vessels, regardless of where they are placed
- Power receptacle in back of unit
- Reads multiple pans regardless of placement
- Removable controls allow for use on countertop or drop-in



INDUCTION RANGES

## FEATURES



**DAISY CHAIN**  
Outlet in back, connect up to five units on one 15-amp circuit

**HOLD-ONLY 300 WATT RANGE**  
**SM-300CR**  
Countertop or Built-in  
300 W | 110-120 V | 2.5 amps | 60 Hz  
4 Settings | 145-185°F/62-85°C  
NEMA 5-15P  
10.0 lbs  
14.0"W x 14.0"D x 3.6"H  
FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197  
7 ft. cord  
Minimum vessel size 4.7"/12cm

RECONFIGURABLE





RECONFIGURABLE

MAX INDUCTION®


PATENTED



**COOK & HOLD 2500 X 2 WATT DOUBLE RANGE**

**SM-251-2CR**

Countertop or Built-in  
 2500x2 W | 208-240 V | 10.4 x 2 amps | 60 Hz  
 20 Settings | 110-400°F/43-204°C  
 NEMA 6-30P  
 29.1 lbs  
 28.0"W x 18.1"D x 4.6"H  
 FCC, ETL, ETL-Sanitation to NSF-4,  
 CETL, UL 197  
 7 ft. cord

SM-253-2CR   
 2500x2 W | 220-240 V | 20.8 x 2 amps | 50-60 Hz  
 Plug & receptacle to be supplied by the  
 customer, based on country code



**REMOVABLE CONTROLS** for four possible applications - countertop or drop-in in either horizontal or vertical position

**GRIDDLE ATTACHMENT**

Effortlessly cook breakfast items, burgers, cheesesteaks, and other grilled favorites by harnessing the power and precision of MAX Induction with this griddle overlay attachment.



**MAX INDUCTION COUNTERTOP GRIDDLE OVERLAY**

**SMG251-6**

Product dimensions: 32.25" W x 15.25" D x 6" H  
 Cooking Area: 28.25" W x 15.15" D  
 Weight: 54 lbs.  
 10 mm thick stainless steel cooking surface  
 Hard chromium plating  
 Designed for use with/ retrofits, SM-251-2CR & SM-253-2CR



**COOK & HOLD 3500 WATT WOK RANGE W/CONCAVE TOP**

**SM-351WCR**

Countertop or Built-in  
 3500 W | 208-240 V | 14.6 amps | 60 Hz  
 20 Settings | 110-400°F/43-204°C  
 NEMA 6-20P | 17.6 lbs | 14.6"W x 19.1"D x 5.7"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197  
 7 ft. cord



**COOK & HOLD 3500 WATT WOK RANGE W/CONCAVE TOP**

**SM-351WCR-8**

Includes 8217-60/32 Vulcano Wok Pan  
 Countertop or Built-in  
 3500 W | 208-240 V | 14.6 amps | 60 Hz  
 20 Settings | 110-400°F/43-204°C  
 NEMA 6-20P | 17.6 lbs | 14.6"W x 19.1"D x 5.7"H  
 FCC, ETL, ETL-Sanitation to NSF-4,  
 CETL, UL 197  
 7 ft. cord

SM-353WCR-8 	SM-353WCRU-8 UK
3500 W   220-240 V	3000 W   220-240 V
14.6 amps   50-60 Hz	12.5 amps   50-60 Hz
CEE 7/7 16 A Schuko	BS 1363 (13A) U.K. Plug



**COOK & HOLD 3500 WATT WOK RANGE W/CONCAVE TOP**

**SM-351WCR-6**

Includes 8216-60/34 Primo Wok Pan  
 Countertop or Built-in  
 3500 W | 208-240 V | 14.6 amps | 60 Hz  
 20 Temp Settings | 110-400°F/43-204°C  
 NEMA 6-20P | 17.6 lbs | 14.6"W x 19.1"D x 5.7"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197  
 7 ft. cord

SM-353WCR-6 	SM-353WCRU-6 UK
3500 W   220-240 V	3000 W   220-240 V
14.6 amps   50-60 Hz	12.5 amps   50-60 Hz
CEE 7/7 16 A Schuko	BS 1363 (13A) U.K. Plug

## DROP-IN INDUCTION

**REMOVABLE CONTROLS & FLUSHMOUNT GLASS TOP** for drop-in application

**MAX INDUCTION**®

PATENTED



**HOLD ONLY 650 WATT RANGE**

**SM-651R**

Built-in  
 650 W | 110-120 V | 5.4 amps | 60 Hz  
 4 Settings | 145-185°F/62-85°C  
 NEMA 5-15P | 10.6 lbs  
 12.6"W x 13.4"D x 3.3"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197



SM-653R  
 650 W | 220-240 V | 2.7 amps | 50-60 Hz  
 CEE 7/7 16 A Schuko Plug

SM-653RU UK  
 650 W | 220-240 V | 2.7 amps | 50-60 Hz  
 BS 1363 (13A) U.K. Plug

**COOK & HOLD 1800 WATT RANGE**

**SM-181R**

Built-in  
 1800 W | 110-120 V | 15 amps | 60 Hz  
 20 Settings | 110-400°F/43-204°C  
 NEMA 5-15P | 10.8 lbs  
 12.6"W x 13.4"D x 3.3"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197

**COOK & HOLD 2600 WATT RANGE**

**SM-261R**

Built-in  
 2600 W | 208-240 V | 10.8 amps | 60 Hz  
 20 Settings | 110-400°F/43-204°C  
 NEMA 6-20P | 11.7 lbs  
 12.6"W x 13.4"D x 3.3"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197



SM-263R  
 2600 W | 220-240 V | 10.8 amps | 50-60 Hz  
 CEE 7/7 16 A Schuko Plug

SM-263RU UK  
 2600 W | 220-240 V | 10.8 amps | 50-60 Hz  
 BS 1363 (13A) U.K. Plug



## HIDDEN MULTISURFACE

**REMOVABLE CONTROLS & SPECIALIZED GLASS TOP** for countertop undermount application

**MAX INDUCTION**®

PATENTED

Intentionally designed to work with Spring USA SmartStone® to be mounted under the countertop for a completely hidden operation. Hold-only range can be hidden under approved surfaces for a completely seamless operation.

**SEEMLESSLY MOUNTS** beneath the countertop to eliminate any cutting

**SAFE FOR USE** under SmartStone or other approved surfaces up to 2 cm thick

**INDUCTION TECHNOLOGY** safely senses & heats the serving vessel, not the countertop

**HOLD ONLY MULTISURFACE 650 WATT RANGE**

**SM-651SS**

Built-in  
 650 W | 110-120 V | 5.4 amps | 60 Hz  
 4 Settings | 145-185°F/62-85°C  
 NEMA 5-15P | 10.6 lbs  
 12.6"W x 13.4"D x 3.3"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197



**SURFACEGUARD SES651**  
 8" Dia. x 1"H

SURFACE BRAND	SURFACE MATERIAL	SURFACE THICKNESS	VESSELS
SMARTSTONE™	PORCELAIN	1.2 cm / 2 cm max.	1.2 cm Thick: All Spring USA Induction Ready Vessels
SILESTONE*	QUARTZ	1.2 cm / 2 cm max.	
FIANDRE*	PORCELAIN	1.2 cm / 2 cm max.	
EIFFELGRES*	PORCELAIN	1.2 cm / 2 cm max.	2 cm Thick: Round Sauteuse Server, Square Server, Oatmeal/Soup Server, Servella, Ironlite, Wynwood by Skyra
IRIS CERAMICA*	PORCELAIN	1.2 cm / 2 cm max.	
FMG*	PORCELAIN	1.2 cm / 2 cm max.	
ARIOSTEA*	PORCELAIN	1.2 cm / 2 cm max.	

\*Requires SurfaceGuard. For All Other Surfaces & Vessels, Please Inquire for Testing.

## CUSTOM INDUCTION RANGE CASES

Ranges offer front-of-house warming and cooking with back-of-house power and durability.



### SINGLE RANGE CUSTOM CASES

#### HIDDEN HOLD ONLY 650 WATT RANGE W/CUSTOM CASE

##### SRC-651SS

650 W | 110-120 V | 5.4 amps | 60 Hz  
 4 Settings | 145-185°F/62-85°C  
 NEMA 5-15P  
 14.125"W x 20.125"D x 6.0"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197  
 7 ft. cord

### DOUBLE RANGE CUSTOM CASES

#### TWO HIDDEN HOLD ONLY 650 WATT DOUBLE RANGES W/CUSTOM CASE

##### SRC-2-651SS

650x2 W | 110-120 V | 5.4 x 2 amps | 60 Hz  
 4 Settings | 145-185°F/62-85°C  
 NEMA 5-15P  
 33.5"W x 20.125"D x 6.0"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197  
 7 ft. cord

#### COOK & HOLD 1800 WATT RANGE W/CUSTOM CASE

##### SRC-181SS

1800 W | 110-120 V | 15 amps | 60 Hz  
 20 Settings | 110-400°F/43-204°C  
 NEMA 5-15P  
 14.125"W x 20.125"D x 6.0"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197  
 7 ft. cord

#### TWO COOK & HOLD 1800 WATT DOUBLE RANGES W/CUSTOM CASE

##### SRC-2-181SS

1800x2 W | 110-120 V | 15 x amps | 60 Hz  
 20 Settings | 110-400°F/43-204°C  
 NEMA 5-15P  
 33.5"W x 20.125"D x 6.0"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197  
 7 ft. cord

#### COOK & HOLD 2600 WATT RANGE W/CUSTOM CASE

##### SRC-261SS

2600 W | 208-240 V | 10.8 amps | 60 Hz  
 20 Settings | 110-400°F/43-204°C  
 NEMA 6-20P  
 14.125"W x 20.125"D x 6.0"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197  
 7 ft. cord

#### TWO COOK & HOLD 2600 WATT DOUBLE RANGES W/ CUSTOM CASE

##### SRC-2-261SS

2600x2 W | 208-240 V | 10.8 x 2 amps | 60 Hz  
 20 Settings | 110-400°F/43-204°C  
 NEMA 6-20P  
 33.5"W x 20.125"D x 6.0"H  
 FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197  
 7 ft. cord

## PROFESSIONAL COOKWARE

*Back of the House Durable.  
 Front of the House Beautiful.*

“When you buy quality, you buy only once.  
 Spring USA cookware can last a lifetime. Spring USA  
 offers great quality at reasonable prices.”

RANDY ZWEIBAN | EXECUTIVE CHEF | CHICAGO