

ThinkCentre M720 Tiny 10T7004K++

Region
EMEA

Machine Type
10T7

TopSeller
TopSeller

Processor
Core i5-8400T (6C, 1.7 / 3.3GHz, 9MB)

vPro
No

Graphics
Integrated Intel UHD Graphics 630

Monitor Cable
None

Memory
8GBx1

Storage
256GB SSD Opal

Optical
None

WLAN + Bluetooth
Intel 8265 ac, 2x2 + BT4.2

Ethernet
Integrated

Optional Rear Ports
VGA + Serial

Extension Card
None

Kensington Cable Lock
None

Adapter Cage
Adapter Cage

Toolless Chassis Screw
None

Speaker
1.5Wx1

Dust Filter
None

VESA Mount
VESA Mount

Stand
None

Keyboard / Mouse
USB / USB

Power Supply
65W 88% Adapter

TUV Low Noise
None

Operating System
None

Warranty
3-year, Onsite

End of Support
Jul 26, 2024

Ann Date (mm/yy)
06/18

Note:

* Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "***" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



WWW.LENOVO.COM

This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<http://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2017. All rights reserved.



ThinkCentre M720 Tiny Platform Specifications

Product Specifications Reference (PSREF)



Processor	Intel® Celeron®, Intel Pentium®, or 8th Generation Intel Core™ i3 / i5 / i7 Processor						Manageability Security chip Security features	None										
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics		Discrete TPM 2.0, TCG Certified										
	Celeron G4900T	2 / 2	2.9G	2 MB	DDR4-2400	UHD 610		● Security slot (in rear for optional Kensington® MicroSaver® cable)										
	Pentium Gold G5400T	2 / 4	3.1G	4 MB	DDR4-2400	UHD 610		● Boot sequence control										
	Pentium Gold G5500T	2 / 4	3.2G	4 MB	DDR4-2400	UHD 630		● Boot without keyboard and mouse										
	Core i3-8100T	4 / 4	3.1G	6 MB	DDR4-2400	UHD 630		● Individual USB port disablement										
	Core i3-8300T	4 / 4	3.2G	8 MB	DDR4-2400	UHD 630		● Power-on password										
	Core i5-8400T	6 / 6	1.7G / 3.3G	9 MB	DDR4-2666	UHD 630		● Administrator password										
	Core i5-8500T	6 / 6	2.1G / 3.5G	9 MB	DDR4-2666	UHD 630		● Hard disk password										
	Core i5-8600T	6 / 6	2.3G / 3.7G	9 MB	DDR4-2666	UHD 630		● Smart USB protection, allows keyboard/mouse only, blocks all storage devices										
Core i7-8700T	6 / 12	2.4G / 4.0G	12 MB	DDR4-2666	UHD 630													
Memory	32GB max, DDR4-2666*, two 260-pin SO-DIMM sockets, non-ECC, dual-channel capable * System automatically clocks down for the processors with lower memory controller						Mechanical	Tiny (1L), black color; metal case										
Storage	<i>Some:</i> Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" <i>Some:</i> M.2 SSD / PCIe NVMe, PCIe 3.0 x 4", 32Gb/s * 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s <i>Some:</i> Intel Optane™ Memory (not support Celeron / Pentium Processor), M.2 <i>Some:</i> DVD-ROM, slim (9.0mm), via USB external ODD box <i>Some:</i> DVD Burner (DVD±RW), slim (9.0mm), via USB external ODD box							● Toolless chassis open (need optional toolless chassis screw)										
Optical	One onboard SATA 6.0Gb/s connector							● Toolless HDD, SSD, memory removal										
Onboard SATA	One onboard SATA 6.0Gb/s connector							● Optional dust filter										
Graphics	Intel HD Graphics 610/630 in processor, uses main memory, DirectX® 12, one DisplayPort™, one HDMI, one optional video port (2nd HDMI, VGA, 2nd DP, or USB 3.1 Type-C Gen1 with DisplayPort function), up to 3 independent displays; <i>Max resolution:</i> 4096x2304 (DP)@60Hz; 4096x2304 (Type-C)@60Hz; 4096x2160 (onboard HDMI)@24Hz; 2048x1536 (VGA)@50Hz							one 2.5" bay for HDD/SSD, one PCIe 3.0 x8 slot (low-profile), two M.2 slots (one for WLAN, one for M.2 SSD), 2.5" HDD/SSD and PCIe card are mutually exclusive										
Monitor cable	Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle (for Collage Display with intel integrated graphics), or DP to HDMI 1.4 dongle							<table border="1"> <thead> <tr> <th></th> <th>Dimensions (WxDxH)</th> <th>Weight (Approx.)</th> </tr> </thead> <tbody> <tr> <td>Tiny only</td> <td>7.05" X 7.20" X 1.36" 179mm X 182.9mm X 34.5mm</td> <td>2.91 lb (1.32 kg), vary by config</td> </tr> <tr> <td>With VESA mount & ODD box</td> <td>7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm</td> <td>3.66 lb (1.66 kg), vary by config</td> </tr> </tbody> </table>			Dimensions (WxDxH)	Weight (Approx.)	Tiny only	7.05" X 7.20" X 1.36" 179mm X 182.9mm X 34.5mm	2.91 lb (1.32 kg), vary by config	With VESA mount & ODD box	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	3.66 lb (1.66 kg), vary by config
	Dimensions (WxDxH)	Weight (Approx.)																
Tiny only	7.05" X 7.20" X 1.36" 179mm X 182.9mm X 34.5mm	2.91 lb (1.32 kg), vary by config																
With VESA mount & ODD box	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	3.66 lb (1.66 kg), vary by config																
Chipset	Intel B360 Chipset							Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation										
Front ports (Std.)	one USB 3.1 Gen1 (Always On and fast charge), one USB 3.1 Type-C Gen 1, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm)						Power supply											
Rear ports (Std.)	2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x ethernet (RJ-45), 1x DisplayPort, 1x HDMI						<i>Some:</i> 65 watts AC/DC adapter, autosensing, 88% PSU											
Rear ports (Opt.)	Two optional ports (mutually exclusive with PCIe card): Port 1 for VGA / 2nd DP / 2nd HDMI / serial / USB 3.1 Type-C Gen 1 with DP function); Port 2 for serial; Optional ports via PCIe card: 2x USB 3.1 Gen1 via PCIe x1, 4x serial (9-pin) via PCIe x1						<i>Some:</i> 90 watts AC/DC adapter, autosensing, 88% PSU											
Audio support	Realtek ALC233VB2 / optional internal speaker (1.5 watt or 2 watt)						<i>Some:</i> 135 watts AC/DC adapter, autosensing, 88% PSU											
WLAN	<i>Some:</i> 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 <i>Some:</i> 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 <i>Some:</i> 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 <i>Some:</i> 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2						VESA mount Floor Stand											
Bluetooth	<i>Some:</i> Bluetooth 4.2 wireless, integrated in Wi-Fi + BT combo adapter						Limited warranty											
Ethernet	Gigabit ethernet, Intel Ethernet Connection I219-V (Jacksonville), Wake on LAN®						<i>Some:</i> 1-year or 3-year, depot service / service upgrades available											
Ethernet (Opt.)	<i>Some:</i> Intel Ethernet Server Adapter I350-T4, gigabit ethernet, 4x RJ-45, PCIe x4						<i>Some:</i> 1-year or 3-year, limited onsite service / service upgrades available											

Note: The specifications above may not be available in all regions.

Lenovo, July 2018

ThinkCentre M720 Tiny

