



INDEX

Symbols

* (asterisk)

- autolearned entries [46-20](#)
- port security wildcard [46-15](#)
- port security wildcards [46-15](#)

Numerics

12-port 4-Gbps switching modules

- BB_credit buffers [22-20](#)
- configuration guidelines [22-31](#)
- default settings [22-43](#)
- See also switching modules

16-port switching modules

- configuring BB_credits [20-26](#)
- LEDs [20-19](#)
- See also switching modules

24-port 4-Gbps switching modules

- bandwidth fairness [22-37](#)
- configuration guidelines [22-30](#)
- default settings [22-43](#)
- example configurations [22-19](#)
- oversubscription [22-34](#)
- shared resources [22-10](#)
- See also switching modules

24-port 8-Gbps switching modules

- default settings [22-43](#)
- example configurations [22-15](#)

32-port switching modules

- configuring BB_credits [20-26](#)
- SPAN guidelines [60-6](#)
- See also switching modules

3DES encryption

- IKE [44-7](#)
- IPsec [44-6](#)

4/44-port 8-Gbps switching modules

- default settings [22-43](#)
- example configurations [22-16](#)

48-port 4-Gbps switching modules

- bandwidth fairness [22-37](#)
- configuration guidelines [22-30](#)
- default settings [22-43](#)
- example configurations [22-17](#)
- oversubscription [22-34](#)
- shared resources [22-10](#)

See also switching modules

48-port 8-Gbps switching modules

- default settings [22-43](#)
- example configurations [22-14](#)
- See also switching modules

4-port 10-Gbps switching modules

- BB_credit buffers [22-21](#)
- configuration guidelines [22-31](#)
- default settings [22-43](#)
- See also switching modules

A

AAA

- authentication process [41-6](#)
- authorization process [41-6](#)
- configuring information [7-53](#)
- default settings [41-30](#)
- description [41-1](#)
- DHCHAP authentication [45-10](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- distributing with CFS (procedure) [41-24](#)
- enabling server distribution [41-22](#)
- local services [41-26](#)
- remote services [41-4](#)
- service configuration options [41-4](#)
- setting authentication [41-26](#)
- starting a distribution session [41-22](#)
- AAA authentication
- AAA servers
 - groups [41-4](#)
 - monitoring [41-5](#)
 - remote authentication [41-4](#)
- access control
 - enforcing iSCSI
 - enforcing access control [50-27](#)
 - iSCSI [50-26](#)
- Access Control Lists. See IPv4-ACLs; IPv6-ACLs
- access control zoning based access control iSCSI
 - zoning based access control [50-27](#)
- accounting
 - viewing lists [7-10](#)
- ACL based access control
 - configuring for iSCSI [50-26](#)
- ACLs
 - configuring for iSCSI [50-26](#)
- active zone sets
 - considerations [30-4](#)
 - enabling distribution [30-26](#)
- adapters
 - Fibre Channel-to-Ethernet [9-2](#)
- adminDown tooltip [67-14](#)
- administrative speeds
 - configuring [20-12](#)
- administrative states
 - description [20-7](#)
 - setting [20-11](#)
- administrator passwords
 - default [2-5](#)
 - recovering [39-20](#)
- Admin tab
 - description [7-44](#)
- Advanced Encrypted Standard encryption. See AES encryption
- advertisement packets
 - setting time intervals [51-11](#)
- AES encryption
 - description [40-4](#)
 - IKE [44-7](#)
 - IPsec [44-6](#)
 - SNMP support [40-4](#)
- AES-XCBC-MAC
 - IPsec [44-6](#)
- AFIDs
 - configuring [29-11, 29-12](#)
 - configuring default [29-12](#)
 - description [29-4, 29-7, 29-15](#)
- aliases
 - switching between global device aliases and FC aliases [31-8](#)
 - switching between global device aliases and fc aliases [3-7](#)
 - using as enclosure names [5-33](#)
 - using with Fabric Manager [3-7](#)
- ALPA caches
 - clearing [B-2](#)
 - description [20-25](#)
 - displaying contents [B-2](#)
- ANSI T11 FC-GS-3
 - support [2-16](#)
- applications
 - management [2-17](#)
- ARP caches
 - clearing [B-2](#)
 - displaying [B-2](#)
- authentication
 - Fabric Manager Web Services [4-4](#)
 - fabric security [45-1](#)
 - guidelines [41-4](#)
 - iSCSI setup [50-56](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- local [41-3, 50-30](#)
 - MD5 [51-12](#)
 - mechanism [50-29](#)
 - mutual CHAPmutual CHAP authentication [50-30](#)
 - remote [41-3, 41-4](#)
 - restricting iSLB initiatorinitiator authentication
 - restrictingiSLB
 - simple text [51-12](#)
 - user IDs [41-3](#)
 - See also MD5 authentication
 - See also simple text authentication
 - authentication, authorization, and accounting. See AAA
 - autogenerated iSCSI targetiSCSI
 - autogenerated target [50-28](#)
 - auto-negotiation
 - configuring Gigabit Ethernet interfaces [52-5, 53-3](#)
 - autonomous fabric ID
 - See AFIDs
 - autonomous fabric identifiers. See AFIDs
 - AutoNotify
 - description [62-5](#)
 - auto port mode
 - description [20-7](#)
 - interface configuration [20-3](#)
 - autosensing speed
 - Generation 2 switching modules [20-13](#)
 - auto-topology
 - configuration guidelines [29-10](#)
 - IVR [29-6](#)
 - modifying (procedure) [29-11](#)
-
- B**
 - bandwidth fairness
 - disabling [22-39](#)
 - enabling [22-38](#)
 - Generation 2 switching modules [22-37](#)
 - BB_credit buffers
 - 12-port 4-Gbps switching module allocations [22-20](#)
 - 12-port 4-Gbps switching module
 - considerations [22-20](#)
 - 24-port 4-Gbps switching module allocations [22-18](#)
 - 24-port 4-Gbps switching module
 - considerations [22-19, 22-20](#)
 - 24-port 8-Gbps switching module
 - considerations [22-15](#)
 - 4/44-port 8-Gbps switching module
 - considerations [22-16](#)
 - 48-port 4-Gbps switching module
 - considerations [22-17](#)
 - 48-port 8-Gbps switching module
 - considerations [22-14](#)
 - 4-port 10-Gbps switching module allocations [22-21](#)
 - 4-port 10-Gbps switching module
 - considerations [22-21, 22-22](#)
 - allocation defaults (table) [22-14, 22-15, 22-16, 22-17](#)
 - BB_credits
 - configuring [20-26](#)
 - description [20-25](#)
 - FICON port swapping [36-32](#)
 - reason codes [20-9, C-1](#)
 - beacon modes
 - configuring [20-20](#)
 - description [20-20](#)
 - identifying LEDs [20-19](#)
 - Berkeley Packet Filter library. See BPF library
 - bit errors
 - reasons [20-20](#)
 - bit error thresholds
 - configuring [20-20](#)
 - description [20-20](#)
 - bitErrRTThresExceeded tooltip [67-14](#)
 - bootflash:
 - description [16-2](#)
 - file system [15-2](#)
 - recovering from corruption [B-1](#)
 - space requirements [15-3](#)
 - boot variables
 - synchronizing [17-3](#)
 - border switches

Send documentation comments to mdsfeedback-doc@cisco.com

- description [29-4](#)
 - IVR configuration guidelines [29-14](#)
 - BPF library
 - description [66-21](#)
 - See also libpcap freeware
 - B port mode
 - description [20-7](#)
 - interface modes [20-7](#)
 - B ports
 - configuring [48-27](#)
 - interoperability mode [48-25](#)
 - SAN extenders [48-26](#)
 - bridge port mode. See B port mode
 - bridge ports. See B ports
 - broadcast
 - in-band addresses default [19-13](#)
 - routing [32-14](#)
 - Brocade
 - native interop mode [37-9](#)
 - buffer pools
 - Generation 2 switching modules [22-10](#)
 - buffer sizes
 - configuring in FCIP profiles [48-21](#)
 - buffer-to-buffer credits. See BB_credits
 - build fabric frames
 - description [25-3](#)
 - bundleMisCfg tooltip [67-14](#)
-
- C**
 - Call Home
 - alert groups [62-9 to 62-11](#)
 - AutoNotify feature [62-5](#)
 - CFS support [13-2](#)
 - configuration distribution [62-18](#)
 - configuring [62-5 to 62-19](#)
 - configuring e-mail options [62-14](#)
 - contact information [62-6](#)
 - database merge guidelines [62-19](#)
 - default settings [62-40](#)
 - description [62-1](#)
 - destination profiles [62-7 to 62-9](#)
 - duplicate message throttle [62-16](#)
 - enabling [62-17](#)
 - features [62-2](#)
 - inventory notifications [62-15](#)
 - message format options [62-2](#)
 - RMON-based alerts [62-13](#)
 - syslog-based alerts [62-12](#)
 - testing communications [62-19](#)
 - Call Home alert groups
 - configuring [62-9](#)
 - customizing messages [62-10](#)
 - description [62-9](#)
 - Call Home destination profiles
 - attributes [62-7](#)
 - description [62-7](#)
 - Call Home messages
 - configuring levels [62-11](#)
 - format options [62-2](#)
 - Call Home notifications
 - full-txt format for syslog [62-24](#)
 - XML format for RMON [62-28](#)
 - XML format for syslog [62-24](#)
 - CAs
 - authenticating [43-10](#)
 - certificate download example [43-19](#)
 - configuring [43-6 to 43-17](#)
 - creating a trust point [43-8](#)
 - default settings [43-37](#)
 - deleting digital certificates [43-16](#)
 - description [43-1 to 43-5, 69-1 to ??](#)
 - enrollment using cut-and-paste [43-4](#)
 - example configuration [43-17 to 43-36](#)
 - Fabric Manager Web Services [7-5](#)
 - identity [43-2](#)
 - maintaining [43-14](#)
 - maximum limits [43-36](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- monitoring **43-14**
- multiple **43-4**
- multiple trust points **43-3**
- peer certificates **43-5**
- purpose **43-2**
- CDP**
 - configuring **12-12 to 12-13**
 - configuring hold times **12-13**
 - configuring refresh time interval globally **12-12**
 - disabling globally **12-12**
 - disabling on interfaces **12-12**
 - packet transmission interval **12-12**
- certificate authorities.** See **CAs**
- certificate revocation lists.** See **CRLs**
- CFS**
 - application requirements **13-5**
 - configuring for NTP **12-8**
 - default settings **13-23**
 - description **13-1 to 13-4**
 - disabling on a switch **13-4**
 - displaying configuration information **13-9**
 - distribution modes **13-4**
 - distribution over IP **13-10**
 - distribution scopes **13-3**
 - enabling on a switch **13-4**
 - example configuration using Device Manager **13-23**
 - example configuration using Fabric Manager **13-20**
 - example using Fabric Manager **12-8**
 - feature description **13-2**
 - iSLB config distribution **50-46**
 - merge support **13-9**
 - merge support (procedure) **13-22**
 - protocol description **13-3**
 - SAN-OS features supported **13-2**
 - saving configurations **13-8**
- CFS applications**
 - clearing session locks **13-8**
 - committing changes **13-7**
 - discarding changes **13-8**
- enabling **13-5**
- enabling (procedure) **13-6**
- fabric locking **13-6**
- CFS over IP**
 - configuring static IP peers **13-11**
 - default settings **13-23**
 - description **13-10**
- CFS regions**
 - assigning features **13-17**
 - creating **13-17**
 - deleting **13-19**
 - description **13-16**
 - moving a feature **13-18**
 - removing a feature **13-19**
 - using Fabric Manager **13-17**
- channelAdminDown tooltip** **67-14**
- channelConfigurationInProgress tooltip** **67-14**
- channelOperSuspended tooltip** **67-14**
- CHAP challenge** **50-30**
- CHAP response** **50-30**
- CHAP user name** **50-30**
- CIM**
 - configuring **37-1, B-3**
 - description **37-1**
 - support **2-16**
- CIM servers**
 - default settings **66-25**
- Cisco Access Control Server.** See **Cisco ACS**
- Cisco ACS**
 - configuring for RADIUS **41-26 to 41-30**
 - configuring for TACACS+ **41-26 to 41-30**
- cisco-av-pair**
 - specifying for SNMPv3 **41-13**
- Cisco Discovery Protocol.** See **CDP**
- Cisco Fabric Service.** See **CFS**
- Cisco MDS 9000 Family**
 - connecting a terminal **12-11**
 - description **1-1**
 - initial setup **2-2 to 2-12**

Send documentation comments to mdsfeedback-doc@cisco.com

- starting a switch **2-1**
- Cisco MDS 9100 Series
 - Cisco MDS 9120 switches **1-4**
 - Cisco MDS 9124 switches **1-4**
 - Cisco MDS 9140 switches **1-4**
 - description **1-4**
 - high availability **17-1**
 - overview **1-4**
- Cisco MDS 9200 Series
 - Cisco MDS 9216A switches **1-3**
 - Cisco MDS 9216i switches **1-3**
 - connecting a terminal **12-11**
 - description **1-3**
 - high availability **17-1**
- Cisco MDS 9216
 - supervisor modules **19-2**
- Cisco MDS 9216A switches
 - description **1-3**
- Cisco MDS 9216i switches
 - configuring extended BB_credits **20-27**
 - description **1-3**
- Cisco MDS 9500 Series
 - Cisco MDS 9506 Directors **1-2**
 - Cisco MDS 9509 Directors **1-2**
 - Cisco MDS 9513 Directors **1-2**
 - description **1-2**
 - high availability **17-1**
- Cisco MDS 9506 Directors
 - description **1-2**
- Cisco MDS 9509 Directors
 - description **1-2**
 - supervisor modules **19-1**
- Cisco MDS 9513 Directors
 - description **1-2**
 - supervisor modules **19-1**
- Cisco MDS SAN-OS
 - software images **15-1**
- Cisco SAN-OS features
 - changed (table) **1-**lvii****
- new (table) **1-**lvii****
- Cisco Traffic Analyzer
 - configuring with Performance Manager **58-9**
 - description **9-3**
 - installing (procedure) **9-3**
 - statistics reports **66-3**
 - troubleshooting tools **66-2**
 - using for troubleshooting **66-2**
 - using with Fabric Manager **9-2**
- Cisco Transport Controller. See CTC
- Cisco vendor ID
 - description **41-13**
- class maps
 - configuring for data traffic **64-6**
 - creating **64-7**
- CLI
 - accessing **D-2**
 - description **1-5**
 - Fabric Manager alternative **1-6**
 - firewall **4-2**
- clients
 - disconnecting **7-50**
 - viewing **7-50**
- clock modules
 - managing **B-2**
- cloud discovery. See iSNS cloud discovery
- code pages
 - FICON text string formatting **36-19**
- COM1 ports
 - configuring **B-1**
- command-line interface. See CLI
- command schedulers
 - configuring **B-2**
- command scripts
 - executing **B-2**
- Common Information Model. See CIM
- common roles
 - deleting (procedure) **39-3**
- communities

Send documentation comments to mdsfeedback-doc@cisco.com

- adding [7-51](#)
- removing [7-52](#)
- CompactFlash
 - devices [16-2](#)
 - slot0: [15-2](#)
- company IDs
 - FC ID allocations [37-7, 66-24](#)
- configuration
 - overview [1-6 to 1-8](#)
 - saving automatically for FICON [36-23](#)
 - saving to NVRAM [16-8](#)
 - software tools [1-5](#)
- configuration files
 - backing up [16-9](#)
 - copying (procedure) [16-8](#)
 - displaying [B-2](#)
 - downloading [16-7](#)
 - FICON [36-29](#)
 - saving (procedures) [16-8](#)
 - saving across the fabric [16-9](#)
- configurations
 - changing initial [2-12](#)
- configuring NPV [21-7](#)
- congestion control methods. See FCC; edge quench
- congestion control
- congestion window monitoring. See CWM
- connectivity
 - troubleshooting tool [5-35](#)
 - verifying [66-7](#)
- console logging
 - configuring [61-4](#)
- console ports
 - parameters [2-2](#)
- console sessions
 - message logging severity levels [61-4](#)
- console settings
 - configuring [B-1](#)
- Contiguous Domain ID Assignments
 - About [25-15](#)
- contract IDs
- description [62-33](#)
- control traffic
 - disabling QoS [64-4](#)
 - enabling for QoS [64-4](#)
- Control Unit Port. See CUP in-band management
- core dumps
- IPS modules [B-2](#)
- core files
 - clearing directory [68-4](#)
 - displaying information [68-3](#)
 - saving to CompactFlash [B-3](#)
- CRLs
 - configuring [43-15](#)
 - configuring revocation checking methods [43-12](#)
 - description [43-5](#)
 - downloading example [43-34](#)
 - generation example [43-33](#)
 - importing example [43-36, ?? to 43-36](#)
- crossbars
 - compatibility with Generation 1 modules [18-10](#)
 - description [18-8](#)
 - management [18-7](#)
 - removal considerations [18-9](#)
- crypto IPv4-ACLs
 - any keyword [44-25](#)
 - configuration guidelines [44-22](#)
 - creating [44-25](#)
 - mirror images [44-24](#)
- crypto map entries
 - global lifetime values [44-37](#)
 - setting SA lifetimes [44-31](#)
- crypto maps
 - auto-peer option [44-32](#)
 - configuration guidelines [44-29](#)
 - configuring perfect forward secrecy [44-35](#)
 - entries for IPv4-ACLs [44-28](#)
 - perfect forward secrecy [44-34](#)
 - SA lifetime negotiations [44-30](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- SAs between peers [44-28](#)
- crypto map sets
 - applying to interfaces [44-36](#)
- CTC
 - description [48-17](#)
 - launching [48-17](#)
- CUP in-band management
 - blocking restriction [36-25](#)
 - description [36-37](#)
- current VSANs
 - description [29-3](#)
- custom reports
 - creating a template [7-37](#)
 - modifying a template [7-41](#)
- Custom tab
 - description [7-37](#)
- Cut-through routing mode [50-33](#)
- CWM
 - configuring in FCIP profiles [48-20](#)

D

- D_S_TOV
 - default setting [66-25](#)
 - errors when setting [67-7](#)
 - modifying [66-15](#)
- data
 - management [2-17](#)
- database files
 - resolving lock errors [7-45](#)
- Data Encryption Standard encryption. See DES encryption
- data traffic
 - class maps [64-6](#)
 - comparing VSANs and QoS [64-5](#)
 - defining service policies [64-8](#)
 - DWRR queues [64-8](#)
 - enforcing service policies [64-8](#)
 - example configuration [64-10](#)
- dates
- configuring [12-3](#)
- daylight saving time
 - adjusting for [B-1](#)
- dead time intervals
 - configuring for FSPF [32-8](#)
 - description [32-8](#)
- dedicated rate mode
 - description [22-6](#)
 - migrating from shared rate mode [22-29, 22-30](#)
 - migrating to shared rate mode [22-29, 22-30](#)
- default gateways. See IPv4 default gateways
- default networks
 - configuring [2-6, 2-10](#)
- default networks. See IPv4 default networks
- default users
 - description [2-3](#)
- default VSANs
 - description [26-8](#)
- default zones
 - configuring [30-21](#)
 - configuring policies [30-38](#)
 - configuring QoS priorities [30-37](#)
 - description [30-20](#)
 - interoperability [37-9](#)
 - policies [30-20](#)
- deficit weighted round robin schedulers. See DWRR schedulers
- deniedDueToPortBinding tooltip [67-14](#)
- DES encryption
 - IKE [44-7](#)
 - IPsec [44-6](#)
- desktops
 - shortcuts not visible [67-4](#)
- destination IDs
 - exchange based [23-5](#)
 - flow based [23-4](#)
 - in-order delivery [32-15](#)
 - path selection [26-11](#)
- device alias database

Send documentation comments to mdsfeedback-doc@cisco.com

- committing changes **31-6**
- discarding changes **31-7**
- distribution to fabric **31-4**
- merging **31-8**
- device aliases
 - CFS support **13-2**
 - clearing statistics **31-8**
 - comparison with zones (table) **31-4**
 - default settings **31-9**
 - description **31-1**
 - features **31-3**
 - modifying the database **31-4**
 - requirements **31-3**
 - zone alias conversion **31-7**
- device IDs
 - Call Home format **62-34**
- Device Manager
 - color definitions **6-5**
 - connection failures **67-10**
 - context menus **6-7**
 - downgrading **67-4**
 - FAQs **67-1**
 - installation failures **67-6, 67-7**
 - label definitions **6-5**
 - launching (procedure) **6-2**
 - login failure recovery **67-6**
 - managing ports **6-7**
 - performance monitoring **58-1**
 - PortChannels **6-7**
 - preferences **6-8**
 - setting preferences **6-8**
 - tabs **6-5**
 - troubleshooting tools **66-1**
 - trunking **6-7**
 - upgrade failures **67-4**
 - upgrading **67-4**
 - using interface (figure) **6-3**
 - viewing license information **10-16**
 - viewing port status **6-5**
- viewing supervisor modules **6-7**
- viewing switch modules **6-7**
- viewing system messages **61-11**
- devices
 - discovery **57-1**
 - management **2-17**
 - modifying groupings (procedure) **5-32**
 - searching in Fabric Manager **67-22**
- DH
 - IKE **44-6**
- DHCHAP
 - AAA authentication **45-10**
 - authentication modes **45-5**
 - compatibility with other SAN-OS features **45-3**
 - configuring **45-2 to 45-10**
 - configuring AAA authentication **45-10**
 - default settings **45-10**
 - description **45-2**
 - enabling **45-4**
 - group settings **45-7**
 - hash algorithms **45-6**
 - licensing **45-2**
 - passwords for local switches **45-7**
 - passwords for remote devices **45-8**
 - timeout values **45-9**
 - See also FC-SP
- differentiated services code point. See DSCP
- Diffie-Hellman Challenge Handshake Authentication Protocol. See DHCHAP
- Diffie-Hellman protocol. See DH
- digital certificates
 - configuration example **43-17 to 43-19**
 - configuring **43-6 to 43-17**
 - default settings **43-37**
 - deleting from CAs **43-16**
 - description **43-1 to 43-5, 69-1 to ??**
 - exporting **43-5, 43-14**
 - generating requests for identity certificates **43-12**
 - importing **43-5, 43-14**

Send documentation comments to mdsfeedback-doc@cisco.com

- installing identity certificates **43-13**
- IPsec **44-7 to 44-10**
- maintaining **43-14**
- maximum limits **43-36**
- monitoring **43-14**
- peers **43-5**
- purpose **43-2**
- requesting identity certificate example **43-24**
- revocation example **43-30**
- digital signature algorithm. See DSA key pairs
- DirectX
 - installing **67-6**
- Distributed Services Time Out Value. See D_S_TOV
- DNS
 - configuring **2-6, 2-10**
 - configuring IP addresses **2-7**
 - default settings **51-13**
- DNS servers
 - configuring **51-12**
- documentation
 - additional publications **i-ixvii**
 - related documents **i-ixvii**
- domainAddrAssignFailureIsolation tooltip **67-14**
- domain ID
 - CFS support **13-2**
- domain IDs
 - allowed lists **25-11**
 - assignment failures **20-10**
 - configuring allowed lists **25-11**
 - configuring CFS distribution **25-12 to 25-15**
 - configuring fcalias members **30-21**
 - contiguous assignments **25-15**
 - description **25-8**
 - distributing **25-2**
 - duplicates causing errors **67-13**
 - enabling contiguous assignments **25-15**
 - failures **C-2**
 - interoperability **37-9**
 - IVR configuration guidelines **29-13**
 - non-unique and IVR NAT **29-5**
 - preferred **25-10**
 - static **25-10**
 - unique **29-13**
- domainInvalidRCFReceived tooltip **67-14**
- domain manager
 - isolation **20-10**
- domainManagerDisabled tooltip **67-14**
- domainMaxReTxFailure tooltip **67-14**
- domain names
 - configuring **2-6**
- domainOtherSideEportIsolation tooltip **67-14**
- domainOverlapIsolation tooltip **67-14**
- domains
 - overlap isolations **C-2**
- DPVM
 - CFS support **13-2**
 - default settings **28-15**
 - description **28-1**
 - enabling **28-2**
 - requirements **28-2**
 - using DPVM Setup Wizard (procedure) **28-2**
 - wizard **5-34**
- DPVM databases
 - autolearned entries **28-8**
 - clearing **28-9**
 - comparing differences **28-14**
 - configuring CFS distribution **28-10 to 28-13**
 - copying **28-14**
 - description **28-5**
 - enabling autolearning **28-9**
 - merging guidelines **28-13**
- drill down reports
 - description **7-1**
- drivers
 - iSCSI **50-2**
- drop latency time
 - configuring **32-18**
- dsa key pairs

Send documentation comments to mdsfeedback-doc@cisco.com

- generating **39-16**
 - DSCP
 - configuring **48-28**
 - DWRR queues
 - changing weights **64-9**
 - DWRR schedulers
 - description **64-5**
 - dynamic bandwidth management
 - description **22-9**
 - dynamic iSCSI initiator
 - converting **50-40**
 - convert to staticiSCSI
 - convert dynamic initiator to static **50-19**
 - dynamic mapping **50-8, 50-39**
 - dynamic mappingiSCSI
 - dynamic mappingiSCSI
 - static mappingstatic mapping **50-7**
 - Dynamic Port VSAN Membership. See DPVM
-
- E**
- E_D_TOV
 - default setting **66-25**
 - errors when setting **67-7**
 - modifying **66-15**
 - EBCDIC
 - FICON string format **36-19**
 - edge quench congestion control
 - description **64-2**
 - edge switches
 - description **29-4**
 - edge VSANs
 - description **29-3**
 - EFMD
 - fabric binding **47-1**
 - EISLs
 - PortChannel links **23-2**
 - ELP
 - verifying using Device Manager (procedure) **48-16**
 - elpFailureClassFParamErr tooltip **67-14**
 - elpFailureClassNParamErr tooltip **67-15**
 - elpFailureInvalidFlowCTLParam tooltip **67-15**
 - elpFailureInvalidPayloadSize tooltip **67-15**
 - elpFailureInvalidPortName tooltip **67-15**
 - elpFailureInvalidTxBBCredit tooltip **67-15**
 - elpFailureIsolation tooltip **67-15**
 - elpFailureLoopbackDetected tooltip **67-15**
 - elpFailureRatovEdtovMismatch tooltip **67-15**
 - elpFailureRevMismatch tooltip **67-15**
 - ELP failures
 - reason codes **C-2**
 - elpFailureUnknownFlowCTLCode tooltip **67-15**
 - e-mail addresses
 - assigning for Call Home **62-7**
 - e-mail notifications
 - Call Home **62-1**
 - enclosure names
 - aliases **5-33**
 - end devices
 - viewing storage port traffic and errors **7-16**
 - end-to-end connectivity
 - troubleshooting **66-5**
 - enhanced ISLs. See EISLs
 - enhanced zones
 - advantages over basic zones **30-43**
 - changing from basic zones **30-44**
 - creating attribute groups **30-45**
 - default settings **30-48**
 - description **30-43**
 - enabling **30-45**
 - merging databases **30-45**
 - enterprise package licenses
 - description **10-4**
 - entity status inquiry. See ESI
 - EPLD images
 - configuring **B-2**
 - E port mode
 - classes of service **20-4**

Send documentation comments to mdsfeedback-doc@cisco.com

- description **20-4**
 - ePortProhibited tooltip **67-15**
 - E ports
 - 32-port guidelines **20-3**
 - 32-port switching module configuration guidelines **23-8**
 - configuring **20-12, 48-28**
 - fabric binding checking **47-2**
 - FCS support **63-1**
 - FSPF topologies **32-2**
 - isolation **20-10, C-2**
 - recovering from link isolations **30-28**
 - SPAN sources **60-3**
 - eppFailure tooltip **67-15**
 - Error Detect Time Out Value. See E_D_TOV
 - errorDisabled tooltip **67-15**
 - error messages
 - gen error messages **67-7**
 - error reports
 - clearing previous **B-3**
 - escFailureIsolation tooltip **67-15**
 - ESC failures
 - reason codes **C-2**
 - ESI
 - non-resp threshold **50-72**
 - ESI retry count **50-72**
 - Ethereal freeware
 - analyzer **66-18**
 - URL **66-17**
 - Ethernet
 - reducing traffic **66-2**
 - Ethernet PortChannels
 - adding Gigabit Ethernet interfaces **52-10**
 - configuring **52-10**
 - description **52-9**
 - iSCSI **50-55**
 - redundancy **48-6**
 - evaluation
 - stop in Device Manager **10-17**
 - events
 - displaying using Device Manager **57-5**
 - displaying using Fabric Manager **57-5**
 - displaying using Fabric Manager Web Services **57-5**
 - viewing **7-10**
 - Exchange Fabric Membership Data. See EFMD **47-1**
 - exchange IDs
 - in-order delivery **32-15**
 - path selection **26-11**
 - exchange link parameter. See ELP
 - exchange link parameter failures. See ELP failures
 - expansion port mode. See E port mode
 - expiry alerts
 - licenses **10-15**
 - explicit fabric logout **50-16**
 - extended BB_credits
 - configuring **20-28**
 - description **20-27**
 - Generation 2 switching modules **22-23**
 - licensing **22-23**
 - Extended Binary-Coded Decimal Interchange Code. See EBCDIC **36-19**
 - Extended Link Protocol. See ELP
 - external CompactFlash
 - formatting **B-2**
 - external loopback tests
 - description **68-7**
 - performing **68-7**
 - external RADIUS server
 - CHAP **50-57**
 - external RADIUS servers
 - CHAP **50-57**
-
- F**
- fabric
 - editing monitoring **7-47**
 - Fabric Analyzer
 - configuring **66-19**

Send documentation comments to mdsfeedback-doc@cisco.com

- description **66-17**
- Ethereal freeware **66-17**
- libpcap freeware **66-17**
- using display filters **B-3**
- fabric binding
 - activation **47-4**
 - checking for Ex ports **47-2**
 - clearing statistics **47-6**
 - compatibility with DHCHAP **45-3**
 - configuration **47-3 to 47-6**
 - default settings **47-9**
 - deleting database **47-6**
 - description **47-1 to 47-2**
 - EFMD **47-1**
 - enforcement **47-2**
 - forceful activation **47-5**
 - licensing requirements **47-1**
 - port security comparison **47-1**
 - saving configurations **47-5**
 - verifying configuration **47-6 to 47-9**
- fabricBindingDBMismatch tooltip **67-15**
- fabricBindingDomainInvalid tooltip **67-15**
- fabricBindingNoRspFromPeer tooltip **67-15**
- fabricBindingSWWNNotFound tooltip **67-15**
- Fabric Configuration Server. See FCS
- Fabric Configuration Servers. See FCSS
- Fabric-Device Management Interface. See FDMI
- fabric lock
- fabric login. See FLOGI
- fabric loop port mode. See FL port mode
- Fabric Manager
 - authentication **4-1 to ??**
 - browser support **2-19**
 - Cisco Traffic Analyzer **9-2**
 - connection failures **67-10**
 - corrupted jar file errors **67-22**
 - description **1-5, 2-13**
 - detachable tables **5-24**
 - downgrading **67-4**
 - downloading software **2-18**
 - error recovery **67-7**
 - FAQs **67-1**
 - FCIP **67-19**
 - installation failures **67-6, 67-7**
 - installing **2-18**
 - integrating with other tools **2-40**
 - ISL statistics **58-3**
 - Java support **2-19**
 - launching troubleshooting **67-3**
 - login failure recovery **67-6**
 - missing Information pane **67-9**
 - mixed software environments **67-22**
 - network discovery **5-32**
 - preinstallation tasks **2-18**
 - problems with map changes **67-8**
 - running behind firewalls **2-40**
 - running with multiple NICs **67-20**
 - searching for devices **67-22**
 - setting preferences **5-30**
 - shows as disabled service **67-6**
 - support operating systems **2-19**
 - uninstalling **2-43**
 - upgrade failures **67-4**
 - upgrading **2-38, 67-4**
 - viewing license information **10-16**
- Fabric Manager authentication
 - description **4-1**
 - discovery best practices **4-3**
 - Web Server support **4-4**
- Fabric Manager Clients
 - advanced mode **5-2**
 - description **2-14, 5-1**
 - displaying physical attributes **5-20**
 - Fabric pane **5-24**
 - filtering **5-20**
 - Information pane **5-23**
 - launching **5-2**
 - main menu **5-13**

Send documentation comments to mdsfeedback-doc@cisco.com

- setting preferences **5-30**
- status bar **5-30**
- toolbar icons (table) **5-17**
- troubleshooting tools **5-35**
- using interface (figure) **5-12**
- wizards **5-34**
- Fabric Manager features
 - changed (table) **1-Ivii**
 - new (table) **1-Ivii**
- Fabric Manager Server
 - authentication **4-2**
 - configuring preferences **7-51**
 - continuously monitoring fabrics **3-3**
 - database failed to start **67-10**
 - description **2-14, 3-1**
 - disk space requirements **3-1**
 - fabric discovery **4-3**
 - features **3-1**
 - full fabric rediscovery **3-7**
 - installation overview **3-2**
 - installing **3-2**
 - local host error messages **67-20**
 - modifying settings **3-5**
 - passwords **3-7**
 - performing administrative tasks **7-44**
 - performing configuration tasks **7-44**
 - polling periods **3-7**
 - properties files **3-4**
 - Red Hat Linux support **3-1**
 - Solaris support **3-1**
 - troubleshooting tools **66-1**
 - user names **3-7**
 - viewing logs **7-62**
 - Windows support **3-1**
- Fabric Manager Server package license
 - description **10-6**
- Fabric Manager Web Server
 - authentication **4-4**
 - configuring RADIUS authentication **4-4**
- configuring TACACS+ authentication **4-5**
- description **2-15**
- viewing system messages **61-11**
- Fabric Manager Web Services
 - configuring communities **7-51**
 - configuring users **7-53**
 - description **7-1**
 - exporting performance data **7-3**
 - initial screen **7-9**
 - installing **7-3**
 - launching **7-7**
 - navigating **7-2**
 - printing **7-3**
 - recovering passwords **7-45**
 - TCP ports **7-4, 7-5**
 - using with SSL **7-5**
- fabric port mode. See F port mode
- fabric pWWNs
 - zone membership **30-2**
- fabric reconfiguration
 - fcdomain phase **25-2**
- fabrics
 - discovery **5-32**
 - management **2-17**
 - monitoring **3-3**
 - See also build fabric frames
- fabrics. See RCFs; build fabric frames
- fabric security
 - authentication **45-1**
 - default settings **45-10**
- Fabric Shortest Path First. See FSPF
- FabricWare
 - events **D-2**
 - Fabric Manager support (table) **D-3**
 - Fibre Channel support **D-1**
 - installing Fabric Manager Web Services **7-3**
 - roles **D-2**
 - security **D-2**
 - SNMP traps **D-2**

Send documentation comments to mdsfeedback-doc@cisco.com

- syslog traps **D-2**
- zoning support **D-2**
- fabric WWNs. See fWWNs
- fan module LEDs
 - failure status **18-12**
- fan modules
 - description **18-12**
 - displaying status **18-12**
 - failures **18-12**
- FAQs
 - Device Manager **67-1**
 - Fabric Manager **67-1**
- fault tolerant fabrics
 - example (figure) **32-2**
- faliases
 - adding members **30-22**
 - cloning **30-35**
 - configuring for zones **30-21**
 - creating **30-22**
 - renaming **30-34**
 - using with Fabric Manager **3-7**
- FCC
 - assigning priority **64-3**
 - benefits **64-1**
 - default settings **64-12**
 - description **64-1**
 - enabling **64-2**
 - frame handling **64-2**
 - logging facility **61-2**
 - process **64-2**
- fcdomains
 - autoreconfigured merged fabrics **25-7**
 - configuring CFS distribution **25-12 to 25-15**
 - default settings **25-22**
 - description **25-2**
 - disabling **25-6**
 - domain IDs **25-8**
 - displaying statistics **25-22**
 - enabling **25-6**
- enabling autoreconfiguration **25-8**
- incoming RCFs **25-6**
- initiation **25-5**
- overlap isolation **20-10**
- restarts **25-3**
- switch priorities **25-5**
- FC-GS-3 requests
 - device grouping support **5-32**
- FC ID allocation
 - FICON implementation **36-14**
 - FC IDs
 - allocating **25-2, 37-7, 66-24**
 - allocating company IDs **66-24**
 - allocating default company ID lists **37-8**
 - allocating for FICON **36-14**
 - allocation for HBAs **37-7**
 - configuring fcalias members **30-21**
 - description **25-16**
 - persistent **25-17 to ??**
 - FCIP **50-1**
 - advanced features **48-29**
 - checking trunk status (procedure) **48-17**
 - compatibility with DHCHAP **45-3**
 - compression **48-37**
 - configuring **48-7 to ??**
 - configuring using FCIP Wizard **48-8 to 48-15**
 - default parameters **48-38**
 - discarding packets **48-25**
 - enabling **48-8**
 - FICON support **36-5**
 - Gigabit Ethernet ports **52-4, 53-1**
 - high availability **48-4 to 48-7**
 - IPS modules **48-2**
 - IP storage services support **52-1**
 - link failures **48-5**
 - MPS-14/2 module **48-2**
 - reserving ports for FICON **36-13**
 - restrictions **67-19**
 - specifying number of TCP connections **48-25**

Send documentation comments to mdsfeedback-doc@cisco.com

- tape acceleration [48-32 to ??](#)
- time stamps [48-25](#)
- VE ports [48-2](#)
 - verifying ELP (procedure) [48-16](#)
 - verifying interfaces (procedure) [48-16](#)
 - virtual ISLs [48-2](#)
 - VRRP [48-6](#)
 - write acceleration [48-29](#)
- FCIP compression
 - configuring (procedure) [48-12](#)
 - description [48-37](#)
- FCIP interfaces
 - configuring advanced features [48-21 to 48-28](#)
 - configuring peers [48-22](#)
 - configuring QoS [48-28](#)
 - configuring special frames [48-24](#)
 - creating [48-22](#)
 - parameters [48-4](#)
 - SPAN sources [60-3](#)
- FCIP links
 - B port interoperability mode [48-25](#)
 - configuring [48-15](#)
 - configuring peers [48-22](#)
 - configuring QoS [48-28](#)
 - creating [48-16](#)
 - description [48-3](#)
 - endpoints [48-3](#)
 - initiating IP connections [48-25](#)
 - TCP connections [48-3](#)
- FCIP peers
 - configuring IP addresses [48-22](#)
 - enabling special frames [48-24](#)
- fcipPortAdminCfgChange tooltip [67-15](#)
- fcipPortKeepAliveTimerExpire tooltip [67-15](#)
- fcipPortMaxReTx tooltip [67-16](#)
- fcipPortPersistTimerExpire tooltip [67-16](#)
- fcipPortSrcAdminDown tooltip [67-16](#)
- fcipPortSrcLinkDown tooltip [67-16](#)
- FCIP profiles
- configuring TCP parameters [48-19 to ??](#)
- creating [48-15](#)
- description [48-4](#)
- fcipSrcModuleNotOnline tooltip [67-16](#)
- fcipSrcPortRemoved tooltip [67-16](#)
- FCIP tape acceleration
 - configuring [48-36](#)
 - description [48-32 to 48-36](#)
- FCIP TCP parameters
 - configuring buffer size [48-21](#)
 - configuring CWM [48-20](#)
 - configuring keepalive timeouts [48-19](#)
 - configuring maximum jitter [48-21](#)
 - configuring maximum retransmissions [48-19](#)
 - configuring minimum retransmit timeouts [48-19](#)
 - configuring PMTUs [48-20](#)
 - configuring SACKs [48-20](#)
 - configuring window management [48-20](#)
- FCIP write acceleration
 - configuring [48-31](#)
 - configuring (procedure) [48-12](#)
 - description [48-29](#)
- fcotChksumErr tooltip [67-16](#)
- fcotNotPresent tooltip [67-16](#)
- fcotVendorNotSupported tooltip [67-16](#)
- FCP
 - intermixing protocols [36-5](#)
 - routing requests [50-3](#)
- fcping. See Ping Tool
- FCS
 - description [63-1](#)
 - logging facility [61-2](#)
 - significance [63-2](#)
- FC-SP
 - authentication [45-1](#)
 - enabling [45-4](#)
 - enabling on ISLs [45-10](#)
 - See also DHCHAP
- fcspAuthenfailure tooltip [67-16](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- FCSs
 - default settings **63-6**
 - description **63-1**
 - displaying information **63-3 to ??**
- fctimers
 - CFS support **13-2**
 - configuring CFS **B-3**
 - distribution **37-4**
- ftrace. See traceroute
- FDMI
 - description **34-4**
 - displaying database information **34-4**
- Federal Information Processing Standards. See FIPS
- Fibre Channel **50-1**
 - configuring time out values **66-15**
 - iSCSI targets **50-7 to 50-13**
 - sWWNs for fabric binding **47-4**
 - time out values **37-2 to 37-5**
 - TOVs **37-3**
- Fibre Channel Analyzers
 - configuring using SPAN **60-12**
- Fibre Channel analyzers
 - capturing frames locally **B-3**
 - clearing configured information **B-3**
 - monitoring without SPAN **60-10**
 - sending frames to remote IP addresses **B-3**
- Fibre Channel Congestion Control. See FCC
- Fibre Channel domains. See fcdomains
- Fibre Channel interface
 - default settings **20-31**
- Fibre Channel interfaces
 - administrative states **20-7**
 - BB_credits **20-25**
 - characteristics **20-2 to 20-11**
 - configuring beacon modes **20-20**
 - configuring bit error thresholds **20-20**
 - configuring frame encapsulation **20-18**
 - configuring port modes **20-12**
 - configuring receive data field sizes **20-18**
 - configuring speeds **20-12**
 - deleting from PortChannels **23-20**
 - disabling **20-11**
 - enabling **20-11**
 - extended BB_credits **20-27**
 - graceful shutdown **20-11**
 - modes **20-3 to 20-7**
 - operational states **20-8**
 - performance buffers **20-26**
 - reason codes **20-8**
 - states **20-7**
 - taking out of service on Generation 2 switching modules **22-40**
 - troubleshooting operational states **20-9**
 - See also interfaces **20-7**
- Fibre Channel over IP. See FCIP
- Fibre Channel Protocol. See FCP
- Fibre Channel Security Protocol. See FC-SP
- Fibre Channel targets
- Fibre Channel traffic
 - analyzing **66-2**
 - SPAN sources **60-3**
 - statistics **66-3**
- Fibre Channel write acceleration
 - default settings **56-3**
 - description **56-1**
 - enabling **56-2**
 - estimating number of write buffers **56-1**
 - licensing **56-1**
 - modifying number of write buffers **56-2**
- Fibre Channel zoning-based access control **50-27**
- Fibre Connection. See FICON
- FICON
 - advantages on MDS switches **36-3 to 36-7**
 - automatic configuration save **36-23**
 - basic configuration **36-16**
 - calculating flow load balance (procedure) **36-39**
 - cascading **36-7**
 - configuration files **36-28 to 36-31**

Send documentation comments to mdsfeedback-doc@cisco.com

- configuring [36-15 to 36-24](#)
- configuring ports [36-24 to 36-28](#)
- CUP in-band management [36-37](#)
- default settings [36-42](#)
- description [36-1 to 36-7](#)
- displaying information [36-40 to 36-42](#)
- fabric binding requirements [47-3](#)
- Fabric Manager Client support [5-2](#)
- FC4 protocols [36-2](#)
- FC ID allocations [36-14](#)
- FCIP support [36-5](#)
- host timestamp control [36-22](#)
- implemented ports [36-11](#)
- installed ports [36-12](#)
- manually enabling [36-18](#)
- MDS-supported features [36-5](#)
- PortChannel support [36-5](#)
- port numbering [36-8 to 36-14](#)
- port swapping [36-31 to 36-33](#)
- RLIRs [36-27 to 36-28](#)
- saving configuration changes [36-23](#)
- suspending a VSAN [36-19](#)
- sWWNs for fabric binding [47-4](#)
- tape acceleration [36-33 to 36-37](#)
- text string formatting codes [36-19](#)
- unimplemented port [36-11](#)
- VSAN offline state [36-19](#)
- ficonBeingEnabled tooltip [67-16](#)
- FICON configuration files
 - applying to running configuration [36-29](#)
 - copying [36-31](#)
 - description [36-29](#)
 - displaying [36-30](#)
 - editing [36-30](#)
 - view latest information [36-30](#)
- ficonNoPortnumber tooltip [67-16](#)
- ficonNotEnabled tooltip [67-16](#)
- FICON port numbers
 - assigning to slots [36-13](#)
- default numbering scheme [36-8](#)
- FCIP interfaces [36-13](#)
- implemented addresses [36-11](#)
- installed ports [36-12](#)
- logical interfaces [36-13](#)
- numbering guidelines [36-12](#)
- PortChannel interfaces [36-13](#)
- port swapping [36-11](#)
- reserved numbering scheme [36-11](#)
- unimplemented addresses [36-11](#)
- uninstalled ports [36-12](#)
- FICON ports
 - assigning address names using Device Manager [36-27](#)
 - blocking [36-25](#)
 - displaying address information [36-41](#)
 - prohibiting [36-26](#)
 - swapping configurations [36-33](#)
- FICON port swapping
 - configuring (procedure) [36-33](#)
 - guidelines [36-32](#)
- FICON tape acceleration
 - configuration considerations [36-35](#)
 - configuring [36-35](#)
 - description [36-33](#)
- ficonVsanDown tooltip [67-16](#)
- FICP
 - wizard [5-34](#)
- field replaceable units. See FRUs
- files
 - compressing [B-2](#)
 - displaying contents [B-1](#)
 - displaying last lines [B-2](#)
 - uncompressing [B-2](#)
- file systems
 - formatting [16-2](#)
 - volatile: [16-2](#)
- File Transfer Protocol. See FTP
- filtering
 - end port groups [5-28](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- switch groups **5-28**
- filters
 - capture **66-21**
 - defining displays **66-21**
 - permitted **66-22**
 - selective viewing **66-20**
- FIPS
 - configuration guidelines **38-1**
 - self-tests **38-3**
- firewalls
 - configuring **2-14**
 - running with Fabric Manager **2-40**
- firstPortNotUp tooltip **67-16**
- firstPortUpAsEport tooltip **67-16**
- Flash devices
 - bootflash: **16-2**
 - formatting **16-2**
 - overview **16-1**
- FLOGI
 - description **34-1**
 - displaying details **34-1**
 - logging facility **61-2**
- flows
 - performance statistics **8-1**
 - viewing performance information **7-22**
- flow statistics
 - description **8-6**
- FL port mode
 - classes of service **20-5**
 - description **20-5**
- FL ports
 - configuring **20-12**
 - description **20-5**
 - DPVM support **28-8**
 - nonparticipating code **20-10**
 - nonparticipating codes **C-2**
 - persistent FC IDs **25-17**
 - SPAN sources **60-3**
 - See also Fx ports
- F port mode
 - classes of service **20-5**
 - description **20-5**
- F ports
 - configuring **20-12**
 - description **20-5**
 - DPVM support **28-8**
 - SPAN sources **60-3**
 - See also Fx ports
- FPSF
 - load balancing (example) **48-5**
- frame encapsulation
 - configuring **20-18**
- frames
 - configuring MTU size **52-5, 53-3**
 - viewing **66-20**
- frequently asked questions. See FAQs
- FSPF
 - computing link cost **32-7**
 - configuring globally **32-4 to 32-6**
 - configuring Hello time intervals **32-7**
 - configuring link cost **32-6**
 - configuring on interfaces **32-6 to 32-10**
 - dead time intervals **32-8**
 - default settings **32-19**
 - description **32-2**
 - disabling on interfaces **32-9**
 - disabling routing protocols **32-6**
 - displaying databases **32-10**
 - fail-over with PortChannels **32-3**
 - fault tolerant fabrics **32-2**
 - flow statistics **8-6 to 32-19**
 - in-order delivery **32-15 to 32-19**
 - interoperability **37-10**
 - link state record defaults **32-4**
 - multicast root switches **32-14**
 - path selection protocol **D-1**
 - reconvergence times **32-2**
 - redundant links **32-3**

Send documentation comments to mdsfeedback-doc@cisco.com

- retransmitting intervals **32-8**
- routing services **32-1**
- support **2-16**
- topology examples **32-2 to 32-4**
- FSPF multicast roots
 - configuring switches **32-14**
- FSPF routes
 - configuring **32-12**
 - description **32-12**
- FSPF routing
 - multicast **32-14**
- FTP
 - logging facility **61-2**
 - support **2-16**
- full zone sets
 - considerations **30-4**
 - enabling distribution **30-26**
- fWWNs
 - configuring fcalias members **30-21**
- Fx ports
 - 32-port default **20-3**
 - configuring **20-12**
 - description **20-7**
 - FCS **63-1**
 - FCS support **63-1**
 - interface modes **20-7**
 - VSAN membership **26-4**
 - See also F ports; FL ports **20-7**

G

- Generation 1 switching modules
 - combining with Generation 2 switching modules **?? to 22-28**
 - extended BB_credits **20-27**
 - port index allocations **22-24**
 - QoS behavior **64-8**
- Generation 2 switching modules
 - buffer groups **22-10 to 22-22**
- combining with Generation 1 switching modules **?? to 22-28**
- configuring **22-28 to ??**
- configuring port speeds **22-32**
- configuring rate modes **22-33**
- default settings **22-43**
- description **22-1 to ??**
- dynamic bandwidth management **22-9**
- extended BB_credits **20-28, 22-23**
- installing in Generation 1 chassis **15-16**
- out-of-service interfaces **22-10**
- port groups **22-3**
- port index allocations **22-24**
- port rate modes **22-4**
- QoS behavior **64-8**
- recovering from powered-down state **22-25**
- releasing shared resources **22-41**
- taking interfaces out of service **22-40**
- Generation 3 switching modules
 - default settings **22-43**
- Gigabit Ethernet
 - IPv4 example configuration **52-4**
- Gigabit Ethernet interface example **50-53**
- Gigabit Ethernet interfaces
 - configuring **52-4 to 52-10**
 - configuring auto-negotiation **52-5, 53-3**
 - configuring CDP **12-12**
 - configuring high availability **52-8 to 52-10**
 - configuring IPv4 **53-2**
 - configuring MTU frame sizes **52-5, 53-3**
 - configuring promiscuous mode **52-6, 53-4**
 - configuring VRRP **52-9**
 - default parameters **53-6**
 - IPv4-ACL guidelines **53-6**
 - subinterfaces **52-6, 53-5**
 - subnet requirements **52-6, 53-5**
 - viewing performance information **7-23**
- Gigabit Ethernet subinterfaces
 - configuring VLANs **53-5**

Send documentation comments to mdsfeedback-doc@cisco.com

global keys

 assigning for RADIUS **41-8**

H

hardware

 default settings **18-13**

 displaying inventory **18-1**

 displaying temperatures **18-11**

 overview **1-1**

 viewing list **7-10**

hardware failures

 configuring actions **B-3**

hard zoning

 description **30-26**

HA solution example **50-52**

HBA port **50-15, 50-20**

HBA ports

 configuring area FCIDs **25-19**

HBAs

 device aliases **31-1**

 FC ID allocations **37-7, 66-24**

Health tab

 description **7-9**

Hello time intervals

 configuring for FSPF **32-8**

 description **32-7**

high availability

 automatic synchronization **17-4**

 compatibility with DHCHAP **45-3**

 description **17-1**

 Ethernet PortChannel **50-55**

 Ethernet PortChannels **48-6**

 Fibre Channel PortChannels **48-7**

 licensing **10-8**

 process restartability **17-3**

 protection against link failures **17-1**

 software upgrades **15-5**

 supervisor module switchover mechanism **17-2**

switchover characteristics **17-2**

 synchronizing supervisor modules **17-3**

 VRRP **48-6, 50-54**

 VRRPVRRP-based high availability **50-54**

historical data

 preserving **67-19**

host control

 FICON **36-21**

host names

 configuring for digital certificates **43-6**

hosts

 performance statistics **8-1**

HTTP

 port used **2-41**

 support **2-16**

HTTP proxy servers

 configuring **67-21**

HTTPS

 support **2-16**

hwFailure tooltip **67-16**

I

IBM PPRC

 FICON support **36-5**

ICMP

 IPv6 **54-6**

ICMP packets

 type value **42-4**

IDs

 Cisco vendor ID **41-13**

 contract IDs **62-33**

 login IDs **2-5**

 serial IDs **62-34, 62-35, 62-37, 62-39**

 server IDs **62-35**

 site IDs **62-33**

IKE

 algorithms for authentication **44-6**

 default settings **43-37, 44-39**

Send documentation comments to mdsfeedback-doc@cisco.com

- description [44-3](#)
- initializing [44-13](#)
- refreshing SAs [44-20](#)
- terminology [44-5](#)
- transforms for encryption [44-6](#)
- viewing configuration (procedure) [44-11](#)
- IKE domains
 - clearing [44-20](#)
 - description [44-13](#)
- IKE initiators
 - configuring version [44-18](#)
- IKE peers
 - configuring keepalive times [44-17](#)
- IKE policies
 - configuring negotiation parameters [44-15](#)
 - negotiation [44-14](#)
- IKE tunnels
 - clearing [44-20](#)
 - description [44-13](#)
- images
 - See kickstart images; software images; system images
 - Software Installation Wizard [15-8](#)
- images. See kickstart images; software images; system images
- in-band access
 - configuring [2-9](#)
 - IPFC [2-12](#)
- in-band management
 - configuring [2-9, 2-10](#)
 - CUP [36-37](#)
 - Ethernet connection [2-17](#)
 - IPFC [51-5](#)
 - IPFC connection [2-17](#)
 - logical interface [2-9](#)
- incomAdminRxBBCreditPerBuf tooltip [67-16](#)
- incompatibleAdminMode tooltip [67-16](#)
- incompatibleAdminRxBBCredit tooltip [67-16](#)
- incompatibleAdminRxBufferSize tooltip [67-16](#)
- incompatibleLeadminSpeed tooltip [67-16](#)
- indirect link failures
 - recovering [65-1](#)
- initialization string
 - configuring [B-1](#)
- initializing tooltip [67-16](#)
- initiators
 - statically mapped iSCSI [50-35](#)
- in-order delivery
 - configuring drop latency time [32-18](#)
 - enabling for VSANs [32-18](#)
 - enabling globally [32-18](#)
 - guidelines [32-17](#)
 - reordering network frames [32-15](#)
 - reordering PortChannel frames [32-16](#)
- install all command
 - failure cases [15-7](#)
- Intelligent Storage Services
 - disabling (procedure) [55-6](#)
 - disabling with force option [55-6](#)
 - enabling (procedure) [55-3](#)
 - Fibre Channel write acceleration [56-1 to 56-3](#)
 - SCSI flow services [55-1 to 55-8](#)
 - SCSI flow statistics [55-1 to 55-8](#)
- interfaceRemoved tooltip [67-16](#)
- interfaces
 - adding to PortChannels [23-17, 23-18](#)
 - assigning to VSANs [26-8](#)
 - configuring data field size [20-18](#)
 - configuring fcalias members [30-21](#)
 - default settings [20-31](#)
 - deleting from PortChannels [23-20](#)
 - forced addition to PortChannels [23-19](#)
 - isolated states [23-18](#)
 - nonoperational reason codes [C-1](#)
 - reason codes [C-1](#)
 - SFP types [20-22](#)
 - suspended states [23-18](#)
 - VSAN membership [26-7](#)
- interface statistics

Send documentation comments to mdsfeedback-doc@cisco.com

- description [20-22](#)
- gathering [20-22](#)
- internal bootflash:
 - Flash devices [Flash devices 16-2](#)
- internal loopback tests
 - description [68-6](#)
 - performing [68-6](#)
- Internet Control Message Protocol. See ICMP
- Internet Explorer
 - Fabric Manager support [2-19](#)
- Internet Key Exchange. See IKE
- Internet Storage Name Service. See iSNS
- interoperability
 - configuring interop mode 1 [37-11](#)
 - description [37-8](#)
 - verifying status [37-12](#)
 - VSANs [26-12](#)
- interop modes
 - configuring mode 1 [37-11](#)
 - default settings [37-13](#)
 - description [37-9](#)
- Inter-VSAN Routing. See IVR
- Inter-VSAN Routing zones. See IVR zones
- Inter-VSAN Routing zone sets. See IVR zone sets
- invalidAttachment tooltip [67-16](#)
- invalidConfig tooltip [67-16](#)
- invalidFabricBindExh tooltip [67-16](#)
- inventories
 - managing [57-3](#)
 - viewing details for switches [7-30](#)
 - viewing details for VSANs [7-29](#)
 - viewing information [7-28](#)
 - viewing ISL information [7-34](#)
 - viewing module details [7-32](#)
 - viewing zone information [7-36](#)
- Inventory tab
 - description [7-28](#)
- IOD. See in-order delivery
- IP-ACLs
 - wizard [5-34](#)
 - See also IPv4-ACLs; IPv6-ACLs
 - IP addresses
 - management interfaces [2-2](#)
 - IP connections
 - active mode [48-25](#)
 - initiating [48-25](#)
 - passive mode [48-25](#)
 - IP domain names
 - configuring for digital certificates [43-6](#)
 - IPFC
 - configuration guidelines [51-5](#)
 - description [51-5](#)
 - errors caused by configuration [67-8](#)
 - in-band access [2-12](#)
 - in-band management [2-17](#)
 - logging facility [61-2](#)
 - IP filters
 - contents [42-2](#)
 - restricting IP traffic [42-1](#)
 - using IP-ACL Wizard (procedure) [42-5](#)
 - IP routing
 - enabling [2-6, 2-10](#)
 - IPsec
 - algorithms for authentication [44-6](#)
 - configuring with FCIP Wizard (procedure) [48-9](#)
 - crypto IPv4-ACLs [44-21 to 44-25](#)
 - default settings [44-39](#)
 - description [44-2](#)
 - digital certificate support [44-7 to 44-10](#)
 - enabling with FCIP Wizard (procedure) [44-10](#)
 - fabric setup requirements [44-4](#)
 - global lifetime values [44-37](#)
 - hardware compatibility [44-4](#)
 - licensing requirements [44-3](#)
 - maintenance [44-37](#)
 - prerequisites [44-3](#)
 - RFC implementations [44-1](#)
 - terminology [44-5](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- transform sets [44-25](#)
- transforms for encryption [44-6](#)
- unsupported features [44-4](#)
- viewing configuration (procedure) [44-11](#)
- IP security. See IPsec
- IPS modules
 - CDP support [52-10](#)
 - core dumps [B-2](#)
 - FCIP [48-2](#)
 - port modes [52-4, 53-1](#)
 - software upgrades [52-3](#)
 - supported features [52-1](#)
- IPS port mode
 - description [52-4](#)
- IPS ports [50-8](#)
 - modes [53-1](#)
 - multiple connections [50-53](#)
 - SPAN sources [60-3](#)
- IP storage services
 - default parameters [52-10](#)
- IP Storage services modules. See IPS modules
- IPv4
 - configuring Gigabit Ethernet interfaces [53-2](#)
 - default settings [53-6](#)
 - description [53-1](#)
 - transitioning to IPv6 [54-15](#)
- IPv4-ACLs
 - adding entries [42-7](#)
 - applying to interfaces [42-10, 42-11](#)
 - configuration guidelines [42-2](#)
 - creating complex IPv4-ACLs (procedure) [42-6](#)
 - creating with IP-ACL Wizard (procedure) [42-5](#)
 - crypto [44-21 to 44-25](#)
 - crypto map entries [44-28](#)
 - example configuration [42-12](#)
 - FabricWare support [D-2](#)
 - guidelines for Gigabit Ethernet interfaces [53-6](#)
 - reading dump logs [42-9](#)
 - removing entries [42-8](#)
- IPv4 addresses
 - configuring fcalias members [30-21](#)
 - configuring IPv6 and IPV6 protocol stacks [54-13](#)
 - IPv6 protocol stacks [54-10](#)
- IPv4 default gateways
 - configuring [2-10, 12-10, 51-3](#)
 - configuring mgmt0 interfaces [20-29](#)
 - description [51-3](#)
 - static routes (tip) [51-4](#)
- IPv4 default networks
 - description [51-4](#)
- IPv6
 - address types [54-3](#)
 - configuring addressing [54-11](#)
 - configuring management interfaces [51-3](#)
 - enabling routing [54-11](#)
 - IPv6-ACL guidelines [54-14](#)
 - neighbor discovery [54-7](#)
 - path MTU discovery [54-7](#)
 - router advertisement messages [54-9](#)
 - router discovery [54-9](#)
 - static routes [54-13](#)
- IPv6 addresses
 - configuring fcalias members [30-2, 30-21](#)
 - link-local type [54-4](#)
- IPv6 neighbor discovery
 - advertisement messages [54-7](#)
- IPv6 routing
- IPv6 static routes
- IQN
 - formats [50-8](#)
- IQNs
 - formats [50-8](#)
- iSCSI
 - enforcing access control [50-27](#)
- iSCSI
 - access control [50-24 to 50-28](#)
 - add initiator to zone database [50-25](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- advanced VSAN membership
 - advanced VSAN membership **50-24**
- checking for WWN conflicts **50-19**
- compatible drivers **50-2**
- configuring **50-1, 50-1 to ??, 50-4, ?? to 50-56**
- configuring AAA authentication **50-28, 50-29**
- configuring ACLs **50-26**
- configuring VRRP **50-54**
- default parameters **50-75**
- discovery phase **50-27**
- drivers **50-2**
- enabling **50-4**
- error **50-15**
- Fabric Manager Client support **5-2**
- Fibre Channel targets **50-7 to 50-13**
- Gigabit Ethernet ports **52-4, 53-1**
- GW flagiSCSI
 - gateway device **50-16**
- HA with host without multi-path software **50-51**
- initiator idle timeout
 - initiator idle timeout
 - iSCSI initiator idle timeout
- initiator name **50-30**
- IPS module support **52-2**
- IQNs **50-14**
- login redirect **50-37**
- LUN mapping for targets **50-62 to ??**
- MPS-14/2 module support **52-2**
- multiple IPS ports **50-53**
- PortChannel-based high availability **50-55**
- PortChannel-based high availabilityEthernet
 - PortChannel-based high availability **50-55**
- protocol **50-2**
- requests and responses **50-3**
- restrict an initiator to a specific user name for CHAP authentication **50-30**
- routing **50-2**
- routing modes chart
 - routing modes chart for iSCSI **50-34**
- session creation **50-27**
- statically mapped initiators **50-35**
- transparent initiator mode **50-15**
- transparent mode initiator **50-58 to ??**
- users with local authentication **50-30**
- VSAN membership **50-22**
- VSAN membership example **50-23**
- wizard **5-34**
- iSCSI authentication
 - configuring **50-28, 50-43**
 - external RADIUS servers **50-57**
 - global override **50-29**
 - local authentication **50-30**
 - mechanisms **50-29**
 - restricting on initiators **50-30**
 - scenarios **50-56**
 - setup guidelines **50-56**
- iSCSI-based access control **50-26**
- iSCSI devices
 - example membership in VSANs **50-23**
 - iscsi-gw **50-20**
- iSCSI high availability
 - configuring **50-50 to 50-56**
- iSCSI hosts
 - VSAN membership **50-22**
- iSCSI hosts
 - initiator identification **50-14**
 - initiator presentation modes **50-14**
 - initiator presentation modes
 - initiator presentation modes **50-14**
- iSCSI initiators
 - configuring static IP address mapping **50-18**
 - idle timeout **50-16**
 - making dynamic WWN mapping static **50-19**
 - proxy mode **50-20**
 - static mapping **50-17**
 - transparent mode **50-15**
 - WWN assignments **50-17**
- iSCSI interfaces
 - configuring **50-14, 50-14 to ??**
 - configuring listener ports **50-32**

Send documentation comments to mdsfeedback-doc@cisco.com

- configuring listener ports*iSCSI*
 - listener port **50-32**
- configuring QoS **50-32**
- configuring routing mode **50-33 to ??**
- configuring routing modes*iSCS*
 - configuring routing modes*routing modes* **50-33**
- configuring TCP tuning parameters **50-32**
- creating **50-5**
- creating*iSCSI*
 - creating interfaces **50-5**
 - SPAN sources **60-3**
 - VSAN membership **50-23**
- iSCSI LUs* **50-8**
- iSCSI protocol* **50-1**
- iSCSI server load balancing* **50-35**
- iSCSI targets*
 - advertising **50-12**
 - dynamic importing **50-8**
 - dynamic mapping **50-8**
 - examples **50-12**
 - secondary access **50-52**
 - static importing **50-10**
 - static importing static mapping*iSCSI targets*
 - static mapping **50-10**
- iSLB*
 - activating zones **50-41, 50-42**
 - auto-zoning **50-46**
 - CFS support **13-2**
 - committing configuration changes*committing configuration changes*
 - iSLB* **50-48**
 - configuration distribution **50-46 to ??, 50-47**
 - configuration prerequisites **50-36**
 - configuring **50-35**
 - configuring initiators and targets **50-41**
 - configuring VRRP **50-45**
 - configuring zones **50-41, 50-42**
 - default settings **50-76**
 - distributing configuration using CF **50-46**
- dynamic initiator mapping **50-40**
- enabling configuration distribution **50-47**
- initiator WWN assignment **50-35**
- load balancing algorithm **50-45 to ??**
- static initiator configuration*initiator configuration*
 - static iSLB **50-35**
- VSAN membership **50-40**
- zone set activation failed **50-42**
- iSlb*
 - default settings **50-76**
- iSLB initiators* **50-37**
 - activating zones **50-42**
 - assigning WWNs **50-39**
 - configuring **50-39 to 50-43**
 - configuring load balancing metrics **50-40**
 - configuring zones **50-42**
 - dynamic initiator mapping **50-40**
 - VSAN membership **50-40**
- iSLB initiator targets*
 - activating zones **50-42**
 - configuring zones **50-42**
 - description **50-41**
- iSLB sessions*
 - authentication **50-43**
 - authentication*iSLB*
 - sessions authentication **50-43**
 - maximum per IPS port*iSLB*
- ISLs*
 - graph past 24 hours performance **7-26**
 - performance statistics **8-1**
 - PortChannel links **23-2**
 - statistics **58-3**
 - viewing detailed inventory information **7-34**
 - viewing performance information **7-17**
- iSMS servers*
 - enabling **50-71**
- iSNS*
 - CFS support **13-2**
 - client registration **50-72**

Send documentation comments to mdsfeedback-doc@cisco.com

- cloud discovery [50-73](#)
- configuring [50-73](#)
- configuring servers [50-71 to 50-73](#)
- description [50-67](#)
- ESI [50-72](#)
- iSNS cloud discovery
 - automatic [50-75](#)
 - CFS distribution [50-75](#)
 - description [50-73](#)
 - enabling [50-74](#)
 - initiating on-demand [50-74](#)
- iSNS profiles
- iSNS servers
 - configuration distribution [50-71](#)
 - configuring ESI retry count [50-72](#)
 - enabling [50-71](#)
 - example scenario [50-70](#)
- isolated VSANs
 - description [26-8](#)
 - displaying membership [26-9](#)
- IVR
 - activating topologies [29-16](#)
 - AF IDs [29-15](#)
 - auto-topology [29-6](#)
 - border switch [29-4](#)
 - border switch, guidelines [29-14](#)
 - border switch configuration guidelines [29-14](#)
 - border switches [29-4](#)
 - configuring (procedure) [29-14](#)
 - configuring logging levels [29-20](#)
 - configuring without auto topology [29-13](#)
 - configuring without IVR NAT [29-13](#)
 - current VSANs [29-3](#)
 - database merge guidelines [29-31](#)
 - default settings [29-34](#)
 - default zone policy [29-22](#)
 - description [29-2](#)
 - domain ID configuration guidelines [29-13](#)
 - domain ID guidelines [29-13](#)
 - edge switch [29-4](#)
 - edge switches [29-4](#)
 - edge VSANs [29-3](#)
 - Fabric Manager Client support [5-2](#)
 - features [29-3](#)
 - Fibre Channel header modifications [29-4](#)
 - FICON support [B-2](#)
 - interoperability [29-7](#)
 - logging [29-20](#)
 - modifying [29-9](#)
 - native VSANs [29-3](#)
 - paths [29-3](#)
 - persistent FC IDs [29-19](#)
 - read-only zoning [29-31](#)
 - SDV limitations [27-9](#)
 - service groups [B-2](#)
 - sharing resources [29-2](#)
 - terminology [29-3](#)
 - transit VSAN configuration guidelines [29-14](#)
 - transit VSANs [29-3](#)
 - virtual domains [29-18](#)
 - VSAN topologies [29-6](#)
 - wizard [5-34](#)
 - zone communication [29-22](#)
 - zones [29-3, 29-22 to ??](#)
 - zone sets [29-3](#)
 - Zone Wizard [29-7](#)
 - IVR databases
 - merge guidelines [29-31](#)
 - IVR logging
 - configuring levels [29-20](#)
 - IVR NAT
 - auto-topology [29-6](#)
 - border switch, guidelines [29-10](#)
 - configuration guidelines [29-10](#)
 - description [29-5](#)
 - load balancing [29-5](#)
 - modifying (procedure) [29-11](#)
 - transit VSANs, guidelines [29-10](#)

Send documentation comments to mdsfeedback-doc@cisco.com

IVR persistent FC IDs

 configuring [29-19](#)

 persistent [29-19](#)

IVR topologies

 CFS support [13-2](#)

 clearing manual entries [29-17](#)

 creating manually [29-15](#)

 manually activating [29-16](#)

 migrating from automatic mode to user-configured mode [29-17](#)

 recovering [29-29](#)

IVR virtual domains

 configuring [29-18](#)

 description [29-18](#)

IVR zones

 activating with force option [29-26](#)

 automatic creation [29-22](#)

 clearing database [29-31](#)

 configuring [29-23 to ??](#)

 configuring LUNs [29-30](#)

 configuring QoS attributes [29-30](#)

 configuring with IVR Zone Wizard [29-7](#)

 description [29-3, 29-21, 29-22](#)

 differences with zones (table) [29-22](#)

 downgrading considerations [29-31](#)

 LUN zoning [29-30](#)

 maximum number of members [29-4](#)

 maximum number of zones [29-4](#)

 recovering the full database [29-28](#)

 renaming [29-30](#)

IVR zone sets

 configuring [29-23 to ??](#)

 description [29-3, 29-21](#)

 downgrading considerations [29-31](#)

 maximum number [29-4](#)

 renaming [29-30](#)

J

Java

 execution failures [67-6](#)

 java.lang.ArrayIndexOutOfBoundsException
 errorArrayIndexOutOfBoundsException error [67-7](#)

Java RMI

 ports used [2-41](#)

Java Runtime Environment. See JRE

Java Web Start

 checking installation [67-3](#)

 clearing the cache [67-6](#)

 Fabric Manager support [2-19](#)

 hangs on the download dialog [67-5](#)

 not detected [67-4](#)

 running from command line [67-5](#)

 setting up on *.jnlp files [67-5](#)

jitter

 configuring estimated maximum in FCIP profiles [48-21](#)

JNLP

 verifying settings [67-3](#)

JRE

 Fabric Manager requirements [7-4](#)

jumbo frames. See MTUs

K

keepalive timeouts

 configuring in FCIP profiles [48-19](#)

kernel core dumps

 configuring [B-3](#)

kickstart images

 description [15-2](#)

 KICKSTART variable [15-1](#)

 selecting for supervisor modules [15-2](#)

Konqueror

 configuring for Java Web Start [67-5](#)

Send documentation comments to mdsfeedback-doc@cisco.com

L

- latency
 - forwarding **50-33**
- LEDs
 - beacon mode states **20-19**
 - speed **20-19**
- license key files
 - description **10-2**
 - installing **10-10**
 - obtaining **10-9**
 - updating **10-9**
- licenses
 - backing up files **B-1**
 - claim certificate **10-2**
 - description **10-1**
 - displaying information **10-16**
 - enterprise package **10-4**
 - expiry alerts **10-15**
 - extended BB_credits **20-27, 22-23**
 - Fabric Manager **67-24**
 - Fabric Manager Server **10-17**
 - Fabric Manager Server package **10-6**
 - factory-installed **10-9**
 - feature-based **10-3**
 - features supported (table) **10-4**
 - grace period alerts **10-15**
 - grace period expiration **10-15**
 - high availability **10-8**
 - identifying features in use **10-13**
 - installation options **10-8**
 - installing manually **10-9**
 - installing using Device Manager **10-12**
 - installing using License Wizard **10-11**
 - installing with License Wizard **10-11**
 - key files **10-9 to 10-13**
 - mainframe package **10-6**
 - module-based **10-3**
 - moving between switches **B-1**
 - obtaining **10-9**
 - on-demand port activation **11-1**
 - One-Click License Install failed **67-9**
 - PAK **10-2**
 - SAN extension package **10-5**
 - Storage Services Enabler package **10-7**
 - terminology **10-1**
 - transferring between switches **10-16**
 - uninstalling **10-14**
 - unsupported features **B-1**
 - updating **10-14**
 - viewing in Device Manager **10-16**
 - viewing in Fabric Manager **10-16**
 - viewing in Fabric Manager Web Services **10-17**
 - viewing switch information **7-31**
 - viewing with Fabric Manager Web Server (procedure) **10-17**
 - wizard **5-34**
 - line cards. See switching modules; services modules
 - link costs
 - configuring for FSPF **32-7**
 - description **32-6**
 - linkFailCreditLossB2B tooltip **67-17**
 - linkFailCreditLoss tooltip **67-17**
 - linkFailDebounceTimeout tooltip **67-17**
 - linkFailLineCardPortShutdown tooltip **67-17**
 - linkFailLinkReset tooltip **67-17**
 - linkFailLIPF8Rcvd tooltip **67-17**
 - linkFailLIPRcvdB2B tooltip **67-17**
 - linkFailLossOfSignal tooltip **67-17**
 - linkFailLossOfSync tooltip **67-17**
 - linkFailLRRcvdB2B tooltip **67-17**
 - linkFailNOSRcvd tooltip **67-17**
 - linkFailOLSRcvd tooltip **67-17**
 - linkFailOPNyRETB2B tooltip **67-17**
 - linkFailOPNyTMOB2B tooltip **67-17**
 - linkFailPortInitFail tooltip **67-17**
 - linkFailPortUnusable tooltip **67-17**
 - linkFailRxQOverFlow tooltip **67-17**

Send documentation comments to mdsfeedback-doc@cisco.com

- linkFailTooManyINTR tooltip **67-17**
- link failures
 - protection against **17-1**
 - reason codes **C-1**
 - recovering **65-1**
- linkFailure tooltip **67-17**
- Link Incident Records. See LIRs
- link-local addresses
- link redundancy
 - Ethernet PortChannel aggregation **52-9**
- Linux **2-34**
 - Fabric Manager support **2-19**
 - installing Fabric Manager Web Services **7-4**
 - install scripts **2-34**
- LIRs
 - description **36-27**
- load balancing **50-35, 50-37**
 - attributes **26-11**
 - attributes for VSANs **26-5**
 - configuring **26-11**
 - description **23-4, 26-11**
 - FSPF (example) **48-5**
 - PortChannels **23-2**
 - PortChannels (example) **48-5**
 - weighted **50-40**
 - load metric **50-40**
 - lock the fabric **50-48**
 - log files
 - configuring **61-6**
 - default names **61-6**
 - description **68-3**
 - sizes **61-6**
 - logging
 - default settings **61-11**
 - disabling **61-3**
 - enabling **61-3**
 - message severity levels **61-3**
 - logical unit numbers. See LUNs
 - logins
 - failure recovery **67-6**
 - SSH **41-4**
 - Telnet **41-4**
 - logs
 - increasing log window size **67-10**
 - RMON **59-16**
 - viewing information **7-62**
 - viewing using Device Manager **57-4**
 - viewing using Fabric Manager Web Server **57-4**
 - loopbackDiagFailure tooltip **67-17**
 - loopbackIsolation tooltip **67-17**
 - loopback tests
 - configuring frequency **B-3**
 - external **68-6, 68-7**
 - loops
 - monitoring **B-3**
 - LUN **50-8**
 - LUN mapping **50-52**
 - iSCSI **50-62 to ??**
 - LUNs
 - explicit access control **50-20**
 - IVR zoning **29-30**
 - mapping and assignment **50-20**
 - LUN zoning
 - configuring **30-40**
 - description **30-40**
 - LUs **50-8**

M

 - MAC addresses
 - configuring secondary **37-6, 66-23**
 - mainframe package licenses
 - description **10-6**
 - mainframes
 - FICON parameters **36-22**
 - VSAN clock **36-22**
 - management
 - role-based **5-34**

Send documentation comments to mdsfeedback-doc@cisco.com

- management access
 - configuring in-band **2-9 to 2-12**
 - configuring out-of-band **2-4 to 2-9**
 - description **2-12**
 - in-band **2-3**
 - out-of-band **2-3**
- management interfaces
 - configuring **20-29, 51-3**
 - configuring for IPv6 **51-3**
 - default settings **20-31**
 - features **20-29**
 - IP addresses **2-2**
 - See also mgmt0 interfaces
- management protocols
 - supported (table) **2-15**
- map preferences
 - Automatically Save Layout default **5-32**
 - Detach Overview Window default **5-32**
 - Display End Device Labels default **5-31**
 - Display End Devices default **5-31**
 - Display Unselected VSAN Members default **5-31**
 - Expand Loops default **5-31**
 - Expand Multiple Links default **5-31**
 - Layout New Devices Automatically default **5-31**
 - Open New Device Manager Each Time default **5-31**
 - Override Preferences for Non-default Layout default **5-31**
 - Select Switch or Link from Table default **5-31**
 - Use Quick Layout when Switch has >=30 End Devices default **5-31**
- maps
 - black squares **67-14**
 - brown squares **67-14**
 - clearing license orange X **67-24**
 - clearing topologies **67-21**
 - color definitions **67-13**
 - default preferences **5-31**
 - freezing the layout look **67-13**
 - green squares with mode **67-14**
- grouping end devices **5-32**
- highlighting **5-26**
- icon descriptions **5-24**
- light gray squares **67-14**
- module warnings **67-13**
- no squares **67-14**
- orange crosses **67-14**
- orange squares with mode **67-14**
- purging down elements **5-27**
- red crosses **67-14**
- red line through switches **67-13**
- red squares **67-14**
- refreshing **5-27**
- saving **5-26**
- shows two switches when only one **67-13**
- tab descriptions **5-25**
- upgrade software without losing map settings **67-19**
- viewing large **5-26**
- Visio diagrams **5-27**
- maps module failuresmaps
 - fan failuresmaps
 - power supply failures **67-13**
 - maximum retransmissions
 - configuring in FCIP profiles **48-19**
- McAfee Internet Suite 6.0 Professional
 - Device Manager installation failures **67-7**
 - Fabric Manager installation failures **67-7**
- McData
 - native interop mode **37-9**
- MD5 authentication
 - IKE **44-7**
 - IPsec **44-6**
 - VRRP **51-12**
- merged fabrics
 - autoreconfigured **25-7**
 - selecting severity level **7-50**
- mgmt0
 - out-of-band management **2-17**
- mgmt0 interfaces

Send documentation comments to mdsfeedback-doc@cisco.com

- configuring [12-10, 20-29](#)
- configuring out-of-band access [2-6](#)
- default settings [20-31](#)
- features [20-29](#)
- local IPv4 routing [51-5](#)
- out-of-band access [2-12](#)
- Microsoft Challenge Handshake Authentication Protocol.
See [MSCHAP](#)
- minimum retransmit timeouts
 - configuring in FCIP profiles [48-19](#)
- modems
 - configuring settings [B-1](#)
- module configurations
 - preserving [B-2](#)
 - purgung [B-2](#)
 - saving to NVRAM [19-7](#)
- modules
 - configuring message logging [61-5](#)
 - connecting to [B-2](#)
 - displaying temperatures [18-11](#)
 - preserving the configuration [19-7](#)
 - replacing [15-17](#)
 - resetting [19-5](#)
 - state descriptions [19-4](#)
 - temperature monitoring [18-11](#)
 - verifying status [12-2, 19-3](#)
- module tests
 - configuring [B-3](#)
- monitoring traffic
 - SPAN [60-6](#)
- Mozilla
 - configuring for Java Web Start [67-5](#)
- MPS-14/2 modules [50-1, 50-2, 50-3, 50-5, 50-20, 50-27](#)
 - CDP support [52-10](#)
 - configuring extended BB_credits [20-27](#)
 - FCIP [48-2](#)
 - port modes [52-4, 53-1](#)
 - software upgrades [52-3](#)
 - supported features [52-1](#)
- MSCHAP
 - description [41-25](#)
- MTU frame sizes
 - configuring Gigabit Ethernet interfaces [52-5](#)
- MTUs
 - configuring frame sizes [53-3](#)
 - configuring size
- multicast addresses
- multicast root switches
 - configuring [32-14](#)
 - description [32-14](#)
- multi-path software example [50-51](#)
- multiple fabrics [57-3](#)
 - managing [67-24](#)
- multiple VSANs
 - configuring [51-7](#)
- Multiprotocol Services modules. See [MPS-14/2 modules](#)
- mutual CHAP authentication
 - configuring for iSCSI [50-30](#)
 - configuring for iSLB [50-43](#)
 - configuring for iSLBI [50-43](#)

- N**
- name servers
 - displaying database entries [34-3](#)
 - interoperability [37-10](#)
 - LUN information [35-1](#)
 - proxy feature [34-2](#)
 - registering proxies [34-2](#)
 - rejecting duplicate pWWNs [34-3](#)
- NAT. See [IVR NAT](#)
- native VSANs
 - description [29-3](#)
- Network Address Translation. See [IVR NAT](#)
- network administrator roles
 - FabricWare [D-2](#)
- network administrators
 - additional roles [41-3](#)

Send documentation comments to mdsfeedback-doc@cisco.com

permissions [41-3](#)

network monitoring

- device discovery [57-1](#)
- mapping topologies [57-2](#)

network operator roles

- FabricWare [D-2](#)

network operators

- permissions [41-3](#)

Network Time Protocol. See NTP

NICs

- manually specifying for Device Manager [67-21](#)
- manually specifying for Fabric Manager Client [67-21](#)
- manually specifying for Fabric Manager Server [67-20](#)

NL ports

- hard zoning [30-26](#)
- interface modes [20-7](#)
- zone enforcement [30-26](#)

node world wide names. See nWWNs

nondisruptive upgrades

- methods [15-5](#)

None authentication [50-28](#)

nonparticipating codes

- description [20-10](#)

nonParticipating tooltip [67-17](#)

nonvolatile storage

- bootflash: [16-2](#)

notifications

- adding forwards [7-49](#)
- conditions for sending [7-59](#)
- removing forwards [7-50](#)

NPIV

- configuring [B-2](#)

NP links [21-3](#)

N-Port identifier virtualization. See NPIV

N ports

- hard zoning [30-26](#)
- zone enforcement [30-26](#)
- zone membership [30-2](#)

See also Nx ports

NL ports

- See also Nx ports

NP-ports [21-3](#)

NPV

- wizard [5-34](#)

NPV, configuring [21-7](#)

NPV mode [21-3](#)

ntop freeware

- batch files [9-5](#)
- modifying launch scripts [9-5](#)

NTP

- CFS support [13-2](#)
- configuration guidelines [12-5](#)
- configuring [12-4 to 12-10](#)
- configuring CFS distribution [12-8](#)
- configuring with CFS [12-8](#)
- logging facility [61-2](#)
- time-stamp option [48-25](#)

NTP peers

- deleting [12-7](#)
- editing [12-6](#)

NTP servers

- configuring [2-7](#)
- deleting [12-7](#)
- editing [12-6](#)

nWWNs

- DPVM [28-1](#)

Nx ports

- FCS support [63-1](#)
- See also N ports; NL ports

O

offline tooltip [67-17](#)

OHMS

- configuring [B-3](#)
- description [68-6](#)

ohmsExtLBTest tooltip [67-17](#)

On-Demand Port activation license

Send documentation comments to mdsfeedback-doc@cisco.com

- acquiring for ports **11-6**
 - checking status of licenses **11-4**
 - configuring **11-4 to ??**
 - description **11-1**
 - making ports eligible **11-5**
 - port licensing **11-2**
 - port naming conventions **11-2**
 - Online Certificate Status Protocol. See OCSP
 - Online Health Management System. See OHMS
 - Opera
 - configuring for Java Web Start **67-5**
 - operational states
 - configuring on Fibre Channel interfaces **20-12**
 - description **20-8**
 - OSCP
 - support **43-5**
 - other tooltip **67-17**
 - out-of-band access
 - mgmt0 interfaces **2-12**
 - out-of-band management
 - configuring **2-4, 2-10**
 - Ethernet connection **2-17**
 - out-of-service interfaces
 - description **22-10**
 - overlay VSANs
 - configuring **51-6**
 - description **51-6**
 - oversubscription
 - diagnosing with Device Manager **66-14**
 - disabling restrictions **22-35**
 - enabling restrictions **22-37**
 - Generation 2 switching modules **22-34**
 - ratios **22-34**
-
- P**
- PAA
 - description **66-2**
 - troubleshooting tools **66-2**
 - PAA-2s
 - Cisco Traffic Analyzer **9-3**
 - description **9-2**
 - PAAs
 - compared with PAA-2s **9-3**
 - packets
 - discarding in FCIP **48-25**
 - parentDown tooltip **67-18**
 - passwords
 - administrator **2-2**
 - assigning using Fabric Manager **5-34**
 - DHCHAP **45-7, 45-8**
 - recovering **7-45**
 - setting administrator default **2-9**
 - path MTUs. See PMTUs
 - pcAnyWhere
 - replacing with DirectX **67-6**
 - stopping **67-6**
 - PDU **50-33**
 - peerFCIPPPortClosedConnection tooltip **67-18**
 - peerFCIPPPortResetConnection tooltip **67-18**
 - performance
 - configuring collections **7-56**
 - customizing reports **7-37**
 - custom monitoring **7-26**
 - data **8-3**
 - event triggers **8-2**
 - graphs **58-6**
 - historical monitoring **58-4**
 - host-optimized port groups **58-6**
 - ISL statistics (procedure) **58-3**
 - monitoring **8-1**
 - monitoring in Device Manager (procedure) **58-1**
 - per-port monitoring (procedure) **58-2**
 - real-time monitoring **58-1**
 - summary reports **58-6**
 - tables **58-6**
 - using thresholds **8-2, 58-4**
 - viewing future predictions **7-25**

Send documentation comments to mdsfeedback-doc@cisco.com

- viewing summaries [7-14](#)
- performance buffers
 - configuring [20-27](#)
 - description [20-26](#)
- performance collections
 - adding [7-56](#)
 - configuring thresholds [7-59](#)
 - removing [7-57](#)
- Performance Manager
 - architecture [8-1](#)
 - authentication [4-4](#)
 - configuring data collection [8-3](#)
 - configuring flows [8-3](#)
 - configuring with Traffic Analyzer [58-9](#)
 - creating collections [58-4](#)
 - creating flows [58-4](#)
 - data collection [8-2](#)
 - data interpolation [8-2](#)
 - description [2-15](#)
 - shows as disabled service [67-6](#)
 - thresholds [58-4](#)
 - using thresholds [8-2](#)
 - verifying collections [3-3](#)
 - viewing reports [58-5](#)
 - wizard for configuring [58-5](#)
- Performance Manager reports
 - exporting as CSV [58-8](#)
 - exporting as XML [58-7](#)
 - generating top 10 [58-7](#)
 - viewing events [58-6](#)
 - viewing graphs [58-6](#)
 - viewing host-optimized port group performance [58-6](#)
 - viewing summary reports [58-6](#)
 - viewing tables [58-6](#)
- Performance tab
 - description [7-13](#)
- persistent domain ID
 - FICON VSANs [47-3](#)
- persistent FC IDs
- configuring [25-17](#)
- description [25-17, 29-19](#)
- enabling [25-17](#)
- purging [25-21](#)
- Ping Tool
 - troubleshooting tools [66-7](#)
- PKI
 - enrollment support [43-4](#)
- PLOGI
 - name server [34-3](#)
- PMTUs
 - configuring in FCIP profiles [48-20](#)
- polling periods
 - changing [3-7](#)
- port addresses
 - FICON [36-11](#)
- Port Analyzer Adapters. See PAAs
- Port Analyzer Adapters 2. See PAA-2s
- portBindFailure tooltip [67-18](#)
- portBlocked tooltip [67-18](#)
- PortChannel
 - interfaces [50-12](#)
 - subinterfaces [50-12](#)
- portChannelMembersDown tooltip [67-18](#)
- PortChannel modes
 - description [23-6](#)
- PortChannel Protocol
 - autocreation [23-22](#)
 - configuring autocreation [23-23](#)
 - converting autocreated groups to manually configured [23-23](#)
 - creating channel group [23-21](#)
 - description [23-20](#)
 - enabling autocreation [23-23](#)
- PortChannels
 - adding interfaces [23-17, 23-18](#)
 - administratively down [20-10](#)
 - comparison with trunking [23-3](#)
 - compatibility checks [23-17](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- compatibility with DHCHAP **45-3**
- configuration guidelines **23-10**
- configuring **23-9 to ??**
- configuring for FCIP high availability **48-5**
- configuring using Device Manager **6-7**
- creating **23-16**
- creation dialog box too small **67-8**
- default settings **23-25**
- deleting **23-16**
- deleting interfaces **23-20**
- description **23-1**
- down states **C-2**
- examples **23-2**
- FICON support **36-5**
- forcing interface additions **23-19**
- Generation 2 switching module interfaces **22-26**
- high availability **17-1**
- incompatible modes **C-2**
- incompatible remote switch **C-2**
- incompatible speeds **C-2**
- in-order guarantee **32-16**
- interface states **23-18**
- interoperability **37-10**
- IQN formats **50-8**
- link changes **32-16**
- link failures **32-3**
- load balancing **23-4**
- load balancing (example) **48-5**
- logging facility **61-2**
- member combinations **52-9**
- misconfiguration error detection **23-11**
- redundancy **48-7**
- reserving ports for FICON **36-13**
- SPAN sources **60-3**
- verifying configurations **23-24**
- wizard **5-34**
- portFabricBindFailure tooltip **67-18**
- portGracefulShutdown tooltip **67-18**
- port groups
- assigning extended BB_credits **20-27**
- description **22-3**
- Generation 2 Fibre Channel switching modules **22-3**
- Generation 3 Fibre Channel switching modules **22-7**
- host-optimized performance **58-6**
- port indexes
 - description **22-24**
- port modes
 - auto **20-7**
 - description **20-3 to 20-7**
 - IPS **52-4, 53-1**
- port rate limiting
 - configuring **64-11**
 - default **64-12**
 - description **64-11**
 - hardware restrictions **64-11**
- port rate modes
 - configuring **22-33**
 - dedicated **22-6**
 - description **22-4**
 - oversubscribed **22-7**
 - shared **22-7**
 - See also rate modes
- ports
 - aggregation **17-1**
 - disabling using Device Manager **6-7**
 - enabling using Device Manager **6-7**
 - on-demand port activation licensing **11-1**
 - virtual E **48-2**
 - VSAN membership **26-7**
- Port Security
 - wizard **5-34**
- port security
 - activating **46-9**
 - activation **46-3**
 - activation rejection **46-10**
 - auto-learning **46-2**
 - CFS support **13-2**
 - cleaning up databases **46-23**

Send documentation comments to mdsfeedback-doc@cisco.com

- compatibility with DHCHAP **45-3**
- configuration guidelines **46-3**
- configuring CFS distribution **46-17 to 46-20**
- deactivating **46-9**
- default settings **46-23**
- deleting entries from database (procedure) **46-17**
- disabling **46-8**
- displaying settings (procedure) **46-12**
- displaying statistics (procedure) **46-12**
- enabling **46-8**
- enforcement mechanisms **46-2**
- fabric binding comparison **47-1**
- forcing activation **46-10**
- license requirement **46-2**
- manual configuration guidelines **46-4**
- preventing unauthorized accesses **46-1**
- unauthorized accesses prevented **46-1**
- WWN identification **46-16**
- port security auto-learning
 - description **46-2**
 - device authorization **46-14**
 - disabling **46-13**
 - distributing configuration **46-19**
 - enabling **46-13**
 - guidelines for configuring with CFS **46-3**
 - guidelines for configuring without CFS **46-4**
- port security databases
 - cleaning up **46-23**
 - copying **46-22**
 - copying active to config (procedure) **46-11**
 - deleting **46-22**
 - interactions **46-20**
 - manual configuration guidelines **46-4**
 - merge guidelines **46-20**
 - reactivating **46-11**
 - scenarios **46-21**
- port speeds
 - configuring **20-12**
- configuring on Generation 2 switching module interfaces **22-32**
- port swapping. See FICON port swapping
- port tracking
 - default settings **65-6**
 - description **65-1**
 - enabling **65-3**
 - guidelines **65-2**
 - monitoring ports in a VSAN **65-6**
 - multiple ports **65-5**
 - shutting down ports forcefully **65-6**
- portVsanMismatchIsolation tooltip **67-18**
- port world wide names. See pWWNs
- power cycling
 - modules **19-6**
- powering off
 - switching modules **19-8**
- power supplies
 - configuration guidelines **18-5 to 18-7**
 - configuring modes **18-4**
 - configuring power attributes **18-5**
 - default state **18-13**
 - displaying configuration **18-5**
- power usage
 - displaying **18-3**
- preferences
 - Confirm Deletion default **5-31**
 - default **5-30**
 - Device Manager **6-8**
 - Export Tables with Format default **5-31**
 - Fabric Manager Clients **5-30**
 - Show CFS Warnings default **5-31**
 - Show Device Name by default **5-30**
 - Show End Device Using default **5-30**
 - Show Shortened iSCSI Names default **5-30**
 - Show Timestamps as Date/Time default **5-30**
 - Show WorldWideName (WWN) Vendor default **5-30**
 - Telnet Path default **5-30**
 - Use Secure Shell instead of Telnet default **5-31**

Send documentation comments to mdsfeedback-doc@cisco.com

preshared keys
 RADIUS **41-8**
 TACACS+ **41-15**

principal switches
 assigning domain ID **25-10**

processes
 nondisruptive restarts **17-1**
 restartability **17-3**

product IDs
 displaying **18-1**

promiscuous mode
 configuring Gigabit Ethernet interfaces **52-6, 53-4**

protocol **50-1**

Protocol Analyzer
 description **66-2**
 troubleshooting tools **66-2**
 using for troubleshooting **66-3**

protocols
 analyzing **66-17**
 VRRP **50-8**

proxies
 registering for name servers **34-2**

proxy initiator
 configuring iSCSI
 configuring proxy initiator **50-21**

proxy initiator mode **50-14, 50-25**
 configuring **50-20**
 zoning **50-22**

proxy initiator mode iSCSI
 proxy initiator mode **50-20**

Public Key Infrastructure. See PKI

pWWNs
 configuring fcalias members **30-21**
 DPVM **28-1**
 rejecting duplicates **34-3**
 zone membership **30-2**

Q

QoS
 class maps **64-6**
 comparison with VSANs **64-5**
 control traffic support **64-3**
 creating class maps **64-7**
 data traffic support **64-4 to 64-10**
 default settings **64-12**
 description **64-1**
 DSCP value **48-28**
 DWRR queues **64-8**
 enabling control traffic **64-3**
 example data traffic configuration **64-10**
 logging facilities **61-2**
 port rate limiting **64-11**
 service policies **64-8**
 wizard **5-34**

QoS values
 configuring **50-32**

R

R_A_TOV
 default setting **66-25**
 modifying **66-15**
 AAA authentication **50-28, 50-43**
 AAA protocols **41-1**
 CFS merge guidelines **41-24**
 CFS support **13-2**
 clearing configuration distribution sessions **41-24**
 configuring an iSCSI RADIUS server iSCSI
 configuring Cisco ACS **41-26 to 41-30**
 configuring test idle timer **41-11**
 configuring test user name **41-11**
 default settings **41-31**
 description **41-7**
 discarding configuration distribution changes **41-23**
 enabling configuration distribution **41-22**

Send documentation comments to mdsfeedback-doc@cisco.com

FabricWare support **D-2**
 setting preshared keys **41-8**
 specifying server at user login **41-12**
 specifying time-out **41-9**
 starting a distribution session **41-22**
 rate limiting
 default settings **64-12**
 rate modes
 configuring on Generation 2 switching module interfaces **22-33**
 See also port rate modes
 rcfInProgres tooltip **67-18**
 RCFs
 description **25-3**
 incoming **25-6**
 rejecting incoming **25-7**
 read-only zones
 configuration guidelines **30-41**
 configuring **30-42**
 default settings **30-48**
 description **30-41**
 reason codes
 description **20-8**
 description (table) **C-1**
 receive buffer groups. See buffer groups
 receive data field sizes
 configuring **20-18**
 reconfigure fabric frames. See RCFs
 recovering passwords **39-20**
 recovery
 from powered-down state **22-25**
 passwords **7-45**
 Red Hat Linux
 Fabric Manager Server **3-1**
 redundancy
 Ethernet PortChannels **48-6, 48-7**
 Fibre Channel PortChannels **48-7**
 VRRP **48-6**
 VSANs **26-4**
 redundancy states
 value descriptions **17-4**
 redundant physical links
 example (figure) **32-3**
 Registered Link Incident Reports. See RLIRs
 Registered State Change Notifications. See RSCNs
 reloading
 switches **19-6**
 remote AAA server
 delayed authentication **4-2**
 Remote Capture Protocol. See RPCAP
 remote file systems
 accessing **B-2**
 remote SPAN
 configuring **B-2**
 Resource Allocation Time Out Value. See R_A_TOV
 Resource Manager Essentials. See RME
 resources
 management **2-17**
 retransmitting intervals
 configuring for FSPF **32-9**
 description **32-8**
 RLIRs
 description **36-27**
 displaying information (procedure) **36-27**
 RME
 support **1-6**
 RMON
 alarms **59-1**
 configuring using Threshold Manager **59-1**
 default settings **59-16**
 defining an event (procedure) **59-14**
 description **59-1**
 enabling alarms **59-2**
 enabling alarms (procedure) **59-9, 59-13**
 events **59-1**
 setting alarms (procedure) **59-3, 59-4, 59-6**
 viewing alarms (procedure) **59-15**
 viewing logs (procedure) **59-16**

Send documentation comments to mdsfeedback-doc@cisco.com

role-based management

controlling access **5-34**

roles

adding web services roles **7-54**

CFS support **13-2**

default permissions **41-3**

deleting (procedure) **39-3**

privileges **5-34**

removing web services roles **7-55**

user profiles **41-3**

round-trip response time

monitoring **9-3**

route costs

computing **32-6**

router discovery

routing

multicast **32-14**

See also broadcast routing

See also IP routing

RPCAP

Ethereal communication **66-18**

RRD

configuring database **7-60**

rsa1 key pairs

generating **39-16**

RSA key-pairs

deleting **43-16**

description **43-2**

exporting **43-5, 43-14**

generating **43-6**

importing **43-5, 43-14**

multiple **43-4**

rsa key pairs

generating **39-16**

RSCNs **50-16**

clearing statistics **34-7**

default settings **34-8**

description **34-5**

displaying information **34-5**

logging facility **61-2**

multiple port IDs **34-6**

RSCN timers

CFS support **13-2**

RSPAN

configuring **B-2**

running configuration files

saving to startup configuration file **16-8**

runtime checks

static routes **32-12**

S

SACKs

configuring in FCIP profiles **48-20**

SAN extension package licenses

description **10-5**

SAN extension tuner

configuring **49-2, B-2**

data patterns **49-3**

default settings **49-7**

description **49-1**

license requirements **49-3**

tuning guidelines **49-2**

SAN operating system. See Cisco MDS SAN-OS

SAs

establishing between IPsec peers **44-28**

lifetime negotiations **44-30**

refreshing **44-20**

setting lifetime **44-31**

scalability

VSANs **26-4**

schedulers. See command schedulers

SCP

support **2-16**

scripts

FMServer.sh **2-34**

SCSI

displaying LUN discovery results **35-3**

Send documentation comments to mdsfeedback-doc@cisco.com

- monitoring frame counts **9-3**
- monitoring I/Os per second **9-3**
- monitoring read throughput **9-3**
- monitoring traffic throughput **9-3**
- routing requests **50-2**
- traffic reports **66-3**
- SCSI flow configuration clients
 - description **55-3**
- SCSI flow data path support
 - description **55-3**
- SCSI flow managers
 - description **55-2**
- SCSI flow services
 - CFS support **13-2**
 - configuring **55-3 to ??, 55-3 to 55-6**
 - configuring (procedure) **55-4**
 - default settings **55-8**
 - description **55-1**
 - functional architecture (figure) **55-2**
 - SCSI flow configuration clients **55-3**
 - SCSI flow data path support **55-3**
 - SCSI flow managers **55-2**
- SCSI flow statistics
 - clearing (procedure) **55-8**
 - default settings **55-8**
 - description **55-6**
 - enabling **55-7**
- SCSI LUNs
 - customized discovery **35-2**
 - discovering targets **35-1**
 - displaying information **35-3**
 - starting discoveries **35-2**
- SCSI sessions
 - monitoring status **9-3**
- SCSI traffic
 - analysis **66-2**
 - analyzing at LUN level **66-2**
- SD port mode
 - description **20-6**
- interface modes **20-6**
- SD ports
 - bidirectional traffic **60-12**
 - characteristics **60-5**
 - Cisco Traffic Analyzer **9-4**
 - configuring **20-12**
 - configuring for SPAN monitoring **60-6**
 - monitoring bidirectional traffic **60-12**
- SDV
 - IVR limitations **27-9**
 - secondary MAC addresses
 - configuring **37-6**
 - Secure Hash Algorithm. See SHA-1
 - Secure Shell Protocol
 - See SSH
 - Secure Shell Protocol. See SSH
 - security
 - accounting **41-3**
 - managing on the switch **41-1**
 - security associations. See SAs
 - security control
 - local **41-2**
 - remote **41-2, 41-14**
 - remote AAA servers **41-7**
 - security parameter index. See SPI
 - selective acknowledgments. See SACKs
 - sensors
 - temperature monitoring **18-11**
 - serial console ports
 - accessing switches **2-12**
 - serial IDs
 - description **62-34**
 - serial numbers
 - displaying **18-1, 18-3**
 - server groups
 - configuring **41-20**
 - service policies
 - defining **64-8**
 - enforcement **64-8**

Send documentation comments to mdsfeedback-doc@cisco.com

- services
 - restarting **7-45**
 - starting **7-45**
 - stopping **7-45**
- services modules
 - description **19-3**
 - managing **19-1**
 - power cycling **19-6**
 - replacing **15-17**
 - resetting **19-5**
 - state descriptions **19-4**
 - verifying status **19-3**
- setup command
 - using **2-12**
- SFPs
 - displaying transmitter types **20-22**
 - not present reason codes **C-1**
 - transmitter types **20-21**
- SFTP
 - support **2-16**
- SHA-1
 - IKE **44-7**
 - IPsec **44-6**
- shared rate mode
 - description **22-7**
 - migrating from dedicated rate mode **22-29, 22-30**
 - migrating to dedicated rate mode **22-29, 22-30**
 - oversubscription **22-34**
- shell scripts
 - \$HOME/.cisco_mds9000/bin directory **67-4**
 - DeviceManager.sh **67-4**
 - FabricManager.sh **67-4**
 - for uninstalling Fabric Manager **2-44**
- shortcuts
 - not visible on desktops **67-4**
- site IDs
 - description **62-33**
- small computer system interface. See SCSI
- SMTP
- assigning contact names **62-7**
- server address **62-14**
- SNMP
 - access control **40-2**
 - access groups **40-3**
 - assigning contact **40-2**
 - assigning location **40-2**
 - configuring notification target users **40-11**
 - creating users **40-4**
 - default settings **40-12**
 - enabling access **2-7**
 - enabling SNMP notifications **40-9**
 - encryption-based privacy **40-4**
 - FICON control **36-22**
 - group-based access **40-3**
 - modifying users **40-4**
 - port used **2-41**
 - proxy services **2-14**
 - security features **41-2**
 - server contact name **62-5**
 - user synchronization with CLI **40-3**
 - versions supported **40-1**
 - See also SNMPv1; SNMPv2c; SNMPv3
- SNMP_TRAP
 - port used **2-41**
- SNMP community strings
 - configuring **2-10**
- SNMP manager
 - FCS **63-2**
- SNMP preferences
 - Enable Audible Alert when Event Received
default **5-31**
 - Retry request 1 time(s) after 5 sec timeout
default **5-31**
 - Trace SNMP packets in Log default **5-31**
- SNMPv1
 - community strings **40-2**
 - description **40-2**
 - FabricWare support **D-2**

Send documentation comments to mdsfeedback-doc@cisco.com

- support [2-16](#)
 - See also SNMP
- SNMPv2
 - community strings [40-2](#)
 - FabricWare support [D-2](#)
- SNMPv2c
 - configuring notifications [40-8](#)
 - description [40-2](#)
 - support [2-16](#)
 - See also SNMP
- SNMPv3
 - assigning multiple roles [40-6](#)
 - CLI user managementSNMPv3
 - sdescription [40-2](#)
 - enforcing message encryption [40-5](#)
 - restricting switch access [40-3](#)
 - security features [40-2](#)
 - specifying cisco-av-pair [41-13](#)
 - support [2-16](#)
 - See also SNMP [40-2](#)
- software configuration
 - overview [1-6 to 1-8](#)
- software images
 - default settings [15-17](#)
 - selecting for supervisor modules [15-2](#)
 - space requirements [15-4](#)
 - synchronizing [17-4](#)
 - upgrade prerequisites [15-3 to 15-5](#)
 - upgrading SAN-OS images [15-1](#)
 - variables [15-1](#)
- software installation
 - Software Installation Wizard [15-8](#)
- software upgrades
 - disruptive [15-5](#)
 - mechanisms [15-5](#)
 - nondisruptive [17-1](#)
 - Software Installation Wizard [15-8](#)
- soft zoning
 - description [30-26](#)
- See also zoning
- Solaris [2-34](#)
 - Fabric Manager Server [3-1](#)
 - installing Fabric Manager Web Services [7-4](#)
 - install scripts [2-34](#)
- source IDs
 - Call Home event format [62-34](#)
 - exchange based [23-5](#)
 - flow based [23-4](#)
 - in-order delivery [32-15](#)
 - path selection [26-11](#)
- SPAN
 - configuration guidelines [60-6](#)
 - configuring [60-6 to 60-10](#)
 - configuring Fibre Channel analyzers [60-11](#)
 - configuring on switch ports [9-4](#)
 - conversion behavior [60-9](#)
 - default settings [60-13](#)
 - description [60-1](#)
 - egress sources [60-2](#)
 - Fibre Channel analyzers [60-10](#)
 - filters [60-5](#)
 - monitoring traffic [9-1, 60-1](#)
 - SD ports [60-5](#)
 - sessions [60-5](#)
 - sources [60-4](#)
 - sources for monitoring [60-2](#)
 - VSAN sources [60-4](#)
 - SPAN destination port mode. See SD port mode
 - SPAN filters
 - description [60-5](#)
 - guidelines [60-5](#)
 - SPAN ports
 - viewing detailed traffic information [7-24](#)
 - SPAN sessions
 - deleting using Device Manager [60-9](#)
 - description [60-5](#)
 - VSAN filters [60-5](#)
 - SPAN sources

Send documentation comments to mdsfeedback-doc@cisco.com

- editing with Device Manager **60-8**
- egress **60-2**
- ingress **60-2**
- interface types **60-3**
- IPS ports **60-3**
- VSANs configuration guidelines **60-4**
- SPAN traffic
 - real-time analysis **66-2**
- SPAN tunnel port mode. See ST port mode
- special frames
 - enabling for FCIP **48-24**
- SPF
 - computational hold times **32-4**
- SPI
 - configuring virtual routers **51-12**
- srcPortNotBound tooltip **67-18**
- SSH
 - default service **39-18**
 - enabling **2-7, 2-10**
 - FabricWare support **D-2**
 - host key pair **39-16**
 - logins **41-4**
 - port used **2-41**
 - support **2-16**
- SSH key pair
 - overwriting **39-18**
- SSH sessions
 - message logging **61-3**
- SSI boot images
 - configuring **B-2**
- SSL certificates
 - using with Fabric Manager Web Services **7-5**
- SSMs
 - default settings **19-13**
 - disabling Intelligent Storage Services (procedure) **55-6**
 - enabling Intelligent Storage Services (procedure) **55-3**
 - Fibre Channel write acceleration **56-1 to 56-3**
- managing **19-13, B-2**
- provisioning Intelligent Storage Services (procedure) **55-3**
- replacing considerations **19-13**
- SCSI flow services **55-1 to 55-8**
- SCSI flow statistics **55-1 to 55-8**
- standby supervisor modules
 - boot alert **15-16**
 - boot variable version **15-15**
 - copying image to **B-2**
 - managing bootflash: **15-16**
 - monitoring **17-2**
 - synchronizing **17-4**
- startup configuration files
 - saving running configuration file **16-8**
 - unlocking **B-2**
- statically imported iSCSI targets **50-52**
- static iSLB initiator
 - converting **50-40**
- static mapped iSCSI target*i*SCSI
 - static mapped target **50-27**
- static mapping **50-39**
- static routes
 - configuring **2-6**
 - runtime checks **32-12**
- static WWN mapping **50-25**
- statistics
 - SCSI I/O **9-3**
 - supervisor modules **19-4**
- storage devices
 - access control **30-1**
 - performance statistics **8-1**
 - permanent **16-2**
 - temporary **16-2**
- Storage Services Enabler package licenses
 - description **10-7**
- storage traffic
 - viewing performance information **7-22**
- ST port mode

Send documentation comments to mdsfeedback-doc@cisco.com

- description [20-6](#)
- interface modes [20-6](#)
- limitations [20-6](#)
- ST ports
 - interface modes [20-6](#)
- subnet masks
 - configuring mgmt0 interfaces [20-29](#)
 - configuring switches [2-2](#)
 - default setting [19-13](#)
 - initial configuration [2-6, 2-10](#)
- subnets
 - requirements [52-6, 53-5](#)
- summary reports
 - description [7-1](#)
- Sun JRE
 - Fabric Manager support [2-19](#)
- Supervisor-1 modules
 - migrating from Supervisor-2 modules (note) [15-15](#)
 - selecting software images [15-2](#)
- Supervisor-2 modules
 - description [1-2](#)
 - Generation 1 chassis [15-16](#)
 - migrating from Supervisor-1 modules [15-15 to ??](#)
 - select software images [15-2](#)
 - USB ports [1-2](#)
- supervisor modules
 - active state [19-5](#)
 - capturing local traffic [66-18](#)
 - default settings [19-13](#)
 - description [1-2, 19-1](#)
 - high availability [17-1](#)
 - managing standby bootflash: [15-16](#)
 - manual switchovers [17-2](#)
 - migrating to Supervisor-2 modules [15-15 to ??](#)
 - redundancy [17-1](#)
 - replacing [15-15, 15-17](#)
 - replacing considerations [19-13](#)
 - resetting [19-5](#)
 - standby boot alert [15-16](#)
- standby state [17-4, 19-5](#)
- standby supervisor boot variable version [15-15](#)
- state descriptions [17-4, 19-4](#)
- statistics [19-4](#)
- switchover mechanisms [17-2](#)
- switchovers after failures [17-1](#)
- synchronizing [17-3](#)
- upgrading a dual supervisor switch [B-1](#)
- verifying status [19-3](#)
- viewing using Device Manager [6-7](#)
 - See also Supervisor 1 modules; Supervisor 2 modules
- suspendedByMode tooltip [67-18](#)
- suspendedBySpeed tooltip [67-18](#)
- suspendedByWWN tooltip [67-18](#)
- swFailure tooltip [67-18](#)
- Switched Port Analyzer. See SPAN
- switches
 - accessing [2-12](#)
 - comparing configurations [66-4](#)
 - displaying power usage [18-3](#)
 - displaying serial numbers [18-3](#)
 - initial setup [2-2](#)
 - internal states [17-4](#)
 - reloading [19-6](#)
 - starting [2-1](#)
 - starting up [B-1](#)
 - status of device health [66-3](#)
 - upgrading with dual supervisors [B-1](#)
 - viewing license information [7-31](#)
- switching modules
 - description [19-3](#)
 - managing [19-1](#)
 - power cycling [19-6](#)
 - powering off [19-8](#)
 - preserving configuration [19-8](#)
 - replacing [15-17](#)
 - resetting [19-5](#)
 - state descriptions [19-4](#)
 - verifying status [19-3](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- viewing using Device Manager **6-7**
 - switch management
 - architecture **2-16**
 - in-band **2-17, 51-5**
 - out-of-band **2-17**
 - switch names
 - assigning **12-1**
 - switchover mechanism
 - warm state **19-5**
 - switchovers
 - characteristics **17-2**
 - guidelines **17-3**
 - initiating manually **17-2**
 - supervisor modules **17-1**
 - VRRP **48-6**
 - switch port interfaces
 - configuring default **2-11**
 - switch ports
 - configuring attribute default values **20-21**
 - configuring trunk modes **2-11**
 - switch priorities
 - configuring **25-5**
 - default **25-5**
 - description **25-5**
 - switch security
 - default settings **39-24, 41-30**
 - sWWNs
 - configuring for fabric binding **47-3**
 - syslog
 - CFS support **13-2**
 - port used **2-41**
 - viewing information **7-11**
 - viewing registration information **7-48**
 - viewing with Events tab **7-9**
 - syslog servers
 - verifying using Fabric Manager Web Services **61-10**
 - system health
 - default settings **68-7**
 - initiating **B-3**
 - system images
 - description **15-2**
 - selecting for supervisor modules **15-2**
 - SYSTEM variable **15-1**
 - system messages
 - configuring log files **61-6**
 - configuring logging **61-3**
 - configuring logging servers **61-7**
 - default settings **61-11**
 - monitoring **61-1**
 - severity levels **61-3**
 - viewing **7-11**
 - viewing from Device Manager **61-11**
 - viewing from Fabric Manager Web Server **61-11**
 - viewing using Device Manager **57-4**
 - viewing using Fabric Manager Web Server **57-4**
 - viewing with Events tab **7-9**
 - system processes
 - displaying **68-1**
-
- T**
- tables
 - filtering **7-3**
 - navigating **7-3**
 - searching for information **7-3**
 - TACACS+
 - AAA authentication **50-43**
 - AAA protocols **41-1**
 - CFS merge guidelines **41-24**
 - CFS support **13-2**
 - clearing configuration distribution sessions **41-24**
 - configuring Cisco ACS **41-26 to 41-30**
 - default settings **41-31**
 - description **41-14**
 - discarding configuration distribution changes **41-23**
 - displaying server statistics **41-18**
 - enabling configuration distribution **41-22**
 - global keys **41-15**

Send documentation comments to mdsfeedback-doc@cisco.com

- setting default server encryption [41-15](#)
- setting default server timeout [41-15](#)
- setting preshared key [41-15](#)
- specifying server at login [41-18](#)
- starting a distribution session [41-22](#)
- validating [41-17](#)
- tape acceleration
 - FICON [36-33 to 36-37](#)
- target discovery [50-72](#)
- TCP connections
 - FCIP profiles [48-4](#)
 - specifying number [48-25](#)
- TCP parameters
 - configuring in FCIP profiles [48-19 to ??](#)
- TCP ports
 - IPv4-ACLs [42-3](#)
- TCP tuning parameters [50-32](#)
- Telnet
 - default service [39-15](#)
 - enabling [2-7, 2-10](#)
 - logins [41-4](#)
 - port used [2-41](#)
 - support [2-16](#)
- Telnet server connections
 - description [12-11](#)
 - disabling [12-11](#)
- Telnet sessions
 - message logging [61-3](#)
- temperatures
 - displaying [18-11](#)
 - major thresholds [18-11](#)
 - minor thresholds [18-11](#)
 - monitoring hardware [18-11](#)
- templates
 - creating for custom reports [7-37](#)
 - modifying custom report templates [7-41](#)
- TE port mode
 - classes of service [20-6](#)
 - description [20-6](#)
- TE ports
 - fabric binding checking [47-2](#)
 - FCS support [63-1, 63-2](#)
 - FSPF topologies [32-2](#)
 - interoperability [37-10](#)
 - recovering from link isolations [30-28](#)
 - SPAN sources [60-3](#)
 - trunking restrictions [24-3](#)
- terminals
 - configuring settings [B-1](#)
- TF port mode
 - classes of service [20-6](#)
 - description [20-6](#)
- TFTP
 - port used [2-41](#)
 - support [2-16](#)
- Threshold Manager
 - configuring RMON [59-1](#)
- thresholds
 - baselines for performance [8-2](#)
- time
 - configuring [12-3](#)
- time delays
 - setting [B-2](#)
- timeouts
 - configuring with Fabric Manager [66-15](#)
- time out values. See TOVs
- timers
 - configuring [66-15](#)
- timer values
 - modifying [66-14](#)
- timestamps
 - FICON host control [36-22](#)
- time zones
 - configuring [12-3](#)
- TL port mode
 - classes of service [20-5](#)
 - description [20-5](#)
- TL ports

Send documentation comments to mdsfeedback-doc@cisco.com

- ALPA caches **20-25**
- configuring **20-12, 20-24**
- description **20-23**
- FCS **63-1, 63-2**
- FCS support **63-1, 63-2**
- logging facility **61-2**
- SPAN sources **60-3**
- tools
 - software configuration **1-5**
- tooManyInvalidFLOGIs tooltip **67-18**
- topologies
 - clearing maps **67-21**
 - mapping **57-2**
- topology map
 - mapping multiple fabrics **57-3**
- topology maps
 - custom **57-2**
 - description **57-2**
 - enclosures **57-3**
 - saving custom layouts (procedure) **57-2**
- tovMismatch tooltip **67-18**
- TOVs
 - configuring across all VSANs **37-2**
 - configuring for a VSAN **37-3**
 - default settings **37-13, 66-25**
 - interoperability **37-9**
 - ranges **37-2, 66-14**
- traceroute
 - description **66-7**
 - troubleshooting connectivity **66-7**
- tracked ports
 - binding operationally **65-3**
- traffic
 - local captures **66-19**
 - managing using Cisco Traffic Analyzer **9-2**
 - monitoring using Cisco Traffic Analyzer **9-2**
 - remote captures **66-18, 66-19**
 - text-based captures **66-18**
 - viewing captured frames **66-20**
- Traffic Analyzer. See Cisco Traffic Analyzer
- traffic isolation
- VSANs **26-4**
- transform sets
 - description **44-25**
- transient failure **50-16**
- transit VSANs
 - configuration guidelines **29-10**
 - description **29-3, 29-16**
 - IVR configuration guidelines **29-14**
- translative loop port mode. See TL port mode
- transparent initiator mode **50-14**
- transparent initiator modeiSCSI
 - transparent initiator mode **50-20**
- traps
 - viewing registration information **7-48**
- Triple DES. See 3DEC encryption
- troubleshooting
 - analyzing switch health **66-3**
 - analyzing zone merges **66-8**
 - CTC **48-17**
 - Fabric Manager tools **5-35**
 - locating other switches **66-13**
 - monitoring oversubscription **66-14**
 - show tech command **66-9**
 - testing end-to-end connectivity **66-5**
 - tools **66-1**
 - using Fabric Configuration tool (procedure) **66-4**
 - using Ping Tool **66-7**
 - using traceroute (procedure) **66-7**
 - with Cisco Traffic Analyzer **66-2**
 - with Protocol Analyzer **66-3**
- troubleshooting reports
 - Cisco Traffic Analyzer **66-2**
- trunk-allowed VSAN lists
 - description **24-9 to 24-11**
- trunking
 - comparison with PortChannels **23-3**
 - configuration guidelines **24-4**

Send documentation comments to mdsfeedback-doc@cisco.com

- configuring modes **24-7**
 - configuring using Device Manager **6-7**
 - default settings **24-11**
 - description **24-1**
 - interoperability **37-9**
 - link state **24-7**
 - merging traffic **24-4**
 - restrictions **24-3**
 - trunking E port mode. See TE port mode
 - trunking F port mode. See TF port mode
 - trunking mode
 - FCIP interface **48-4**
 - trunking ports
 - associated with VSANs **26-8**
 - trunking protocol
 - default settings **24-11, 24-12**
 - default state **24-6**
 - description **24-6**
 - detecting port isolation **24-4**
 - disabling **24-7**
 - enabling **24-7**
 - trunk mode
 - configuring **24-7, 24-8**
 - default settings **24-11**
 - status **24-7**
 - trunkNotFullyActive tooltip **67-18**
 - trust points
 - creating **43-8**
 - description **43-2**
 - multiple **43-3**
 - saving configuration across reboots **43-14**
-
- U**
 - UDP ports
 - IPv4-ACLs **42-3**
 - UDP traffic
 - blocking **2-14**
 - unique area FC IDs
 - configuring **25-19**
 - description **25-19**
 - UNIX
 - install scripts **2-34**
 - launching Fabric Manager Web Services **7-7**
 - UNIX issues
 - parent menus disappear **67-12**
 - too many open files error **67-12**
 - web browser cannot find web server **67-12**
 - upgradeInProgress tooltip **67-18**
 - upgrades. See disruptive upgrades; nondisruptive upgrades; software upgrades
 - upgrading
 - switches **B-1**
 - user accounts
 - creating additional at setup **2-5**
 - User-based roles
 - FabricWare support **D-2**
 - user IDs
 - authentication **41-3**
 - user profiles
 - role information **41-3**
 - users
 - adding **7-53**
 - CFS support **13-2**
 - default **2-3**
 - deleting (procedure) **39-15**
 - removing **7-54**
 - SNMP support **40-4**

V

- vendor-specific attributes. See VSAs
- VE ports
 - description **48-2**
 - FCIP **48-2**
 - virtual E ports. See VE ports
 - virtual Fibre Channel host **50-3**
 - virtual ISLs

Send documentation comments to mdsfeedback-doc@cisco.com

- description [48-2](#)
- Virtual LANs. See VLANs
- virtual LANs. See VLANs
- virtual router IDs. See VR IDs
- Virtual Router Redundancy Protocol. See VRRP
- Virtual Router Redundancy Protocolprotocols
 - Virtual Router Redundancy [50-35](#)
- virtual routers
 - adding [51-10](#)
 - adding primary IP addresses [51-11](#)
 - authentication [51-12](#)
 - default settings [51-13](#)
 - deleting [51-10](#)
 - initiating [51-11](#)
 - setting priorities [51-11](#)
- virtual SANs. See VSANs
- Visio diagrams
 - saving maps as [5-27](#)
- VLANs
 - configuring on Gigabit Ethernet subinterfaces [53-5](#)
 - description [52-6, 53-4](#)
- volatile:
 - description [16-2](#)
- VR IDs
 - description [51-9](#)
 - mapping [51-9](#)
- VRRP [50-35](#)
 - algorithm for selecting Gigabit Ethernet interfaces [50-45 to ??](#)
 - backup switches [51-9](#)
 - configuring advertisement time intervals [51-11](#)
 - configuring for Gigabit Ethernet interfaces [52-9](#)
 - configuring for iSLB [50-45](#)
 - configuring virtual routers [51-10](#)
 - default settings [51-13](#)
 - description [51-9, 52-8](#)
 - group members [52-8](#)
 - initiating virtual routers [51-11](#)
 - IQN formats [50-8](#)
- iSCSI parameter change impact [50-45](#)
- iSLB [50-43 to ??](#)
- logging facility [61-2](#)
- master switches [51-9](#)
- MD5 authentication [51-12](#)
- primary IP address [51-11](#)
- priority preemption [51-11](#)
- security authentication [51-12](#)
- setting priorities [51-11](#)
- setting priority [51-11](#)
- simple text authentication [51-12](#)
- VRRP group [50-23](#)
- VRRP-I f iSCSI login redirect [50-37](#)
- VSAN IDs
 - allowed list [24-11](#)
 - description [26-5](#)
 - multiplexing traffic [20-6](#)
 - range [26-4](#)
 - VSAN membership [26-4](#)
- vsanInactive tooltip [67-18](#)
- VSAN interfaces
 - configuring [20-30](#)
 - creating [20-30](#)
 - description [20-30](#)
- VSAN membership
 - iSCSI hosts [50-22](#)
 - iSCSI hostsiSCSI
 - VSAN membership for hosts [50-22](#)
 - iSCSI interfaces [50-23](#)
- vsanMismatchIsolation tooltip [67-18](#)
- VSANs
 - advantages [26-3](#)
 - allowed-active [24-4](#)
 - allowed list [60-4](#)
 - broadcast addresses [32-14](#)
 - clocks [36-22](#)
 - comparison with QoS [64-5](#)
 - comparison with zones (table) [26-4](#)
 - compatibility with DHCHAP [45-3](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- configuring **26-6 to ??**
 - configuring allowed-active lists **24-11**
 - configuring FSPF **32-4**
 - configuring multiple IPv4 subnets **51-7**
 - configuring trunk-allowed lists **24-9 to 24-11**
 - default settings **26-12**
 - default VSANs **26-8**
 - deleting **26-9**
 - description **26-1 to 26-4**
 - domain ID automatic reconfiguration **25-8**
 - example membership for iSCSI devices **50-23**
 - fabric optimization for FICON **36-3**
 - FC IDs **26-1**
 - FCS **63-1**
 - FCS support **63-1**
 - features **26-1**
 - FICON-enabled **26-12**
 - flow statistics **8-6**
 - FSPF connectivity **32-2**
 - gateway switches **51-4**
 - interop mode **37-10**
 - IP routing **42-1**
 - IPv4 static routing **51-6**
 - iSLB **50-40**
 - iSLB initiators **50-40**
 - isolated **26-8**
 - load balancing **26-11**
 - load balancing attributes **26-5**
 - mismatches **20-10, C-2**
 - multiple zones **30-4**
 - names **26-5**
 - name server **34-2**
 - operational states **26-9**
 - overlaid routes **51-6**
 - port membership **26-7**
 - port tracking **65-6**
 - Rules and features **39-4**
 - SPAN filters **60-5**
 - SPAN source **60-4**
 - SPAN sources **60-4**
 - states **26-5**
 - suspending for FICON **36-19**
 - TE port mode **20-6**
 - TF port mode **20-6**
 - timer configuration **37-3**
 - traffic isolation **26-3**
 - traffic routing between **51-1**
 - transit **29-16**
 - trunk-allowed **24-4**
 - trunking ports **26-8**
 - VRRP **51-9**
 - wizard **5-34**
 - VSAN trunking. See trunking
 - VSAs
 - communicating attributes **41-13**
 - protocol options **41-13**
-
- W**
- window management
 - configuring in FCIP profiles **48-20**
 - Windows
 - Fabric Manager Server **3-1**
 - Fabric Manager support **2-19**
 - installing Fabric Manager Web Services **7-4**
 - Windows issues
 - blue screen **67-11**
 - Device Manager window content disappears **67-11**
 - Fabric Manager window content disappears **67-11**
 - icons disappear from desktop **67-11**
 - printing causes an application crash **67-11**
 - SCP/SFTP failures **67-12**
 - text fields are too small **67-11**
 - Windows XP hangs **67-11**
 - Windows workstations
 - modifying **2-14**
 - wizards
 - DPVM Wizard **5-34**

Send documentation comments to mdsfeedback-doc@cisco.com

FCIP Wizard **5-34**
 IP ACL Wizard **5-34**
 iSCSI Wizard **5-34**
 IVR Zone Wizard **5-34**
 License Install Wizard **5-34**
 NPV Wizard **5-34**
 PortChannel Wizard **5-34**
 Port Security Wizard **5-34**
 QoS Wizard **5-34**
 Quick Config Wizard **30-7**
 Software Install Wizard **5-35**
 VSAN Wizard **5-34**
 Zone Edit Tool Wizard **5-34**

world wide names. See WWNs
 WWNs
 configuring **37-5, 66-23**
 displaying configurations **66-24**
 displaying information **37-6**
 link initialization **37-6**
 port security **46-16**
 secondary MAC addresses **37-6**
 static binding **50-20**
 suspended connection **C-2**
 suspended connections **20-10**

zone configurations
 test for compatibility **66-8**
 zone databases
 migrating a non-MDS database **30-35**
 zone members
 adding to zones **30-14**
 converting to pWWN members **30-24**
 displaying information **30-20**
 zoneMergeFailureIsolation tooltip **67-18**
 zone policies
 configuring **2-11**
 zoneRemoteNoRespIsolation tooltip **67-18**
 zones
 access control **30-16**
 adding zone members **30-14**
 analyzing merges **66-8**
 assigning LUNs to storage subsystems **30-41**
 backing up (procedure) **30-30**
 changing from enhanced zones **30-44**
 cloning **30-35**
 compacting for downgrading **30-47**
 comparison with device aliases (table) **31-4**
 comparison with VSANs (table) **26-4**
 configuring **30-10 to 30-25**
 configuring aliases **30-21**
 configuring and activating for iSLB **50-41**
 configuring broadcasting **30-38**
 configuring fcaliases **30-21**
 default policies **30-2**
 default settings **30-48**
 differences with IVR zones (table) **29-22**
 displayed as bold **67-9**
 editing full zone databases **30-11**
 enforcing restrictions **30-26**
 exporting databases **30-28**
 features **30-1, 30-3**
 importing databases **30-28**
 iSLB **50-41, 50-42**
 IVR communication **29-22**

X

XML
 support **2-16**
 XRC
 FICON support **36-5**

Z

zone aliases
 conversion to device aliases **31-7**
 zone attribute groups
 cloning **30-35**

Send documentation comments to mdsfeedback-doc@cisco.com

- logging facility [61-3](#)
- LUN-based [30-40](#)
- membership using pWWNs [26-4](#)
- merge failures [20-10](#)
- read-only for IVR [29-31](#)
- renaming [30-34](#)
- restoring (procedure) [30-30](#)
- troubleshooting tools [5-35](#)
- viewing information [30-42](#)
- viewing inventory information [7-36](#)
- wizard [5-34](#)
- See also default zones
- See also enhanced zones
- See also hard zoning; soft zoning
- See also LUN zoning
- See also read-only zones
- See also zoning; zone sets
- zone server databases
 - clearing [30-36](#)
- zone sets
 - activating [30-17](#)
 - cloning [30-35](#)
 - configuring [30-15 to 30-21](#)
 - considerations [30-4](#)
 - copying [30-29](#)
 - creating [30-16](#)
 - default settings [30-48](#)
 - distributing configuration [30-26](#)
 - enabling distribution [30-26](#)
 - exporting [30-28](#)
 - exporting databases [30-28](#)
 - features [30-1](#)
 - importing [30-28](#)
 - importing databases [30-28](#)
 - one-time distribution [30-27](#)
 - recovering from link isolations [30-28](#)
 - renaming [30-34](#)
 - viewing information [30-42](#)
 - See also active zone sets
- See also active zone sets; full zone sets
- See also zones; zoning
- zone traffic priorities
 - description [30-36](#)
- zoning
 - configuring broadcasting [30-38](#)
 - description [30-1](#)
 - example [30-2](#)
 - FabricWare support [D-2](#)
 - implementation [30-3](#)
 - Quick Config Wizard [30-7 to 30-10](#)
 - See also LUN zoning
 - See also zones; zone sets
 - zoning based access control
 - configuring for iSCSI [50-25](#)
 - configuring for iSCSiSCSI
 - configuring zoning based access control [50-25](#)

Send documentation comments to mdsfeedback-doc@cisco.com