



# **Features and Benefits**

#### Design

Touch control with SteelTouch™ Buttons for Easier Operation of the Oven

### Performance

- 12 Specialized Cooking Modes Gourmet Cooking Made Easy
- Custom Cooking Modes: Pizza, Pie, Warm and Proof
- Genuine European Convection for Even Baking Results on Multiple Racks
- Temperature Conversion for Convection Cooking
- Meat Probe Takes Guesswork out of Cooking
- Fast Preheat Reduces Preheat Time

### Efficiency

EcoClean™ 2-Hour Self-Clean Cycle

## Convenience


- Two Oven Lights to Better Monitor Cooking Progress
- Timer with Cook Time and Delay Start Function
- Extra Large Door Window for Easy Monitoring of Cooking Process
- Star-K certified. 100°-450° F

# Capacity


- . Large Capactiy at 4.1 Cu Ft.
- Recessed 8 Pass Broil Element for Increased Capacity and Safety

Notes: All height, width and depth dimensions are shown in inches. \*Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.






measurements in inches (mm)




measurements in inches (mm)



\* For single ovens installed into a wall cabinet, the junction box may be located above or beneath the unit within reach of the power cord.

measurements in inches (mm)



**Features** 

Cooking method primary cavity	3rd element convection,
	Convection Bake,
	Convection Broil,
	Convection Roast,
	Conventional heat,
	Dough proving setting,
	Half width variable grill,
	Pizza setting, Sabbath
	function, Top heating, 1/3
	bottom heat., warming
Cleaning system - primary cavity	Self Clean
Interior Lights - primary cavity	2
Pull-out system	
Timer settings	Alarm, Off, On, timer
Included accessories	3 x Oven racks /
	upper, 1 x Temperature
	probe /upper
Bake Element Wattages primary cavity (W)	2400
Broil Element Wattages primary cavity (W)	3800
Convection Element Wattages primary cavity	2000
(W)	
Microwave Wattages (W)	
Drawer wattage (W)	

**Technical Specification** 

reciffical opecification	
UPC code	825225907053
Product color	Stainless steel
Alternative colors available	
Energy source	Electric
Watts (W)	5000
Current (A)	30
Volts (V)	240/208
Frequency (Hz)	60
Approval certificates	CSA
Power Cord Length	50"
Plug type	fixed connection, no plug
Required cutout size (HxWxD) (in)	27" - 28 5/8" x
	25 1/2" x 23 1/2"
Product packaging dimensions (HxWxD) (in)	31 1/4" x 34" x 31 1/2"
Net weight (lbs)	174
Gross weight (lbs)	193

Notes: All height, width and depth dimensions are shown in inches. \*Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.

For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.

Copyright ©2014 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.