



•

•



We, young people from Poland creates Savio Brand.
We have a positive attitude towards the world, and we are geeks when it comes to new technologies.

We made a brand, to introduce products on a market, that we need on a daily basis for our work, entertainment and to develop our passions.

The products are modern, reliable and in a reasonable price.

Thanks to Your acknowledgement, we quickly domesticated on shelves of the biggest commercial networks, wholesales and hundreds of internet stores.

Thank You for your trust!







- 4 MULTIMEDIA PLAYERS
- 7 WIRELESS KEYBOARDS
- 8 REMOTE CONTROLLERS
- 10 VIDEO CABLES
- 14 SWITCHES AND SPLITTERS
- 15 ADAPTERS AND CONNECTORS
- **18 USB CABLES**
- **20 COMPUTER ACCESSORIES**
- 23 WIRELESS COMMUNICATION
- **24 NETWORK CABLES**
- **25 POWER SUPPLY**
- 27 AUDIO CABLES AND ACCESSORIES
- 29 BLUETOOTH SPEAKERS
- **30 BLUETOOTH EARPHONES**
- 32 POWER BANKS
- 34 CAR ACCESSORIES
- **35 PARKING SENSORS**
- **36 DETECTORS**
- 37 PHOTO PAPER
- 38 OTHERS
- 39 SAVIO GAMING
- **46 TYPES OF PACKAGING**
- **48** SAVIO VALUES



MULTIMEDIA PLAYERS



Smart TV Box Basic One

Model: TB-B01 ROM: 8GB RAM: 1GB

Smart TV Box Premium One

Model: TB-P01 ROM: 16GB RAM: 2GB

- Operating system: Android 7.1 Nougat
- OPU: Amlogic S905W Quad- Core ARM Cortex-A53 CPU, 4x1.2 GHz
- ◆ Resolution: 4K Ultra HD Max. 3840 x 2160
- Supports: KODI, TVN Player, TVP Player, HBO GO, IPLA, NC+, Netflix, Facebook, Skype, YouTube, Showbox and many more applications available for free at Google Play Store.
- Power: DC 5V/2A

Product features:

- Supported audio files format: MP3/WMA/AAC/WAV/OGG/AC3/DDP/TrueHD/DTS/DTS/HD/FLAC/APE, DOLBY TrueHD i DTS HD
- Supported video files format: AVI/RM/RMVB/TS/VOB/MKV/MOV/ISO/WMV/ASF/FLV/DAT/MPG/MPEG in resolution SD/HD/4K2K Ultra HD
- Supported picture format: JPEG/BMP/GIF/PNG/TIFF
- Supported video compression format: HD MPEG1/2/4, H.264/H.265, HD AVC HP, MVC, RM/RMVB, Xvid/DivX3/4/5/6, RealVideo8/9/10, HEVC MP-10
- USB ports: 2 high-speed USB 2.0, support U DISK and USB HDD
- Memory Card Reader: Micro SD
- Support of the external drives: Fat16/Fat32/NTFS
- Supports the subtitles: SRT/SMI/SUB/SSA/IDX+USB
- ▼ Video Output: SD/HD/2K/4K Ultra HD
- 👽 The menu in languages: Polish, English, German, Spanish, Portugal, Greek, Latvian, Lithuanian, Russian, Ukrainian, Czech, Slovak and many more
- ◆ LAN: Ethernet: 10/100M, standard RJ-45
- Pointing device: Computer mice support, keyboard through USB port, pointing wireless devices (USB dongle 2,4 GHz)
- HDMI standard: HDMI 2.0 (support for CEC I HDPC), 4K x 2K at 30 fps
- AV: Yes
- IR Connector: (possibility of attaching the "eye" to the remote controllers)

The content of package:

- ◆ Android TV Box
- ◆ HDMI Cable
- Remote controller
- User Manual

Savio TV Box

The multifunctional device, thanks to which every TV can become something more than a regular Smart TV



Android 7.1



CPU: Amlogic S905W Quad-Core ARM Cortex-A53 CPU, 4x1.2 GHz



GPU: Penta-Core Mali-450, 750 Mhz(DVFS)



Resolution: 4K Ultra HD - Max. 3840 x 2160



Wi-Fi: IEEE 802.11 b/g/n, 2.4G WiFi





Build in Wi-Fi module

Micro SD card slot

2 USB ports

IR receiver output

www.savio.net.pl



MULTIMEDIA PLAYERS

Smart TV Box Gold

Model: TB-G01 ROM: 16GB RAM: 2GB

- Operating system: Android 8.1 Oreo
 CPU: Amlogic S905X2 Quad-Core-A53 CPU, 4x1,8 GHz
- GPU: Mali G31
- Rom: 16GB eMMC
- Ram: 2GB DDR4
- ❷ Bluetooth Version: 4.1
- ◆ Resolution 4K Ultra HD max. 3840 x 2160
- Supports: KODI, TVN Player, TVP Player, HBO GO, IPLA, NC+, Netflix, Facebook, Skype, YouTube, Showbox and many more applications available for free at Google Play Store.
- Power: DC 5V/2A

Product features:

- 👽 Video Compression format: VP9, H.265, H.264, MPEG-4, WMV/VC-1, AVS-P16, MPEG-2, MPEG-1, RealVideo 8/9/10, WebM
- ◆ USB ports: 1x USB 3.0, 1x USB 2.0
- Memory Card Reader: Micro SD
- Support of the external drives: Fat16/Fat32/NTFS
- Supports the subtitles:TXT/SRT/SMI/SUB/SSA/IDX
- ▼ Video Output: SD/HD/2K/4K Ultra HD
- SPDIF output: output used to send digital sound
- The menu in languages: Polish, English, German, Spanish, Portugal, Greek, Latvian, Lithuanian, Russian, Ukrainian, Czech, Slovak and many more
- ◆ Lan: 1000Mbps, standard RJ45
- Pointing devices: Computer mice support, keyboards, gamepads through the USB port, wireless pointing devices support (receiver USB2.4 GHz), Bluetooth support
- ◆ HDMI Standard: HDMÍ 2.1 (support for CEC and HDCP), 4Kx2K@60fps
- AV: YES

The content of Package:

- Android TV BOX
- AC adapter 5V
- HDMI cable
- Remote controller
- User Manual





Wireless keyboard

Model: KW-01

Backlit wireless keyboard

Model: KW-02

Backlit wireless keyboard RGB

Model: KW-03

Wireless KW-01 keyboard is a compact, multifunctional device. It combines features of a full-size QWERTY keyboard and a touchpad. Thanks to keyboard KW-01 You can surf websites and use the installed apps quickly and comfortably.

Product specification:

- zasięg działania: do 10 metrów
- opojemność baterii: 300 mAh
- o pobór prądu: 8-15 mA, poniżej 15mA w uśpieniu
- moc nadawania: +5dBm Max
- napięcie podczas pracy: 3,7V
- wymiary: 147*85*16 mm

The device works with systems:

- Windows 2000, XP, Vista, 7, 8, 10
- Linux
- Android



The device is compatible with:

- Android TV BOX
- smart TV/android TV
- PC
- Laptop
- Raspberry Pi
- smartphone/tablet with OTG function (connected by the USB OTG cable)

The content of the package:

- Wireless keyboard
- USB receiver
- Ocable USB (M) Micro USB (M)
- Li-ion battery
- User manual



Universal 8in1 remote controller

Model: RC-01

- Supports up to 8 devices like TV, DVB-T, DVD, SAT, AUDIO, VCR, HOME CINEMA, AMP, PROJECTOR
- Learning function from an original remote
- MACRO function a sequence of any activities under one button
- The function of volume breakthrough controlling the TV volume without switching a device
- Controlling chosen functions of different devices without the need for switching a device
- Backlit button of device choice

Universal 7in1 remote controller

Model: RC-02

- Replaces original remote controller, which is damaged or lost
- Matches most of the brands on the market
- Simultaneously supports up to 7 devices like: TV, DVD, SAT, VCR, AUX, CABLE, DVB-T

d D,

Universal TV remote controller Easy

Model: RC-04

- Supports TV's: LED, Smart TV, 3D, LCD, Plasma
- Remote Controller has big clear buttons, which makes it very easy to use
- Simple construction and choice of buttons with most commonly used functions enables an intuitive operating of a TV
- ◆ After pulling of the batteries it "remembers" entered code
- Enables multiple programming
- This Remote controller is perfect for elder users (it is not possible to alter the adjustment of a TV).



Universal TV remote controller Kids

Model: RC-04

- Supports TV's: LED, Smart TV, 3D, LCD, Plasma
- Remote has big clear buttons, which makes it very easy to use
- Simple construction and choice of buttons with most commonly used functions enables an intuitive operating of a TV.
- ◆ After pulling of the batteries it "remembers" entered code
- Enables multiple programming
- This Remote controller is perfect for the youngest users (it is not possible to alter the adjustment of a TV)



Air condition remote controller

Model: K-1028

- Universal remote controller for air condition devices of most common brands
- Equipped with big, clear LED screen, which enables the precise setting of the air conditioner
- Additional function backlit screen and makes it easier to use it when it is dark
- Supports brands: Samsung, Toshiba, Hitachi, Fujitsu, Electrolux, Olympus and many more

Organiser/Stand for the remote controllers

Model: RCA-010

- Space for 4 Remotes
- Dimensions: Height: 20,5 cm Width: 11 cm Length: 21 cm



REMOTE CONTROLLERS

Replacement remote controllers

- Successfully replaces the original remote controller
- Maps functions of the original remote controller
- Oboes not need any programming, it is enough to just put the batteries inside and remote controller is ready to use

LG TV Remote controller

Model: RC-05

Compatible among other with:

32LA66**	32LN577*	39LN577*	42LA74**	42LN578*	7LA74**	47LN578*	0LN575*	55LA69**	55LN577*	60LN577*
32LN61**	32LN578*	39LN578*	42LN570*	42LN61**	47LN570*	47LN61**	50LN577*	55LA74**	55LN578*	60LN578*
32LN570*	39LN570*	42LA66**	42LN575*	47LA66**	47LN575*	50LA66**	50LN578*	55LN570*	60LA74**	
32LN575*	39LN575*	42LA69**	42LN577*	47LA69**4	47LN577*	50LN570*5	55LA66**	55LN575*	60LN570*	

...and many others * Replaces any number or letter

PANASONIC TV Remote controller

Model: RC-06

Compatible amo	ong other with:							
EUR050406,	EUR501380,	EUR511022,	EUR511226,	EUR51913,	EUR51971,	EUR644666,	EUR762830,	EUR7726020,
EUR501101,	EUR501390,	EUR511023,	EUR511228,	EUR51914,	EUR51973,	EUR645406,	EUR7635040,	EUR7737250,
EUR501120,	EUR50700,	EUR511026,	EUR511251,	EUR51915,	EUR51974,	EUR646920,	EUR7635050,	HT511273,
EUR501121A,	EUR50701,	EUR511029,	EUR511254,	EUR51916,	EUR51975,	EUR646921,	EUR7636070R,	TELORMD1170
EUR501301,	EUR50702,	EUR511030,	EUR511257,	EUR51918,	EUR51976,	EUR646922,	EUR7651030A,	
EUR501302,	EUR50703,	EUR511032,	EUR511267,	EUR51921,	EUR51977,	EUR646925,	EUR7651110,	
EUR501310,	EUR50705,	EUR511032Z,	EUR511268AR,	EUR51923,	EUR641550,	EUR646930,	EUR76511120,	
EUR501320,	EUR50707,	EUR5110352,	EUR511300,	EUR51930,	EUR641951,	EUR646932,	EUR76511150,	
EUR501331,	EUR50708,	EUR511200,	EUR51851,	EUR51931,	EUR641952,	EUR648053,	EUR7717010,	
EUR501337,	EUR50710,	EUR511212A,	EUR51902,	EUR51932,	EUR641952M,	EUR648080,	EUR7717020,	
FI IR501371	FLIR50711	FI IR511218	FI IR51906	FLIR51940	FLIR644660	FLIR648081	FI IR7717030	

EUR51912,

...and many others

EUR501377.

SAMSUNG TV Remote controller

EUR511220,

EUR511000A,

Model: RC-07

Compatible among other with: HG22EA470UW, HG28EB670BW, HG32AA690NW, HG32EA670SK, HG39EB670FW, HG40AB690QJ, HG46AA690NR, HG46EA670SK HG26AA470PR. HG28EB675BB. HG32AB460GW. HG32EA670SW. HG39EB675FB. HG40AB6900W. HG46AA690NW. HG46EA670SW. HG26AA470PW, HG28EB690BB, HG32AB670BJ, HG32EA790MS, HG40AA570LR, HG40EA570LW, HG46AA790MJ, HG26AA475RW, HG32AA470PR, HG32AB670BW, HG32EB460GW, HG40AA570LW, HG40EA590LS, HG46AB670FJ, HG26EA470PW, HG32AA470PW, HG32AB6900W HG32EB670BW, HG40AA690NR, HG40EA670SK, HG46AB670FW HG26EA475RW, HG32AA473PW. HG32EA470PW, HG32EB675FB. HG40AA690NW, HG40EA670SW, HG46AB6900J. HG26FA476RS HG32AA475RW. HG32FA475RW HG32EB6900B. HG40AA790MJ. HG40FA790MS HG46AB6900W HG28AB670BW, HG32AA570LW, HG32EA476RS, HG39AB460HW, HG40AB670FJ, HG40EB690QB, HG46AB890XW HG28EB460BW, HG32AA690NR, HG32EA590LS. HG39EB460HW HG40AB670FW, HG42EB675FB, HG46EA590LS

EUR51970,

EUR644661.

EUR648083.

...and many others

SONY TV Remote controller

Model: RC-08

Compatible among other with KDL-22EX550, KDL-32EX650, KDL-32W656A, KDL-40EX655, KDL-42W807A, KDL-42W656A, KDL-47W807A, KDL-55W905A KDL-46EX655. KDL-26EX550, KDI -32FX655 KDL-40EX650, KDL-40W905A, KDL-42W654A, KDL-46EX650, KDL-46W905A, KDI -50W656A KDL-26EX555, KDL-32W655A, KDL-40EX653, KDL-42W805A, KDL-42W655A, KDL-46EX653, KDL-47W805A, KDL-50W685A and many others.

SAMSUNG Smart TV Remote controller

Model: RC-09

Compatible among other with: UF40H6240A UA32H5500AWXXY. UF40H5303AKXRU. UE40H4203AKXUA, UF105S9WATXUA. UF40H6270SS. UA105S9WAWXXY UF40H5500AKXRU UE32H6350AKXUA UF48H6270SS UE46H6203AW. UE40H5203AKXUA. UF50H5500AW UA40H6300AWXXY UA55H6800AWXXY UF40H5303AKXRU UF48H5500AKXUA UF48H6350AKXUA UA32H5500AWXXY UF32H5500AKXUA UF48H5203AKXUA. UF50H6200AW. LIA55H6300AWXXY LIE40H5500AKXRII LIA60H6300AWXXY UE32H5500AKXRU, UF32H4500AKXUA. UF55H6270SS. UA48H6300AWXXY UF32H6200AKXUA UE58H5203AW. UA32H6300AWXXY. UA32FH4003RPXD. UF32H6350AKXRU. UF32H5303AKXUA. UF46H6203AKXUA. UF58.J5200AW UA40H5500AWXXY UF48H6350AKXRU UF32H5500AKXRU UF46H5303AKXUA UF40H5500AKXUA UE40H6350AKXRU, UF55HU7100S UA48H5500AWXXY. UE40H6350AKXUA. UE55H6203AKXUA. UE40H6203AKXUA. and many others

PHILIPS TV Remote controller

32PFL3507H/12,

Model: RC-10

32PFL3208H/12.

...and many others

32PFL3517H/12, 46PFL8007T/12, 32PFL3208T/12. 32PFL3517H/12. 40PFL5507H/12. 42PFL6007T/60. 32PFL3307H/60, 46PFL7007H/12 47PFL6007H/12, 32PFI 3517H/60. 32PFI 3517T/60. 40PFL5507K/12. 32PFL 3507H/60. 32PFI 3088H/60. 32PFI 4508H/12. 42PFI 6007T/12. 46PFI 7007T/12. 47PFI 6007K/12. and many others

32PFL4258H/12.

LG Smart TV Remote controller

Compatible among other with:

Model: RC-1

 Compatible among other with: 6710900010A/E/F, 6710T00079F, 6710300010G/J/S, 6710T00022D/F/S, 6710T0008B/C/G, 6710V00091A/G/Z, 6710T00017M/Q/V, 6710V00126L/Q, 6710T00017B/H. 6710V00126R/M.

6710V00138N/T/F, 6710V00138L/M, 6710V00141A/, 6710V00151S AKB14972914204, AKB33871407. AKB33871409, AKB33871410, AKB69680403, AKB69680404, AKB69680416, AKB72914009,

39PFL3088H/12,

AKB72914020, AKB72915207, AKB72915210, AKB72915211, AKB72976005, MKJ30036801.

42PFL6007K/12,

MKJ32022805, MKJ32022814, MKJ32022826, MKJ32022835, MKJ32022838, MKJ33981404,

46PFL8007H/12,

MKJ33981406, MKJ33981410, MKJ33981413, MKJ33981422





EUR7717040R,









HDMI v2.0 High Speed

- Ethernet up to 100 Mb/sec.
- 3D image support, Deep Color and HDR
- Audio Return Channel
- Dolby TrueHD and DTS-HD Master Audio multi-channel audio support
- Supports high resolutions up to 4K x 2K max 4096x2160p60 Hz and 1080p@240 Hz
- Maximum signal bandwidth: 600MHz
- ●Maximum biť rate TMDS: 18.00Gbit /s
- Maximum video bit rate:14.40Gbit /s
- HDR
- Dual View & 4 audio streams
- Gold plated plugs 24k
- Full shielding of signal wires resistant to external interference
- OFC oxygen-free conductors with a high degree of purity (99.96%)
- No loss in the transmission of high image and sound quality
- Range of operation: Audio-video transfer
- Compatible with previous versions 1.0-1.4
- Example use: Transfer of the video and sound from a computer, console, laptop, tuner, DVBT to the TV.

HDMI Cable v2.0, 1,5m

Model: CL-95 HDMI A male 30 AWG OD: 6.0mm

HDMI Cable v2.0, 3m

Model: CL-96 HDMI A male 30 AWG OD: 6.0mm

HDMI Cable v2.0, 5m

Model: CL-113 HDMI A male 30 AWG OD: 6.0mm

HDMI Cable v2.0, 7,5m

Model: CL-140 HDMI A male 30 AWG OD: 6.0mm

HDMI Cable v2.0, 10m

Model: CL-141 HDMI A male 30 AWG OD:6.0mm



HDMI Cable v2.0, angular, 1,5m

Model: CL-108 HDMI A male 30 AWG OD: 6.0mm KĄTOWY

HDMI Cable v2.0, angular, 3m

Model: CL-109 HDMI A male 30 AWG OD:6.0mm KĄTOWY



HDMI v1.4 High Speed

- Supports Ethernet up to 100 Mb / sec.
- Supports 3D and Deep Color
- Supports Audio Return Channel,
- Supports Dolby TrueHD multi-channel audio and DTS-HD
- Master Audio
- Supports high resolutions up to 4K x 2K max 4096x2160p30 Hz and 1080p@144 Hz
- 24k gold-plated connectors
- Full shielding of signal wires resistant to external interference
- No losses in the transmission of high image and sound
- Range of operation: Audio-video transfer
- Example use:

Transfer of the video and sound from a computer, console, laptop, tuner, DVBT to the computer monitor or TV.

HDMI Cable nylon braid black, 1,5m

Model: CL-02 HDMI A male 30 AWG OD: 5.8mm BLACK NYLON

HDMI Cable nylon braid white, 1,5m

Model: CL-119 HDMI A male 30 AWG OD: 5.8mm

HDMI Cable nylon braid red, 1,5m

Model: CL-120 HDMI A male 30 AWG OD: 5.8mm RED NYLON

HDMI Cable nylon braid black, 2m

Model: CL-48 HDMI A male 30 AWG OD: 5.8mm

HDMI Cable nylon braid black, 3m

Model: CL-07 HDMI A male 30 AWG OD:5.8mm

HDMI Cable nylon braid black, 5m


Model: CL-49 HDMI A male 30 AWG OD:5.8mm






VIDEO CABLES





BEST VIDEO AND SOUND QUALITY



HDMI - VGA Cable/Adapter 1,8m

Connectors: HDMI 19-pin, male VGA 15-pin, male

- Gold plated connectors
- Supported resolution: HDTV: 480i, 576i, 480p, 576p, 1080i, 1080p(60 Hz)
- Does not need a power supply
- ▼The range of operation: video transfer
- ◆ Direction: HDMI->VGA
- Example use:

A connection of a monitor or a projector with VGA connector to any source equipped with HDMI output.

HDMI - VGA Cable/Adapter + Audio 1,8m

- Ocnnectors:
 - HDMI 19-pin, male VGA 15-pin, male
- Gold plated connectors
- Supported resolution: HDTV: 480i, 576i, 480p, 576p, 1080i, 1080p(60 Hz)
- Does not need a power supply
- ▼ The range of operation: audio-video transfer

Example use:

A connection of a monitor or a projector with VGA connector to any source equipped with HDMI output.

mini DisplayPort Cable - HDMI 1,8m

mini DisplayPort Cable - HDMI 3m

Model: CL-84

- Connectors: HDMI A, male Mini DisplayPort, male
- **⊘**30AWG, OD:5.0mm
- Gold plated connectors
- The range of operation: audio-video transfer
- ODirection: mini DP-> HDMI
- Sample application:

Connecting the notebook or a computer to a TV or a monitor.

Kabel DisplayPort - HDMI 1,5m

Model: CL-56

- Ocnnectors: DisplayPort, male HDMI, male
- Gold plated connectors
- ◆ Direction: DisplayPort-> HDMI
- Maximum resolution: 1080p
- Example use:

Connecting a computer to a monitor or a home cinema.



DisplayPort Cable v1.2, 1m

DisplayPort Cable v1.2, 2m

DisplayPort Cable v1.2, 3m

Model: CL-137

- **⊘** Connectors:
- DisplayPort v1.2, male
- Gold plated connectors
- The range of operation: audio-video transfer
- Works both ways
- Example use:

Connecting a computer to a monitor or a home cinema.

DisplayPort v1.1 Cable 1,8m

DisplayPort v1.1 Cable 3m

Model: CL-86

- Ocnnectors:
 - DisplayPort v1.1, male
- Gold plated connectors
- The range of operation: audio-video transfer
- Works both ways
- Example use:

Connecting a computer to a monitor or a home cinema.



DisplayPort - DVI Cable 1,8m

Display Port - DVI Cable 3m

Connectors:

- DisplayPort, male DVI-D, male
- Gold plated connectors
- Supported resolutions:
 - 1920x1200, 1920x1080, 1440x900, 1280x720 HDTV I VGA
- The range of operation: Audio-video transfer
- Ø Direction: DisplayPort → DVI
- Example use:

Connecting a computer equipped with a graphics card to a DisplayPort connector monitor.



DVI cable 1,8m

Model: CL-31

DVI cable 3m

Model: CL-53

- Connectors: DVI-D 24+1, male
- 30 AWG, OD:7.0mm
- Gold plated connectors
- 2 ferrites
- ♦ The range of operation: video transfer
- Works both ways
- Example use:

Video transfer from a computer to a monitor or a TV.



VIDEO CABLES

VGA Cable

- ◆Connectors: VGA, male
- ●30AWG, OD: 5,5mm
- Shielded + 2 ferrites
- The range of operation: video transfer
- Works both ways
- Sample Application: Video transfer from a computer, console, laptop, tuner to a monitor or a TV.

VGA Cable 1,8m

Model: CL-29

VGA Cable 3m

Model: CL-30

VGA Cable 5m

Model: CL-50

VGA Cable 10m

Model: CL-51

VGA Cable 15m

Model: CL-52



HDMI-DVI-D Cable 1,5m

Model: CL-10

HDMI-DVI-D Cable 1,8m

Model: CL-139

- ◆ Connectors: DVI-D 24+1, male 30 AWG, OD:7.0mm
- Gold plated connectors
- 2 ferrites
- ◆The range of operation: video transfer
- Works both ways
- Example use: Video transfer from a computer to a monitor or a TV.

DisplayPort - VGA Cable 1,8m

Model: CL-92

- ◆ Connectors: Display port, male VGA, male
- **⊘**30AWG, OD:5.5mm
- ✓ Maximum resolution: 1080p
- ◆ The range of operation: audio-video transfer
- ◆ Direction: DisplayPort->HDMI
- Example use: Connecting a computer to a monitor or a projector.



SCART audio/video Cable - 3xRCA

Model: CL-133

- ◆ Connectors: SCART, 21pin, male (Euro) 3xRCA, male (Cinch)
- ◆ Two ways cable with signal direction switch



Connecting DVD player or others RTV devices to a TV.



Model: CL-134

- ◆ Connectors: SCART, 21 pins, male (Euro)
- Shielded
- Works both ways
- Example use: Connecting the DVBT decoder, DVD player to a TV.







SWITCHES AND SPLITTERS

3 inputs HDMI switch

Model: CL-26

Ocnnectors:
Inputs: 3xHDMI
Outputs: 1xHDMI

- Has two modes of operation:
 - 1. Intelligent automatic
 - 2. Manual with a button on a device
- Supported resolution: FULL HD TV do 1080p, graphics up to 1440p, picture from a computer up to 1920x1200
- Ocmpensating losses in a cable through digital signal amplification
- Support of 12-bit Deep Colour
- High performance: up to 2.5Gps
- Active input LED indicator diode
- Does not need an additional power
- Example use:

It enables to connect 3 devices i.e. DVBT decoder, computer, DVD, console PS3/Xbox, etc. to one receiver, i.e. TV or a monitor. After applying an additional power supply it also works as a signal amplifier (recommended for long cables – more than 10m).

Full HD HDMI Splitter 2 outputs

Model: CL-42


- ◆ Connectors: Inputs: 1xHDMI Outputs: 2xHDMI
- Ø HDMİ Version − 1.4b
- Supports: Full HD, 3D, Ethernet
- Supports resolution: 1920x1080/60Hz
- Supports: Deep Color 30bit, 36bit
- Support for Blu-Ray 24/50/60fs/HD-DVDc/xvYCC
- Supports audio formats: DTS-HD/Dolby-TrueHD/LPCM7.1/DTS/Dolby-AC3/DSD/HD (HBR)
- Supports retiming signal
- Indicator diode
- OC5V power supply / 1A adapter
- Example use:

Enables to split the signal from one HDMI source to two monitors or projectors simultaneously.

HDMI Switch 3 inputs + remote controller

Model: CL-28

◆ Connectors: Inputs: 3 x HDMI Outputs: 1 x HDMI



- 1. Intelligent automatic
- 2. Manual with a button on a device
- 3. Remote by a remote controller
- Supported resolution: FULL HD TV do 1080p, graphics up to 1440p, picture from a computer up to 1920x1200
- Ocmpensating losses in a cable through digital signal amplification
- Support of 12-bit Deep Colour
- ✓ High performance: up to 2.5Gps
- ✓ Active input LED diode indication
- Opes not need an additional power
- Remote controller and an infrared receiver in the package
- Example use:

It enables to connect 3 devices i.e. DVBT decoder, computer, DVD, console PS3/Xbox, etc. to one receiver, i.e. TV or a monitor. After applying an additional power supply it also works as a signal amplifier (recommended for long cables – more than 10m).

HDMI 4k Splitter 2 outputs

Model: CL-93

- ◆ Connectors: Inputs: 1xHDMI Outputs: 2xHDMI
- ♦ HDMİ Version 1.4b
- Supports: Full HD, 3D, Ethernet, 4K
- Supports resolution: 3840 x 2160/30Hz
- Supports: Deep Color 30bit, 36bit
- Support for Blu-Ray 24/50/60fs/HD-DVDc/xvYCC
- Supports audio formats: DTS-HD/Dolby-TrueHD/LPCM7.1/DTS/Dolby-AC3/DSD/HD (HBR)
- Indicator diode
- **⊘** Example use:

Enables to split the signal from one HDMI source to two monitors or projectors simultaneously.

Can be used as an HDMI signal amplifier.





Adapter HDMI straight

Model: CL-111

Adapter HDMI angular

Model: CL-112

- Connectors: HDMI A 19 pin, female HDMI A 19pin, female/male
- The range of operation: data transfer
- Works both ways
- ♥ Example use: Extending HDMI cable





HDMI - micro HDMI adapter

Model: CL-17

- ✓ Connectors:
 HDMI A, female
 Micro HDMI D, male
- Gold plated connectors
- The range of operation: data transfer
- Works both ways
- $\ensuremath{ \bigodot}$ Example use: Connecting a smartphone or a tablet to a TV.

DVI - VGA adapter

Model: CL-25

- Connectors: DVI D 24+5, male VGA 15 pin, female
- Range of operation: analogue video transfer
- O Direction: DVI->VGA
- Example use: Connecting a computer to a monitor or a TV.



VGA divider for 2 ports

Model: CL-66

- ◆ Connectors: VGA,male 2x VGA, female
- ♦ High frequency 250 MHz(VS-92A/VS/94A) or 200MHz (VS 98A)
- Amplifyingvideo signal up to 65m
- Support DDC2B
- ✔ Plug&Play does not need drivers
- The range of operation: dividing VGA signal
- ◆ Direction: 1xVGA male-> 2xVGA, female
- Example use: Connecting a computer or a laptop with VGA output to one or two projectors, monitors or TV sets.



HDMI - VGA adapter with audio

Model: CL-23

- Connectors:
 HDMI A, male
 VGA 15 pin, female
 Mini Jack 3,5mm, stereo, male
- Resolution up to 1080p
- Does not need an external power supply
- The range of operation: transfer of audio and video
- ◆ Direction: HDMI->VGA
- Example use: Connecting a computer to a monitor or projector or TV.

HDMI - DVI adapter

Model: CL-21

- ◆ Connectors: DVI-D 24+1, male HDMI A, female
- Gold plated connectors
- The range of operation: digital video transfer
- Works both ways
- Example use: Connecting a computer to a monitor or a TV.

VGA - HDMI Converter

Model: CL-110

- Connectors: VGA: male Mini Jack 3.5mm, stereo, male HDMI, female
- Supports resolutions: 1080p/60Hz, 720p/60Hz
- Range of operation: Converting audio/video signal
- ◆ Direction: VGA/mini Jack 3.5mm → HDMI
- Example use: Video and sound transfer from a device with VGA output to a TV or a monitor.

HDMI - VGA adapter

Model: CL-27

- ◆ Connectors: HDMI A, male VGA 15 pin, female
- Maximal HDMI resolution: 1080p
- Maximal resolution VGA: 1920x1200x60Hz (WUXGA)
- Does not need an additional power supply
- The range of operation: video transfer
- Direction: HDMI -> VGA
- Example use: Connecting a computer to a monitor, a projector or a TV.



DisplayPort - VGA adapter

Model: CL-90

- Connectors: DisplayPort, male VGA, female
- Range of operation: video transfer
- Direction: DisplayPort -> VGA
- Example use: Connecting a computer to a monitor or a projector.



DisplayPort - DVI adapter

Model: CL-91

- Connectors: DisplayPort, male DVI 24 pin, female
- Resolution: 1920x1080p
- Range of operation: video transfer
- Direction: DisplayPort -> DVI
- Example use: Connecting computer to a monitor or a projector.



Mini DisplayPort - DVI adapter

Model: CL-94

- Ocnnectors: Mini DisplayPort, male DVI 24 pin, female
- Resolution QXGA (2560x1300)
- Supports two-direction transfér form an AUX channel with a bandwidth of 1Mbps
- The range of operation: video transfer
- Direction: mini DisplayPort -> DVI
- Example use: Connecting a computer to a monitor.

DisplayPort - HDMI adapter

Model: CL-55

- Connectors: DisplayPort, male HDMI A, female
- Maximal resolution: 1080p
- Range of operation: audio-video transfer
- Direction: DisplayPort -> HDMI
- Example use: Connecting computer to a monitor or a projector.

Mini DisplayPort - HDMI adapter

Model: CL-57

- 🗸 Connectors: Mini DisplayPort, male HDMI A. female
- Gold plated connectors
- The range of operation: audio-video transfer
- Direction: mini DisplayPort -> HDMI
- Example use: Connecting a computer to a monitor or a TV.

GT-P100 - USB Adapter

Model: CL-18

- Connectors: Samsung 30 pin USB A, female OTG
- USB standard: 2.0
- OTG function
- The range of operation: data transfer
- 🗸 Works both ways
- Example use: Connecting tablet, smartphone or another device supporting OTG standard to a USB storage device, keyboard, mouse, HDD drive.

MHL micro USB - HDMI adapter

Model: CL-32

- Connectors: MHL: micro USB 5 pin HDMI A, female
- For all smartphones and tablets supporting MHL technology with micro USB 5 pin output
- While applying additional power supply it works as a charger
- Also works with TV sets, which are not supporting MHL (needs additional power supply micro USB-USB)
- Example use: Video transfer from a smartphone, tablet to a TV.

USB - SAMSUNG GALAXY TAB cable

- Connectors: USB A, male Samsung Galaxy Tab 30 pin
- Supported models: P1000, N8000, P5110, P7510, P7500, P7300, P6200, P6800, P3100, P1000, P1010 and other....
- The range of operation: data transfer, charging
- Works both ways
- Example use: Connecting Samsung brand tablet to a computer.

OTG USB - mini USB adapter

Model: CL-58

- Connectors: Mini USB B, male USB A, female, OTG
- USB standard: 2.0
- The range of operation: Data transfer
- Works both ways

Connecting tablet, smartphone or any other device supporting OTG standard to a USB storage device, keyboard, computer mouse, HDD drive.

OTG USB - micro USB adapter

Model: CL-59

- Connectors: Micro USB B, male USB A, female, OTG
- USB standard: 2.0
- The range of operation: data transfer
- Works both ways
- Example use: Connecting a tablet, a smartphone or any other device supporting OTG standard with a USB storage device, keyboard, mouse or HDD drive.



OTG USB - mini USB angular adapter

Model: CL-60

- Connectors: Micro USB B, male, angular USB A. female, OTG
- USB standard: 2.0
- The range of operation: data transfer
- Works both ways
- Example use: Connecting a tablet, a smartphone, or any other device supporting OTG standard with a USB storage device, keyboard, computer mouse or HDD drive.

OTG USB - micro USB angular adapter

Model: CL-61

- Connectors: Micro USB B, male, angular USB A. female, OTG
- USB standard: 2.0
- The range of operation: data transfer
- Works both ways
- Example use: Connecting a tablet, a smartphone, or any other device supporting OTG standard with a USB storage device, keyboard, computer mouse or HDD drive.

OTG USB - micro USB adapter

- Connectors: USB OTG A, female Micro USB B, male
- USB standard: 3.0
- The range of operation: data transfer up to 625Mbps
- Works both ways
- Example use: Connecting a tablet, a smartphone, or any other device supporting OTG standard with a USB storage device, keyboard, computer mouse or HDD drive.

USB type C - Jack 3.5mm audio adapter

Model: AK-35

- Connectors: USB type C, male Mini Jack 3.5mm, stereo, female
- Stereo sound
- USB standard: 3.1
- The range of operation: sound transfer
- Direction: USB type C -> Jack 3.5mm
- Example use: Connecting earphones to a smartphone, a tablet or any other device that does not have a Jack 3.5mm socket.

Micro USB adapter

Model: AK-30 White

Micro USB adapter

Model: AK-31 Black

- Connectors: Micro USB 2.0 female USB 3.1 type C, male
- Size: 19.9 x 10.5 x 5.8mm
- The range of operation: data transfer, charging, device synchronisation
- Works both ways
- Example use: Connecting devices with USB type C socket to a micro USB cable.

Window transition

Model: LB0076BLACK/GOLD Gold

Window transition

Model: LB0076/WHITE White

Connectors:

Antenna socket type F, female Antenna socket type F, female

- ♥ Ultra-thin tape(0,1mm)
- Attenuation: 6db

Under-window tape, that allows on letting through an antenna cord under the window frame in a un-invasive way, without the need of drilling. Thanks to the fact, that it is flat, it does not cause a leak, and multiple closing a window does not influence its properties



Antenna divider

Model: LB0077

Connectors: IEC 9.5mm, female 2xIEC 9.5mm, male



Example use: Dividing the signal from one RF female socket to two RF male sockets.

Antenna divider

Model: LB0078

Connectors: IEC 9.5mm, male Coaxial, clockwise plug



Example use: Connecting an antenna to a TV

Angular antenna adapter

Model: LB0079

- Ocnnectors: IEC 9.5mm, female, angular
- Ocaxial, clockwise socket
- Example use: Connecting an antenna to a TV



Angular antenna adapter

Model: LB0080

- Connectors:
- IEC 9.5mm, male, angular
- Coaxial, clockwise socket
- Example use: Connecting an antenna to a TV






USB 3.0 - Micro USB type B 1m

Model: CL-102

- Connectors: USB 3.0 A, male USB Type C, male
- OD: 4.0mm
- Data transfer up to 625MB/s, charging
- Works both ways





USB 3.0 - USB type C cable 1m

- Ocnnectors: USB 3.0 A, male USB 3.1 type C, male
- OD: 4.0mm
- Data transfer up to 625 MB/s
- Works both ways

Example use: Connecting a computer, laptop, camera, charger etc. with a USB 3.1 Type C connector to a device with fast USB 3.0 socket.

USB - micro USB cable 1m

Model: CL-123

USB - micro USB cable 2m

Model: CL-124

- Connectors: USB 2.0 A, male Micro USB 2.0, male
- Output current: max. 2.1A
- Data transfer: up to 480 Mbps
- The range of operation: data transfer, charging
- Works both wavs
- Example use: connecting a tablet, a smartphone to a charger or a computer.

USB - USB Type C cable 1m

Model: CL-125 Biały

USB - USB Type C cable 2m

Model: CL-129 Czarny

- Connectors: USB 2.0A, male USB type C, male
- Output current: max. 2.1A
- Data transfer: up to 480Mbps
- The range of operation: data transfer, charging
- Works both ways
- Example use: connecting a tablet, a smartphone to a charger or a computer.

USB - micro USB cable with Quick Charge support 1m

Model: CL-127

- Ocnnectors: USB 2.0 A, male Micro USB, male
- Output current: max. 5A
- O Data transfer: up to 480Mbps
- The range of operation: data transfer, charging (Quick Charge technology)
- Works both ways
- Example use: Connecting a tablet, a smartphone to a charger or a computer to charge and transfer data. Ability to 4-times faster charging, when connecting to a charger that supports Quick Charge technology.

USB - USB type C cable with Quick Charge 1m

Model: CL-126

- Connectors: USB 2.0A, male USB type C, male
- Output currency: max. 5A
- O Data transfer: up to 480Mbps
- The range of operation: data transfer, charging (Quick Charge technology)
- Works both ways
- Example use: Connecting a tablet, a smartphone to a charger or a computer to charge and transfer data. Ability to 4-times faster charging, when connecting to a charger that supports Quick Charge technology.



USB - USB type C cable 1m

Model: CL-79

- Connectors: USB 2.0A, male USB type C, male
- 28 AWG/1P + 24 AWG/2C, OD: 3,5mm
- The range of operation: data transfer, charging
- Works both ways
- Example use: Connecting a tablet, smartphone to a charger or a computer.

iPhone 5/6 IOS8 cable 1m

Model: CL-64

- ◆ Connectors: USB A, male Lightning 8 pin, male
- Compatible with iOS8, iPhone 5/5c/5s/6, iPad mini, iPad 4, iPod touch 5, iPodnano 7
- The range of operation: data transfer, charging
- Works both ways
- Example use: Connecting the Apple brand smartphone or tablet with a computer.

118

USB - iPhone cable retractable 0.8m

Model: CL-71

- ◆ Connectors: USB 2.0 A, male Lightning 8 pin, male
- Compatible with iOS8, iPhone 5/5c/5s/6, iPad mini, IPad 4, iPod touch 5, iPodnano 7
- The range of operation: data transfer, charging
- Works both ways
- Example use: Connecting Apple brand smartphone or tablet with a computer

USB 2.0 extender 0,8m

Model: CL-68

USB 2.0 extender 1,8m

Model: CL-69

- ◆ Connectors: USB 2.0 A, male USB 2.0 A, female
- 28AWG, OD:4.0mm
- The range of operation: data transfer
- Works both ways
- Example use: Extending USB input.

USB-A - micro-B USB cable 1m

Model: CL-11

- ◆ Connectors: USB A, male USB micro B, male
- Spiral cable
- The range of operation: data transfer, charging
- Works both ways
- Example use: Connecting a tablet or a smartphone to a charger or a computer.

USB - micro USB/type C 2in1 cable 1m

Model: CL-128

- Connectors: USB 2.0 A, male Micro USB/USB type C, male
- Output current: max. 2.1A
- Data transfer: up to 480Mbps
- The range of operation: data transfer, charging
- Works both ways
- Example use: Connecting a tablet or a smartphone to a charger or a computer

USB - Lightning cable 1m

Model: CL-73

USB - Lightning cable 1m

Model: CL-74

- ◆ Connectors: USB A, male Lightning 8 pin, male
- Ocompatible with iOS8, iPhone 5/5c/5s/6, iPad mini, IPad 4, iPod touch 5, iPodnano 7
- The range of operation: data transfer, charging
- Works both ways
- Example use: Connecting Apple brand smartphone or tablet with a computer

USB - iPhone splitter retractable cable 0,8m

Model: CL-72

- Connectors:
 Lightning 8 pin, male, for iPhone 5
 Lightning 30 pin, male for iPhone 4
- Micro USB 2.0, male ◆ Compatible with iPhone 5/5c/5s/6, iPad mini, iPad 4, iPod touch 5, iPod nano 7, iPod air and other
- Apple brand products. ◆ The range of operation: data transfer, charging
- Works both ways
- Example use: Connecting a smartphone or a tablet to a charger or a computer.

USB port active extender 5m

Model: CL-76

USB port active extender 10m

Model: CL-130

- ◆ Connectors: USB 2.0 AM, male USB 2.0A, female
- ◆ 28AWG/1P 26AWG/2C, OD 4.5mm
- The rangeof operation: data transfer
- Works both ways
- Example use: extending USB cable.



USB 2.0A - USB mini-B cable 1m

Model: CL-12

- Connectors: USB A, male USB mini B, male
- 🗸 Spiral Cable
- The range of operation: data transfer, charging
- Works both ways
- Example use: Connecting a tablet or a smartphone to a charger or a computer.





USB 7.1 soundcard

Model: AK-01


Ocnnectors: 3.5mm mini Jack, headphone 3.5mm mini Jack, microphone USB, male



- Full 16-bit recording and playback without soundcard in a PC
- 7.1 stereo system simulation
- USB 2.0 interface
- MPU-401 MIDI UART compatible MIDI interface and SoundBlaster MIDI.
- ♥ Plug & Play does not need additional drivers
- Volume regulation on a device
- Diode indicating the device operation
- Mute button
- Example use: Connecting a microphone, headphones, speakers to a computer not equipped with a sound card. Can also be used as an additional headphone or microphone input.

USB 7.1 soundcard

Connectors: 2x 3.5mm mini Jack, headphone 2x 3.5mm mini Jack, microphone USB, male



- Stereo 7.1 system simulation
- USB 2.0 interface
- MPU-401 MIDI UART compatible MIDI interface and SoundBlaster MIDI
- Plug & Play does not need additional drivers
- System requirements: Windows XP/Vista/7/8/8.1/10 with USB2.0 port
- Volume regulation on a device
- Example use: Connecting a microphone, headphones, speakers to a computer not equipped with a sound card. Can also be used as an additional headphone or microphone input.

SATA/IDE - IDE/SATA adapter

Connectors: PATA 40pin, female SATA 7pin, female



- High-quality IDE-SATA-SATA-IDE connector in one device
- Element is mounted to a motherboard IDE port (IDE->SATA) or directly to a drive (SATA->IDE)
- Works with all motherboards equipped with IDE(ATA 100/133)
- Plug & Play does not need additional drivers
- Example use: Enables to use SATA drives with motherboards equipped with IDE interface and also ATA drives with motherboards only having SATA interface.

IDE SATA/ATA - USB 2.0 adapter

Connectors: IDE/ATA 3,5", 40pin female IDE/ATA 2.5", 44pin female SATA 7 pin USB 2.0 male



Supports drives: 2.5", 3.5", 5.25"

- In the set: USB 2.0 adapter for IDE/SATA(ATA100/133), power cable 17cm, SATA cable 24cm, power adapter (input 100-240V AC, 50/60Hz, 0.8A, output: 12V/2A, 5V/2A)
- Example use: IDE/SATA adapter is used to connect HDD drive, CD/CDRW-ROM, DVD/DVDRW-ROM, COMBO drive to a computer through USB port.

USB 2.0 - RS 9-pin adapter

Connectors: USB A, male RS-232 DB 9 pin, male



- Data transfer more than 1Mbps
- Supports remote wake up and power control
- Supports operating systems: XP/VISTA/Win7/WIN8 32/64
- The range of operation: data transfer
- Example use: Connecting a device with RS232 serial port with a computer equipped with a USB port.





Model: CL-24

Data transfer up to 100Mbps

- Supports operating system: XP/VISTA/Win7, Win8, Win10 32/64
- The range of operation: data transfer

USB 2.0 - RJ45 adapter

Example use: It functions as an external network card.





3x IDE MOLEX power adapter

- Connectors: IDE Molex 4pin, male 2x IDE 4 pin, male
- Length: 18cm

Powering hard drives and optical drives, internal ventilators.



MOLEX - SATA power adapter

Model: AK-10

- Connectors: IDE Molex 4 pin, male SATA 15 pin, female
- Length: 18cm

Powering hard drives and SATA II optical drives using Molex socket.

IDE MOLEX-SATA power adapter

Model: AK-11

- Ocnnectors: IDE Molex 4 pin, male SATA 15 pin, female angular
- Lenath: 18cm
- Ocable parameters: 12V DC/5V DC




IDE MOLEX - 2x SATA power adapter

Model: AK-12

- Ocnnectors: IDE Molex 4 pin, female 2x 15 pin SATA, female angular
- Length: 18cm

Powering hard drives and SATA II optical drives using Molex socket.



IDE MOLEX - 2x SATA power adapter

- Connectors: IDE Molex 4pin, male 2x 15 pin SATA, female
- ULength: 18cm
- Ocable parameters: 12V DC/5V DC
- Example use:

Powering hard drives and SATA II optical drives using Molex socket.

IDE MOLEX - 3x power adapter

- Connectors: IDE Molex 4 pin, male IDE Molex 4 pin, female IDE Molex 3 pin, male
- Length: 18cm

Example use: Powering hard drives optical drives, ventilators using Molex socket.



4x IDE MOLEX power adapter

Model: AK-16

- Ocnnectors: IDE Molex 4pin, male 3x IDE Molex 4 pin, female
- Length: 18cm
- Ocable parameters: 12V DC/5V DC
- Example use:

Powering hard drives and optical drives using the Molex socket.



- Connectors: SATA 15 pin, male 2x SATA 15 pin, female
- Length: 18cm
- Ocable parameters: 12V DC/5V DC
- Example use:

Powering hard drives and SATA II optical drives using SATA socket.



2x IDE MOLEX - EPS power adapter

Model: AK-18

- Ocnnectors: 2x IDE Molex 4 pin male EPS 8 pin
- Length: 18cm
- Ocable parameters: 12V DC/5V DC
- Example use: Additional processor powering.



IDE MOLEX - 2x SATA power adapter

Model: AK-19

- Connectors: Ide Molex 4 pin, male 2x 15 pin SATA, female angular
- Length: 18 cm
- Cable parameters: 12V DC/5V DC
- Example use: Powering hard drives and SATA II optical drives using Molex socket.



Riser PCI-Express 1x - 16x, USB 3.0, 6 pins SATA HDMI 4K/UHD connectors monitor emulator

Build in 6 pin power socket and 6 pin SATA

Fits all PCI-E 1x, 4x, 8x, 16x sockets

- Gold plated connectors enhancing the quality of the connection and lifespan of the device
- Compatible with PCI Express Version 1.0, 2.0 specification
- 4 build in condensation, that stabilise the power supply
- of the graphics card
- Compatible with PCI-E 1.0, 2.0 specification Plug & Play device

In the set: Plate with PCI-E 1x - USB male socket Plate with PCI-E 16x - USB female socket USB 3.0 60cm long cable SATA M - 6 pin M power cable

Example use: Connecting a devices equipped with PCI-E 16x, 8x, 4x input to a PCI-E 1x input

Emulating monitor for a cryptocurrency excavator Supports resolutions: 1920x1080 for HDMI 1.2 connector 3840 x 2160 (4K UHD) for HDMI 1.4 connectors



♥ Plug & Play device

Example use:

Emulating monitor, that is not physically plugged to a graphics card, enhancing the graphics card performance while mining cryptocurrency.

SATA - PCI power adapter

- Connectors: SATA 15 pin, male PCI Express 6 pin, male
- Length: 18cm
- Ocable Parameters: 12V DC/5V DC
- Example use:

Powering devices and graphics cards using SATA socket.



Printer USB cable 1,8m

- Connectors: USB 2.0, male USB B, male
- 28 AWG
- OData transfer: 480Mbit/s
- High-quality copper cords
- Ferrite filter
- Works both ways
- Example use: Connecting a printer to a computer.



USB - LPT male adapter

Connectors: USB A. male

Centronics IEEE 1284 36 pins, male

- Compatible with USB 2.0 and USB 1.1
- Transfer up to 2Mb/s
- Systems: 98SE/ME/2000/XP/7/8
- The range of operation: data transfer
- Works both ways
- Example use:

Connecting a printer to a computer.



USB-LPT female adapter

- Connectors: USB A, male DB-25, female

- Systems: 98SE/ME/2000/XP/7/8
- Plug & Play device
- The range of operation: data transfer
- Works both ways
- Example use:

Connecting a printer to a computer.



PCI-E to M2 NVME Adapter M-KEY

- M.2 disk interface supported
- Supported PCI-E interfaces: PCI-E 4x, PCI-E 8x, PCI-E16x
- Supported disk sizes: 2230, 2242, 2260,
- The motherboard must support NVMe for proper operation
- Application example: Mounting M.2 drives to the PCI-E expansion slot on the motherboard.





Bluetooth 2.0 computer adapter

- Ocompatible with USB 2.0 and 1.1
- System requirements: Windows 2000/XP/Vista/7/10
- Compatible with Bluetooth 2.0 and 1.2
- Supports profile: Networking, Dial-up, Fax, LAN Access
- Data transmission bandwidth: 3Mbps
- ✓ Range: up to 20m✓ Plug & Play device
- Example use:

Wireless connection with any device using Bluetooth (smartphone, tablet, computer, mouse, keyboard, speaker, etc.)

Wi-Fi 12dBi 41 RP-SMA PODS antenna

- ▼ Working frequency: 2,400-2483GHz
- Radiation angle vertically 12°
- Radiation angle horizontally 360°
- O Polarisation: vertical

- Maximal input power: 50W
- Ocable length: 2m
- Example use: Omnidirectional antenna can be used in active devices(Access Point,



Wi-Fi USB adapter

- Interface: USB
- Compatible with a standards: IEEE 802.11b. IEEE802.11g, IEEE802.11n
- System requirements: Windows 2000, XP, Vista, Windows 7/10, Linux
- Intelligent Energy Saver
- OB49 Chip: Realtek RTL 8188CU
- Supports 64/128-bit WEP, WPA, WPA2 and WPS
- Power consumption: <1,5W</p>
- Example use: Connecting Wi-Fi network to a computer



Bluetooth 4.0 computer adapter

- Compatible with USB 2.0 and 1.1
- System requirements: Windows 2000/XP/Vista/7/10
- Compatible with Bluetooth 4.0, 3.0 + HS, 2.1 + EDR and 2.0
- Supports profile: Networking, Dial-up, Fax, LAN Access
- Data transmission bandwidth: 3Mbps
- Range: up to 100mPlug & Play device
- Example use: Wireless connection with any device using Bluetooth(smartphone, tablet, computer, mouse, keyboard, speaker, etc.)

Wi-Fi 12dBi 38cm RP-SMA PODS antenna

- ◇ Work frequency: 2,400 2,483 GHz
 ◇ Energy profit: 9~12dBi
- VSWR<1.5 Average
- Radiation angle vertically 12°
- Radiation angle horizontally 360°
- Polarisation: vertical
- ✓ Impedance: 500hm
- ♥ Work temperature: from -10°C to +60°C
- Maximal input power: 50W
- Example use: Omnidirectional antenna can be used in active devices (Access Point, wireless PCI or USB card), as well as in laptops equipped with RP-SMA port.

Wi-Fi - USB adapter

- Interface: USB
- Compatible with a standards: IEEE 802.11b, IEEE802.11g, IEEE802.11n
- System requirements: Windows 2000/XP/ Vista/7/10, WIN CE, Linux, MAC OS
- Frequency: 2,4 ~ 2.4835 GHz
 1 − 14 transmitting/receiving channels
- Supports 64/128-bit WPA, WPA-PSK, WPA2, WPA2-PSK, TKIP/AES
- Power consumption: <1,5W
- Maximum transmitting power: 20dBm
 External omnidirectional antenna 2dBi
- LED indicator
 - Connecting Wi-Fi network to a computer, that does not have an internal Wi-Fi card.





NETWORK CABLES

Patchcord, UTP Cat. 5e 3m

Model: CLA-01

Patchcord, UTP Cat. 5e 5m

- Connectors: RJ45, male RJ45, male
- 26AWG, OD:5.0 mm
- Category UTP 5e
- Transferring data in a frequency band up to 100 MHz
- Bandwidth up to 1Gbit/s
- Applicable in networks: Full-duplex, Fast Ethernet 100Mbit/s, 1Gbit/s
- Example use: Connecting network devices with a computer.

Patchcord, UTP Cat. 61m

- Ocnnectors: RJ45, ma**l**e RJ45, male
- 26AWG, OD:5.0mm
- Category FTP 6
- Shielded Patchcord less vulnerable to external interference and minimalize radio interference emission
- Transmitting data in a band frequency up to 250MHz
- Applicable in networks: Full-duplex, Fast Ethernet 100Mbit/s, 1Gbit/s
- Example use: Connecting network devices with a computer.

Installation cord UTP Cat. 5e 305m

- Ocnnectors: none
- 26 AWG, OD:5.5mm
- Ocategory UTP 5e
- Transferring data in a frequency band up to 100 MHz
- Bandwidth up to 1Gbit/s
- Applicable in networks: Full-duplex, Fast Ethernet 100Mbit/s, 1Gbit/s
- Example use: Connecting network devices with a computer.



Patchcord, UTP Cat. 6 3m

Model: CLA-03

Patchcord, UTP Cat. 6 5m

- Connectors: RJ45, male RJ45, male
- 26AWG, OD:6.0 mm
- Category UTP 6
- Transferring data in a frequency band up to 250MHz
- Bandwidth up to 10Gbit/s
- Applicable in networks: Full-duplex, Fast Ethernet 100Mbit/s, 1Gbit/s
- Example use: Connecting network devices with a computer.

Patchcord, FTP Cat. 63m

- Connectors: RJ45, ma**l**e RJ45, male
 - 26AWG, OD:5.0 mm
- Category FTP 6
- Shielded Patchcord less vulnerable to external interference and minimalize radio interference emission
- Transferring data in a frequency band up to 250MHz
- Bandwidth up to 10Gbit/s
- Applicable in networks: Full-duplex, Fast Ethernet 100Mbit/s, 1Gbit/s
- Example use: Connecting network devices with a computer.

Installation cord UTP Cat. 6 305m

- Ocnnectors: none
- 26 AWG, OD:6.0mm
- Ocategory UTP 6
- Wire − full copper
 Transferring data in a frequency band up to 250 MHz Bandwidth up to 10Gbit/s
- Applicable in networks: Full-duplex,
- ▼ Fast Ethernet 100Mbit/s, 1Gbit/s
- Example use: Connecting network devices with a computer.





Power cord 1,2m

Model: CL-67

- Connectors:
 IEC C5, female
 Hybrid C/E/F plug grounded, male
- ▼ Type: 3-pin
- Standard of the wire: H03VV-F
- Cable Parameters: 250V, 10A
- ✓ Work temperature: -30°C +80°C
- Example use: Power cord for laptops and portable projectors.

Power cord 1,2m

Model: CL-89

- ◆ Connectors: IEC C13, female C/F Schuko, male
- Type: 3-pin
- Oable parameters: 250V max, 10A max
- Example use: Universal power cord for monitors, computers, printers, projectors.

Power cord angular 1,8m

Model: CL-98

- Connectors: C/F Schuko, male, angular IEC C13, female
- Type: 3-pin
- Cable parameters: 250V max, 10A max
- Example use: Universal power cord for monitors, computers, printers, projectors.



Power cord 1,2m

Model: CL-97

Power cord 1,8m

Model: CL-100

Power cord 3m

Model: CL-105

- Connectors:
 Moulded mains connector, male
 Euro (figure 8), female
- **⊘** 2*0.5mm2
- Type: 2-pin
- Oable parameters: 250V max, 5A max
- Example use: Universal power cord for radio, tape recorder or a TV.

Power cord 1,8m

Model: CL-81

- Connectors:
 IEC C5, female
 Hybrid C/E/F plug grounded, male
- ▼ Type: 3-pin
- Standard of the wire: H03VV-F
- Ocable Parameters: 250V, 10A
- ✓ Work temperature: -30°C +80°C
- Example use: Power cord for laptops and portable projectors.

Power cord 1,2m

Model: CL-99

- ◆ Connectors: IEC C14, male IEC C13, female
- 🦻 3*0.5mm², OD:5.5mm
- ▼ Type: 3-pin
- Example use: Extender for a universal power cord for monitors, computers and projectors.

Power cord angular 1,2m

Model: CL-115

Power cord angular 1,8m

Model: CL-116

- Connectors:
 C/F Schuko, male, angular
 IEC C13, female, angular
- 3*0.5mm2, OD:5.5mm
- Tyne: 3-nin
- Cable parameters: 250V max, 10A max
- Example use: Universal power cord for monitors, computers, printers, projectors.

Power cord angular 1,2m

Model: CL-117

Power cord angular 1,8m

Model: CL-118

- Connectors:
 Moulded power plug, male
 Euro (8 figure), female, angular
- 2*0.5mm2
- ✓ Type: 2-pin
- Example use: Universal power cord for radio, tape recorder or a TV.



3.0A wall charger with Quick Charge technology support

- Output voltage: 5V=3A/8V=2A/12V=1,5A
- Compatible with standards: Quick Charge 3.0, 2.0 and 1.0
- Protection: against overload current and overheating
- Example use: Charging a smartphone or a tablet.

SAVIO LA-03 charger is compatible with Quick Charge 3.0, 2.0 and 1.0 technology and thanks to that the devices can be charged up to 4-times faster.



Power strip

- Rated Voltage: 230-250V/50Hz
- Max. load: 2500W
- Rated load current: 10A
- Protection against overvoltage: varistor (90J)

Power strip 1,5m

Model: LZ-01 **5 sockets**

Power strip 3m

Model: LZ-02 5 sockets

Power strip 5m

Model: LZ-03 **5 sockets**

Power strip 5m

Model: LZ-04

6 sockets





Speaker cord 10m 2x1.00mm2, OFC

Model: CLS-01

Speaker cord 20m 2x1.00mm2, OFC

Model: CLS-02

- Wire cross-section 2x1.00mm2
- Anaerobic copper cord OFC (Oxygen Free Copper) with high degree of purity 99,96%
- Elastic isolation
- Ensures clear and sharp sound
- Example use: Connecting a sound system.

Optical cords

- Connectors(Optical SPDiF T-T Standard)
 Toslink, male
 Toslink, male
- **⊘** OD:2.2mm
- Gold plated connectors
- Without the potential difference, transmission through a beam of light
- Multi-channel sound: DolbyDigital, Surround, DTS, Prologic
- ▼ Ensures crystal clear digital sound

Connecting home cinema, TV, projector, receiver, amplifier, console, speaker set with a digital connector and other evices equipped with a Toslink type digital socket.

Toslink optical cord 0,5m

Model: CLS-07

Toslink optical cord 1m

Model: CLS-08

- Connectors (Optical SPDiF T-T Standard) Toslink, male Toslink. male
- OD:5.0mm
- Gold plated connectors
- Without the potential difference, transmission through a beam of light
- Multi-channel sound: DolbyDigital, Surround, DTS, Prologic
- Ensures crystal clear digital sound
- Example use:

Connecting home cinema, TV, projector, receiver, amplifier, console, speaker set with a digital connector and other devices equipped with a Toslink type digital socket.

Speaker cord 10m 2x2.00mm2, OFC

Model: CLS-03

Speaker cord 20m 2x2.00mm2, OFC

Model: CLS-04

- Wire cross-section 2x2.00mm2
- Anaerobic copper cord OFC (Oxygen Free Copper) with a high degree of purity 99,96%
- Elastic isolation
- Ensures clear and sharp sound
- Example use: Connecting a sound system

Toslink optical cord 0,5m

Model: CLS-05

Toslink optical cord 1m

Model: CLS-06

Toslink optical cord 2m

Model: CLS-10

Toslink optical cord 3m

Model: CLS-09



Mini Jack 3.5mm audio cable 2m

Model: CLS-12

- Connectors:
 Mini Jack 3.5mm, male
 Mini Jack 3.5mm, male
- High-quality copper wires
- AUX stereo extender
- Example use:

Connecting a smartphone with a home cinema or a car radio.



AUDIO CABLES AND ACCESSORIES

Mini Jack 3.5mm - 2x RCA cable

Model: CLS-15

- Connectors:
 Mini Jack 3.5mm, male
 RCA (Cinch), male
 RCA (Cinch), male
- Gold plated connectors
- Example use: Transmitting an audio signal to a laptop equipped with a mini Jack 3.5mm socket to speakers with RCA (Cinch) connector.



RCA - RCA audio cable 5m

Model: CLS-16

RCA - RCA audio cable 3m

Model: CLS-17

- Connectors; 2xRCA (Cinch), male 2xRCA (Cinch), male
- OD:2.8 mm
- Gold plated
- High-quality copper wires
- Example use: Connecting active subwoofer to a home cinema amplifier.



Audio/video RCA - RCA cable 2m

Model: CLS-14

- ◆ Connectors: 3xRCA (Cinch), male 3xRCA (Cinch), male
- Gold plated connectors
- High-quality copper wires
- Example use: Transmitting an analogue audio/video signal from a camera to a TV or a recorder.

RCA - RCA audio cable 2m

Model: CLS-11

- ◆ Connectors: RCA (Cinch), male RCA (Cinch), male
- OD:2.8mm
- Gold plated connectors
- High quality copper wires
- Example use: Connecting active subwoofer to a home cinema amplifier.

RCA - 2xRCA adapter

Model: CLS-18

 Connectors: RCA, male 2xRCA, female



 Example use: Dividing a signal from one RCA (Cinch) on two RCA (Cinch) sockets.

Mini Jack 3.5mm - 2xRCA audio adapter

Model: CLS-19

Connectors:
 Mini Jack 3.5mm, stereo, male 2xRCA, female



 Sample application: Dividing a signal from one RCA (Cinch) on two RCA (Cinch) sockets.





The Savio BS-02 wireless Bluetooth speaker is the best way to make your favorite music everywhere! Garden party, trip to the lake - from now on you can enjoy clean sound wherever you want. The loudspeaker has a handle so you can move or hang it anywhere. Thanks to the large battery, you can enjoy yourself and listen to music for a long time. You can send audio via Bluetooth via the USB input or the micro SD card slot. Savio BS-02 also has a built-in radio and hands-free function, which is a great conference organizer.

Stereo Bluetooth speaker

Model: BS-021 Niebieski

Model: BS-022 Czerwony

Model: BS-023 Czarny

- Output power: 2x5W Stereo
- Impedance: 3Ω
- Operating voltage: DC 5V
- SNR: ≥80dB
- Maximum volume: ≥90dB

- Maximum capacity of SD card: 32GB
- ◆ FM radio frequency range: 87.5 - 108.0MHz
- Operating time: up to 7 hours (depending on the volume)
- ◆ Charging time: 2.5 hours
- Weight: 700g





Bluetooth speaker

Niebiesk	Model: BS-011			
Szary	Model: BS-012			
Czarny	Model: BS-013			

- - Output power: 3W 🔮
 - Bluetooth range: up to 10m ♥

 - Maximum volume: ≥65dB •
- Frequency range: 100Hz 18kHz 🔮
- Maximum USB capacity: 32GB ♥
- Maximum capacity of SD card: 32GB ♥
- FM radio frequency range: 87.5 108.0MHz
 - Operating time: up to 4 hours (depending on volume)
 - Charging time: 1.5 hours ♥
 - Dimensions: 115x75x36mm
 - Weight: 200g 🔮



Wireless Bluetooth Earphones

Model: WE-01

- ⊗ Bluetooth version: 4.2
- Range: up to 10m
- Work time: up to 3 hours
- Charging time: up to 1 hour
- Stand-by time: up to 120 hours
- Impedance: 16 Ω
- Sensitivity: -38dB
- Built-in microphone: Yes
- Indicator LED diode: Yes
- Weight: 10g
- Function keys allow: on/off the device, change track, answer/reject an incoming call, dialing the last selected number.

Wireless Bluetooth Earphones

Model: WE-02

- Bluetooth version: 4.2
- Range: up to 10m
- Work time: up to 3 hours
- Charging time: up to 1 hour
- Stand-by time: up to 120 hours
- Impedance: 16 Ω
- ◆ Frequency response: 20HZ 20kHz
- Sensitivity: -38dB
- Built-in microphone: Yes

- Function keys allow: on/off the device, change track, answer/reject an incoming call, dialing the last selected number.

Wireless Bluetooth Earphones

Model: WF-03

- Bluetooth version: 4.2
- Range: up to 10m
- Work time: up to 3 hours
- Charging time: up to 1 hour
- Stand-by time: up to 120 hours
- Impedance: 16 Ω
- ◆ Frequency response: 20HZ 20kHz
- Sensitivity: -38dB
- Built-in microphone: Yes
- Weight: 16,4g
- Function keys allow: on/off the device, change track, answer/reject an incoming call, dialing the last selected number.







Wireless Bluetooth Earpgones

Model: TWS-01 Biały

Model: TWS-02 Czarny

- Bluetooth version: 4.2
- Range: up to 10m
- Earphones work time on a single charging cycle: up to 2 hours
- Charging time: up to 1 hour
- Stand-by time: up to 100 hours
- Impedance: 16 Ω
- ◆ Frequency response: 20HZ 20kHz
- Sensitivity: -38dB
- Build in microphone: Yes
- Weight: 7,4g
- ♥ Function keys allow: on/off the device, change track, answer/reject an incoming call, dialling the last selected number.



Wireless Bluetooth Earphones

Model: TWS-03

- Bluetooth version: 5.0
- Earphones work time on a single
- charging cycle: up to 5 h
- Earphones charging time: up to 1,5 h
- Standby time: up to 100 h
- Impedance: 32 Ω
- Sensitivity: -38 db
- Built-in microphone: Yes
- Earphones weight: 18,8 g
- ▼ Function keys allow: on/off earphones, selectionnext/previous track, play/pause, volume up/volume down, answer/reject incoming call, connection with the last selected number.



Wireless Bluetooth Earphones

Model: TWS-04

- Working Distance: up to 10 meters
- ▼Total earphones work time: up to 8 h (including power bank)
- Earphones work time on a single charging cycle: up to 2 h
- Earphones charging time: up to 1 h
- Standby time: up to 100 h
- Impedance: 16 Ω
- Sensitivity: -38 dB
- Built-in microphone: Yes
- ▼ Function keys allow: on/off earphones, next track, play/pause, answer/ reject incoming calls, connection with the last selected number.



Wireless Bluetooth Earphones

- Working Distance: up to 10 meters
- Total earphones work time: up to 17,5 h (including power bank)
- Earphones work time on a single charging cycle: up to 2,5 h
- Earphones charging time: up to 40 min
- Standby time: up to 120 h
- Impedance: 32 Ω
- Sensitivity: -42 dB
- Built-in microphone: Yes
- ▼ Function keys allow: on/off earphones, next/previous track, play/pause, answer/reject incoming calls





POWER BANKS

The power bank is available energy anywhere, anytime!

Thanks to the 20000mAh battery you can fully charge your phone, tablet or another device, wherever you want. Dual drive technology USB with intensity 2.1A allows charging your device faster. The automatic adaptation of charging power is compatible with devices from well-known brands: Apple, Samsung, Xiaomi, HTC, Google, Huawei, LG, Motorola, Nokia, Blackberry.

Power bank 10000mAh

Model: BA-02

- Battery type: lithium-polymer
- Capacity: 10000mAh
- Outputs 2xUSB: 2.1A
- Content of package: Micro USB cable, user manual
- Weight: 194g

Protection:

- overcharge/over-discharge protection
- short-circuit protection
- input/output overvoltage protection
- over-temperature protection

Additional information:

- LED charge level indicator
- automatic detection of connection/disconnection of the device

Power bank 20000mAh

Model: BA-03

- Battery type: lithium-polymer
- Capacity: 20000mAh
- Input: Micro USB (5V/2.1A), Type-C (5V/3A)
- Outputs 2xUSB: 2.1A
- Ocntent of package: Micro USB cable, user manual
- Weight: 397g

Protection:

- overcharge/over-discharge protection
- short-circuit protection
- input/output overvoltage protection
- over-temperature protection

Additional information:

- LED charge level indicator
- automatic detection of connection/disconnection of the device







CAR ACCESSORIES

FM transmitter

Model: TR-05

- Supports USB storage drives and SD cards up to 8GB
- Supports MP3 format
- ✓ LED screen shows frequency and volume.
- USB 2.0 port
- ▼ Frequency range: 87.5-108 MHz



FM transmitter

Model: TR-08

- Supports USB storage drives and SD cards up to 8GB
- Supports MP3 format
- USB 2.0 port
- ▼ Frequency range: 87.5-108 MHz



FM transmitter with Bluetooth and charging function

- Supports USB storage drives up to 32GB
- Supports MP3 format
- currency in the charging socket and Bluetooth connection status
- Ports: 2xUSB (with 2.4A charging function and music playback)
- Power supply: 12V/24V
- Frequency Range: 87.5-108 MHz
- → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1 + EDR

 → Bluetooth version: 2.1
- ◆ Additional functions: loudspeaker system (built-in microphone), A2DP support

FM transmitter with Bluetooth and charging function

Model: TR-10

- Supports USB storage drives up to 32GB
- Supports MP3 format
- ◆ LED screen shows frequency, number of played track, currency in the charging socket, and Bluetooth connection status
- ◆ Ports: 2xUSB (with 2.4A charging function and music playback)
- Power supply: 12V/24V
- Frequency Range: 87.5-108 MHz
- Additional functions: loudspeaker system (built-in microphone), A2DP support


Bluetooth audio transmitter/adapter

Model: TR-11/W White

Bluetooth audio transmitter/adapter

Model: TR-11/B Black

- Range: up to 15m
- Work time: approx. 3 hours
- Charging time: approx. 30 minutes
- Build in microphone
- Indicating diode
- In the set with the adapter: Jack 3.5mm – Jack 3.5mm, Charging cable Jack 3.5mm - Jack 3.5mm cable



Cassette - car adapter

Model: TR-07

- Enables music playback from a device with headphone socket (i.e. MP3 players, Discmans, smartphones, tablets)
- ◆ Has a cord with a mini Jack3.5mm connector
- Auto reverse function
- Stereo sound
- Noise reduction system ensures a high quality of transmitted sound



Magnetic holder

Model: CH-01

- Ventilation car cage mounted
- 4 strong magnets of various shape, covered with glue. Two metal plates, that enables to mount the smartphone, that can be hidden under the case or a flap
- Ultra-thin plates does not cause deformation of a flap or case and does not bother when the plate is sticked to the back of a smartphone.
- Fits every device



Car charger 3.0A 2xUSB

Model: SA-06/W White

Car charger 3.0A 2xUSB

Model: SA-06/B Black

- Input voltage: 12V/24V
 Output Voltage 1 (green socket): 3.6V-6.5V/3A, 6.5V-9V/2A, 9V-12V/1.5A
- Output voltage 2: 5V/2.4A
- Led diode indicates the work of the device
- Protection: from overvoltage and short-circuits; from overloading and overheat
- Ocompatible with standards: Quick Charge 3.0, 2.0 and 1.0
- Size: 68 x 30.8 x 30.8mm





Car charger 3.0A USB

Model: SA-05/W White

Car charger 3.0A 2xUSB

Model: SA-05/B Black

- Output Voltage: 3.6V-6.5V/3A, 6.5V-9V/2A, 9V-12V/1.5A
- ✓ Led diode indicates the work of the device
- Protection: from overvoltage and short-circuits; from overloading and overheat
- Ocompatible with standards: Quick Charge 3.0, 2.0 and 1.0
- Size: 50 x 24.5 x 19.6mm





Car charger 2xUSB

Model: SA-03

- Ocar charger 2xUSB
- Output voltage: 5.0V 1000mA
- Protection from overloading
- Oclour: white/black



Car charger 2xUSB 3.1A

Model: SA-04

- Car charger 2xUSB
- Input voltage: 12V
- Output voltage: 5.0V 3100mA
- Protection from overloading
- Oclour: black



Car charger 1xUSB

Model: SA-02

- Ocar charger: 1 x USB
- Output voltage: 5.0V 500mA
- Led diode indicating work
- Colour: white/black



Car divider 12V with USB

Model: SA-023

- 3 socket divider
- Output: 3 x 12V/24V
- ◆ USB output: 5V/500mA max
- Has a fuse
- Has a power supply indicating diode



QUICK CHARGE 3.0

CHARGE UP TO 4X TIMES FASTER





Parking sensors

Model: CP-03/S Silver

Parking sensors

Model: CP-03/B Black

- Energy consumption: <0,5W</p>
- Range of operation: 0.3-2.0m
- Sensor diameter: 22mm
 Sensor's angle of view: 60°
- ▼ The volume of the sound signal: 65DB
- Work temperature: from -30°C to +80°C

Display screen technical specification:

- Nominal voltage: 9-15V
- Power supply: 12V
- ✓ Energy consumption: <3
 </p>
- ✓ Work temperature: from -30°C to + 80°C



Parking sensors

Model: CP-02/S Silver

Parking sensors

- Power supply: 12V
- ▼ Energy consumption: <0,5W
 </p>
- Range of operation: 0.3-2.0m
- Sensor diameter: 22mm
 Sensor's angle of view: 60°
- ▼ The volume of the sound signal: 65DB
- ✓ Work temperature: from -30°C to +80°C

Display screen technical specification:

- Nominal voltage: 9-15V
- Power supply: 12V
- Energy consumption: <3W</p>



Parking sensors


Model: CP-01/B Black

- Nominal voltage: 9-15V
- Power supply: 12VEnergy consumption: <0,5W
- Sensor diameter: 22mm
- Sensor's angle of view: 60°
- ▼ The volume of the sound signal: 65DB
- Work temperature: from -30°C to +80°C



Mount scheme:

- 1. Measure the correct distance
- 2. Make holes (hole saw included)
- 3. Install the sensors, connect the wires





PHOTOGRAPHIC PAPER

Photo paper	Format	Weight	Package	Туре
Model: PA-01	A6	180g/m²	50pcs	gloss
Photo paper				
Model: PA-02	A6	115g/m²	50pcs	gloss
Photo paper		150 (2		
Model: PA-03	A6	150g/m ²	50pcs	gloss
Photo paper Model: PA-04	A6	180g/m²	50pcs	gloss
Photo paper Model: PA-05	A6	210g/m²	50pcs	gloss
Photo paper			•	
Model: PA-17	A6	260g/m ²	20pcs	gloss
Photo paper Model: PA-06	A4	180g/m²	20pcs	matt
Photo paper				
Model: PA-07	A4	180g/m ²	20pcs	gloss
Photo paper				
Model: PA-08	A4	210g/m ²	20pcs	gloss
Photo paper		150 (2		
Model: PA-09	A4	150g/m ²	50pcs	gloss
Photo paper	Δ.4	220 /2	50555	
Model: PA-10	A4	220g/m ²	50pcs	matt both sides
Photo paper Model: PA-11	A4	128g/m²	100pcs	matt
Photo paper				
Model: PA-12	A4	210g/m ²	50pcs	gloss
Photo paper Model: PA-13	A4	115g/m²	100pcs	gloss
Photo paper				
Model: PA-14	A4	150g/m²	100pcs	gloss
Photo paper				<u>.</u>
Model: PA-15	A4	180g/m ²	100pcs	gloss
Photo paper	A4	260g/m²	20pcs	alocc
Model: PA-16	A4	200g/III-	20008	gloss



Hand 3D printer

Model: DRP-040

- ▼ Type of supported filaments: ABS/PLA
- The diameter of the printing nozzle: 0.7mm
- Work temperature range: from 160°C to 230°C
- ◆ AC adapter: AC-110-230V, DC12V

The content of the package:

- ◆ Hand 3D printer Savio DRP-04 Creative Design
- AC Adapter
- Desk stand
- 3 colours filament
- User manual

What can you do with the Savio 3D pen?

Printing with a Savio 3D pen is incredible fun. It allows to put a drawing into a 3D world. The 3D print is at your fingertips, and imagination is your only limit. Start to create dimensional solids, toys an even a jewellery. Start a 3D fun creating and drawing whatever You like.

Set of filaments for 3D printers 6x3m Full Color

Model: DRP-041

- **⊘** ABS, 1.75mm
- 6 colours x 3m. Black Red Yellow Blue

Green Pink



Cable organizer, black, 10m

Model: OC-01/B Black

Cable organizer, black, 3m

Model: OC-02/B Black

- Cable and cords organiser in shape of tape with
- Can be used multiple times
- Possible to cut and adjust the right length of tape to any bundle and diameter of wires.
- Example use: Ting the cords in one beam.





Set of filaments for 3D printers 6x3m transparent

Model: DRP-042

- 6 colours x 3m: Green Blue Red Orange

Yellow Ivorv



High-quality ABS filament of a 1.75mm diameter. Fits all devices working on materials of this diameter. It is recommended for 3D pens as well as 3D printers. Recommended temperature of print: from 180°C to 230°C

Cable organizer, Grey, 10m

Model: OC-03/B Grey

Cable organizer, Grey, 3m

Model: OC-04/B Grey

- Cable and cords organiser in shape of tape wit
- Can be used multiple times
- OPossible to cut and adjust the suitable length of tape to any bundle and diameter of wires.
- Example use: Ting the cords in one beam.





SAVIO GAMING

PROFESSIONAL GAMING MOUSEPADS

Two versions of surface:

- Turbo Dynamic (mouse pad surface that provides better dynamic),
- Precision Control (mouse pad surface that provides better precision).

Anti-slip rubber base keeps the mouse pad from sliding during use. High quality material provides high precision and smooth

the motion of a mouse.

Stitched edge design provides durability and prevents edge fraying during intensive use.

The texture of the mouse pad surface works with all kinds of mouse sensors.



TWO VERSIONS OF SURFACE




SPEED TYPE SURFACE ENSURES FAST MOVEMENT



CONTROL TYPE SURFACE ENSURES PRECISE MOVEMENT

PRECISION CONTROL

Model: GTDXXLL 500x1000mm 3mm





SAVIO GAMING



TEMPEST RX MECHANICAL KEYBOARDS







Gaming keyboard TEMPEST RX Switch Outemu Blue

Model: TEMPEST RX BLUE

Gaming keyboard TEMPEST RX Switch Outemu Red


Model: TEMPEST RX RED

Gaming keyboard TEMPEST RX Switch Outemu Brown

Model: TEMPEST RX BROWN

Interfejs: USB
Przełączniki: Outemu Blue/Red/Brown
(w zależności od modelu)
Ilość klawiszy: 87
Żywotność klawiszy: 50 000 000 kliknięć
Długość kabla: 1,5m
Wymiary klawiatury: 357x125x38mm
Waga klawiatury: 830g
Układ klawiszy: US






3 COLORS OF BACKLIGHTS

Blue - for switches OUTEMU Blue Green - for switches OUTEMU Brown Red - for switches OUTEMU Red





Switch BLUE - is the most classic. It has a palpable activation moment with a simultaneous click.

Switch RED - is the quietest. It is a linear, fluent switch. There is no perceptible moment of activation. Switch RED is perfect for text writing.

Switch BROWN - is a compromise. It is a silent switch, you can feel the delicate response at the time of activation.

SAVIO GAMING

TKL (TENKEYLESS)

The advanced mechanical keyboard TK is a short tournament keyboard, without a number block and was created for players by players.

Thanks to this solution you have more space on your desk and you do not feel a lack of comfort when you play.



357x125x38mm



FULL ANTI-GHOSTING

We used **Anti-Ghosting** and **N-KRO**(N-Key Rollover technology) in our keyboards.
It means that each key is registered regardless of the number of keys pressed. That technology and used WinKey lock are helpful during virtual games.

10 MODES BACKLIGHT



Remarkable lighting effects and the ability to personalize the backlight of the keys to your needs, stable metal surface will increase comfort during use, regardless of the color version and switches.



Model: VFRTIGO

Type of headset: Virtual 7.1 Kind of headset: Closed Interface: USB Cable length: 2,4m Weight: 370g

Technical specification of headset Speaker diameter: 50mm Impedance: 320hm +/- 15% Sensitivity: 116dB +/- 3dB Frequency range: 20Hz - 20000Hz

Technical specification of microphone Impedance: 2.2kOhm Sensitivity:: -56dB +/- 2dB Frequency range: 20Hz - 20000Hz Microphone type: Retractable



RETRACTABLE MICROPHONE



PILOT NA KABLU





7.1 Virtual Surround technology allows with incredible precision to determine the direction from which sounds arrive, as well as its distance and depth. It is thanks to this you will ensure a clear advantage over your opponents in every game. Modern design, lightweight construction, and contoured, soft ear pads make the VERTIGO synonymous with uncompromising comfort and high-quality sound.

Take the fun to a higher level, plunge into a virtual fight and enjoy the game like never before.

STRIKE PROFESSIONAL GAMING HEADSET

Model: STRIKE

Type of headset: Stereo Kind of headset: Closed Interface: Jack 2 x 3,5mm + USB Cable length: 2m Weight: 350g

Technical specification of headset Speaker diameter: 40mm Impedance: 320hm +/- 15% Sensitivity: 118dB +/- 3dB Frequency range: 20Hz - 20000Hz

Technical specification of microphone Impedance: 2.2kOhm Sensitivity: -36dB +/- 3dB Frequency range: 20Hz - 20000Hz



VERY LIGHT AND COMFORTABLE SHAPE



RETRACTABLE MICROPHONE



FORGE PROFESSIONAL GAMING HEADSET

Model: FORGE

Type of headset: Stereo
Kind of headset: Closed
Interface: Jack 3,5mm + PC adapter

Cable length: 2,2m Weight: 350g

Technical specification of headset Speaker diameter: 50mm Impedance: 320hm +/- 15% Sensitivity: 105dB +/- 3dB Frequency range: 20Hz - 20000Hz

Technical specification of microphone Impedance: 2.2kOhm Sensitivity: -42dB +/- 3dB Frequency range: 10Hz - 16000Hz



VERY LIGHT AND COMFORTABLE SHAPE



RETRACTABLE MICROPHONE



COMPATIBLE WITH: PLAYSTATION, XBOX, PC, LAPTOP, SMARTPHONE



DEDICATED HDMI v2.0 CABLES



HDMI V2.0 HIGH SPEED WITH ETHERNET

Ethernet support up to 100 Mb / sec.

3D image support, Deep Color and HDR

Audio Return Channel

Dolby TrueHD and DTS-HD Master Audio multi-channel

audio support

Supports high resolutions up to 4K x 2K (max 4096x2160p

60 Hz and 1080p@240 Hz)

Maximum signal bandwidth: 600MHz Maximum bit rate TMDS: 18.00Gbit /s

Maximum video bit rate:14.40Gbit /s

HDR

Dual View & 4 audio streams

Gold plated plugs 24k

Full shielding of signal wires – resistant to external interference OFC oxygen-free conductors with a high degree of purity (99.96%) No loss in the transmission of high image and sound quality

Compatible with previous versions 1.0-1.4

Example use:

Transfer of the video and sound from a computer, console, laptop, tuner, DVBT to the TV.

HDMI cable v2.0, 1,8m

Model: GCL-01	HDMI A male	30 AWG	OD: 6.0mm	PC	_
HDMI cable v2.0, 1,8m					
Model: GCL-02	HDMI A male	30 AWG	OD: 6.0mm	PlayStation	\
HDMI cable v2.0, 1,8m					
Model: GCL-03	HDMI A male	30 AWG	OD: 6.0mm	Xbox	\
HDMI cabl	e v2.0, 3r	n			
Model: GCL-04	HDMI A male	30 AWG	OD: 6.0mm	PC	`
HDMI cable v2.0, 3m					
Model: GCL-05	HDMI A male	30 AWG	OD: 6.0mm	PlayStation	1
HDMI cable v2.0, 3m					
Model: GCL-06	HDMI A male	30 AWG	OD: 6.0mm	Xbox	1








Packaging types

Cardboard bands



String bags



String bags in two sizes additionally there is a detailed specification written on the back.

Packaging types



Plastic blisters with euro hole. The name is written in two languages with the most important information marked.

There is also a detailed specification placed on the back.



www.savio.net.pl 37

There are at least four reasons, that you should introduce Savio products to your company offer:



It sometimes happens that neither the client nor the salesman knows exactly what cable they need to connect two devices. It is not a surprise, with a huge amount of types of connectors and standards of signal transmission in connection. With every cable and adapter Savio, you will find a precise explanation, of what you can connect with it. All the information is right on the package, as well as in the product catalogue and on the internet site. Also, products from other categories have detailed information about their functions and applications.



In Savio, every lot of our products is precisely checked before introducing it on the market.


Our employees conduct tests of all technical parameters and functionality of our particular products.

We specifically pay attention to safety and durability for overload and voltage spikes.

Results of every test are saved and recorded, and based on them the decisions are made about optimising of production method.



Thanks to the very small number of complaints, we give a warranty, that every complaint will be dealt with by our service in 48 hours from the moment of receiving the parcel. In this time we will check the reason of complaint, we will qualify it (repair, exchange, correction invoice) and we will send the return parcel and will inform you about the course of the case, that you immediately can contact with your client. The term warranty covers the working days and does not apply to individual customers.



Why our prices are low? Because we worked out great conditions of cooperation with our partners, and to prices of our products we do not have to add a cost of a satin layout of the package or a television advertisement, sponsor actions, banquets and payments for the celebrities pretending to recommend us.

We give you the maximum "product in the product". And why not always we are the cheapest?

Because we do not want to introduce products to the market, that do not meet the declared parameters, that always get broken, and are not safe to use.

Brand owner: Elmak Sp. z o.o.

ul. Morgowa 81 35-323 Rzeszów

tel. +48(17)7844037 tel./fax. +48(17)8549814

e-mail: elmak@elmak.pl www.elmak.pl

Sales department: Al. Żołnierzy I Armii Wojska Polskiego 22 35-30 I Rzeszów

> tel. +48 (17)7779599 e-mail: zamowienia@elmak.pl

www.savio.net.pl