



### **CAT-5E Patch Cords**

- Exceeds ANSI/TIA/EIA 568-C.2
- Exceeds ISO 11801 CLASS D
- Stranded 24 AWG UTP, CMR Rated
- Universal Wiring T568A/B
- 200 MHz Factory Tested
- Superior Performance

### **Technical Specifications**

NEWLINK patch cords meet the communication's most stringent requirements and exceed them with enhanced technical characteristics. Flexibility, resilience, perfect geometry matching, gold plated contacts, fire-retardant jacket, low resistance copper stranded conductors and many other details are the base for this product series. Available in attractive colors for easy identification. Most used lengths available from stock. Special dimensions available upon request, minimum orders apply.

- 4-pair straight universal termination
- Exceeds TIA/EIA568-C.2-1CAT5E performance
- Exceeds ISO/IEC 11801:2002 Class D
- Very low Insertion Loss
- Superior Extra NEXT and ACR Headroom
- 24 AWG stranded UTP construction
- CMR Rated jacket
- Meets TIA-968-A and IEC 60603-7
- 50 micro-inches gold plated contacts
- Excellent bend relief colored boots
- Available colors: blue, gray, red, green, yellow
- Available lengths: (1, 2, 3, 7, 10 feet)

### **Supported Applications**

- Voice, Fax, T1, ISDN
- 10BASE-T
- 100BASE-TX, 100BASE-T4, 100VG-AnyLan
- ATM-25, ATM-51, ATM-155
- 1000BASE-T

### **Ordering Information**

- NEW-158XXYY Newlink Patch Cord Cat 5e 50um

Where:      XX      = length in Feet (1, 2, 3, 7 or 10Ft)  
              YY      = color (BL = blue, GY = grey, RD = red, YW = yellow, GN = green)