



MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time				
(MHz)	Strength (V/m)	m) Strength (A/m) (mW/cm²)		(minute)				
Limits for General Population/Uncontrolled Exposure								
0.3-1.34	614	1.63	*(100)	30				
1.34-30	824/f	2.19/f	*(180/f ²)	30				
30-300	27.5	0.073	0.2	30				
300-1500	/	/	F/1500	30				
1500-15000	/	/	1.0	30				

F = frequency in MHz

Prediction of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S=PG/4\pi R^2$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or ap-

pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279

f (886-2) 2298-0488

^{* =} Plane-wave equipment power density





802.11n_HT20 Max. output power (Worst Case)

802.11n HT20 Main

	_						
СН	Frequency (MHz)	Data Rate	TOTAL POWER (dBm)		REQUIRED LIMIT (dBm)		RESULT
36	5180	MCS0	10.72	23.98		PASS	
44	5220	MCS0	10.70	23.98		PASS	
48	5240	MCS0	10.68	23.98		PASS	
52	5260	MCS0	10.70	23.98	or 11+10log(B) =	23.47	PASS
60	5300	MCS0	10.73	23.98	or 11+10log(B) =	23.52	PASS
64	5320	MCS0	10.59	23.98	or 11+10log(B) =	23.48	PASS
100	5500	MCS0	10.51	23.98	or $11+10\log(B) =$	23.57	PASS
116	5580	MCS0	10.71	23.98	or 11+10log(B) =	23.52	PASS
140	5700	MCS0	10.45	23.98	or 11+10log(B) =	23.49	PASS
149	5745	MCS0	10.65	30		PASS	
157	5785	MCS0	10.73	30		PASS	
165	5825	MCS0	10.66	30		PASS	

MPE Prediction (802.11a_HT20 5725~5850)

Average output power at antenna input terminal:	10.73	(dBm)
Average output power at antenna input terminal:	11.830416	(mW)
Duty cycle:	86.2	(%)
Maximum Pav :	10.197818	(mW)
Peak Antenna gain (Maximum):	2	(dBi)
Peak Antenna gain (linear):	1.5848932	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5785	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.003	(mW/cm2)
·-		

Measurement Result

The predicted power density level at 20 cm is 0.003 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5785MHz.

Note: This device doesn't support simultaneous transmission.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless otherwise stated the results shown in this test report reter only to the sample(s) tested and sucn sample(s) are retained for 90 days only. 除非另有說明,此根告结果僅對測試之樣品負責,同時此樣品僅保留的天。本根告未經本公司書面許可,不可可的夜糧型。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appropriate in planting and approval of the law pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279