

## LED Lamps

### ProLED T8 Linear Type-A

- 2', 3', 4' Options
- No Re-Wiring Necessary
- Instant On - No Flicker
- 5-Year Warranty

### Specifications

#### Product Description

The QuickConnect Type A lamp operates on most instant start and electronic ballasts, making LED lighting retrofit easier than ever.

#### Construction:

- Glass Lens
- 2', 3' and 4' Metal End Caps

#### Installation:

- Quick Plug&Play Installation
- Refer to ballast Compatibility Chart for Compatible Ballasts
- Suitable for use in Totally Enclosed Luminaires



Easy To Install



Food Equipment Certification



50,000 Hours



Direct Ballast Compatible



Intertek 4005203  
CONFORMS TO IEC 61324  
Made in China



DLC Qualified

#### Performance

- Operates on Compatible T8 Instant Start, Programmed Start and Emergency Ballasts
- 120-277V
- 8W, 11W, 12W Option (2', 3', 4')
- 1325 - 2000 Lumens
- L70>50,000
- 82 CRI
- Dimmable (4' only)

#### Certifications:

- cUL Approved for Damp Locations
- Conforms to Requirements of NSF/ANSI Standard 2 Food Equipment
- DLC Qualified. Refer to [designlights.org](http://designlights.org) for Full List of Qualified Products.
- 5 Year Warranty



## ProLED T8 Linear Type-A

### Ordering Logic

#### Product Description

Lamp Size and Wattage	CCT	Lamp Type	Source
<b>T824FR8</b> = 2' 8W <b>T836FR10</b> = 3' 11W <b>T824FR13</b> = 4' 12W	<b>835</b> = 82 CRI, 3500K <b>840</b> = 82 CRI, 4000K <b>850</b> = 82 CRI, 5000K	<b>DIR</b> = Direct Replacement	<b>LED</b> = LED Source

### Stock Guide

Watt	System Watt	Base	Product #	Product Code	Description	Voltage	CCT	CRI	Lumens	Useful Life	Pkg. Qty.	MOL	Equivalent Wattage	End Cap
8	11	G13	82355	T824FR8/835/DIR3/LED	T8 Linear QuickConnect 3500K	120-277V	3500K	82	1325	50,000	1/25	24"	17	Metal
8	11	G13	82356	T824FR8/840/DIR3/LED	T8 Linear QuickConnect 4000K	120-277V	4000K	82	1350	50,000	1/25	24"	17	Metal
8	11	G13	82357	T824FR8/850/DIR3/LED	T8 Linear QuickConnect 5000K	120-277V	5000K	82	1350	50,000	1/25	24"	17	Metal
11	14	G13	82358	T836FR11/835/DIR3/LED	T8 Linear QuickConnect 3500K	120-277V	3500K	82	1675	50,000	1/25	36"	25	Metal
11	14	G13	82359	T836FR11/840/DIR3/LED	T8 Linear QuickConnect 4000K	120-277V	4000K	82	1700	50,000	1/25	36"	25	Metal
11	14	G13	82360	T836FR11/850/DIR3/LED	T8 Linear QuickConnect 5000K	120-277V	5000K	82	1700	50,000	1/25	36"	25	Metal
12	14	G13	83880	T8FR12/835/DIR4/LED	T8 Linear QuickConnect 3500K	120-277V	3500K	82	1800	50,000	1/25	48"	32	Metal
12	14	G13	83881	T8FR12/840/DIR4/LED	T8 Linear QuickConnect 4000K	120-277V	4000K	82	1900	50,000	1/25	48"	32	Metal
12	14	G13	83882	T8FR12/850/DIR4/LED	T8 Linear QuickConnect 5000K	120-277V	5000K	82	2000	50,000	1/25	48"	32	Metal

### Dimensions

\* For more detail visit installation instructions

