

Continuous Hot Water Invisible Comfort

The Greentherm 9000 Series brings homeowners more than endless hot water. It saves time, money, space and unnecessary stress.

Meet the Greentherm 9000 Series

From its gorgeous exterior to the sophisticated technology on the inside, the Greentherm 9000 water heater was designed to impress. It can deliver endless hot water and dazzle you with features never seen on a water heater before.

Features

- ▶ Space-saving, state-of-the-art tankless design
- ▶ Industry leading efficiency rating of 0.97 UEF
- ▶ High resolution color LCD interface
- ▶ Wi-Fi accessory & App increases functionality
- ▶ Ability to control external pumps
- ▶ Industry leading 22:1 turn down ratio
- ▶ 60ft venting using 2" pipe
- ▶ Ultra Low NOx Certified
- ▶ Integrated freeze protection
- ▶ Stainless Steel condensing heat exchanger
- ▶ Dedicated outdoor unit eliminates the cost of a vent kit



Professional Benefits

- ▶ Top water connections for easy tank replacement
- ▶ Included LP conversion kit
- ▶ Auto-tuning for optimal performance
- ▶ Integrated flush ports and included PRV



Greentherm T9800 SE outdoor


Greentherm T9800/9900 SE Indoor

Greentherm T9900i SE indoor

Built To Make Things Easy

Designed For Comfort Inside & Out

With top water connections, a built-in recirculation pump, WiFi, auto-tuning, and a sleek design, the Greentherm 9000 Series is designed for ultimate ease.



Greentherm 9000 Series							
Technical Specifications	T9900i SE 199	T9900 SE 199	T9900 SE 160	T9800 SE 199	T9800 SE 160	T9800 SEO 199	T9800 SEO 160
Part Number	7736503732	7736503731	7736503730	7736503581	7736503725	7736503727	7736503726
NG Min-Max input (kBtu)	9-199	9-199	9-160	9-199	9-160	9-199	9-160
Uniform Energy factor	0.96	0.96	0.97	0.96	0.97	0.96	0.97
Dimension (W x H x D)	18 9/16" x 31 1/2" x 9 13/16"						
Temperature range	100-140 °F						
Temperature stability	+/- 2 °F						
Activation water flow rate	0.45GPM						
Required NG pressure	3.5" - 10.5"						
Required LPG pressure	8" - 13"						
Recirculation pump	✓	✓	✓	-	-	-	-
Electrical requirements	120 VAC 60Hz						
Noise level	<57 dB						
Max flue length	Twin pipe	2": 60ft + 60ft; 3": 280ft + 280ft					
	Concentric pipe	2"/4": 60ft; 3"/5": 280ft					

Wi-Fi Connection

The Greentherm 9000 app allows you to remotely control the water temp, activate the recirculation pump, and monitor usage and sensor values.



(2) WiFi connectivity can be built-in or optional. (3) Integrated pump only on T9900 models (4) Glass cover only on T9900i model