

Cisco Secure Firewall Threat Defense Compatibility Guide

First Published: 2022-05-05 **Last Modified**: 2023-09-29

Cisco Secure Firewall Threat Defense Compatibility Guide

This guide provides software and hardware compatibility for Cisco Secure Firewall Threat Defense. For related compatibility guides, see Additional Resources, on page 1.



Note

Not all software versions, especially patches, apply to all platforms. A quick way to tell if a version is supported is that its upgrade/installation packages are posted on the Cisco Support & Download site. If the site is "missing" an upgrade or installation package, that version is not supported. You can also check the release notes and End-of-Life Announcements, on page 30. If you feel a version is missing in error, contact Cisco TAC.

Additional Resources

Table 1:

Description	Resources
Sustaining bulletins provide support timelines for the Cisco Next Generation Firewall product line, including management platforms and operating systems.	Cisco NGFW Product Line Software Release and Sustaining Bulletin
Compatibility guides provide detailed compatibility information for supported hardware models and software versions, including bundled components and integrated products.	Cisco Secure Firewall Management Center Compatibility Guide Cisco Firepower 4100/9300 FXOS Compatibility
Release notes provide critical and release-specific information, including upgrade warnings and behavior changes. Release notes also contain quicklinks to upgrade and installation instructions.	Cisco Secure Firewall Threat Defense Release Notes Cisco Firepower 4100/9300 FXOS Release Notes
New Feature guides provide information on new and deprecated features by release.	Cisco Secure Firewall Management Center New Features by Release Cisco Secure Firewall Device Manager New Features by Release

Description	Resources
Documentation roadmaps provide links to currently available and legacy documentation. Try the roadmaps if what you are looking for is not listed above.	Navigating the Cisco Secure Firewall Threat Defense Documentation Navigating the Cisco FXOS Documentation

Threat Defense Platform Summary

These tables summarize the supported devices and management methods for threat defense. For details on device management, including managing an older device with a newer management center, see Threat Defense Management, on page 12.



Note

Version 7.4.0 is available *only* on the Secure Firewall Management Center and the Secure Firewall 4200. A Version 7.4.0 management center can manage older versions of other device models, but you **must** use a Secure Firewall 4200 for features that require threat defense 7.4.0.

Threat Defense Hardware

Table 2: Secure Firewall Threat Defense Hardware by Manager and Version

Device Platform	Device Versions: W Center	ith Management	Device Versions: With Device Manager		
	Customer-Deployed Management Center	Cloud-delivered Firewall Management Center *	Device Manager Only	Device Manager + CDO	
Firepower 1010, 1120, 1140	6.4+	7.0.3+	6.4+	6.4+	
Firepower 1010E	7.2.3+	7.2.3+	7.2.3+	7.2.3+	
	No support in 7.3	No support in 7.3	No support in 7.3	No support in 7.3	
Firepower 1150	6.5+	7.0.3+	6.5+	6.5+	
Firepower 2110, 2120, 2130, 2140	6.2.1+	7.0.3+	6.2.1+	6.4+	
Secure Firewall 3105	7.3.1+	7.3.1+	7.3.1+	7.3.1+	
Secure Firewall 3110, 3120, 3130, 3140	7.1+	7.0.3+	7.1+	7.1+	
Firepower 4110, 4120, 4140	6.0.1 to 7.2	7.2+	6.5 to 7.2	6.5 to 7.2	
Firepower 4150	6.1 to 7.2	7.2+	6.5 to 7.2	6.5 to 7.2	

Device Platform	Device Versions: W Center	ith Management	Device Versions: With Device Manage		
	Customer-Deployed Management Center	Cloud-delivered Firewall Management Center *	Device Manager Only	Device Manager + CDO	
Firepower 4115, 4125, 4145	6.4+	7.0.3+	6.5+	6.5+	
Firepower 4112	6.6+	7.0.3+	6.6+	6.6+	
Secure Firewall 4215, 4225, 4245	7.4.0+	7.4.0+	_	_	
Firepower 9300: SM-24, SM-36, SM-44	6.0.1 to 7.2	7.0.3+	6.5 to 7.2	6.5 to 7.2	
Firepower 9300: SM-40, SM-48, SM-56	6.4+	7.0.3+	6.5+	6.5+	
ISA 3000	6.2.3+	7.0.3+	6.2.3+	6.4+	
ASA 5506-X, 5506H-X, 5506W-X	6.0.1 to 6.2.3	_	6.1 to 6.2.3	_	
ASA 5508-X, 5516-X	6.0.1 to 7.0	7.0.3 to 7.0.x	6.1 to 7.0	6.4 to 7.0	
ASA 5512-X	6.0.1 to 6.2.3	_	6.1 to 6.2.3	_	
ASA 5515-X	6.0.1 to 6.4	_	6.1 to 6.4	6.4	
ASA 5525-X, 5545-X, 5555-X	6.0.1 to 6.6	_	6.1 to 6.6	6.4 to 6.6	

^{*} The cloud-delivered Firewall Management Center cannot manage threat defense devices running Version 7.1, or Classic devices running any version. You cannot upgrade a cloud-managed device from Version 7.0.x to Version 7.1 unless you unregister and disable cloud management. We recommend you upgrade the device directly to Version 7.2+.

Threat Defense Virtual

Table 3: Threat Defense Virtual by Manager and Version

Device Platform	Device Versions: W Center	ith Management	Device Versions: With Device Manager		
	Customer-Deployed Management Center	Cloud-delivered Firewall Management Center *	Device Manager Only	Device Manager + CDO	
Public Cloud	,		-		

Device Platform	Device Versions: W Center	ith Management	Device Versions: With Device Manage		
	Customer-Deployed Management Center	Cloud-delivered Firewall Management Center *	Device Manager Only	Device Manager + CDO	
Alibaba	7.2+	7.2+	_	<u> </u>	
AWS	6.0.1+	7.0.3+	6.6+	6.6+	
Azure	6.2+	7.0.3+	6.5+	6.5+	
GCP	6.7+	7.0.3+	7.2+	7.2+	
OCI	6.7+	7.0.3+	_	_	
On-Prem/Private Cl	oud	1			
HyperFlex	7.0+	7.0.3+	7.0+	7.0+	
KVM	6.1+	7.0.3+	6.2.3+	6.4+	
Nutanix	7.0+	7.0.3+	7.0+	7.0+	
OpenStack	7.0+	7.0.3+	_	_	
VMware 7.0	7.0+	7.0.3+	7.0+	7.0+	
VMware 6.7	6.5+	7.0.3+	6.5+	6.5+	
VMware 6.5	6.2.3+	7.0.3+	6.2.3+	6.4+	
VMware 6.0	6.0 to 6.7	_	6.2.2 to 6.7	6.4 to 6.7	
VMware 5.5	6.0.1 to 6.2.3	_	6.2.2 to 6.2.3	_	
VMware 5.1	6.0.1 only	_	_	_	

^{*} The cloud-delivered Firewall Management Center cannot manage threat defense devices running Version 7.1, or Classic devices running any version. You cannot upgrade a cloud-managed device from Version 7.0.x to Version 7.1 unless you unregister and disable cloud management. We recommend you upgrade the device directly to Version 7.2+.

Threat Defense Hardware

Firepower 1000/2100 Series

Firepower 1000/2100 series devices use the FXOS operating system. Upgrading threat defense automatically upgrades FXOS. For information on bundled FXOS versions, see Bundled Components, on page 15.

These devices can also run ASA instead of threat defense; see Cisco Secure Firewall ASA Compatibility.

Table 4: Firepower 1000/2100 Series Compatibility

Threat Defense	Firepower 1150	Firepower 1010E	Firepower 1010 Firepower 1120 Firepower 1140	Firepower 2110 Firepower 2120 Firepower 2130 Firepower 2140
7.4	_	_	_	_
7.3	YES	_	YES	YES
7.2	YES	YES Requires 7.2.3+	YES	YES
7.1	YES	_	YES	YES
7.0	YES	_	YES	YES
6.7	YES	_	YES	YES
6.6	YES	_	YES	YES
6.5	YES	_	YES	YES
6.4	_	_	YES	YES
6.3	_	_	_	YES
6.2.3	_	_	_	YES
6.2.2	_	_	_	YES
6.2.1	_	_	_	YES

Secure Firewall 3100/4200 Series

Secure Firewall 3100/4200 series devices use the FXOS operating system. Upgrading threat defense automatically upgrades FXOS. For information on bundled FXOS versions, see Bundled Components, on page 15.

These devices can also run ASA instead of threat defense; see Cisco Secure Firewall ASA Compatibility.

Table 5: Secure Firewall 3100/4200 Series Compatibility

Threat Defense	Secure Firewall 4215 Secure Firewall 4225 Secure Firewall 4245	Secure Firewall 3105	Secure Firewall 3110 Secure Firewall 3120 Secure Firewall 3130 Secure Firewall 3140
7.4	YES	_	_
7.3	_	YES	YES

Threat Defense	Secure Firewall 4215 Secure Firewall 4225 Secure Firewall 4245	Secure Firewall 3105	Secure Firewall 3110 Secure Firewall 3120 Secure Firewall 3130 Secure Firewall 3140
7.2	_	_	YES
7.1	_	_	YES

Firepower 4100/9300

For the Firepower 4100/9300, major threat defense versions have a specially qualified and **recommended** companion FXOS version, listed below in **bold**. Use these combinations whenever possible, because we perform enhanced testing for them.

These devices can also run ASA instead of threat defense. With ASA 9.12+ and threat defense 6.4.0+, you can run both ASA and threat defense on separate modules in the same Firepower 9300 chassis. For more information, see Cisco Firepower 4100/9300 FXOS Compatibility.

To resolve issues, you may need to upgrade FXOS to the latest build. To help you decide, see the Cisco Firepower 4100/9300 FXOS Release Notes.



Note

To perform flow offload in the following major version sequences, you must be running a specific combination of threat defense and FXOS:

- Version 6.2.2.x: Version 6.2.2.2+ on FXOS 2.3.1.130+
- Version 6.2.0.x: Version 6.2.0.3+ on either FXOS 2.2.1.x or FXOS 2.2.2, builds 17-86

Table 6: Firepower 4100/9300 Compatibility

Threat	FXOS	Firepower	9300	Firepower 4100 Series			
Defense		SM-24	SM-40	4110	4150	4112	4115
		SM-36	SM-48	4120			4125
		SM-44	SM-56	4140			4145
7.4	_	_	_	_	_	_	_
7.3	2.13.0.198+	_	YES	_	<u> </u>	YES	YES
7.2	2.12.0.31+	YES	YES	YES	YES	YES	YES
	2.13.0.198+	no 2.13+		no 2.13+	no 2.13+		
7.1	2.11.1.154+	YES	YES	YES	YES	YES	YES
	2.12.0.31+	no 2.13+		no 2.13+	no 2.13+		
	2.13.0.198+						

Threat	FXOS	Firepower	9300	Firepower 4100 Series			
Defense		SM-24	SM-40	4110	4150	4112	4115
		SM-36	SM-48	4120			4125
		SM-44	SM-56	4140			4145
7.0	2.10.1.159+	YES	YES	YES	YES	YES	YES
	2.11.1.154+	no 2.13+		no 2.13+	no 2.13+		
	2.12.0.31+						
	2.13.0.198+						
6.7	2.9.1.131+	YES	YES	YES	YES	YES	YES
	2.10.1.159+	no 2.13+		no 2.13+	no 2.13+		
	2.11.1.154+						
	2.12.0.31+						
	2.13.0.198+						
6.6	2.8.1.105+	YES	YES	YES	YES	YES	YES
	2.9.1.131+	no 2.13+		no 2.13+	no 2.13+		
	2.10.1.159+						
	2.11.1.154+						
	2.12.0.31+						
	2.13.0.198+						
6.5	2.7.1.92+	YES	YES	YES	YES	_	YES
	2.8.1.105+						
	2.9.1.131+						
	2.10.1.159+						
	2.11.1.154+						
	2.12.0.31+						
6.4	2.6.1.157+	YES	YES	YES	YES		YES
	2.7.1.92+						
	2.8.1.105+						
	2.9.1.131+						
	2.10.1.159+						
	2.11.1.154+						
	2.12.0.31+						

Threat	FXOS	Firepowe	Firepower 9300		Firepower 4100 Series			
Defense		SM-24 SM-36 SM-44	SM-40 SM-48 SM-56	4110 4120 4140	4150	4112	4115 4125 4145	
6.3	2.4.1.214+	YES	_	YES	YES	_		
	2.6.1.157+							
	2.7.1.92+							
	2.8.1.105+							
	2.9.1.131+ 2.10.1.159+							
	2.10.1.139+							
	2.12.0.31+							
6.2.3	2.3.1.73+	YES		YES	YES			
0.2.3	2.4.1.214+	ILS		ILS	1 ES			
	2.6.1.157+							
	2.7.1.92+							
	2.8.1.105+							
	6.2 req FX	epower .3.16+ uires O\$.1.157+.						
6.2.2	2.2.2.x	YES		YES	YES			
	2.3.1.73+							
	2.4.1.214+							
	2.6.1.157+							
	2.7.1.92+							
6.2.1	_	_	_	_	_	_	_	
6.2.0	2.1.1.x, 2.2.1.x, 2.2.2.x	YES	_	YES	YES	_	_	
	2.3.1.73+							
	2.4.1.214+							
	2.6.1.157+							

Threat Defense	FXOS	Firepowe	Firepower 9300		Firepower 4100 Series			
		SM-24 SM-36 SM-44	SM-40 SM-48 SM-56	4110 4120 4140	4150	4112	4115 4125 4145	
6.1	2.0.1.x 2.1.1.x 2.3.1.73+	YES	_	YES	YES		_	
6.0.1	1.1.4.x 2.0.1.x	YES	_	YES	_	_	_	

ASA 5500-X Series and ISA 3000

ASA 5500-X series and ISA 3000 devices use the ASA operating system. Upgrading threat defense automatically upgrades ASA. For information on the bundled ASA versions, see Bundled Components, on page 15.

Version 7.0 is the last major threat defense release that supports ASA 5500-X series devices.

Table 7: ASA 5500-X Series and ISA 3000 Compatibility

Threat Defense	ISA 3000	ASA 5508-X	ASA 5525-X	ASA 5515-X	ASA 5506-X
		ASA 5516-X	ASA 5545-X		ASA 5506H-X
			ASA 5555-X		ASA 5506W-X
					ASA 5512-X
7.4	_	_	_	_	_
7.3	YES	_	_	_	_
7.2	YES	_	_	_	_
7.1	YES	_	_	_	_
7.0	YES	YES	_	_	_
6.7	YES	YES	_	_	_
6.6	YES	YES	YES	_	_
6.5	YES	YES	YES	_	_
6.4	YES	YES	YES	YES	_
6.3	YES	YES	YES	YES	_
6.2.3	YES	YES	YES	YES	YES
6.2.2	_	YES	YES	YES	YES

Threat Defense	ISA 3000	ASA 5508-X ASA 5516-X	ASA 5525-X ASA 5545-X ASA 5555-X	ASA 5515-X	ASA 5506-X ASA 5506H-X ASA 5506W-X ASA 5512-X
6.2.1	_	_		_	_
6.2.0	_	YES	YES	YES	YES
6.1		YES	YES	YES	YES
6.0.1	_	YES	YES	YES	YES

Threat Defense Virtual

In Version 7.0 and later, threat defense virtual supports performance-tiered Smart Software Licensing, based on throughput requirements and remote access VPN session limits. For more information on supported instances, throughputs, and other hosting requirements deployments, see the *Cisco Secure Firewall Threat Defense Virtual Getting Started Guide* for your version.

Table 8: Threat Defense Virtual Compatibility: Public Cloud

Threat Defense Virtual	Alibaba	Amazon Web Services (AWS)	Microsoft Azure (Azure)	Google Cloud Platform (GCP)	Oracle Cloud Infrastructure (OCI)
7.4	_	_	_	_	_
7.3	YES	YES	YES	YES	YES
7.2	YES	YES	YES	YES	YES
7.1	_	YES	YES	YES	YES
7.0	_	YES	YES	YES	YES
6.7	_	YES	YES	YES	YES
6.6	_	YES	YES	_	_
6.6	_	YES	YES	_	_
6.4	_	YES	YES	_	_
6.3	_	YES	YES	_	_
6.2.3	_	YES	YES	_	_
6.2.2	_	YES	YES	_	_
6.2.1	_	_	_	_	_
6.2	_	YES	YES	_	_

Threat Defense Virtual	Alibaba	Amazon Web Services (AWS)	Microsoft Azure (Azure)	Google Cloud Platform (GCP)	Oracle Cloud Infrastructure (OCI)
6.1	_	YES	_	_	_
6.0.1	_	YES	_	_	_

Table 9: Threat Defense Virtual Compatibility: On-Prem/Private Cloud

Threat Defense Virtual	VMware vSphere/VMware ESXi	Cisco HyperFlex (HyperFlex)	Kernel-Based Virtual Machine (KVM)	Nutanix Enterprise Cloud (Nutanix)	OpenStack
7.4	_	_	_	_	_
7.3	YES VMware 6.5, 6.7, 7.0	YES	YES	YES	YES
7.2	YES VMware 6.5, 6.7, 7.0	YES	YES	YES	YES
7.1	YES VMware 6.5, 6.7, 7.0	YES	YES	YES	YES
7.0	YES VMware 6.5, 6.7, 7.0	YES	YES	YES	YES
6.7	YES VMware 6.0, 6.5, 6.7	_	YES	_	_
6.6	YES VMware 6.0, 6.5, 6.7	_	YES	_	_
6.5	YES VMware 6.0, 6.5, 6.7	_	YES	_	_
6.4	YES VMware 6.0, 6.5	_	YES	_	_
6.3	YES VMware 6.0, 6.5	_	YES	_	_

Threat Defense Virtual	VMware vSphere/VMware ESXi	Cisco HyperFlex (HyperFlex)	Kernel-Based Virtual Machine (KVM)	Nutanix Enterprise Cloud (Nutanix)	OpenStack
6.2.3	YES VMware 5.5, 6.0, 6.5	_	YES	_	_
6.2.2	YES VMware 5.5, 6.0	_	YES	_	_
6.2.1	_	_	_	_	_
6.2.0	YES VMware 5.5, 6.0	_	YES	_	
6.1	YES VMware 5.5, 6.0	_	YES	_	_
6.0.1	YES VMware 5.1, 5.5	_	_	_	_

Threat Defense Management

Depending on device model and version, we support several management methods.

Customer-Deployed Management Center

All devices support remote management with a customer-deployed management center, which must run the *same or newer* version as its managed devices. This means:

- You *can* manage older devices with a newer management center, usually a few major versions back. However, we recommend you always update your entire deployment. New features and resolved issues often require the latest release on both the management center and its managed devices.
- You *cannot* upgrade a device past the management center. Even for maintenance (third-digit) releases, you must upgrade the management center first.

Note that in most cases you can upgrade an older device directly to the management center's major or maintenance version. However, sometimes you can manage an older device that you cannot directly upgrade, even though the target version is supported on the device. And rarely, there are issues with specific management center-device combinations. For release-specific requirements, see the release notes.

Table 10: Customer-Deployed Management Center-Device Compatibility

Management Center Version	Oldest Device Version You Can Manage
7.4	7.0
7.3	6.7

Management Center Version	Oldest Device Version You Can Manage
7.2	6.6
7.1	6.5
7.0	6.4
6.7	6.3
6.6	6.2.3
6.5	6.2.3
6.4	6.1
6.3	6.1
6.2.3	6.1
6.2.2	6.1
6.2.1	6.1
6.2	6.1
6.1	5.4.0.2/5.4.1.1
6.0.1	5.4.0.2/5.4.1.1
6.0	5.4.0.2/5.4.1.1
5.4.1	5.4.1 for ASA FirePOWER on the ASA-5506-X series, ASA5508-X, and ASA5516-X.
	5.3.1 for ASA FirePOWER on the ASA5512-X, ASA5515-X, ASA5525-X, ASA5545-X, ASA5555-X, and ASA-5585-X series.
	5.3.0 for Firepower 7000/8000 series and legacy devices.

Cloud-delivered Firewall Management Center

The cloud-delivered Firewall Management Center can manage threat defense devices running:

- Version 7.2+
- Version 7.0.3 and later maintenance releases

The cloud-delivered Firewall Management Center cannot manage threat defense devices running Version 7.1, or Classic devices running any version. You cannot upgrade a cloud-managed device from Version 7.0.x to Version 7.1 unless you unregister and disable cloud management. We recommend you upgrade the device directly to Version 7.2+.

You can add a cloud-managed device to a Version 7.2+ customer-deployed management center for event logging and analytics purposes only. Or, you can send security events to the Cisco cloud with Security Analytics and Logging (SaaS).

Device Manager

You can use the Secure Firewall device manager to locally manage a single threat defense device.

Optionally, add Cisco Defense Orchestrator (CDO) to remotely manage multiple threat defense devices, as an alternative to the management center. Although some configurations still require device manager, CDO allows you to establish and maintain consistent security policies across your threat defense deployment.

Threat Defense High Availability and Clustering

These tables list threat defense support for high availability and clustering. For threat defense hardware, support differs depending on whether you are using standalone devices (also called native instances or application mode) or container instances (also called multi-instance mode). Threat defense virtual does not support container instances.

Standalone Devices

This table lists threat defense hardware support for high availability and clustering with standalone devices. In management center deployments, all threat defense hardware supports high availability. For device manager, high availability support begins in Version 6.3 and clustering is not supported.

Table 11: Hardware Standalone Devices: High Availability and Clustering Support

Platform	High Availability	Clustering
Firepower 1000 series	YES	_
Firepower 2100 series	YES	_
Secure Firewall 3100 series	YES	7.1+ (8 node)
Secure Firewall 4200 series	YES	7.4+ (8 node)
Firepower 4100 series	YES	7.2+ (16 node)
		6.2 to 7.1 (6 node)
Firepower 9300	YES	7.2+ (16 node)
		6.2 to 7.1 (6 node)
		Intra-chassis clustering (3 node) is also supported in all versions.
ASA 5500-X series	YES	_
ISA 3000	YES	_

This table lists threat defense virtual support for high availability (with management center or device manager) and clustering (management center only).

Table 12: Virtual Standalone Devices: High Availability and Clustering Support

Platform	High Availability	Clustering
Public Cloud		

Platform	High Availability	Clustering		
AWS	_	7.2+ (16 node)		
Azure	_	7.3+ (16 node)		
GCP	_	7.3+ (16 node)		
On-Prem/Private Cloud				
KVM	7.3	7.2+ (4 node)		
VMware	6.7	7.2+ (4 node)		

Container Instances

This table lists support for high availability and clustering with container instances, which is available on select threat defense hardware in management center deployments only.

Table 13: Container Instances: High Availability and Clustering Support

Platform	High Availability	Clustering
Firepower 4100 series	6.3+	7.2+ (16 node)
		6.6 to 7.1 (6 node)
Firepower 9300	6.3+	7.2+ (16 node)
		6.6 to 7.1 (6 node)
		Intra-chassis clustering (3 node) is also supported in Version 6.6+.

Bundled Components

These tables list the versions of various components bundled with threat defense. Use this information to identify open or resolved bugs in bundled components that may affect your deployment.

Note that sometimes we release updated builds for select releases. If bundled components change from build to build, we list the components in the *latest* build. (In most cases, only the latest build is available for download.) For details on new builds and the issues they resolve, see the release notes for your version.

Operating Systems

ASA 5500-X series and ISA 3000 devices use the ASA operating system. Firepower 1000/2100 and Secure Firewall 3100/4200 series devices use the FXOS operating system. Upgrading threat defense on these devices automatically upgrades the operating system.

Table 14:

Threat Defense	ASA	FXOS
7.4.0	9.20(1.84)	2.14.0.475

Threat Defense	ASA	FXOS
7.3.1.1	9.19(1.202)	2.13.0.1022
7.3.1	9.19(1.200)	2.13.0.1022
7.3.0	9.19(1)	2.13.0.198
7.2.5	9.18(3.53)	2.12.0.519
7.2.4.1	9.18(3.53)	2.12.0.519
7.2.4	9.18(3.39)	2.12.0.499
7.2.3.1	_	_
7.2.3	9.18(2.219)	2.12.0.1030
7.2.2	9.18(2.200)	2.12.0.1104
7.2.1	9.18(2.4)	2.12.0.442
7.2.0.1	9.18(1.200)	2.12.0.31
7.2.0	9.18(1)	2.12.0.31
7.1.0.3	9.17(1.24)	2.11.1.191
7.1.0.2	9.17(1.201)	2.11.1.1300
7.1.0.1	9.17(1.150)	2.11.1.154
7.1.0	9.17(1.0)	2.11.1.154
7.0.6	9.16(4.35)	2.10.1.1603
7.0.5.1	_	_
7.0.5	9.16(4.200)	2.10.1.1400
7.0.4	9.16(3.18)	2.10.1.208
7.0.3	9.16(3.201)	2.10.1.1200
7.0.2.1	9.16(3.200)	2.10.1.192
7.0.2	9.16(3.11)	2.10.1.192
7.0.1.1	9.16(2.5)	2.10.1.175
7.0.1	9.16(2.5)	2.10.1.175
7.0.0.1	9.16(1.25)	2.10.1.159
7.0.0	9.16(1)	2.10.1.159
6.7.0.3	9.15(1.19)	2.9.1.138

Threat Defense	ASA	FXOS
6.7.0.2	9.15(1.15)	2.9.1.138
6.7.0.1	9.15(1.8)	2.9.1.135
6.7.0	9.15(1)	2.9.1.131
6.6.7.1	9.14(4.21)	2.8.1.192
6.6.7	9.14(4.13)	2.8.1.186
6.6.5.2	9.14(3.22)	2.8.1.172
6.6.5.1	9.14(3.15)	2.8.1.172
6.6.5	9.14(3.6)	2.8.1.165
6.6.4	9.14(2.155)	2.8.1.1148
6.6.3	9.14(2.151)	2.8.1.1146
6.6.1	9.14(1.150)	2.8.1.129
6.6.0.1	9.14(1.216)	2.8.1.105
6.6.0	9.14(1.1)	2.8.1.105
6.5.0.5	9.13(1.18)	2.7.1.129
6.5.0.4	9.13(1.5)	2.7.1.117
6.5.0.3	9.13(1.4)	2.7.1.117
6.5.0.2	9.13(1.151)	2.7.1.115
6.5.0.1	9.13(1.2)	2.7.1.115
6.5.0	9.13(1)	2.7.1.107
6.4.0.17	9.12(4.62)	2.6.1.265
6.4.0.16	9.12(4.54)	2.6.1.260
6.4.0.15	9.12(4.41)	2.6.1.254
6.4.0.14	9.12(4.37)	2.6.1.239
6.4.0.13	9.12(4.37)	2.6.1.239
6.4.0.12	9.12(4.152)	2.6.1.230
6.4.0.11	9.12(2.40)	2.6.1.214
6.4.0.10	9.12(2.38)	2.6.1.214
6.4.0.9	9.12(2.33)	2.6.1.201

Threat Defense	ASA	FXOS
6.4.0.8	9.12(2.18)	2.6.1.166
6.4.0.7	9.12(2.151)	2.6.1.156
6.4.0.6	9.12(2.12)	2.6.1.156
6.4.0.5	9.12(2.4)	2.6.1.144
6.4.0.4	9.12(2.4)	2.6.1.144
6.4.0.3	9.12(1.12)	2.6.1.133
6.4.0.2	9.12(1.10)	2.6.1.133
6.4.0.1	9.12(1.7)	2.6.1.133
6.4.0	9.12(1.6)	2.6.1.133
6.3.0.5	9.10(1.31)	2.4.1.255
6.3.0.4	9.10(1.28)	2.4.1.248
6.3.0.3	9.10(1.18)	2.4.1.237
6.3.0.2	9.10(1.12)	2.4.1.237
6.3.0.1	9.10(1.8)	2.4.1.222
6.3.0	9.10(1.3)	2.4.1.216
6.2.3.18	9.9(2.91)	2.3.1.219
6.2.3.17	9.9(2.88)	2.3.1.217
6.2.3.16	9.9(2.74)	2.3.1.180
6.2.3.15	9.9(2.60)	2.3.1.167
6.2.3.14	9.9(2.55)	2.3.1.151
6.2.3.13	9.9(2.51)	2.3.1.144
6.2.3.12	9.9(2.48)	2.3.1.144
6.2.3.11	9.9(2.43)	2.3.1.132
6.2.3.10	9.9(2.41)	2.3.1.131
6.2.3.9	9.9(2.37)	2.3.1.122
6.2.3.8	9.9(2.37)	2.3.1.122
6.2.3.7	9.9(2.32)	2.3.1.118
6.2.3.6	9.9(2.26)	2.3.1.115

Threat Defense	ASA	FXOS
6.2.3.5	9.9(2.245)	2.3.1.108
6.2.3.4	9.9(2.15)	2.3.1.108
6.2.3.3	9.9(2.13)	2.3.1.104
6.2.3.2	9.9(2.8)	2.3.1.85
6.2.3.1	9.9(2.4)	2.3.1.84
6.2.3	9.9(2)	2.3.1.84
6.2.2.5	9.8(2.44)	2.2.2.107
6.2.2.4	9.8(2.36)	2.2.2.86
6.2.2.3	9.8(2.30)	2.2.2.79
6.2.2.2	9.8(2.22)	2.2.2.75
6.2.2.1	9.8(2.10)	2.2.2.63
6.2.2	9.8(2.3)	2.2.2.52
6.2.1	9.8(1)	2.2.1.49
6.2.0.6	9.7(1.25)	_
6.2.0.5	9.7(1.23)	_
6.2.0.4	9.7(1.19)	_
6.2.0.3	9.7(1.15)	_
6.2.0.2	9.7(1.10)	_
6.2.0.1	9.7(1.7)	_
6.2.0	9.7(1.4)	_
6.1.0.7	9.6(4.12)	_
6.1.0.6	9.6(3.23)	_
6.1.0.5	9.6(2.21)	_
6.1.0.4	9.6(2.16)	_
6.1.0.3	9.6(2.16)	_
6.1.0.2	9.6(2.4)	_
6.1.0.1	9.6(2.4)	_
6.1.0	9.6(2)	_

Threat Defense	ASA	FXOS
6.0.1.4	9.6(1.19)	_
6.0.1.3	9.6(1.12)	_
6.0.1.2	9.6(1.11)	_
6.0.1.1	9.6(1)	_
6.0.1	9.6(1)	_
6.0.0.1	9.6(1)	_
6.0.0	9.6(1)	_

Snort

Snort is the main inspection engine. Snort 3 is available in Version 6.7+ with device manager, and Version 7.0+ with management center.

Table 15:

Threat Defense	Snort 2	Snort 3
7.4.0	2.9.22-181	3.1.53.1-40
7.3.1.1	2.9.21-1109	3.1.36.101-2
7.3.1	2.9.21-1000	3.1.36.100-2
7.3.0	2.9.21-105	3.1.36.1-101
7.2.5	2.9.20-5002	3.1.21.500-21
7.2.4.1	2.9.20-4103	3.1.21.401-6
7.2.4	2.9.20-4004	3.1.21.400-24
7.2.3.1	2.9.20-3100	3.1.21.100-7
7.2.3	2.9.20-3010	3.1.21.100-7
7.2.2	2.9.20-2001	3.1.21.100-7
7.2.1	2.9.20-1000	3.1.21.100-7
7.2.0.1	2.9.20-108	3.1.21.1-126
7.2.0	2.9.20-107	3.1.21.1-126
7.1.0.3	2.9.19-3000	3.1.7.3-210
7.1.0.2	2.9.19-2000	3.1.7.2-200
7.1.0.1	2.9.19-1013	3.1.7.2-200

Threat Defense	Snort 2	Snort 3
7.1.0	2.9.19-92	3.1.7.1-108
7.0.6	2.9.18-6008	3.1.0.600-20
7.0.5.1	2.9.18-5100	_
7.0.5	2.9.18-5002	3.1.0.500-7
7.0.4	2.9.18-4002	3.1.0.400-12
7.0.3	2.9.18-3005	3.1.0.300-3
7.0.2.1	2.9.18-2101	3.1.0.200-16
7.0.2	2.9.18-2022	3.1.0.200-16
7.0.1.1	2.9.18-1026	3.1.0.100-11
7.0.1	2.9.18-1026	3.1.0.100-11
7.0.0.1	2.9.18-1001	3.1.0.1-174
7.0.0	2.9.18-174	3.1.0.1-174
6.7.0.3	2.9.17-3014	3.0.1.4-129
6.7.0.2	2.9.17-2003	3.0.1.4-129
6.7.0.1	2.9.17-1006	3.0.1.4-129
6.7.0	2.9.17-200	3.0.1.4-129
6.6.7.1	2.9.16-7100	_
6.6.7	2.9.16-7017	_
6.6.5.2	2.9.16-5204	_
6.6.5.1	2.9.16-5107	_
6.6.5	2.9.16-5034	_
6.6.4	2.9.16-4022	_
6.6.3	2.9.16-3033	_
6.6.1	2.9.16-1025	_
6.6.0.1	2.9.16-140	_
6.6.0	2.9.16-140	_
6.5.0.5	2.9.15-15510	_
6.5.0.4	2.9.15-15201	_

Threat Defense	Snort 2	Snort 3
6.5.0.3	2.9.15-15201	_
6.5.0.2	2.9.15-15101	_
6.5.0.1	2.9.15-15101	_
6.5.0	2.9.15-7	_
6.4.0.17	2.9.14-27005	_
6.4.0.16	2.9.14-26002	_
6.4.0.15	2.9.14-25006	_
6.4.0.14	2.9.14-24000	_
6.4.0.13	2.9.14-19008	_
6.4.0.12	2.9.14-18011	_
6.4.0.11	2.9.14-17005	_
6.4.0.10	2.9.14-16023	_
6.4.0.9	2.9.14-15906	_
6.4.0.8	2.9.14-15707	_
6.4.0.7	2.9.14-15605	_
6.4.0.6	2.9.14-15605	_
6.4.0.5	2.9.14-15507	_
6.4.0.4	2.9.12-15301	_
6.4.0.3	2.9.14-15301	_
6.4.0.2	2.9.14-15209	_
6.4.0.1	2.9.14-15100	_
6.4.0	2.9.14-15003	_
6.3.0.5	2.9.13-15503	_
6.3.0.4	2.9.13-15409	_
6.3.0.3	2.9.13-15307	_
6.3.0.2	2.9.13-15211	_
6.3.0.1	2.9.13-15101	_
6.3.0	2.9.13-15013	_

Threat Defense	Snort 2	Snort 3
6.2.3.18	2.9.12-1813	_
6.2.3.17	2.9.12-1605	_
6.2.3.16	2.9.12-1605	_
6.2.3.15	2.9.12-1513	_
6.2.3.14	2.9.12-1401	_
6.2.3.13	2.9.12-1306	_
6.2.3.12	2.9.12-1207	_
6.2.3.11	2.9.12-1102	_
6.2.3.10	2.9.12-902	_
6.2.3.9	2.9.12-806	_
6.2.3.8	2.9.12-804	_
6.2.3.7	2.9.12-704	_
6.2.3.6	2.9.12-607	_
6.2.3.5	2.9.12-506	_
6.2.3.4	2.9.12-383	_
6.2.3.3	2.9.12-325	_
6.2.3.2	2.9.12-270	_
6.2.3.1	2.9.12-204	_
6.2.3	2.9.12-136	_
6.2.2.5	2.9.11-430	_
6.2.2.4	2.9.11-371	_
6.2.2.3	2.9.11-303	_
6.2.2.2	2.9.11-273	_
6.2.2.1	2.9.11-207	_
6.2.2	2.9.11-125	_
6.2.1	2.9.11-101	_
6.2.0.6	2.9.10-301	_
6.2.0.5	2.9.10-255	_

Threat Defense	Snort 2	Snort 3	
6.2.0.4	2.9.10-205	_	
6.2.0.3	2.9.10-160	_	
6.2.0.2	2.9.10-126	_	
6.2.0.1	2.9.10-98	_	
6.2.0	2.9.10-42	_	
6.1.0.7	2.9.9-312	_	
6.1.0.6	2.9.9-258	_	
6.1.0.5	2.9.9-225	_	
6.1.0.4	2.9.9-191	_	
6.1.0.3	2.9.9-159	_	
6.1.0.2	2.9.9-125	_	
6.1.0.1	2.9.9-92	_	
6.1.0	2.9.9-330	_	
6.0.1.4	2.9.8-490	_	
6.0.1.3	2.9.8-461	_	
6.0.1.2	2.9.8-426	_	
6.0.1.1	2.9.8-383	_	
6.0.1	2.9.8-224	_	
		L	

System Databases

The vulnerability database (VDB) is a database of known vulnerabilities to which hosts may be susceptible, as well as fingerprints for operating systems, clients, and applications. The system uses the VDB to help determine whether a particular host increases your risk of compromise.

The geolocation database (GeoDB) is a database that you can leverage to view and filter traffic based on geographical location.

Table 16:

Threat Defense	VDB	GeoDB
7.4.0	4.5.0-365	2022-07-04-101
7.3.0 through 7.3.x	4.5.0-358	2022-07-04-101
7.2.0 through 7.2.x	4.5.0-353	2022-05-11-103

Threat Defense	VDB	GeoDB
7.1.0	4.5.0-346	2020-04-28-002
6.7.0 through 7.0.x	4.5.0-338	2020-04-28-002
6.6.1 through 6.6.x	4.5.0-336	2019-06-03-002
6.6.0	4.5.0-328	2019-06-03-002
6.5.0	4.5.0-309	2019-06-03-002
6.4.0	4.5.0-309	2018-07-09-002
6.3.0	4.5.0-299	2018-07-09-002
6.2.3	4.5.0-290	2017-12-12-002
6.0.1 through 6.2.2	4.5.0-271	2015-10-12-001

Integrated Products

The Cisco products listed below may have other compatibility requirements, for example, they may need to run on specific hardware, or on a specific operating system. For that information, see the documentation for the appropriate product.



Note

Whenever possible, we recommend you use the latest (newest) compatible version of each integrated product. This ensures that you have the latest features, bug fixes, and security patches.

Identity Services and User Control

Note that with:

- Cisco ISE and ISE-PIC: We list the versions of ISE and ISE-PIC for which we provide enhanced compatibility testing, although other combinations may work.
- Cisco Firepower User Agent: Version 6.6 is the last management center release to support the user agent software as an identity source; this blocks upgrade to Version 6.7+.
- Cisco TS Agent: Versions 1.0 and 1.1 are no longer available.

Table 17: Integrated Products: Identity Services/User Control

Management Center/Threat	Cisco Identity Service	es Engine (ISE)	Cisco Firepower User Agent	Cisco Terminal Services (TS) Agent	
Defense	ISE	ISE-PIC	Ayent		
Supported with	Management center Device manager	Management center Device manager	Management center only	Management center only	

Management	Cisco Identity Services Engine (ISE)		Cisco Firepower User	
Center/Threat Defense	ISE	ISE-PIC	Agent	Services (TS) Agent
Cloud-delivered	3.2	3.2	_	1.4
management center (no	3.1	3.1		
version)	3.0	2.7 patch 2+		
	2.7 patch 2+			
7.4	3.3	3.2	_	1.4
	3.2	3.1		
	3.1 patch 2			
	3.0 patch 6			
7.3	3.2	3.2	_	1.4
	3.1	3.1		1.3
	3.0	2.7 patch 2+		
	2.7 patch 2+			
7.2	3.2	3.2	_	1.4
	3.1	3.1		1.3
	3.0	2.7 patch 2+		
	2.7 patch 2+			
7.1	3.2	3.2	_	1.4
	3.1	3.1		1.3
	3.0	2.7 patch 2+		
	2.7 patch 2+			
7.0	3.2	3.2	_	1.4
	3.1	3.1		1.3
	3.0	2.7 patch 2+		
	2.7 patch 2+	2.6 patch 6+		
	2.6 patch 6+			
6.7	3.0	2.7 patch 2+	_	1.4
	2.7 patch 2+	2.6 patch 6+		1.3
	2.6 patch 6+			

Management	Cisco Identity Ser	vices Engine (ISE)	Cisco Firepower User		
Center/Threat Defense	ISE	ISE-PIC	Agent	Services (TS) Agent	
6.6	3.0	2.7, any patch	2.5	1.4	
	2.7, any patch	2.6, any patch	2.4	1.3	
	2.6, any patch	2.4		1.2	
	2.4				
6.5	2.6	2.6	2.5	1.4	
	2.4	2.4	2.4	1.3	
				1.2	
				1.1	
6.4	2.4	2.4	2.5	1.4	
	2.3 patch 2	2.2 patch 1	2.4	1.3	
	2.3		2.3, no ASA	1.2	
			FirePOWER	1.1	
6.3	2.4	2.4	2.4	1.2	
	2.3 patch 2	2.2 patch 1	2.3, no ASA	1.1	
	2.3	2.4	FirePOWER		
6.2.3	2.3 patch 2	2.2 patch 1	2.4	1.2	
	2.3		2.3	1.1	
	2.2 patch 5				
	2.2 patch 1				
	2.2				
6.2.2	2.3	2.2 patch 1	2.3	1.2	
	2.2 patch 1			1.1	
	2.2			1.0	
	2.1				
6.2.1	2.1	2.2 patch 1	2.3	1.1	
	2.0.1			1.0	
	2.0				

Management	Cisco Identity Services Engine (ISE)		Cisco Firepower User		
Center/Threat Defense	ISE	ISE-PIC	Agent	Services (TS) Agent	
6.2.0	2.1	_	2.3	_	
	2.0.1				
	2.0				
	1.3				
6.1	2.1	_	2.3	_	
	2.0.1				
	2.0				
	1.3				
6.0.1	1.3	_	2.3	_	

Cisco Secure Dynamic Attributes Connector

The Cisco Secure Dynamic Attributes Connector is a lightweight application that quickly and seamlessly updates firewall policies on the management center based on cloud/virtual workload changes. For more information, see one of:

- On-prem connector: Cisco Secure Dynamic Attributes Connector Configuration Guide
- Cloud-delivered connector: Managing the Cisco Secure Dynamic Attributes Connector with Cisco Defense Orchestrator chapters in Managing Firewall Threat Defense with Cloud-Delivered Firewall Management Center in Cisco Defense Orchestrator
- Cisco Secure Firewall Management Center Device Configuration Guide

Table 18: Integrated Products: Cisco Secure Dynamic Attributes Connector

Management Center	Cisco Secure Dynamic Attributes Connector			
	On-Prem	Cloud-Delivered (with CDO)		
Cloud-delivered management center (no version)	2.2 2.0	YES		
7.1+	2.2 2.0 1.1	YES		
7.0	2.2 2.0 1.1	_		

The Cisco Secure Dynamic Attributes Connector allows you to use service tags and categories from various cloud service platforms in security rules, as listed in the following table.

Table 19: Integrated Products: Data Sources for Cisco Secure Dynamic Attributes Connector

Cisco Secure Dynamic Attributes Connector	AWS	Azure Azure Service Tags	Google Cloud Connector	GitHub	Office 365	VMware vCenter	Webex	Zoom
Cloud-delivered connector (no version)	YES	YES	YES	YES	YES	_	NO	NO
Included with the Secure Firewall Management Center	YES	YES	YES	YES	YES	YES	YES	YES
2.2	YES	YES	YES	YES	YES	YES	NO	NO
2.0	YES	YES	YES	YES	YES	YES	NO	NO
1.1	YES	YES	-	_	YES	YES	NO	NO

Threat Detection

Cisco Security Analytics and Logging (On Premises) requires the Security Analytics and Logging On Prem app for the Stealthwatch Management Console (SMC). For information on Stealthwatch Enterprise (SWE) requirements for the SMC, see Cisco Security Analytics and Logging On Premises: Firepower Event Integration Guide.

Table 20: Integrated Products: Threat Detection

Management Center/Threat Defense		Cisco Security Analytics and Logging (SaaS)	Cisco Security Analytics and Logging (On Prem)	Cisco Secure Malware Analytics	Cisco Security Packet Analyzer
Supported with	Management center Device manager	Management center Device manager	Management center only	Management center only	Management center only
6.5+	YES	YES	YES	YES	_
6.4	YES	YES Requires FMC with FTD 6.4.	YES	YES	YES
6.3	_	_	_	YES	YES

Management Center/Threat Defense	Cisco SecureX	Cisco Security Analytics and Logging (SaaS)	Cisco Security Analytics and Logging (On Prem)	Cisco Secure Malware Analytics	Cisco Security Packet Analyzer
6.1 through 6.2.3	_	_	_	YES	_

Threat Defense Remote Access VPN

Remote access virtual private network (RA VPN) allows individual users to connect to your network from a remote location using a computer or supported mobile device. Keep in mind that newer threat defense features can require newer versions of the client.

For more information, see the Cisco Secure Client/AnyConnect Secure Mobility Client configuration guides.

Table 21: Integrated Products: Threat Defense RA VPN

Threat Defense	Cisco Secure Client/Cisco AnyConnect Secure Mobility Client
6.2.2+	4.0+

End-of-Life Announcements

The following tables provide end-of-life details. Dates that have passed are in **bold**.

Software

These major software versions have reached end of sale and/or end of support.

Table 22: Software EOL Announcements

Version	End of Sale	End of Support	Announcement
7.1	2023-12-22	2025-12-31	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense (FTD) 7.1.(x), Firepower Management Center (FMC) 7.1.(x), Adaptive Security Appliance(ASA) 9.17.(x) and Firepower eXtensible Operating System (FXOS) 2.11.(x)
6.7	2021-07-09	2024-07-31	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense (FTD) 6.7, Firepower Management Center (FMC) 6.7 and Firepower eXtensible Operating System (FXOS) 2.9(x)
6.6	2022-03-02	2025-03-31	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense (FTD/FTDv) 6.6(x), Firepower Management Center (FMC/FMCv) 6.6(x) and Firepower eXtensible Operating System (FXOS) 2.8(x)

Version	End of Sale	End of Support	Announcement
6.5	2020-06-22	2023-06-30	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense (FTD) 6.5(x), Firepower Management Center (FMC) 6.5(x) and Firepower eXtensible Operating System (FXOS) 2.7(x)
6.4	2023-02-27	2026-02-28	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense (FTD) 6.4(X), Firepower Management Center (FMC) 6.4(X) and Firepower eXtensible Operating System (FXOS) 2.6(x)
6.3	2020-04-30	2023-04-30	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense (FTD) 6.2.2, 6.3(x), Firepower eXtensible Operating System (FXOS) 2.4.1 and Firepower Management Center (FMC) 6.2.2 and 6.3(x)
6.2.3	2022-02-04	2025-02-28	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense (FTD) 6.2.3, Firepower Management Center (FMC) 6.2.3 and Firepower eXtensible Operating System (FXOS) 2.2(x)
6.2.2	2020-04-30	2023-04-30	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense (FTD) 6.2.2, 6.3(x), Firepower eXtensible Operating System (FXOS) 2.4.1 and Firepower Management Center (FMC) 6.2.2 and 6.3(x)
6.2.1	2019-03-05	2022-03-31	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense versions 6.2.0 and 6.2.1
6.2	2019-03-05	2022-03-31	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense versions 6.2.0 and 6.2.1
6.1	2019-11-22	2023-05-31	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Threat Defense versions 6.1, NGIPSv and NGFWv versions 6.1, Firepower Management Center 6.1 and Firepower eXtensible Operating System (FXOS) 2.0(x)
6.0.1	2017-11-10	2020-11-30	End-of-Sale and End-of-Life Announcement for the Cisco Firepower Software Releases 5.4, 6.0 and 6.0.1 and Firepower Management Center Software Releases 5.4, 6.0 and 6.0.1

These software versions have been removed from the Cisco Support & Download site.



Note

In Version 6.2.3+, uninstalling a patch (fourth-digit release) results in an appliance running the version you upgraded from. This means that you can end up running a deprecated version simply by uninstalling a later patch. Unless otherwise stated, do *not* remain at a deprecated version. Instead, we recommend you upgrade. If upgrade is impossible, uninstall the deprecated patch.

Table 23: Software Removed Versions

Version	Date Removed	Related Bugs and Additional Details	
6.5.0.3 2020-03-02 : devices		CSCvs86257: FMC Upgrade is failing at 800_post/1025_vrf_policy_upgrade.pl	
	2020-02-04 : FMC	This is an upgrade bug. If you are already running this version it is safe to continue.	
6.5.0.1	2019-12-19	CSCvr52109: FTD may not match correct Access Control rule following a deploy to multiple devices	
6.4.0.6	2019-12-19	CSCvr52109: FTD may not match correct Access Control rule following a deploy to multiple devices	
6.2.3.8	2019-01-07	CSCvn82378: Traffic through ASA/FTD might stop passing upon upgrading FMC to 6.2.3.8-51	
6.2.1	2017-11-17	This version is replaced by Version 6.2.2, which offers the same functionality and supports the full set of platforms.	

Hardware

These platforms have reached end of sale and/or end of support.

Table 24: Threat Defense Hardware EOL Announcements

Platform	Last Version	End of Sale	End of Support	Announcement
Firepower 4110	7.2	2022-01-31	2027-01-31	End-of-Sale and End-of-Life Announcement for the Cisco Firepower 4110 Series Security Appliances & 5 YR Subscriptions
ASA 5508-X, 5516-X	7.0	2021-08-02	2026-08-31	End-of-Sale and End-of-Life Announcement for the Cisco ASA5508 and ASA5516 Series Security Appliance and 5 YR Subscriptions
ASA 5525-X, 5545-X, 5555-X	6.6	2020-09-04	2025-09-30	End-of-Sale and End-of-Life Announcement for the Cisco ASA5525, ASA5545 & ASA5555 Series Security Appliance & 5 YR Subscriptions

Platform	Last Version	End of Sale	End of Support	Announcement
Firepower 4120, 4140, 4150	7.2	2020-08-31	2025-08-31	End-of-Sale and End-of-Life Announcement for the Cisco Firepower 4120/40/50 and FPR 9300 SM24/36/44 Series Security
Firepower 9300: SM-24, SM-36, SM-44 modules				Appliances/Modules & 5 YR Subscription
ASA 5515-X	6.4	2017-08-25	2022-08-31	End-of-Sale and End-of-Life Announcement for the Cisco ASA 5512-X and ASA 5515-X
ASA 5506-X, 5506H-X, 5506W-X	6.2.3	2021-08-02	2026-08-31	End-of-Sale and End-of-Life Announcement for the Cisco ASA5506 Series Security Appliance with ASA software
		2021-07-31	2022-07-31	End-of-Sale and End-of-Life Announcement for the Cisco ASA5506 Series Security Appliance 1 YR Subscriptions
		2020-05-05	2022-07-31	End-of-Sale and End-of-Life Announcement for the Cisco ASA5506 Series Security Appliance 3 YR Subscriptions
		2018-09-30	2022-07-31	End-of-Sale and End-of-Life Announcement for the Cisco ASA5506 Series Security Appliance 5 YR Subscriptions
ASA 5512-X	6.2.3	2017-08-25	2022-08-31	End-of-Sale and End-of-Life Announcement for the Cisco ASA 5512-X and ASA 5515-X

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental

All printed copies and duplicate soft copies of this document are considered uncontrolled. See the current online version for the latest version.

Cisco has more than 200 offices worldwide. Addresses and phone numbers are listed on the Cisco website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/c/en/us/about/legal/trademarks.html. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2022–2023 Cisco Systems, Inc. All rights reserved.