FUJITSU PRIMERGY

Fujitsu PRIMERGY TX1330 M5 / SFF / Hot-Plug PSU 500W / Intel Xeon E-2388G / 1x 32GB DDR4-3200 U ECC / NO HDD / RMK / iRMCs6 eLCM Lic

Brand : Fujitsu

Product family: PRIMERGY

Product code:
VFY:T1335SC041IN

Product name : PRIMERGY
TX1330 M5 / SFF / Hot-Plug PSU
500W / Intel Xeon E-2388G / 1x
32GB DDR4-3200 U ECC / NO
HDD / RMK / iRMCs6 eLCM Lic

PRIMERGY TX1330 M5 / SFF / Hot-Plug PSU 500W / Intel Xeon E-2388G / 1x 32GB DDR4-3200 U ECC / NO HDD / RMK / iRMCs6 eLCM Lic
Fujitsu PRIMERGY TX1330 M5 / SFF / Hot-Plug PSU 500W / Intel Xeon E-2388G / 1x 32GB DDR4-3200 U ECC / NO HDD / RMK / iRMCs6 eLCM Lic. Processor family: Intel Xeon E, Processor frequency: 3.2 GHz, Processor model: E-2388G. Internal memory: 32 GB, Internal memory type: DDR4-SDRAM, Memory layout (slots x size): 1 x 32 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 500 W, Redundant power supply (RPS) support. Chassis type: Tower

Processor

Processor manufacturer *	Intel
Processor family *	Intel Xeon E
Processor model *	E-2388G
Processor frequency *	3.2 GHz
Processor boost frequency	4.6 GHz
Processor cores	8
Processor cache	16 MB
Motherboard chipset	Intel C256
Number of processors installed	1
Maximum number of SMP processors	1

Memory

Internal memory *	32 GB
Internal memory type *	DDR4-SDRAM
Memory slots	4x DIMM
ECC	✓
Memory clock speed	3200 MHz
Memory layout (slots x size)	1 x 32 GB
Maximum internal memory *	128 GB

Storage

Number of HDDs supported	8
Supported HDD sizes	2.5"
RAID support *	✓
RAID levels	0, 1, 5, 6
Hot-Plug support	✓

Network

LAN controller	Intel I210
Ethernet LAN	✓
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet

Ports & interfaces

Ethernet LAN (RJ-45) ports *	3
USB 2.0 ports quantity	4
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2

Expansion slots

PCI Express x4 (Gen 3.x) slots	2
PCI Express x8 (Gen 4.x) slots	2
PCI slots	1

Design

Chassis type *	Tower
Product colour	Black
Rack mounting	✓
Redundant fans support	✓

Performance

Noise level	22 dB
Trusted Platform Module (TPM)	✓
Trusted Platform Module (TPM) version	2.0

Software

Operating system installed *	✗
Compatible operating systems *	Windows Server 2022 Datacenter, Windows Server 2022 Standard, Windows Server 2022 Essentials, Windows Server 2019 Datacenter, Windows Server 2019 Standard, Windows Server 2019 Essentials, VMware vSphere 7.0, Red Hat Enterprise Linux 8, Univention Corporate Server 4

Power

Redundant power supply (RPS) support *	✓
Power supply *	500 W
Power supply input voltage	100 - 240 V
Power supply input frequency	50 / 60 Hz

Operational conditions

Operating temperature (T-T)	5 - 45 °C
Operating relative humidity (H-H)	10 - 85%

Ports & interfaces

USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1
VGA (D-Sub) ports quantity	1
DisplayPorts quantity	1
Total number of SATA connectors	7

Certificates

Certification	CB, GS, CE, NRTLc/us, FCC, ICES-003, NMB-003, VCCI, JIS 61000-3-2, EAC, KC, CCC, RCM, BSMI

Weight & dimensions

Width	177.2 mm
Depth	521.7 mm
Height	456.2 mm
Weight	26.4 kg

Technical details

Sustainability compliance	✓
Sustainability certificates	RoHS, WEEE

4065221880509