



Flexible Self-Service Kiosk

C24

If you're interested in improving the customer experience while serving more customers, look no further than the C24 Flexible self-service kiosk. Made to suit all types of locations, the C24 is designed to deliver on maximum self-service capacity. Cash, card and mobile payment options mean your customers will benefit, however they choose to pay. With the Acrelec Transformation Platform software, take advantage of multi-function capabilities, allowing the kiosk to service more than one business function in the same unit.



More than just hardware, our ATP software provides a powerful platform for rapid and scaleable business application development. What is holding you back?

Dimensions	High door landscape version – 760 × 690 × 1382mm
$(W \times D \times H)$	High door double landscape version – 760 × 691 × 1740mm
	High door portrait version – 613 × 690 × 1589mm
	Short door landscape version – 756 × 691 × 1333mm
	Short door double landscape version – 756 × 691 × 1691mm
	Short door portrait version – 613 × 691 × 1540mm
Weight	130kg*
	*May change depending on version
Power supply	100-240 VAC, 50/60 Hz
Current consumption	8A
Operating	0°C to +40°C, 20 to 80% relative humidity, non-condensing
environment	
Storage environment	-20°C to +70°C, 5 to 90% relative humidity, non-condensing
Max. operating	2000 m
altitude	
Material	Steel, aluminum, stainless steel
Protection	IP20, designed for indoor use
PC Option 1	Processor Intel Core i3-8100T 3.1 GHz
	SSD 128 GB
	RAM 8GB
	Connectivity: 4 × USB 3.0, 4 × USB 2.0, 1 × DP, 1 × HDMI, 2 × COM,
	2 × Gigabit Ethernet, Audio in/out
PC Option 2	Processor Intel Core i5-8259U 2.3 GHz
	SSD 128 GB
	RAM 8GB
	Connectivity: 5 × USB 3.2, 1 × DP, 2 × HDMI, 1 × COM, 1 × Gigabit Ethernet,
	Audio in/out

Screen	LCD Multi-Touch Monitor, 10 points 24", 527 × 296 mm, 1920 × 1080 pixels 16.7 million colours Vision angle typ.: Vertical 178° / Horizontal 178°
	Contrast typ. 3000:1 Brightness typ. 225 nits
Scanner	Type 2D Ambient ligth 0-107369 lux Optical Resolutions : 4.0 mil (Code 39), 5.0 mil (PDF417), 10 mil (Data Matrix)
Printer	Technology: Direct thermal line printing, Black / White, 250mm/s Resolution: 203×180DPI Max. paper roll diameter: 83mm Paper-end sensor, paper-near-end sensor
Semaphore	12V RGB LEDs, controlled by USB
Options Available	EFT: Different preparations available Ready for Glory CASHININFINITY™ Models: CI-10B, CI-10C, CI-10BX, CI-10CX, CI-5B and CI-5C
Safety certifications	IEC / UL / EN62368-1 Planned
EMC, EMI certifications	CISPR 24 / EN55024, CISPR32 / EN55032, EN 61000-3-2, EN 61000-3-3 FCC part 15, CAN ICES 003 Planned

^{*}Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

CI-10X

Compact and high capacity solutions enabling automated cash handling at point of sale positions.



CI-100X

Fast secure cash processing and storage in the back office.



Professional Services

Transaction analysis, connectivity, advisory services, user training through to full project management



Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK



DS-ACRELEC-C24-0223 1.1