



Sunlite 87702-SU LED 6-Inch Round Ultra Slim Recessed Downlight with Junction Box, 14 Watts (100W Equivalent), 120 Volts, 950 Lumen, Dimmable, Tunable 30K/40K/50K Color Temperature, ETL Listed, White Finish 1 Pack

- **ULTRA SLIM DESIGN** - Shallow depth makes for easier installation, especially in low-clearance applications. No housing required. Use these 6-Inch round fixtures for new installations or as a retrofit replacement for existing recessed lighting.
- **COLOR TEMPERATURE TUNABLE** - These dimmable fixtures put out a bright 950 lumen and allow you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back of the fixture.
- **ENERGY EFFICIENT** - Comparable output to 65 watt bulb while only using 11 watts of electricity. Easy installation conveniently with the junction box eliminating the trouble of installing an extra can.
- **LONG LIFE LED** - Built-in long life LED technology means 50,000 hours of maintenance free service. No ladders to climb or difficult to reach bulbs to replace.
- **COMMERCIAL AND RESIDENTIAL USE** - These energy efficient fixtures are a favorite among contractors, electricians, and home improvement professionals. Perfect for residential, commercial, retail, office, hospitality and educational institutions. ETL Listed for Damp Location installations.

General Characteristics

Fixture Life Hours

Material

Lens Material

Lens Finish

Finish

Lumens Per Watt (LPW)

Life (based on 3hr/day)

Estimated Energy Cost

Safety Rating

Ingress Protection

Dimmable

Dimming Type

50000 Hours

Aluminum

Polycarbonate

White

White

67.86

45.7

\$1.69 per Year

ETL - Damp Location

IP20

True

Forward/Reverse Phase (Triac/Elv)

Fixture Characteristics

Collection

Shape

Number of Lights

Mounting

Use Location

IC-Rating

Slim

Round

1 - Light

Recessed

Indoor

True

Electrical Characteristics

Watts

Volts

Equivalent Watts

LED Chip Manufacturer

Number of LEDs

Power Factor

Operating Temperature

14

120

100

SMD2835

72

0.9

-20°-40°

Light Characteristics

Brightness

Color Accuracy (CRI)

Light Appearance

Color Temperature

Beam Angle

950 Lumens

90

CCT Tunable

30K/40K/50K

110°

Product Dimensions

Size

Cord Length

Height (in)

Diameter (in)

Package Dimensions (in)

6"

12" Cord

1

6.875

(W) 7.20 (H) 2.80 (D) 7.70

Product Data

Item Number

Case Quantity

Barcode on SKU

Barcode on Case

Brand

Description

87702-SU

6

653703877020

10653703877027

SUNLITE

LFX/SDL/SCT/6R/14W