



# RF EXPOSURE Test Report

**Report No.:** MTi240226010-01E2  
**Date of issue:** 2024-05-10  
**Applicant:** Dongguan Lingdu Electronic Technology Co.,Ltd  
**Product:** IP Camera  
**Model(s):** K06, K03, K05, K08, K09, K10, K15, K16, K27, K28, C620, C610  
**FCC ID:** 2BEAP-K06

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.cn>

# Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



<b>Test Result Certification</b>	
<b>Applicant:</b>	Dongguan Lingdu Electronic Technology Co.,Ltd
Address:	No.1, Longcheng Street, Qingxi Town, Dongguan City, Guangdong Province, China
<b>Manufacturer:</b>	Dongguan Lingdu Electronic Technology Co.,Ltd
Address:	No.1, Longcheng Street, Qingxi Town, Dongguan City, Guangdong Province, China
<b>Product description</b>	
Product name:	IP Camera
Trademark:	Arpha
Model name:	K06
Series Model:	K03, K05, K08, K09, K10, K15, K16, K27, K28, C620, C610
Standards:	N/A
Test procedure:	KDB 447498 D01 v06
<b>Date of Test</b>	
Date of test:	2024-04-24 to 2024-05-07
Test result:	Pass

**Test Engineer :**

*Yanice Xie*

\_\_\_\_\_  
(Yanice Xie)

**Reviewed By: :**

*David. Lee*

\_\_\_\_\_  
(David Lee)

**Approved By: :**

*Leon Chen*

\_\_\_\_\_  
(Leon Chen)

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

### MPE Calculation Method

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.1415926

$R$  = distance between observation point and center of the radiator in cm (20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

### 2.4GWiFi:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz, n HT40: 2422-2452

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: FPC Antenna;

Antenna gain:

2.4G WIFI: 3.26dBi

R=20cm

$mW=10^{(dBm/10)}$

2.4G antenna gain Numeric= $10^{(dBi/10)}=10^{(3.26/10)}=2.12$

### 2.4G WIFI:

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna		Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain		Power density(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
		Ant A	Ant A	(dBm)	(mW)	(dBi)	Numeric		
2412	802.11b	19.46	20±1	21	125.893	3.26	2.12	0.05306	1
2437		19.96	20±1	21	125.893	3.26	2.12	0.05306	1
2462		19.71	20±1	21	125.893	3.26	2.12	0.05306	1
2412	802.11g	19.39	20±1	21	125.893	3.26	2.12	0.05306	1
2437		20.06	20±1	21	125.893	3.26	2.12	0.05306	1
2462		19.97	20±1	21	125.893	3.26	2.12	0.05306	1
2412	802.11n H20	18.37	19±1	20	100.000	3.26	2.12	0.04214	1
2437		18.90	19±1	20	100.000	3.26	2.12	0.04214	1
2462		18.65	19±1	20	100.000	3.26	2.12	0.04214	1

### Conclusion:

For the max result:  $0.05306 \leq 1.0$  test exclusion threshold, No SAR is required.

----END OF REPORT----