



# 300Mbps Wi-Fi Range Extender

Stable Wi-Fi Extension



TL-WA850RE



Easy Setup



Tether App




Access Point Mode

# Highlights

## Extend the Range of Your Wi-Fi Network

The 300Mbps Wi-Fi Range Extender connects to your router wirelessly, strengthening and expanding its signal into areas it can't reach on its own, achieving speed of 300Mbps.




## Perfect Location at a Glimpse

The Intelligent Signal lights help you quickly find the best location to install the range extender.



TP-Link 300Mbps Wi-Fi Range Extender TL-WA850RE

# Features



## Ease of Use

- Intuitive Web UI – Ensures quick and simple installation without hassle
- Fast Encryption – One-touch wireless security encryption with the WPS button
- Hassle-free Management with Tether App – Network management is made easy with the TP-Link Tether App, available on any Android or iOS device



## Speed

- Ultimate Wireless Speed – Wireless speed of up to 300Mbps
- Fast Ethernet Port – Acts as a wireless adapter to connect wired devices



## Reliability

- Reliable Connection – Internal antennas for optimal Wi-Fi coverage and reliable wireless connections
- Universal Compatibility – Work with any Wi-Fi router

TP-Link 300Mbps Wi-Fi Range Extender TL-WA850RE

# Specifications

## Hardware

Plug Type - AU  
Interface - 1 \* 10/100M Ethernet Port (RJ45)  
Ports - 1 x 10/100Mbps Ethernet Port (RJ45)  
Button - RE (Range Extender) Button, Reset Button  
Input Power - 100-240V~50/60Hz  
Power Consumption - About 3W  
Wireless Standards - IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Dimensions ( W x D x H ) - 4.3x 2.6 x 3.0in. (110.0 x 65.8 x 75.2mm)  
Antenna - 2 \* internal

## Wireless

Wireless Standards - IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Frequency - 2.4~2.4835GHz  
Signal Rate - 11n: Up to 300Mbps (dynamic) 11g: Up to 54Mbps (dynamic) 11b: Up to 11Mbps (dynamic)  
Reception Sensitivity - 270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm @8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER  
Transmit Power - < 20 dBm (EIRP)  
Wireless Modes - Range Extender/Access Point  
Wireless Functions - WMM (Wi-Fi Multimedia)  
Wireless MAC Address Filtering Wireless Statistic Domain Login Function  
Wireless Security - 64/128/152-bit WEP WPA-PSK / WPA2-PSK  
Transmission Power - < 20 dBm (EIRP)

## Others

Certification - CE, RoHS  
Package Contents - 300Mbps Universal Wi-Fi Range Extender TL-WA850RE Quick Installation Guide  
System Requirements - Microsoft® Windows® 98SE, NT, 2000, XP, Vista or Windows 7, 8, 10, Mac® OS, NetWare®, UNIX® or Linux.  
Environment - Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing



For more information, please visit  
<http://www.tp-link.com/en/products/details/TL-WA850RE.html>  
or scan the QR code left

©2021 TP-Link

Maximum wireless speed of up to 300Mbps is the theoretical data rate derived from IEEE standard 802.11 specifications. Actual data throughput and wireless coverage will vary due to network conditions and environmental factors including volume of network traffic, building materials and construction, network overhead, actual data throughput rate, and wireless coverage. TP-Link makes no express or implied representations or warranties about this product's compatibility with any future standards. 2.4GHz Performance Mode requires 256 QAM support on Wi-Fi client.

[www.tp-link.com](http://www.tp-link.com)

TP-Link 300Mbps Wi-Fi Range Extender TL-WA850RE



[www.rxtx.com.au](http://www.rxtx.com.au)