Overview

HP EliteBook 1050 G1



Left

- Speakers
- 2. Power button

- 3. USB 3.0 Charging Port (left), USB 3.0 (right)
- 4. Security lock slot (Lock sold separately.)

Overview



- 1. Ambient light sensor
- 2. IR sensors
- 3. IR camera (Optional)
- 4. Web cam (Optional)
- 5. Web cam (Optional)
- 6. Web cam LED
- 7. Power connector

Right

- 8. (2) USB Type-C™ with Thunderbolt™ ports (Supporting DisplayPort 1.3, USB 3.1 Gen2, PCIe Gen 3 devices)
- 9. HDMI 2.0 (Cable not included.)
- 10. Audio-out/Audio-in combo jack
- 11. SD card reader
- 12. Fingerprint sensor (Optional)
- 13. Glass clickpad

Overview

AT A GLANCE

- Windows 10 Pro 64. Home 64 Plus. Pro 64 Plus. or FreeDOS
- Full performance industrial design, Aluminum chassis with HP's pike silver color and premium logo. Backlight keyboard in full aluminum deck, chemically strengthened glass touchpad, and collaboration keys. HP Spill Resistant Keyboard with Durakeys, touchpad buttons with Duracoat finish. Diamond cut edges for touchpad and finger print sensor
- Designed to pass 12 MIL-STD-810G testing ¹
- Powerful NVIDIA® discrete graphics: NVIDIA® GeForce® GTX 1050 (optional)
- Intel® Integrated graphics: Intel® HD Graphics 630 integrated on Core™ i7
- Choice of 8th generation Intel® Core™ i7 hexa-core with vPro™ or Intel® Core™ i5 quad-core with vPro™ technology
- Up to two SODIMMs, for system memory up to 32 GB DDR4-2667 MHz
- Supports multi-display, including up to three (3) displays without a docking solution, with hybrid graphics enabled
- Two (2) Thunderbolt™ 3 ports (supporting DP 1.3, USB 3.1, PCIe Gen 3 devices) on the new USB-CTM connector for high speed data/video/audio transfer support ²
- Bang and Olufsen audio optimized for high fidelity audio with immersive surround sound with a discrete amp, deep, rich bass and crystal clear dialog without distortion at high volume
- Long life battery solution with a 4-cell (64 WHr) or 6-cell (96 WHr)
- Widescreen 39.6 cm (15.6")-inch diagonal LED-backlit display: FHD (1920x1080, 400 nit) with ultrawide viewing angle, antiglare, and ambient light sensor; FHD (1920x1080, 650 nit) with ultrawide viewing angle, anti-glare, HP SureView; UHD (3840x2160, 400 nit) with ultrawide viewing angle, anti-glare, and ambient light sensor
- Optional HD webcam and IR camera
- · Wireless connectivity options:
- Intel® Dual Band Wireless-AC 9560 802.11 AC/a/b/g/n (2x2) WiFi® and Bluetooth® 5.0 combo adaptor (vPro™) or,
- Intel® Dual Band Wireless-AC 9560 802.11 AC/a/b/g/n (2x2) WiFi® and Bluetooth® 5.0 combo adaptor (non-vPro™)
- Two (2) dedicated M.2 drive slots
- Security features including HP Client Security Manager, HP SureClick, HP WorkWise, HP SureView, and HP SureStart Gen 4
- Low halogen HP BIOS technology, including HP Sure Start to identify and recover from unknown BIOS attacks

1. MIL-STD-810G testing is not intended to demonstrate fitness of U.S. Department of Defense (DoD) contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

2.Thunderbolt[™]3 ports supports DisplayPort 1.3, USB 3.1 Gen 2, and PCIe Gen 3 devices over the new USB-C port connector. The port is compatible with existing DisplayPort displays, devices, and cables. Install all the latest drivers for your Thunderbolt[™] device before connecting the device to the Thunderbolt[™] port. Thunderbolt[™] cable and Thunderbolt[™] device (sold separately) must be compatible with Windows[®]. To determine whether your device is Thunderbolt[™] Certified for Windows, see https://thunderbolttechnology.net/products.

NOTE: See important legal disclosures for all listed specs in their respective features sections.



Features

PRODUCT NAME

HP FliteBook 1050 G1

OPERATING SYSTEM

Preinstalled Windows 10 Pro 64¹

Windows 10 Pro 64 (National Academic only) 1,2

Windows 10 Home 64 1

Windows 10 Home Single Language 64 ¹

FreeDOS 2.0

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See http://www.windows.com/.

2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see https://aka.ms/ProEducation for Windows 10 Pro Education feature information.

PROCESSORS

Intel® Core™ i5-8300H with Intel® UHD Graphics 630 Graphics (2.3 GHz base frequency, up to 4 GHz with Intel® Turbo Boost Technology, 8 MB L3 cache, 4 cores) 3,4,5

Intel® Core™ i5-8400H vPro™ processor with Intel® UHD Graphics 630 Graphics (2.5 GHz base frequency, up to 4.2 GHz with Intel® Turbo Boost Technology, 8 MB L3 cache, 4 cores) ^{2,3,4}

Intel® Core™ i7-8750H with Intel® UHD Graphics 630 Graphics (2.2 GHz base frequency, up to 4.1 GHz with Intel® Turbo Boost Technology, 9 MB L3 cache, 6 cores) ^{2,3,4}

Intel® Core™ i7-8850H vPro™ processor with Intel® UHD Graphics 630 Graphics (2.6 GHz base frequency, up to 4.3 GHz with Intel® Turbo Boost Technology, 9 MB L3 cache, 6 cores) ^{2,3,4}

Processor Family

8th Generation Intel® Core™ i7 processor (i7-8850H and i7-8750H models) ⁴ 8th Generation Intel® Core™ i5 processor (i5-8400H and i5-8300H models) ⁴

- 3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.
- 4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.
 5. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on
- http://www.support.hp.com.

CHIPSET

Chipset is integrated with processor.



Features

GRAPHICS

Integrated

Intel® UHD Graphics 630 6

Discrete

NVIDIA® GeForce® GTX 1050 (4 GB DDR5 dedicated) 7

6. HD content required to view HD images.

7. Integrated graphics depends on processor. NVIDIA® Optimus™ technology requires an Intel processor, plus an NVIDIA® GeForce® discrete graphics configuration and is available on Windows 10 Pro OS. With NVIDIA® Optimus™ technology, full enablement of all discrete graphics video and display features may not be supported on all systems (e.g. OpenGL applications will run on the integrated GPU or the APU as the case may be).

DISPLAY

39.6 cm (15.6") diagonal FHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m^2 , 100% sRGB with Ambient light sensor (1920 x 1080) $^{6.8.9}$

39.6 cm (15.6") diagonal FHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m^2 , 100% sRGB for HD camera with Ambient light sensor (1920 x 1080) 6,8,9

39.6 cm (15.6") diagonal FHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m^2 , 100% sRGB for HD camera and IR camera with Ambient light sensor (1920 x 1080) 6,8,9

39.6 cm (15.6") diagonal UHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m^2 , 100% sRGB with Ambient light sensor (3840 x 2160) 6,8,9

39.6 cm (15.6") diagonal UHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m^2 , 100% sRGB for HD camera with Ambient light sensor (3840 x 2160) 6,8,9

39.6 cm (15.6") diagonal UHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m², 100% sRGB for HD camera and IR camera with Ambient light sensor (3840 x 2160) ^{6,8,9}

39.6 cm (15.6") diagonal FHD IPS eDP + PSR anti-glare LED-backlit with privacy screen, 650 cd/m^2 , 100% sRGB (1920 x 1080) $_{6,8,9}$

39.6 cm (15.6") diagonal FHD IPS eDP + PSR anti-glare LED-backlit with privacy screen, 650 cd/m², 100% sRGB for HD camera and IR camera (1920 x 1080) ^{6,8,9}

- 6. HD content required to view HD images.
- 8. Resolutions are dependent upon monitor capability, and resolution and color depth settings.
- 9. Sold separately or as an optional feature.

Features

Docking station model	Total number of supported displays (incl. the notebook display)	Max.resolutions supported	Dock Connectors	Technical limitations
HP UltraSlim Docking Station	3	Dual 2.5K @ 60Hz	2xDP, 1xVGA	Dual 2.5k only with both displays into DP
HP Elite 120W TB3 Dock	3	Dual 4K @ 60Hz	2xDP, 1xVGA, 1xTB,	Dual 4k only with one display in to DP and + TB port or USB-C alt mode + TB port
HP Elite USB-C Dock G4	3	Dual 2K @ 60Hz	1xUSB-C alt-mode	
HP USB-C Universal Dock	3	Single 4K @ 60Hz (3840 x 1440)	1xHDMI, 2xDP	
HP USB-C Travel Dock	2	Dual 4K @ 60Hz	2xDP	Single external display Only HDMI or VGA at the time
HP USB-C Mini Dock	2	Single 5K @ 60Hz	1xHDMI, 1xVGA	Single external display Only HDMI or VGA at the time

STORAGE AND DRIVES

Primary M.2 Storage SATA

512 GB M.2 SATA FIPS 140-2 SSD TLC ¹⁰ 256 GB SATA SED (Opal 2) TLC ¹⁰

PCle

256 GB PCIe® NVMe™ M.2 SSD TLC 10
512 GB PCIe® NVMe™ M.2 SSD TLC 10
1 TB PCIe® NVMe™ M.2 SSD TLC 10
2 TB PCIe® NVMe™ M.2 SSD TLC 10
256 GB PCIe® NVMe™ M.2 SED SSD TLC Opal 2 10
512 GB PCIe® NVMe™ M.2 SED SSD TLC Opal 2 10

Secondary Storage SATA

512 GB M.2 SATA FIPS 140-2 SSD TLC 10 256 GB SATA SED (Opal 2) TLC 10

PCIe

256 GB PCIe® NVMe™ M.2 SSD TLC ¹⁰
512 GB PCIe® NVMe™ M.2 SSD TLC ¹⁰
1 TB PCIe® NVMe™ M.2 SSD TLC ¹⁰
2 TB PCIe® NVMe™ M.2 SSD TLC ¹⁰
256 GB PCIe® NVMe™ M.2 SSD TLC ¹⁰
512 GB PCIe® NVMe™ M.2 SED SSD TLC Opal 2 ¹⁰
512 GB PCIe® NVMe™ M.2 SED SSD TLC Opal 2 ¹⁰

10. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.



Features

MEMORY

Maximum Memory

32 GB DDR4-2666 SDRAM 11

Memory

8 GB DDR4-2666 SDRAM (1 x 8 GB) ¹¹ 8 GB DDR4-2666 SDRAM (2 x 4 GB) ¹¹ 16 GB DDR4-2666 SDRAM (2 X 8 GB) ¹¹ 16 GB DDR4-2666 SDRAM (1 X 16 GB) ¹¹ 32 GB DDR4-2666 SDRAM (2 X 16 GB) ¹¹

Memory Slots

2 SODIMM Both slots are upgradeable System runs at 2666 Supports Dual Channel Memory

11. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

WLAN

Intel® Dual Band Wireless-AC 9560 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 5 Combo, vPro™ 12 Intel® Dual Band Wireless-AC 9560 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 5 Combo, non-vPro™ 12

NFC

HP Module with NXP NFC Controller NPC300 I2C NCI

Miracast

Support for Miracast 13

12. WLAN is an optional or ad-on feature and requires internet service and sold separately. Availability of public wireless access points limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.

13. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.



Features

AUDIO/MULTIMEDIA

Audio

HP Bang & Olufsen Audio HP Noise Cancellation Software HP Clear Sound Amp Camera Privacy Shutter Skype for Business Certification Intel SST Audio Microphone (Dual Array) Microphone (World Facing)

Camera

720p HD camera ⁶ HD IR webcam ^{6,14}

6. HD content required to view HD images.14. Internet access required.



Features

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

DuraKeys Optional backlit

Pointing Device

Glass ClickPad with chemically etched surface, gesture support, two-way scroll, two-finger zoom (pinch)

Function Keys

F1 - Display switching

F2 - Sure View (if supported otherwise blank)

F3 - Brightness <down>

F4 - Brightness <up>

F5 - Audio mute (with an LED)

F6 - Volume <down>

F7 - Volume <up>

F8 - Mic mute (with an LED)

F9 - Backlit (if supported otherwise blank)

F10 - NumLock (with an LED)

F11 - Wireless (with an LED)

F12 - Calendar

Share screen (with an LED)

Pick Up/Accept/ Answer/Hold (with an LED)

Hang Up/Decline/ Reject (with an LED)



Features

SOFTWARE AND SECURITY

Preinstalled Software BIOS

HP BIOSphere Gen4 14

HP DriveLock & Automatic DriveLock

BIOS Update via Network

Master Boot Record Security

Power On Authentication

Secure Erase 15

Absolute Persistence Module 16

Pre-boot Authentication

HP Wireless Wakeup

Software

HP Native Miracast Support 12

HP Velocity

HP ePrint Driver + JetAdvantage 17

HP Hotkey Support - CMIT

HP Recovery Manager

HP Jumpstart

HP Support Assistant 18

HP Noise Cancellation Software

HP WorkWise 31

HP PhoneWise 25

Buy Office (Sold separately)

Manageability Features

HP Driver Packs 19

HP System Software Manager (SSM)

HP BIOS Config Utility (BCU)

HP Client Catalog

HP Manageability Integration Kit Gen2 [20]

Ivanti Management Suite 21

Client Security Software

HP Client Security Suite Gen4 22 including:

HP Security Manager ²³ (including Credential Manager, HP Password Manager, HP Spare Key)

HP Fingerprint Sensor 27

HP Device Access Manager

HP Power On Authentication

Microsoft Defender 24



Features

Security Management

Secure Erase 18

TPM 2.0 Embedded Security Chip shipped with Windows 10 (Common Criteria EAL4+ Certified)

SATA 0,1 port disablement (viaBIOS)

RAID configurations 28

Serial, USB enable/disable (viaBIOS)

Power-on password (viaBIOS)

Setup password (viaBIOS)

Support for chassis padlocks and cable lock devices

Integrated hood sensor

HP Sure Click 32

HP Sure Start Gen4²⁶

HP Sure Run 29

HP Sure Recover 30

Security

TPM

Model:

Version:

Revision:

FIPS 140-2 Compliant:

IPv6 Certification:

No

MD5 Hash: Please follow the instructions below to access MD5 Hash.

UEFI version:

- 12. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.
- 14. HP BIOSphere Gen4 requires Intel® or AMD 8th Gen processors. Features may vary depending on the platform and configurations.
- 15. Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method.
- 16. Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit:

http://www.absolute.com/company/legal/agreements/ computrace-agreement. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.



Features

- 17. HP ePrint Driver requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see www.hp.com/go/eprintcenter). Print times and connection speeds may vary.
- 18. HP Support Assistant requires Windows and Internet access.
- 19. HP Driver Packs not preinstalled, however available for download at http://www.hp.com/go/clientmanagement.
- 20. HP Manageability Integration Kit can be downloaded from http://www8.hp.com/us/en/ads/clientmanagement/overview.html
- 21. Ivanti Management Suite subscription required.
- 22. HP Client Security Suite Gen 4 requires Windows and Intel® or AMD 8th generation processors.
- 23. HP Password Manager requires Internet Explorer or Chrome or FireFox. Some websites and applications may not be supported. User may need to enable or allow the add-on / extension in the internet browser.
- 24. Microsoft Defender requires Windows 10. Opt in and internet connection required for updates.
- 25. HP PhoneWise Client may not be available with HP Workwise. For supported platforms and HP PhoneWise system requirements see www.hp.com/qo/HPPhoneWise.
- 26. HP Sure Start Gen4 is available on HP EliteBook products equipped with Intel® 8th generation processors.
- 27. HP Fingerprint Sensor sold separately or as an optional feature.
- 28. RAID configuration is optional and does require a second hard drive.
- 29. HP Sure Run is available on HP Elite products equipped with 8th generation Intel® or AMD® processors.
- 30. HP Sure Recover is available on HP Elite PCs with 8th generation Intel® or AMD processors and requires an open, wired network connection. Not available on platforms with multiple internal storage drives, Intel® Optane™. You must back up important files, data, photos, videos, etc. before use to avoid loss of data.
- 31. HP WorkWise smartphone app is available as a free download on the Google Play. As of September 2017, HP WorkWise will no longer support iOS or iPhone® devices
- 32. HP Sure Click is available on select HP platforms and supports Microsoft® Internet Explorer, Google Chrome, and Chromium™. Supported attachments include Microsoft Office (Word, Excel, PowerPoint) and PDF files in read only mode. Check http://h20195.www2.hp.com/v2/GetDocument.aspx?docname=4AA7-0922ENW for all compatible platforms as they become available.



Features

POWER

Power Supply

HP Smart 150 W Slim External AC power adapter

Primary Battery

HP Long Life 6-cell, 95.6 Wh Li-ion polymer ³³ HP Long Life 4-cell, 64 Wh Li-ion polymer ³³

Power Cord

1.0m 3-wire plug (with ground pin)

Battery Life

Up to 16 hours 39

33. Supports HP Fast Charging.

39. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.

WEIGHTS & DIMENSIONS

Weight

Starting at 4.54 lb ³⁴ Starting at 2.06 kg ³⁴

Dimensions (w x d x h)

14.17 x 9.65 x 0.74 in 36 x 25.4 x 1.89 cm

34. Weight will vary by configuration.



Features

PORTS/SLOTS

Ports

2 USB 3.1 Type-C[™] with Thunderbolt[™] support 1 USB 3.0 (charging) 1 USB 3.0 1 HDMI 2.0 (with Discrete graphics) ³⁵ 1 HDMI 1.4 (with Integrated graphics) ³⁵ 1 Headphone/microphone combo jack 1 AC power port

Expansion Slots

1 SD Media Reader Slot Supports SD, SDHC, SDXC

35. Cables are not included.

SERVICE AND SUPPORT

HP Services offers 1 year and 90 day limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year or 3-year limited warranty as the platform. Onsite service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. Service levels and response times for HP Care Packs may vary depending on your geographic location. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/cpc ³⁶

36. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



Technical Specifications

SYSTEM UNIT

Stand-Alone Power Nominal Operating 19V

Requirements (AC Power) **Voltage**

Average Operating Power Win 10

Integrated graphics
Discrete Graphics

Max Operating Power < 150W

Temperature Operating 32° to 95° F (0° to 35° C) (not writing optical)

-41° to 95° F (5° to 35° C) (writing optical)

Non-operating -4° to 140° F (-20° to 60° C)

Relative Humidity Operating 10% to 90%, non-condensing

Non-operating 5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature

Shock Operating Half sine wave shock: 40G, 2ms duration

Non-operating Half sine wave shock: 240G, 2ms duration

Random Vibration Operating Nominal 0.75 grms

Non-operating Nominal 1.50 grms

Altitude (unpressurized) Operating -50 to 10,000 ft (-15.24 to 3,048 m)

Non-operating -50 to 40,000 ft (-15.24 to 12,192 m)

Planned Industry StandardULYesCertificationsCSAYes

FCC Compliance Yes

ENERGY STAR 6.0[®] Selected models¹

EPEAT Gold² **ICES** Planned Australia / Yes NZ A-Tick Compliance Yes CCC Yes **Japan VCCI Compliance** Yes KC Yes **BSMI** Yes CE Marking Compliance Yes **BNCI or BELUS** Planned CIT Planned GOST Yes Saudi Arabian Compliance Planned

Saudi Arabian Compliance Planned

(ICCP)

SABS Planned UKRSERTCOMPUTER Planned



^{1.} Configurations of the HP EliteBook 1050 G1 that are ENERGY STAR® qualified are identified as HP EliteBook 1050 G1 ENERGY STAR on HP websites and on http://www.energystar.gov.

^{2.} EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country. Search keyword generator on HP's 3rd party option store for solar generator accessories at www.hp.com/go/options.

Technical Specifications

DISPLAYS

Panel LCD 15.6 inch FHD (1920x1080) Anti-Glare WLED UWVA 72percent cg 400nits eDP 1.3 + PSR slim N.B.

Outline Dimensions

 $(W \times H \times D)$

Active Area 344.16 x 193.59 (mm) typ.

350.96 x 216.75 (mm) max.

Weight 370 g (max)

Diagonal Size 15.6 (inch)

Thickness 3.2 (mm) max.

Interface eDP 1.3 + PSR (2 lane)

Surface Treatment Anti-glare (AG)

Touch Enabled N/A

Contrast Ratio 600:1 (typical)

Refresh Rate 60 Hz

Brightness 400 nit typical **Pixel Resolution** 1920 X 1080 (FHD)

Format RGB
Backlight LED

Color Gamut Coverage 72% (sRGB)

Color Depth6bit (Hi FRC supportive w/ condition to enable)Viewing Angle85/85/85 (Left/Right/Down/Up) (typical)



Technical Specifications

Panel LCD 15.6 inch FHD (1920x1080) Anti-Glare WLED UWVA 72percent cg 650nits eDP 1.4+PSR ultraslim NB Privacy

Outline Dimensions 350.96 x 216.75 (mm) max.

 $(W \times H \times D)$

Active Area 344.16 x 193.59 (mm) typ.

Weight 320 g (max)

Diagonal Size 15.6 (inch)

Thickness2.6typ.2.8max (mm)InterfaceeDP 1.3 + PSR (2 lane)

Surface Treatment Anti-glare (AG)

Touch Enabled N/A

Contrast Ratio Sharing mode: 600:1 (typ.)

Privacy mode: 150:1 (typ.) 110:1(min.)

Refresh Rate 120 Hz

Brightness 650 nit typical

Pixel Resolution 1920 X 1080 (FHD)

Format RGB
Backlight LED

Color Gamut Coverage Sharing mode: 72% (sRGB)

Privacy mode: 60% (sRGB)

Color Depth 6bit + FRC

Viewing Angle Sharing mode: 85/85/85

Privacy mode: 50/50/85/85



Technical Specifications

Panel LCD 15.6 inch UHD (3840x2160) Anti-Glare WLED UWVA 72percent cg 400nits eDP 1.3 + PSR ultraslim N.B.

Outline Dimensions 350.96 x 216.75 (mm) max.

 $(W \times H \times D)$

Active Area 344.2176 x 193.6224 (mm) typ.

Weight 320 g (max)

Diagonal Size 15.6 (inch)

Thickness 2.6 (mm) max.

Interface eDP 1.3 + PSR (4 lane)

Surface Treatment Anti-glare (AG)

Touch Enabled N/A

Contrast Ratio 1200:1 (typical)

Refresh Rate 60 Hz

Brightness 400 nit typical

Pixel Resolution 3840 x 2160 (UHD)

Format RGB
Backlight LED

Color Gamut Coverage 72% (sRGB)

Color Depth6bit (Hi FRC supportive w/ condition to enable)Viewing Angle85/85/85 (Left/Right/Down/Up) (typical)

NOTE: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Technical Specifications

STORAGE

SSD 1TB 2280 PCIe-3x4 NVMe Form Factor Three Layer Cell single-sided

Form Factor M.2 2280
Capacity 1TB
NAND Type TLC

 Height
 0.09 in (2.3 mm)

 Width
 0.87 in (22 mm)

 Weight
 0.02 lb (<10 g)</td>

 Interface
 PCle NVMe Gen3X4

 Maximum Sequential Read
 2900 MB/s ~ 3000 MB/s

Maximum Sequential Write Up to 2000 MB/s

Logical Blocks 2,000,409,264

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features ATA Security, TRIM; L1.2

SSD 256GB 2280 M2 PCIe-3x4 Form Factor SS NVMe TLC

Form Factor M.2 2280
Capacity 256 GB
NAND Type TLC

 Height
 0.09 in (2.3 mm)

 Width
 0.87 in (22 mm)

 Weight
 0.02 lb (<10 g)</td>

 Interface
 PCIe NVMe Gen3X4

 Maximum Sequential Read
 2580 MB/s ~ 2600 MB/s

 Maximum Sequential Write
 1000 MB/s ~ 1100 MB/s

Logical Blocks 500,118,192

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features ATA Security, TRIM; L1.2

SSD 256GB 2280 M2 SATA-3 Self Encrypted OPAL2 Three Layer Cell Form Factor M.2 2280
Capacity 256 GB
NAND Type TLC

 Height
 0.09 in (2.3 mm)

 Width
 0.87 in (22 mm)

 Weight
 0.02 lb (<10 g)</td>

 Interface
 ATA-8, SATA 3.0

 Maximum Sequential Read
 530 MB/s ~ 560 MB/s

 Maximum Sequential Write
 500 MB/s ~ 530 MB/s

Logical Blocks 500,118,192

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]



Technical Specifications

Features ATA Security; TCG Opal 2.0, DIPM; TRIM; DEVSLP

SSD 256GB 2280 PCIe-3x4 **NVMe Self Encrypted OPAL2 Three Laver Cell**

Form Factor M.2 2280 Capacity 256 GB **NAND Type** TLC

Height 0.09 in (2.3 mm) Width 0.87 in (22 mm) Weight 0.02 lb (<10 q) Interface PCIe NVMe Gen3X4 **Maximum Sequential Read** 2580 MB/s~ 2600 MB/s

Maximum Sequential Write 1000 MB/s~ 1100 MB/s

Logical Blocks 500,118,192

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features ATA Security (Option); TCG Opal 2.0; TRIM; L1.2

SSD 2TB 2280 PCIe-3x4 NVMe Form Factor Three Layer Cell single-sided

M.2 2280 Capacity **2 TB NAND Type** TLC

Height 0.09 in (2.3 mm) Width 0.87 in (22 mm) Weight 0.02 lb (<10 q) PCIe NVMe Gen3X4 Interface **Maximum Sequential Read** Up to 2900MB/s Up to 2100 MB/s **Maximum Sequential Write Logical Blocks** 3,907,029,168

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features ATA Security, TRIM; L1.2

SSD 512GB 2280 M2 PCIe-3x4 Form Factor SS NVMe TLC

M.2 2280 Capacity 512 GB TLC **NAND Type**

Height 0.09 in (2.3 mm) Width 0.87 in (22 mm) Weight 0.02 lb (<10 q) Interface PCIe NVMe Gen3X4 **Maximum Sequential Read** 2800 MB/s~ 2900 MB/s 1000 MB/s~ 1800 MB/s **Maximum Sequential Write**

Logical Blocks 1,000,215,215

Technical Specifications

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features ATA Security, TRIM; L1.2

SSD 512GB 2280 PCIe-3x4 NVMe Self Encrypted OPAL2 Three Laver Cell

Form Factor M.2 2280
Capacity 2 TB
NAND Type TLC

Height 0.09 in (2.3 mm)

Width 0.87 in (22 mm)

Weight 0.02 lb (<10 g)

Interface PCIe NVMe Gen3X4

Maximum Sequential Read Up to 2900MB/s

Maximum Sequential Write Up to 2100 MB/s

Logical Blocks 3,907,029,168

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features ATA Security, TRIM; L1.2

SSD 512GB 2280 M2 SATA-3 Three Layer Cell Federal Information Processing Standard Form Factor M.2 2280
Capacity 512 GB
NAND Type TLC

 Height
 0.09 in (2.3 mm)

 Width
 0.87 in (22 mm)

 Weight
 0.02 lb (<10 g)</td>

 Interface
 ACS-3, SATA 3.2

 Maximum Sequential Read
 Up to 530MB/s

 Maximum Sequential Write
 Up to 400MB/s

 Logical Blocks
 1,000,215,215

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features ATA Security; TCG Opal 2.0; FIPS; DIPM; TRIM; DEVSLP

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

Technical Specifications

POWER

AC Adapter 150 Watt **Smart PFC Slim Barrel** 4.5mm - Vesta

Dimensions 6.02 x 2.60 x .87 in ((153 x 66 x 22 mm)

Weight 0.71 lbs (320 g) Input 100 to 240 VAC

> Input Efficiency 88% min at 115 VAC

Input frequency range 47 to 63 Hz

Input AC current 2.9 A at 90 VAC, 1.45 A at 180 VAC

Output **Output power** 150W 19.5V

DC output

Hold-up time 5 msec at 115 VAC input

Output current limit <16A, Over voltage protection- 29V max

automatic shutdown

Connector 3 pin/grounded, mates with interchangeable cords **Environmental Design** Operating temperature 32° to 95° F (0° to 35° C)

> Non-operating (storage) -4° to 185° F (-20° to 85° C)

temperature

Altitude 32° to 104° F (0° to 40° C) Humidity '-4° to 149° F (-20° to 65° C) **Storage Humidity** 0 to 10,000 ft (0 to 3,048 m)

EMI and Safety Certifications

CE Mark- full compliance with LVD and EMC directives; Worldwide safety standards-IEC950, EN60950, UL1950, Class 1, SELV; Agency approvals- C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCIB, NOM-1 NYCE; MTBF- over 200,000 hours at 25°C ambient condition.

Battery ZG 4 Cell WHr 64 Long Life -PL Fast Charge **Dimensions** $(H \times W \times L)$ 7.9 x 3.49 x 0.32 in (20.08 x 8.86 x 0.81cm)

Weight 0.619lb (281g) Cells/Type 4-cell; Polymer

Energy Voltage 15.4V

Amp-hour capacity 4.155Ah **Watt-hour capacity** 64Wh

Operating (Charging) **Temprature** 32° to 113° F (0° to 45° C)

Operating (Discharging) 14° to 140° F (-10° to 60° C)

Fuel Gauge LED No **Optional Travel Battery**

Available

No

Dimensions $(H \times W \times L)$

13.02 x 3.51 x 0.319 in (33.08 x 8.92 x 0.81 cm)



Technical Specifications

Weight 1.12lb (420g) Cells/Type 6-cell; Polymer

11.55V Energy Voltage

> **Amp-hour capacity** 8.31Ah **Watt-hour capacity** 95Wh

Battery ZG 6 Cell WHr 95 Long Life -PL Fast Charge

Operating (Charging)

32° to 122°F (0° to 50° C)

Operating (Discharging)

14° to 140° F (-10° to 60° C)

Fuel Gauge LED No Warranty 3 year **Optional Travel Battery** No

Available

Temprature

COUNTRY OF ORIGIN

China

^{* 3-}year platform warranty is required for a 3-year Long Life Battery warranty.

Options and Accessories (sold separately and availability may vary by country)



Summary of Changes

Date of change:	Version History:	Description of change:
	v1 to v2	

Copyright © 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Core, Thunderbolt and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. NVIDIA, the NVIDIA logo, GeForce are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. SD, SDHC and SDXC are registered trademarks of SD-3C in the United States, other countries or both. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

