



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: U223-004-IND

### 4-Port Industrial USB 2.0 Hub with 15kV ESD Immunity

#### Highlights

- Industrial-grade, rugged metal enclosure
- ESD Protected to  $\pm 15$  kV
- USB 2.0 Compliant - 480Mbps
- Compatible with all major operating systems



#### Description

Tripp Lite's U223-004-IND is a rugged, all metal constructed USB 4-Port hub for use in data centers, work areas, and Industrial applications. Can be mounted on a wall or din-rail with included mounting hardware. Supports Hi-Speed USB 2.0 transfer rates at 480mbps, but is also backward compatible to USB 1.1 ( 12mbps ). Hub is bus-powered through the computer connection, or can self power with an external adapter ( not included ) or via the included 3-wire terminal block connector ( 9-36V ).

#### Applications

- Use in areas where hub needs to be securely fastened to a surface, such as din rail or wall
- Use in locations where environment is extreme or possible damage could occur

#### System Requirements

- Compatible with all major operating systems

#### Package Includes



- U223-004-IND
- USB cable x 1
- 3-pin power terminal block
- DIN rail mounting hardware
- Wallmount hardware

#### Features

- Industrial-grade, rugged all metal 4-port USB hub
- Supports USB 1.1 and 2.0 transfer speeds ( 12 - 480mbps )
- Wall or Din Rail mountable - hardware included
- Bus Powered or optional 3-Wire DC Terminal Block
- Over-current detection and protection circuit design
- ESD protected to  $\pm 15$  kV
- Automatic link and speed detection
- Plug-and-Play; no software or drivers
- Compatible with all major operating systems

#### Specifications

---

OVERVIEW	
Over Current Protection	Yes
PHYSICAL	
Unit Dimensions (HWD/in)	1 x 2.5 x 5.6
Unit Dimensions (HWD/cm)	2.5 x 6.4 x 14.2
Material of construction	Metal
Mounting accessories included	Yes
Color	Black
ENVIRONMENTAL	
Relative Humidity	5 to 95% RH
Operating Temperature	0C to 60C ( 32F to 140F )
CONNECTIONS	
Connector A	 USB B (FEMALE)
Connector B	 (X4) USB A (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">U022-006</a>	6-ft. USB2.0 A/B Gold Device Cable (A Male to B Male)	1
<a href="#">U022-010</a>	10-ft. USB 2.0 A/B Gold Device Cable (A Male to B Male)	1
<a href="#">U022-015</a>	15-ft. USB 2.0 A/B Gold Device Cable (A Male to B Male)	1
<a href="#">U023-003</a>	3-ft. USB2.0 A/B Gold Device Cable with Ferrite Chokes (A Male to B Male)	1
<a href="#">U023-006</a>	6-ft. USB2.0 A/B Gold Device Cable with Ferrite Chokes (A Male to B Male)	1
<a href="#">U222-004-R</a>	4-Port USB2.0 Ultra-Mini Hub	1
<a href="#">U222-007-R</a>	7-Port USB2.0 Hub	1
<a href="#">U222-010-R</a>	10-Port USB 2.0 Hub	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=5229](http://www.tripplite.com/en/products/model.cfm?txtModelID=5229).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.