

ViewSonic® LED DISPLAY

TD2220-2

Key Features

- 7H hardness screen
- Full HD 1080p resolution
- Supports USB HID
- VGA and DVI inputs
- Energy Star® and EPEAT Silver certification



Product Description

The 22" (21.5"/54.6cm viewable) ViewSonic® TD2220-2 is a multi-touch Full HD LED backlit monitor with 1920x1080 resolution, DVI & VGA inputs and VESA mountable design. It has 20,000,000:1 MEGA Dynamic Contrast Ratio for sharp crisp images and Eco-mode for up to 40%* energy savings come standard in the new 22" (21.5"/54.6cm viewable) offering. Perfect for both commercial and consumer applications, the TD2220-2 supports the USB HID Touch driver and supports Windows® 8 and Windows® 10. The TD2220-2 is a one-stop solution for your multi-touch monitor needs.

Visit Us - www.viewsonic.com

DISPLAY

Display Size (in.):	22
Viewable Area (in.):	21.5
Panel Type:	TN Technology
Resolution:	1920 x 1080
Resolution Type:	FHD
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	20M:1
Light Source:	LED
Colours:	16.7M
Colour Space Support:	8 bit (6 bit + Hi-FRC)
Brightness:	200 cd/m2
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Viewing Angles:	170° horizontal, 160° vertical
Backlight Life (Hours)::	40000 Hrs (Min)
Curvature::	Flat
Refresh Rate (Hz)::	60
Colour Gamut::	NTSC: 72% size (Typ)
Pixel Size::	0.248 mm (H) x 0.248 mm (V)

Touch Screen:: Optical, 2-point multi touch, single touch for Windows XP

Surface Treatment:: Glossy, Hard Coating (7H)

Cover Glass Thickness: 1.88 mm

VIDEO INPUT

Analog:	RGB Analog (75Ω, 0.7 / 1.0 Vp-p)
Digital:	DVI-D (TMDS, 100Ω)
Frequency:	Fh: 24-83KHz; Fv: 50-76Hz
Sync:	Separate Sync / Composite Sync / SOG

COMPATIBILITY

PC:	VGA up to 1920 x 1080
Mac:	MAC up to 1920 x 1080 (Touch function not compatible)

CONNECTOR

Analog:	D-sub *1
Digital:	DVI *1
USB:	Up Stream: Type B *1 Down Stream: Type A *2
Power:	Internal Power Board, 3-pin Plug (CEE22) *1

POWER

Voltage:	AC 100–240V (universal), 50 / 60Hz
Consumption:	(ECO Mode)Standard: 26W; Optimize: 21W; Conserve: 18W

OPERATING CONDITIONS

Temperature:	0° ~ 40° C / 32° ~ 104° F
Humidity:	20%-90% (non-condensing)

DIMENSIONS

Physical:	511mm (width) x 365mm (height) x 240mm (depth)
-----------	--

WEIGHT

Net:	4.9 kg
------	--------

REGULATIONS

cULus, FCC-B, ICES003, Energy Star, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 7.0, EAC, UkrSEPRO, BSMI, RCM, GEMS, VCCI, KC, e-Standby, BIS, CCC, China RoHS, CEL, CECP

WALL MOUNT

100mm x 100mm

PACKAGE CONTENTS

TD2220-2 display, power cable, AC/DC adapter, USB Cable, VGA cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD (available in some countries only)