

HCP36651UC

36" Pyramid Canopy Chimney Hood

300 Series - Stainless Steel



Features and Benefits

Design

- Duct Extension Accessory Kit Available for 9' to 12' Ceilings

Performance

- 2 Halogen Lights - 12 Volt, 20 Watt max., G-4 Base
- 8" round duct at discharge.

Efficiency

- Blower will automatically turn on at high speed if excessive heat is sensed in the control area.
- Absorb odors with charcoal replacement filters.

Convenience

- Convenient timer built into control from 1-60 minutes.
- Signal on LCD display will illuminate as a reminder to check filters for cleaning.
- Audible tone when select controls are pressed.

Notes: All height, width and depth dimensions are shown in inches. *Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be found in a accompanying product literature or you may contact your account manager for further details.

For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.
Copyright ©2014 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.


Litho Date: 03/2014



HCP36651UC

36" Pyramid Canopy Chimney Hood

300 Series - Stainless Steel



* Recirculating installation
** Ducted installation

Installation height above cooking surface:
24"-34" (610 mm-864 mm) to Electric
27"-34" (686 mm-864 mm) to Gas

measurements in inches (mm)

Features

| | |
|------------------------------|--------------------------------------|
| Operating Mode | Convertible: Ducted / Recirculating |
| Number of speed settings | 4-stage |
| Delay Shut off modes | |
| Silence level (dBA) | |
| Required accessories | |
| Optional accessories | HCIFILTUC, HCPEXT5UC, HCREC5UC |
| Number of lights | 2 |
| Type of lamps used | |
| Total power of the lamps (W) | 40 |
| Grease filter material | aluminium |
| Grease filter type | Multilayer cassette |
| Clean filter reminders | Electronic |

Technical Specification

| | |
|---|---|
| UPC code | 825225909033 |
| Material | Stainless steel |
| Watts (W) | 0 |
| Current (A) | |
| Volts (V) | 110 |
| Frequency (Hz) | 60 |
| Approval certificates | CUL, UL |
| Power Cord Length | |
| Plug type | no plug |
| Overall appliance dimensions (HxWxD) (in) | 24 9/16" - 38 7/8" / 28 1/4" - 42 9/16" x 36 " x 19 11/16 " |
| Product packaging dimensions (HxWxD) (in) | 26.37 x 18.11 x 40.55 |
| Height of the chimney (in) | 19 9/16" - 33 7/8"/23 1/4" - 42 9/16" |
| Vertical rise height | |
| Required distance above cooktop/ranges | 24"/27 " |
| Net weight (lbs) | 53 |
| Gross weight (lbs) | 60 |
| Adjustable feet | |
| Motor location | Integrated motor in hood chimney |
| Maximum CFM | |
| Diameter of air duct (in) top | 8 |
| Diameter of air duct (in) back | |
| Discharge direction | |
| No-return airflow flap | Yes |

Notes: All height, width and depth dimensions are shown in inches. *Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be found in a accompanying product literature or you may contact your account manager for further details.

For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.

Copyright ©2014 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.

Litho Date: 03/2014

