



# **Design Considerations: NetApp HCI with RHV**

## **NetApp HCI Solutions**

NetApp  
July 08, 2020

This PDF was generated from [https://docs.netapp.com/us-en/hci-solutions/redhat\\_virtualization\\_design\\_considerations\\_\\_netapp\\_hci\\_with\\_rhv.html](https://docs.netapp.com/us-en/hci-solutions/redhat_virtualization_design_considerations__netapp_hci_with_rhv.html) on October 26, 2021. Always check docs.netapp.com for the latest.

# Table of Contents

Design Considerations: NetApp HCI with RHV ..... 1

# Design Considerations: NetApp HCI with RHV


Review the following design considerations when developing your deployment strategy.

## Networking Requirements

This section describes the networking requirements for the deployment of Red Hat Virtualization on NetApp HCI as a validated solution. It provides physical diagrams of the network ports on both the NetApp HCI compute nodes and the switches deployed in the solution. This section also describes the arrangement and purpose of each virtual network segment used in the solution.

### Port Identification

NetApp HCI consists of NetApp H-Series nodes dedicated to either compute or storage. Both node configurations are available with two 1GbE ports (ports A and B) and two 10/25GbE ports (ports C and D) on board. The compute nodes have additional 10/25GbE ports (ports E and F) available in the first mezzanine slot. Each node also has an additional out-of-band management port that supports Intelligent Platform Management Interface (IPMI) functionality. Each of these ports on the rear of an H410C node can be seen in the following figure.



## Network Design


The NetApp HCI with Red Hat Virtualization solution uses two data switches to provide primary data connectivity at 25Gbps. It also uses two additional management switches that provide connectivity at 1Gbps for in-band management for the storage nodes and out-of-band management for IPMI functionality.

### Cabling Storage Nodes

The management ports A and B must be active on each storage node to configure the NetApp HCI cluster, and provide management accessibility to Element after the solution is deployed. The two 25Gbps ports (C and D) should be connected, one to each data switch, to provide physical fault tolerance. The switch ports should be configured for multi-chassis link aggregation (MLAG) and the data ports on the node should be configured for LACP with jumbo-frames support enabled. The IPMI ports on each node can be used to remotely manage the node after it is installed in a data center. With IPMI, the node can be accessed with a web-browser-based console to run the initial installation, run diagnostics, and reboot or shut down the node if necessary.

## Cabling Compute Nodes

The two 25Gbps ports (C and E) should be connected, one to each data switch, to provide physical fault tolerance. The switch ports should be configured for multi-chassis link aggregation (MLAG), and the data ports on the node should be configured for LACP with jumbo-frames support enabled. The IPMI ports can also be used to remotely manage the node after it is installed in a data center. With IPMI, the node can be accessed with a web-browser-based console to run the initial installation, run diagnostics, and reboot or shut down the node if necessary.



## VLAN Requirements

The solution is designed to logically separate network traffic for different purposes by using Virtual Local Area Networks (VLANs). NetApp HCI requires a minimum of three network segments. However, this configuration can be scaled to meet customer demands or to provide further isolation for specific network services. The following table lists the VLANs that are required to implement the solution, as well as the specific VLAN IDs that are used later in the validated architecture deployment.

VLANs	Purpose	VLAN Used
Out-of-band management network	Management for HCI nodes / IPMI	16
In-band management network	Management for HCI nodes / ovirtmgmt	1172

VLANs	Purpose	VLAN Used
Storage network	Storage network for NetApp Element.	3343
Migration network	Network for virtual guest migration.	3345
VM network	Network for virtual guests.	3346

## Network Infrastructure Support Resources

The following infrastructure should be in place prior to the deployment of the Red Hat Virtualization on NetApp HCI solution:

- At least one DNS server providing full host-name resolution that is accessible from the in-band management network and the VM network.
- At least one NTP server that is accessible from the in-band management network and the VM network.
- Outbound internet connectivity is recommended, but not required, for both the in-band management network and the VM network.

## Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.