

# **SAR Exemption Evaluation**

**Applicant** Huawei Device Co., Ltd.

**FCC ID** 2ATEYLEA-B19

**Product** HUAWEI Smart Band

Model LEA-B19; LEA-B19B

**Report No.** R2205A0473-S1V1

Issue Date June 13, 2022

fany ym wes

Prepared by: Fangying Wei

Guangchang Fan

Approved by: Guangchang Fan

## TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

## **Table of Contents**

1 T	est Laboratory	. 4
1.1	Notes of the Test Report	. 4
1.2.	. Test facility	. 4
	Testing Location	
	Laboratory Environment	
	Description of Equipment under Test	
	Output Power	
	EX A: The EUT Appearance	

Version	Revision description	Issue Date
Rev.0	Initial issue of report.	May 31, 2022
Rev.1	Update information.	June 13, 2022

Report No.: R2205A0473-S1V1

Note: This revised report (Report No. R2205A0473-S1V1) supersedes and replaces the previously issued report (Report No. R2205A0473-S1). Please discard or destroy the previously issued report and dispose of it accordingly.



### 1 Test Laboratory

#### 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology** (shanghai) co., Ltd. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

#### 1.2. Test facility

#### FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

#### 1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.

Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

City: Shanghai

Post code: 201201

Country: P. R. China

Contact: Fan Guangchang

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000

Website: http://www.ta-shanghai.com

E-mail: fanguangchang@ta-shanghai.com

### 1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C			
Relative humidity	Min. = 30%, Max. = 70%			
Ground system resistance	< 0.5 Ω			
Ambient noise is checked and found ve	ery low and in compliance with requirement of standards.			

Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.

## 2 Description of Equipment under Test

#### **Client Information**

Applicant	Huawei Device Co., Ltd.		
Applicant address	No.2 of Xincheng Road, Songshan Lake Zone, Dongguan, Guangdong 523808, People's Republic of China		
Manufacturer	Huawei Device Co., Ltd.		
Manufacturer address	No.2 of Xincheng Road, Songshan Lake Zone, Dongguan, Guangdong 523808, People's Republic of China		

#### **General Technologies**

Model	LEA-B19; LEA-B19B
MAC	DC9166E8F195
Hardware Version	Ver A
Software Version	12.0.2.108
Date of Testing:	May 10, 2022 ~ May 12, 2022
Date of Sample Received:	May 10, 2022

Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.

- 2. All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.
- 3. The customer claims that LEA-B19 and LEA-B19B are only different in model, and the others are the same.

#### 3 Output Power

Bluetooth	Ch	Tune-up		
(Low Energy)	Ch 0/2402 MHz	Ch 19/2440 MHz	Ch 39/2480 MHz	Limit (dBm)
GFSK	4.27	4.55	4.36	6.00

All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR

- > f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- > The result is rounded to one decimal place for comparison

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Band	Configuration	Frequency (MHz)	Distance (mm)	Tune-up (dBm)	Ratio	SAR test exclusion thresholds	Evaluation
Bluetooth (Low Energy)	Extremity	2480	5	6.00	1.25	7.5	No

Note: Based on SAR test exclusion, all values meet the SAR test exclusion thresholds and are exempt from routine RF exposure evaluation.

\*\*\*\*\*END OF REPORT \*\*\*\*\*



## **ANNEX A: The EUT Appearance**

The EUT Appearance are submitted separately.