

F690501/RF-RTL014105-1

Page:

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: BEJIA91270TERG

Equipment Under Test

: Car Navigation System

Model Name

: IA91270TERG

Applicant

: LG Electronics USA

Manufacturer

: LG Electronics Inc.

Date of Receipt

: 2019.06.03

Date of Test(s)

: 2019.06.05 ~ 2019.06.14

Date of Issue

: 2019.07.29

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Date:

2019.07.29

Jinhyoung Cho

Jungmin Yang

Technical Manager:

Date:

2019.07.29

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014105-1 Page: 2 of 6

TABLE OF CONTENTS

	Page
1. General Information	3
2. RF Exposure Evaluation	5



Report Number: F690501/RF-RTL014105-1 Page: 3 of 6

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant : LG Electronics USA.

Address : 1000 Sylvan Avenue, Englewood Cliffs, New Jersey, United States, 07632

Contact Person : Han, Kyung-su Phone No. : +1 201 472 2623

1.3. Details of Manufacturer

Company : LG Electronics Inc.

Address : 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Korea, 07796

1.4. Description of EUT

Kind of Product	Car Navigation System	
Model Name	IA91270TERG	
Power Supply	DC 12 V	
Frequency Range	LTE Band 7: 2 500 Mb ~ 2 570 Mb	
Emission Designator	LTE Band 7 (5 吨): 4M53G7D (QPSK) / 4M53W7D (16QAM) LTE Band 7 (10 吨): 8M94G7D (QPSK) / 8M94W7D (16QAM) LTE Band 7 (15 吨): 13M5G7D (QPSK) / 13M5W7D (16QAM) LTE Band 7 (20 吨): 17M9G7D (QPSK) / 17M9W7D (16QAM)	
Antenna Gain	-1.67 dBi	

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014105-1 Page: 4 of 6

1.5. Test Report Revision

Revision	Report Number	Date of Issue	Description	
0	F690501/RF-RTL014105	2019.07.23	Initial	
1	F690501/RF-RTL014105-1	2019.07.29	Revise RF exposure test result	



Report Number: F690501/RF-RTL014105-1 Page: 5 of 6

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (쌘)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (ﷺ)	Average Time		
(A) Limits for Occupational/Controlled Exposure						
0.3-3.0	614	1.63	*100	6		
3.0-30	1842/f	4.89/f	*900/f ²	6		
30-300	61.4	0.163	1.0	6		
300-1 500	-	-	f/300	6		
1 500-100 000	-	-	5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3-1.34	614	1.63	*100	30		
1.34-30	824/f	2.19/f	*180/f ²	*180/f ² 30		
30-300	27.5	0.073	0.2	0.2 30		
300-1 500	-	-	f/1500	30		
1 500-100 000	-	-	1.0	<u>30</u>		

2.1.1. Friis transmission formula: $Pd = (Pout*G)/(4*pi*R^2)$

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014105-1 Page: 6 of 6

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

LTE Band 7

- Maximum tune up tolerance

Frequency Range (쌘)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (ﷺ/ﷺ)	Limits (mW/cm²)
2 500 ~ 2 570	26.73	-1.67	0.063 787	1

Remark:

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².

- End of the Test Report -