







DELIVERING PRODUCTS THAT PERFORM

TABLE OF CONTENTS

- #01. PORTABLE POWER STATIONS
 AND SOLAR PANEL
 BLUETOOTH® JOBSITE EARBUDS
- #02. POWERBOX 1

 RECHARGEABLE SELF-LEVELING GREEN PLANAR
 LASER LEVEL AND TRIPOD
- **#03.** SLIM-TIP INSULATED SCREWDRIVERS & SETS IMPACT FLIP SOCKETS
- **#04.** 14-IN-1 HVAC ADJUSTABLE-LENGTH SCREWDRIVER WITH FLIP SOCKET 27-IN-1 PRECISION MULTI-BIT SCREWDRIVERS
- **#05.** ELECTRICIAN'S HAMMERS

 PASS-THRU™ MODULAR RJ45 DATA PLUGS
 FOR CAT6A CABLE
- **#06.** STRAIN RELIEF CABLE BOOTS FOR RJ45 DATA PLUGS CABLE MANAGEMENT SOLUTIONS
- **#07.** HARD HAT/SAFETY HELMET COOLING FAN CAMOUFLAGE NECK AND FACE COOLING BAND

- **#08.** HINGED GEL KNEE PADS
 PERFORMANCE THERMAL SOCKS
 HIGH-VISIBILITY WINTER BOMBER JACKET
- **#09.** ADVANCED CIRCUIT TRACER KIT
 TEST KIT WITH MULTIMETER, NON-CONTACT VOLTAGE
 TESTER, AND RECEPTACLE TESTER
- **#10.** INFRARED THERMOMETER WITH GFCI RECEPTACLE TESTER KIT

 NON-CONTACT VOLTAGE TESTER
- **#11.** UTILITY LED LIGHT
- **#12.** 2-IN-1 IMPACT SOCKET SET, 6-POINT, 6-PIECE
- **#13.** 2-IN-1 COATED IMPACT SOCKET WIDE RANGE DISTRIBUTION GRIPS

ELECTRICAL DATA COM HVAC CONSTRUCTION UTILITY INDUSTRIAL FACILITIES/MAINTENANCE TELECOM

Warning Symbols



Warning Symbol



Laser Warning



Risk Of Shock



Strong Magnetic Field



For Use on Bare Live Conductor (Clamp Meter)



Double Insulated



Wear Eye Protection



Read Instructions Before Use



Pinch Point Hazard



Do Not Use On Or Near Live Electrical Circuits



Do Not Use To Chisel



Do Not Use To Pry



Do Not Push Or Hammer



Do Not Strike Hammer Faces Together



Do Not Extend Handle Length



Do Not Sit



Do Not Step or Stand

KTB1000

PORTABLE POWER STATIONS AND SOLAR PANEL

No Gas • No Fumes • Just Power

- Delivers Pure Sine-Wave AC power
- Built-in Lithium-ion battery pack allows for safe indoor use
- Two models charge and power multiple devices
 - 505 Wh features two 120V outlets, four USB ports (60W USB-C PD, USB-C and 2 x USB-A) and a 12V car port
 - 983 Wh features four 120V outlets, six USB ports (3 x 60W USB-C PD and 3 x USB-A) and a 12V car port
- Power to run hammer drills, miter saws and more (Cat. No. KTB1000)
- Lightweight design and collapsible handle maximize portability (Cat. No. KTB500)
- Enough capacity to power a 5,000 lumen, 50W work light for 16 hours (Cat. No. KTB1000) or 8 hours (Cat. No KTB500)
- Extended run time of your KTB1000 or KTB500 with the 60W Portable Solar Panel (Cat. No. 29250)
 - Charge power banks, power stations, and portable batteries
 - Chain an additional panel (up to 120W) to collect more solar power and increase charge times
 - Foldable to easily carry on the jobsite
- Great for customers in: Electrical, Construction, HVAC, Facilities/Maintenance, Industrial, and Utility

(TB1000 Part #: 060X140	KTB500 Part #: 060X143

KIBIOOO FAIL#: OOOXI40							
Cat. No.	Description	AC Power	Number of Outputs	USB Ports	Recharge Time	Solar Panel (29250) Compatibility	Included
KTB1000	Portable Power Station, 983Wh	1500W	11	6	2.5 hrs fast charging (80% charge) 7.5 hrs standard charging (80% charge)	Up to 2 panels	Fast charger, mobile charger, 12V car port adapter
KTB500	Portable Power Station, 505Wh	500W	7	4	8-10 hrs standard charging (Full charge)	1 panel	Wall charger, 12V car port adapter
Cat. No.	Description	Wattage	Amperage	Voltage	Ports	Cable Size	Included
29250	Solar Panel	60	3.34A Maximum	18V Maximum	Output: APP®: 18V/3.34A USB-A: 5V/3.0A Input: APP® USB-A Port	16 AWG	Powerpole® to 8mm DC Adapter, APP® Output Cable and USB-A Output Port

Times and charges are approximate, and not additive, and may vary by application, and ambient environmental conditions. Anderson Powerpole® is a registered trademark of Anderson Power Products, Inc.

BLUETOOTH® JOBSITE EARBUDS

- Noise Reduction Rating (NRR) 28 dB
- Seamlessly stream high-quality stereo audio
- Interchangeable Memory Foam tips provide hearing protection; Silicone tips can be switched out for casual listening
- Easy one-step pairing via trusted Bluetooth 5.0 up to 33 ft
- 15-hour total run time (with charging case)
- Built in microphones for hands-free calling
- IP67 rated: dust- and water-proof (earbuds only)
- Included USB-A to USB-C cable for convenient charging
- **Great for customers in:** Electrical, Construction, HVAC, Facilities/Maintenance, Industrial, Telecom, and Utility

Cat. No.	Description	Overall Length	Overall Height	Overall Width
AESEB1	Bluetooth® Jobsite Earbuds	5.46" (13.8 cm)	5.39" (13.7 cm)	2.34" (5.9 cm)





POWERBOX 1

Magnetic Mounting · LED Lighting · USB-C Power Delivery

- Magnetically mounts to metal job boxes and workbenches
- Four 120V AC outlets, two USB-A ports and one PD capable USB-C port for fast charging of cell phones, laptops, and other compatible devices
- LED lights brighten up any job box to locate stored tools, batteries, and cords
- Surge protection with LED indicator light protects equipment from electrical spikes
- 5' durable power cord supplies power to job boxes and work benches
- Extended strain relief on power cord increases durability for long product life
- Mount to non-magnetic locations with the built-in hanging holes
- **Great for customers in:** Electrical, Construction, HVAC, Facilities/ Maintenance, Industrial, and Utility

Cat. No.	Description	Dimensions
29601	PowerBox 1	5.8" x 1.8" x 4.7" (14.8 x 4.6 x 12 cm)





RECHARGEABLE SELF-LEVELING GREEN PLANAR LASER LEVEL

Three orthogonal planar lasers project 360° lines

- X-, Y-, and Z-planes project independently or together
- Intersection of the Y-plane and Z-plane create plumb marks
- Easy-to-see 360° bright green laser lines
- 9+ hour run time with integrated rechargeable Li-Ion battery
- Integrated magnetic mounting bracket with 1/4-20 tripod mounting threads
- Replacement Li-Ion battery (Cat. No. 29026) sold separately

TRIPOD

- Adjustable legs and non-skid feet add stability
- Built-in bullseye level helps keep the tripod on a level plane
- Compact and made of lightweight aluminum construction
- Quick release plate with 1/4-20 mounting threads
- Pan and tilt handle allows for 360° rotation
- Collapses and stores easily in the provided pouch
- Reaches a height of 61" once the legs and pedestal are fully extended
- **Great for customers in:** Electrical, Construction, HVAC, Facilities/Maintenance, Industrial, Telecom, and Utility





Cat. No.	Description	Dimensions
93PLL	Rechargeable Self-Leveling Green Planar Laser Level	5.5" x 3.5" x 4.8" (2.2 x 1.4 x 1.9 cm)
29026	Lithium-ion Battery Pack (Replacement Part)	1.9" x 3" x 1.9" (0.8 x 1.2 x 0.8 cm)
69345	Tripod	23" x 4.5" x 4.5" (9.1 x 1.8 x 1.8 cm)







SLIM-TIP INSULATED SCREWDRIVERS & SETS

Now with additional lengths and tips plus a 6-piece set

- 6-Piece Set includes 5 screwdrivers and a magnetizer:
 - 1/4" Cabinet Tip, #2 Phillips in 4" (10 cm) shanks
 - 3/16" Cabinet Tip, #1 Phillips, #2 Square Tips in 6" (15 cm) shanks
 - Magnetizer
- Meet or exceed ASTM F1505-16 and IEC 60900: 2018 standards for insulated tools
- 1000 volt rated layer of orange impact and flame-resistant insulation
- Slim-tip blades allow for easier access to terminal blocks, slim-style breakers and other tight spaces
- Tips sit flush with shafts to help reduce insulation chipping and cracking
- · Cushion-Grip handles for greater torque and comfort
- Tip-Ident® identifies tip type and orientation for quick engagement with the fastener
- Great for customers in: Electrical, Construction, HVAC, Facilities/Maintenance, Industrial, Telecom, and Utility





	Cat. No.	Tip	Type	Shank	Blade Length	Overall Length
	6924INS	1//" /6 mm\	_		4" (10 cm)	8.31" (21 cm)
S	6926INS	1/4" (6 mm)			6" (15 cm)	10.31" (26 cm)
VER	6916INS	3/16" (5 mm)			6" (15 cm)	10.31" (26 cm)
SCREWDRIVERS	6956INS	#1			6" (15 cm)	10.31" (26 cm)
EW	6934INS	#2	0	Round	4" (10 cm)	8.31" (21 cm)
SCR	6936INS	#2			6" (15 cm)	10.31" (26 cm)
	6984INS	#1			4" (10 cm)	8.31" (21 cm)
	6986INS	#1			6" (15 cm)	10.31" (26 cm)
INDIVIDUAL	6944INS	#2	0		4" (10 cm)	8.31" (21 cm)
=	6946INS	#2			6" (15 cm)	10.31" (26 cm)
	MAG2	Magnetizer / Demagnetizer				

9519						
33732INS	33734INS	33736INS				
•	•	•				
	•	•				
	·	•				
•	•	•				
	•	•				
		•				

IMPACT FLIP SOCKETS

Patent-pending flip socket design can be used as a screwdriver or with an impact driver

- Quickly and easily change blade between a screwdriver handle and an impact driver
- Multi-function ¼" socket has both shallow (driver) and deep (bit holder) configurations for added versatility
- Powerful Rare-Earth magnet securely holds bits and hex head fasteners
- Features ¼" Quick-Connect adapter for easy use with an impact driver
- · Sockets are color coded for easy identification
- · Detachable sockets allow for easy removal of metal shavings from magnet
- · Sockets store on shaft in any order or orientation
- **Great for customers in:** Electrical, Construction, HVAC, Facilities/Maintenance, and Industrial







IMPACT RATED!

Cat. No.	Description	Hex Sizes Included
32900	7-in-1 Impact Flip Socket Set	1/4", 5/16", 11/32", 3/8", 7/16", 1/2"
32907	7-in-1 Impact Flip Socket Set - No Handle	1/4, 5/10, 11/32, 3/0, 7/10, 1/2
32766	3-in-1 Impact Flip Socket, 3" Length	
32767	3-in-1 Impact Flip Socket, 5" Length	1/4", 5/16"
32768	2-Piece 3-in-1 Impact Flip Socket Set (includes 32766 & 32767)	




14-IN-1 HVAC ADJUSTABLE-LENGTH SCREWDRIVER WITH FLIP SOCKET

Featuring the most commonly used HVAC driver bits and nut drivers on one tool

 Includes ¼" and 5/16" nut drivers with 12 driver bits conveniently housed in the handle

- Adjustable-length blade can be removed for use with an impact driver or Klein Tools screwdriver (Cat. No. 32303)
- Multi-function ¼" socket has both shallow (driver) and deep (bit holder) configurations for added versatility
- Impact rated blade can be removed for use in an impact drill
- Powerful Rare-Earth magnet securely holds bits and hex head fasteners
- Great for various applications including tight spaces, impact driving and long reach
- Great for customers in: Electrical, Construction, HVAC, Facilities/Maintenance, and Industrial





Schrader® is a registered trademark of Schrader-Bridgeport International, Inc.

14-in-1 HVAC Adjustable-Length

Screwdriver with Flip Socket*

Cat. No.

32304

Description

27-IN-1 PRECISION MULTI-BIT SCREWDRIVERS

 Double-sided bits conveniently housed in the handle eliminating the need for a bulky bit block

Barrel contains powerful Rare-Earth magnets for securing bits and fasteners


1/4". 5/16"

Hex Sizes Included

- Stainless steel barrel provides great impact and wear resistance
- Cat. No. 32328 includes bits to repair most Apple® products
- Great for customers in: Electrical, Construction, Datacom, HVAC, Facilities/Maintenance, and Industrial







TORX® is a registered trademark of Acument Intellectual Properties, LLC. Apple® is a trademark of Apple, Inc.

ELECTRICIAN'S HAMMERS

Heavy-duty forged steel heads paired with high-strength fiberglass core handles for optimal shock absorption

- Heavy-duty forged steel heads for durability
- · High-strength fiberglass cores for maximum shock absorption
- Cat. No. H80718 features an engineered claw pulling feature for NMB (Romex®) staple removal
- Tether holes for securing tool when working at height
- Available in a variety of lengths and head weights
- Great for customers in: Electrical, Construction, HVAC, Facilities/Maintenance, Industrial, and Telecom





Cat. No.	Туре	Overall Length	Head Weight	Features
H80816	Straight-Claw	13" (33 cm)	16 oz.	• Tether hole
H80820	Straight-Claw	13" (33 cm)	20 oz.	• Tether hole
H80718	Straight-Claw	15" (38 cm)	18 oz.	• Engineered claw pulling feature for NMB (Romex®) staple removal • Tether hole
H80332	Ball-Peen	15" (38 cm)	32 oz.	Crowned face with uniform bevel Smoothly rounded peen Tether hole



Romex® is a registered trademark of Southwire Company.

PASS-THRU™ MODULAR RJ45 DATA PLUGS FOR CAT6A CABLE

Klein's exclusive Pass-Thru™ connectors provide fast, reliable and consistent data connector installations with less wasted materials

- For CAT6A UTP/STP and larger diameter/thicker jacket CAT6 cable
- · Works with indoor/outdoor CAT6 cable
- CAT6A cable easily passes through connector
- 8 position, 8 contact Pass-Thru[™] type data plugs for solid or stranded wire
- For use with Klein Tools Pass-Thru™ Modular Crimper (Cat. No. VDV226-110)
- Available in 50, 100 and 200-piece packs
- Great for customers in: Electrical, Construction, Datacom, HVAC, Facilities/Maintenance, and Industrial









CAT6A UTP

Cable Type	Cat. No.	Pack Size
	VDV826-728	10
CAT5e	VDV826-702	50
	VDV826-762	200
	VDV826-729	10
CAT6	VDV826-703	50
	VDV826-763	200
CAT6A UTP*	VDV826-704	50
CAIDAUIP	VDV826-764	200
CATEA CTD**	VDV826-705	50
CAT6A STP**	VDV826-754	100

^{*} Unshielded Twisted Pair **Shielded Twisted Pair



STRAIN RELIEF CABLE BOOTS FOR RJ45 DATA PLUGS

Cable identification and connector protection

- · Boots help keep connectors on cable
- Compatible with CAT5e and CAT6 cable
- Includes 5 different colors to color code cables for easy identification
- · Protect against latch damage
- Flexible ABS plastic material does not damage cables
- Available in a pack of 100
- Great for customers in: Electrical, Construction, Datacom, HVAC, Facilities/Maintenance, and Industrial



Cat. No.	Description	Connector Type	Cable Type	Pack Size
VDV824-650	Strain Relief Boots	RJ45 Data Plugs	CAT5e/CAT6	100



Cat. No.	Description	Quantity
450-320	Cable Sleeves, 1.25" Wide, 3' Long	2
450-330	Cable Sleeves, 1.75" Wide, 3' Long	2
450-600	Cinch Straps, 6", 8", 14" Multi-Pack	6
450-400	Cable Mounting Clips, Single Hole	10
450-410	Cable Mounting Clips, Triple Hole	10
450-700	Stretch Cable Tie Roll	75'
450-200	Cable Ties, 7.75" length (Black)	100
450-210	Cable Ties, 11.5" length (Black)	100
450-900	Hook & Loop Dispenser, Belt & Magnet	1
450-950	Hook & Loop Roll, 3/4" width, 25' length, (Black)	1
450-960	Hook & Loop Roll, 3/4" width, 25' length, (White)	1













HARD HAT/SAFETY HELMET COOLING FAN

Effective, lightweight, compact personal cooling solutions

- Attaches directly to Klein Hard Hats & Safety Helmets' exclusive accessory mounts – no straps needed!
- 16 configurations to cool face, neck or under shell
- Dual centrifugal fans feature high and low speed; Up to 6 hours continuous run time
- Rechargeable Battery (29025) included. Also sold separatelyfor use while primary battery is charging
- Modular Battery can also charge or power other products via two input/output USB-C ports
- Cat. No. 60155 includes Cooling Fan, Modular Battery, Short Ducts, Long Ducts, Charging Cables, Cable Clip
- Great for customers in: Electrical, Construction, Datacom, HVAC, Facilities/Maintenance, Industrial, Telecom, and Utility







29025

CAMOUFLAGE NECK AND FACE COOLING BAND

Limited Edition - available while supplies last

Intrinsically Safe LED Headlamp

- Designed using super evaporative performance knit fabric
- · Anti-odor treatment for long lasting freshness
- Machine washable, moisture-wicking fabric can be worn wet or dry
- When wet, cooling is instant and can last for hours
- Also available in Blue (Cat. No. 60439) and High-Visibility Yellow (Cat. No. 60465)
- Great for customers in: Electrical, Construction, Datacom, HVAC, Facilities/Maintenance, Industrial, Telecom, and Utility

Cat. No.	Description	Material	UV Protection	Length	Width
60493	Neck and Face Cooling Band	92% Polyester, 8% Spandex	UPF 50+	20" (50.8 cm)	10" (25.4 cm)





60156

HINGED GEL KNEE PADS

Multi-layer gel padding system for all day comfort and protection

- Designed with a top strap positioned above the knee to reduce shifting and to keep the knee pad centered
- Lightweight multi-layer pressure absorbing gel padding system provides heavy duty knee support for all-day comfort
- Durable slip-resistant rounded synthetic rubber kneecaps grip work surfaces for ultimate stability while allowing side-to-side mobility
- · Adjustable elastic straps allow you to dial in a custom fit
- Quick-release clips secure upper and lower straps for easy on/off
- Breathable mesh and neoprene lining to keep you cool
- Great for customers in: Electrical, Construction, Datacom, HVAC, Facilities/Maintenance, and Industrial

1	7		103	
1		(FUBLES)	M	000
	60344			
nensions x 10 7" x 9 8"	ı `			

Cat. No.	Description	Material	Dimensions
60344	Hinged Gel Knee Pads	35% Nylon, 20% Polyester, 15% Thermoplastic Rubber, 15% EVA, 10% NBR, 5% Iron	3.5" x 10.7" x 9.8" (8.9 x 27.3 x 25.0 cm)

WINTER GEAR

Recent additions to our winter gear line:

PERFORMANCE THERMAL SOCKS

- Merino wool regulates temperature, wicks away moisture, and reduces odor
- Mid-length socks have a seamless toe closure for comfort and reinforced heel for abrasion resistance
- Mesh instep provides breathability and cushioned foot bed provides all day comfort

HIGH-VISIBILITY WINTER BOMBER JACKET

- Now available in XXL (60501)
- Other sizes include L (Cat. No. 60364) and XL (Cat. No. 60380)
- Water and wind resistant with insulation for superior warmth
- Features multiple pockets, attached inset hood, and zippered underarm vents
- ANSI rated Type R, Class 3
- **Great for customers in:** Utility, Electrical, Construction, Facilities/Maintenance, Industrial, Telecom, and Utility







Cat. No.	Description	Size	Machine Washable
60508	Performance Thermal Socks	L	Yes
60509	Performance Thermal Socks	XL	Yes
60501	High-Visibility Winter Bomber Jacket	XXL	Yes





ADVANCED CIRCUIT TRACER KIT

Easily trace energized and non-energized breakers, fuses, and wires

- Easily adjust receiver sensitivity level to detect the transmitted signal on breakers, fuses, and wire through drywall, cement block, and underground
- Audible beep and visual indicator on receiver denotes signal strength
- Receiver features a flashlight for illumination in low-light areas and NCV function to test if wires are energized
- Versatile applications include tracing wires, conduit or pipes, and a single wire in a bundle
- Transmitter has AC/DC external voltage indicators 12V, 48V, 120V, 240V, 480V
- Great for customers in: Electrical, Construction. HVAC, Facilities/Maintenance, and Industrial











Cat. No.	Description	Included
ET450	Advanced Circuit Tracer Kit	Transmitter, Receiver, Blade and Ground Prongs, Alligator Clips, 3' and 20' Lead Adapters, AC Plug Leads, Instructions, All Required Batteries, Hard Carrying Case
Replacement Parts	3	
69357	AC Plug to Banana Jack	
69358	20' Banana Jack Cable	
69359	3' Banana Jack Cables, Red and Black	
69360	Alligator Clamps and Outlet Tabs	

TEST KIT WITH MULTIMETER, NON-CONTACT VOLTAGE TESTER, AND RECEPTACLE TESTER

Meets a variety of electrical testing applications in one convenient kit

MANUAL-RANGING MULTIMETER, 600V WITH TEST LEADS

- Measures up to 600V AC/DC voltage, 10A DC current and 2MOhms resistance
- · Tests continuity with visual and audible continuity indicators

NON-CONTACT VOLTAGE DETECTOR. 50 TO 1000 VAC

 Non-contact detection of voltage in cables, cords, circuit breakers, lighting fixtures, switches, non tamper-resistant outlets and wires

RECEPTACLE TESTER

- Detects wiring configurations and indicates correct wiring, and identifies common wiring faults
- Identifies open ground, open hot, open neutral, hot/ground reversed

Cat. No.	Included
	• Manual
69149P	 Non-Co

- -Ranging Multimeter, 600V with Test Leads (MM300)
- Non-Contact Voltage Detector, 50 to 1000 VAC (NCVT-1P)
- Receptacle Tester (RT105)
- All required batteries and manuals



SPC Part #: 060X375

INFRARED THERMOMETER WITH GFCI RECEPTACLE TESTER KIT

Save over 12% by purchasing this convenient kit with two best sellers

INFRARED DIGITAL THERMOMETER WITH TARGETING LASER, 10:1

- · Optical resolution (distance-to-spot) of 10:1
- Features include targeting laser, automatic hold, backlit display, low battery, auto power-off
- Measurement range is -4 to 752°F (-20 to 400°C)
- Fixed emissivity at 0.95
- Not a medical device; thermometer is NOT intended for use on people or animals

GFCI OUTLET TESTER

- Detects the most common wiring problems in standard and GFCI receptacles
- Works on GFCI outlets and confirms operation of the ground fault protective device
- Nominal Voltage: 110/125V AC at 50/60Hz in 3-wire outlet
- Great for customers in: Electrical, Construction, Datacom, HVAC, Facilities/Maintenance, and Industrial



IR1KIT

Cat. No.	Included
IR1KIT	 Infrared Digital Thermometer with Targeting Laser, 10:1 (IR1) GFCI Outlet Tester (RT210) All required batteries and manuals

NON-CONTACT VOLTAGE TESTER

50 to 1000V AC power operating range allows broad application

- Provides non-contact detection of voltage in cables, cords, circuit breakers, lighting fixtures, switches, non tamper-resistant outlets and wires
- · High intensity, bright green LED indicates the tester is powered on
- When voltage is detected, a high intensity, bright red LED illuminates and an audible tone will sound
- Lightweight compact design with a convenient clip to fit securely in your pocket
- Auto power-off feature conserves and extends battery life
- CAT IV 1000V safety rating
- Drop protection to 6.6' (2 m)
- Great for customers in: Electrical, Construction, Datacom, Facilities/Maintenance, Industrial, and Telecom




Cat. No.	Description	Batteries	Included
NCVT-1P	Non-Contact Voltage Detector, 50 to 1000V AC	2 x AAA	Batteries

UTILITY LED LIGHT

Portable, versatile lighting on the worksite

- Cordless LED Light illuminates both the inside of a utility bucket and the outside working area
- Clamp function locks to either the straight wall or corner of most utility buckets for optimal positioning
- Rotates 300° horizontally and 180° vertically for maximum exposure
- Flood, Spot and both Flood-Spot settings provide a variety of lighting options up to 2,500 lumens
- Second light in mounting handle illuminates the inside of the utility bucket to find tools fast
- Sturdy build to work standalone
- Powered by DEWALT 20V lithium-ion batteries; fits up to 8 Ah batteries (sold separately or with Cat. No. BAT20UBL1)
- Kit (Cat. No. BAT20UBL1) includes two 4 Ah batteries and a charger
- Great for customers in: Electrical, Datacom, HVAC, Facilities/Maintenance, Industrial, Telecom, and Utility







Cat. No.	Description	Lumens	Included
BAT20UBL	Utility LED Light	• Spot: 900 Lumens - 8.5 hours (using 20V 4Ah battery)	Light
BAT20UBL1	Utility LED Light Kit	• Flood: 1600 Lumens - 5 hours (using 20V 4Ah battery) • Spot + Flood: 2500 Lumens - 3.5 hours	Light, 4 AH batteries (2x) and charger



2-IN-1 IMPACT SOCKET SET, 6-POINT, 6-PIECE

6-point design in a 6-piece set

- Single-ended impact socket with hands-free adjustment between socket sizes
- 6-point design is easier to position and work with square fasteners
- Includes 12 commonly used sizes in 6 easy-to-carry sockets
- Deep socket with ½" drive works great for hardware installation and removal
- Two coaxial spring loaded sockets in one tool
- Engineered for use with impact wrenches including Klein's
 1/2" Compact Impact Wrench (Cat. Nos. BAT20-CW, BAT20-CW1)
- Sockets are color coded to quickly identify sizes
- Includes case for storage
- Great for customers in: Electrical, Construction,
 Facilities/Maintenance, Industrial, Telecom, and Utility









2-IN-1 COATED IMPACT SOCKET

20% lighter than traditional impact sockets*

- Blue coating is easy to spot in a crowded tool bag
- Durable plastic coating protects against damage due to scratching and abrasion
- Featuring two of the most commonly used socket sizes (3/4" and 9/16") in one tool
- High-torque, 12-point design is easier to position and works with square fasteners
- Great for customers in: Electrical, Construction, HVAC, Facilities/Maintenance, and Industrial







Cat. No.	Description	Socket Sizes	Points
66030	2-in-1 Coated Impact Socket	3/4" x 9/16"	12

^{*}As compared to Klein Tools 66001 socket.

WIDE RANGE DISTRIBUTION GRIPS

20% lighter with one-handed grip action

- 20% lighter than standard KT4500 grip
- Round jaw holds wider range of cable (#6 copper up to 477)
 less tools in the bucket
- One-handed design makes for easier actuation
- Large opening in the handle accommodates a wide variety of hooks on hoists, winches and tackle blocks
- · Spring closes grip on cable to hold the initial position
- Max Safe Load of 5000-lbs (2,268 kg)
- 0.162" to 0.883" (4.11 to 22.42 mm) diameter cable range
- Great for customers in: Utility





Cat. No.	Body Style	Cable Type	Nominal Guy Strand Sizes	Maximum Safe Load	Spring	Hot Latch	Locking Handle	Jaw Length	Approx. Weight
16477	Darallal	Bare Copper,	0.162" to 0.883"	5,000 lbs		_	_	3.31"	2.9 lbs
16477-20	Parallel	Aluminum, ACSR	(4.11 to 22.42 mm)	(2,268 kg)		•	•	(8.4 cm)	(1.3 kg)





www.specialized.net

Debbi Kosakowski - National Sales Manager • dkosakowski@specialized.net • 727-515-0911

Eleanor Barszowski - NE Regional Sales Manager • <u>ebarszowski@specialized.net</u> • 484-955-3178