

# RF Exposure Evaluation Report

APPLICANT : DZS Inc.  
EQUIPMENT : XGSPON ONT  
BRAND NAME :   
MODEL NAME : 5228XG  
FCC ID : PJZ5228XG  
STANDARD : 47 CFR Part 2.1091

The product evaluation date was started from Jul. 06, 2023 and completed on Jul. 06, 2023. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

**Sporton International Inc. (Kunshan)**

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China



## **Table of Contents**

<b>1. ADMINISTRATION DATA</b> .....	<b>4</b>
1.1. Testing Laboratory .....	4
<b>2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)</b> .....	<b>5</b>
<b>3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS</b> .....	<b>6</b>
<b>4. RF EXPOSURE LIMIT INTRODUCTION</b> .....	<b>9</b>
<b>5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION</b> .....	<b>10</b>
5.1. Standalone Power Density Calculation .....	10
5.2. Collocated Power Density Calculation.....	11



**Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA332120-01	Rev. 01	Initial issue of report.	Jul. 25, 2023



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Table with 4 columns: Test Firm, Test Site Location, Test Site No., and FCC Designation No. / FCC Test Firm Registration No.

Table with 2 columns: Applicant Company Name, Address

Table with 2 columns: Manufacturer Company Name, Address



## 2. Description of Equipment Under Test (EUT)

Product Feature & Specification				
EUT Type	XGSPON ONT			
Brand Name				
Model Name	5228XG			
FCC ID	PJZ5228XG			
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz			
Mode	WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ax HE20/HE40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/VHT160 WLAN 5GHz 802.11ax HE20/HE40/HE80/HE160			
Antenna Gain	WLAN	Ant 0	Ant 1	Ant 2
	WLAN2.4GHz	3.51	3.67	3.47
	WLAN	Ant 0	Ant 1	Ant 2
	WLAN5.2GHz	4.50	4.55	4.55
	WLAN5.3GHz	4.50	4.61	4.55
Antenna Type	WLAN5.5GHz	4.52	4.61	4.57
	WLAN5.8GHz	4.52	4.54	4.46
	Ant 3			
Antenna Type	WLAN: PCB Antenna			
HW Version	V02			
SW Version	S7.0.025			
EUT Stage	Production Unit			

**Remark:**

- The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- WLAN2.4GHz/WLAN5GHz all support SISO and MIMO mode, we chose MIMO tune up power to perform MPE calculation conservatively.
- The device supports 1S3T(CDD&TXBF) mode in WLAN 2.4GHz and 1S4T(CDD&TXBF) mode in WLAN 5GHz.
- This device support beamforming for WLAN 2.4GHz 802.11n/ax HT20/HT40/HE20/HE40, WLAN 5GHz 802.11n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160.
- The gain calculation method of WLAN beamforming mode is referenced to KDB 662911.
- This is a variant report. The difference between current project and previous project is enabled WLAN5.3GHz/5.5GHz by software. According to the difference, added WLAN5.3GHz/5.5GHz evaluation based on original report, and other Bands leverage from original report which can be referred to Sporton Report Number FA332120.

**Comments and Explanations:**

- The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
- The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



**3. Maximum RF average output tune up power among production units**

<For MIMO mode>

**<2.4GHz WLAN >**

Mode		Maximum Average Power (dBm)
		Ant 0+1+2
2.4GHz	802.11b	30.0
	802.11g	30.0
	802.11n-HT20	29.0
	802.11n-HT40	25.0
	802.11ax-HE20	29.0
	802.11ax-HE40	25.0

**<5GHz WLAN >**

Mode		Maximum Average Power (dBm)
		Ant 0+1+2+3
5.2GHz	802.11a	26.0
	802.11n-HT20	27.0
	802.11n-HT40	29.5
	802.11ac-VHT20	27.0
	802.11ac-VHT40	29.5
	802.11ac-VHT80	27.0
	802.11ax-HE20	27.0
	802.11ax-HE40	29.5
5.3GHz	802.11a	19.00
	802.11n-HT20	20.00
	802.11n-HT40	23.00
	802.11ac-VHT20	20.00
	802.11ac-VHT40	23.00
	802.11ac-VHT80	20.00
	802.11ac-VHT160	19.00
	802.11ax-HE20	20.00
	802.11ax-HE40	23.00
	802.11ax-HE80	20.00
5.5GHz	802.11a	19.00
	802.11n-HT20	20.00
	802.11n-HT40	23.00
	802.11ac-VHT20	20.00
	802.11ac-VHT40	23.00
	802.11ac-VHT80	23.98
	802.11ax-HE20	20.00
	802.11ax-HE40	23.00
	802.11ax-HE80	23.98
	5.8GHz	802.11a
802.11n-HT20		22.0



	802.11n-HT40	30.0
	802.11ac-VHT20	22.0
	802.11ac-VHT40	30.0
	802.11ac-VHT80	26.0
	802.11ax-HE20	22.0
	802.11ax-HE40	30.0
	802.11ax-HE80	26.0

<For Beamforming mode>

**<2.4GHz WLAN >**

Mode		Maximum Average Power (dBm)
		Ant 0+1+2
2.4GHz	802.11n-HT20	25.0
	802.11n-HT40	20.0
	802.11ax-HE20	25.0
	802.11ax-HE40	20.0

**<5GHz WLAN >**

Mode		Maximum Average Power (dBm)
		Ant 0+1+2+3
5.2GHz	802.11n-HT20	20.5
	802.11n-HT40	23.0
	802.11ac-VHT20	20.5
	802.11ac-VHT40	23.0
	802.11ac-VHT80	22.0
	802.11ax-HE20	20.5
	802.11ax-HE40	23.0
	802.11ax-HE80	22.0
5.3GHz	802.11n-HT20	14.00
	802.11n-HT40	16.00
	802.11ac-VHT20	14.00
	802.11ac-VHT40	16.00
	802.11ac-VHT80	14.00
	802.11ac-VHT160	12.00
	802.11ax-HE20	14.00
	802.11ax-HE40	16.00
	802.11ax-HE80	14.00
	802.11ax-HE160	12.00
5.5GHz	802.11n-HT20	14.00
	802.11n-HT40	16.00
	802.11ac-VHT20	14.00
	802.11ac-VHT40	16.00
	802.11ac-VHT80	19.00
	802.11ax-HE20	14.00
	802.11ax-HE40	16.00
5.8GHz	802.11n-HT20	15.5
	802.11n-HT40	25.0



**RF Exposure Evaluation Report**

**Report No. : FA332120-01**

	802.11ac-VHT20	15.5
	802.11ac-VHT40	25.0
	802.11ac-VHT80	20.0
	802.11ax-HE20	15.5
	802.11ax-HE40	25.0
	802.11ax-HE80	20.0

Note: This device support beamforming for WLAN 2.4GHz 802.11n/ax HT20/HT40/HE20/HE40, WLAN 5GHz 802.11n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160.



**4. RF Exposure Limit Introduction**

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 22 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



### 5. Radio Frequency Radiation Exposure Evaluation

#### 5.1. Standalone Power Density Calculation

<MIMO mode>

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 22cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Power Density / Limit
2.4GHz WLAN	2412.0	3.67	30.00	33.670	2328.091	0.383	1.000	<b>0.383</b>
5.2GHz WLAN	5180.0	4.55	29.50	34.050	2540.973	0.418	1.000	0.418
5.3GHz WLAN	5260.0	4.61	23.00	27.610	576.766	0.095	1.000	0.095
5.5GHz WLAN	5500.0	4.61	23.98	28.590	722.770	0.119	1.000	0.119
5.8GHz WLAN	5745.0	4.54	30.00	34.540	2844.461	0.468	1.000	<b>0.468</b>

<Beamforming mode>

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 22cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Power Density / Limit
2.4GHz WLAN	2412.0	8.32	25.00	33.320	2147.830	0.353	1.000	<b>0.353</b>
5.2GHz WLAN	5180.0	10.52	23.00	33.520	2249.055	0.370	1.000	0.370
5.3GHz WLAN	5260.0	10.55	16.00	26.550	451.856	0.074	1.000	0.074
5.5GHz WLAN	5500.0	10.58	19.00	29.580	907.821	0.149	1.000	0.149
5.8GHz WLAN	5745.0	10.49	25.00	35.490	3539.973	0.582	1.000	<b>0.582</b>

**Note:**

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. WLAN2.4GHz and WLAN5GHz chose the higher SISO gain as MIMO gain to perform MPE calculation.
4. The gain calculation method of WLAN beamforming mode is referenced to KDB 662911.



5.2. Collocated Power Density Calculation

<For MIMO mode>

WLAN2.4GHz Power Density / Limit	WLAN5GHz Power Density / Limit	$\Sigma$ (Power Density / Limit) of WLAN2.4GHz + WLAN5GH
0.383	0.468	0.851

<For Beamforming mode>

WLAN2.4GHz Power Density / Limit	WLAN5GHz Power Density / Limit	$\Sigma$ (Power Density / Limit) of WLAN2.4GHz + WLAN5GH
0.353	0.582	0.935

Note:

1. According to the EUT characteristic, WLAN2.4GHz and WLAN 5GHz can transmit simultaneously.
2.  $\Sigma$ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WLAN2.4GHz + WLAN5GHz.

**Conclusion:**

According to 47 CFR §2.1091, the MPE was calculated at 22 cm to show compliance with the power density limit, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----