

**Huawei Technologies Co., Ltd**

Application  
For  
Certification  
**FCC ID: QISY520-U03**

**WCDMA Digital Mobile Phone**

**Model: HUAWEI Y520-U03**

**Report No.: 140710013SZN-002**

**2.4GHz Transceiver**

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-13]

Prepared and Checked by:

Approved by:

Sign on file

Jenner Liu  
Assitant Engineer

---

Andy Yan  
Senior Project Engineer  
Date: August 15, 2014

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C\_TX\_b

---

---

# INTERTEK TESTING SERVICES

---

---

## LIST OF EXHIBITS

### *INTRODUCTION*

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Confidentiality request
<i>EXHIBIT 10:</i>	Test Equipment List

---

---

# INTERTEK TESTING SERVICES

---

---

## MEASUREMENT/TECHNICAL REPORT

**Huawei Technologies Co.,Ltd**  
**Model: HUAWEI Y520-U03**

**FCC ID: QISY520-U03**

This report concerns (check one:) Original Grant  Class II Change

Equipment Type: DSS - Part 15 Spread Spectrum Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes  No

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes  No

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-13 Edition] provision.

Report prepared by:

Jenner Liu  
Intertek Testing Services Shenzhen Ltd.  
Kejiyuan Branch  
6F, Block D, Huahan Building, Langshan Road,  
Nanshan District, Shenzhen, P. R. China  
Phone: (86 755) 8614 0639  
Fax: (86 755) 8601 6751

---

---

# INTERTEK TESTING SERVICES

---

---

## Table of Contents

<b>1.0 General Description</b> .....	2
1.1 Product Description .....	2
1.2 Related Submittal(s) Grants.....	2
1.3 Test Methodology.....	2
1.4 Test Facility.....	3
<b>2.0 System Test Configuration</b> .....	5
2.1 Justification .....	5
2.2 EUT Exercising Software.....	5
2.3 Special Accessories .....	5
2.4 Equipment Modification .....	6
2.5 Measurement Uncertainty .....	6
2.6 Support Equipment List and Description .....	6
<b>3.0 Test Results</b> .....	8
3.1 Radiated Test Result.....	9
3.1.1 Field Strength Calculation.....	9
3.1.2 Radiated Emission Configuration Photograph .....	10
3.1.3 Radiated Emissions.....	10
3.1.4 Transmitter Spurious Emissions (Radiated) .....	12
3.2 Conducted Emissions at Mains Terminal .....	16
3.2.1 Conducted Emissions Configuration Photograph .....	16
3.2.2 Conducted Emissions .....	16
3.3 Peak Power.....	19
3.4 20dB Bandwidth.....	22
3.5 Channel Number (Number of Hopping Frequencies) .....	24
3.6 Channel Separation (Carrier Frequency Separation).....	27
3.7 Dwell Time (Time of Occupancy) .....	29
3.8 Band Edge.....	32
3.9 Transmitter Spurious Emissions (Conducted) .....	34
<b>4.0 Equipment Photographs</b> .....	39
<b>5.0 Product Labelling</b> .....	41
<b>6.0 Technical Specifications</b> .....	43
<b>7.0 Instruction Manual</b> .....	45
<b>8.0 Miscellaneous Information</b> .....	47
8.1 Discussion of Pulse Desensitization .....	48
8.2 Transmitter Duty Cycle Calculation.....	49
8.3 Emissions Test Procedures.....	50
<b>9.0 Confidentiality Request</b> .....	53
<b>10.0 Test Equipment List</b> .....	55

---

## INTERTEK TESTING SERVICES

---

List of attached file

Exhibit type	File Description	filename
Test Report	Test Report	report.pdf
Operational Description	Technical Description	descri.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
External Photos	External Photo	external photos.pdf
Internal Photos	Internal Photo	internal photos.pdf
ID Label/Location Info	Label Artwork and Location	label.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Users Manual	User Manual	manual.pdf/safety info.pdf
Cover Letter	Letter of Agency	agency.pdf
Cover Letter	Confidentiality Letter	request.pdf

**EXHIBIT 1**

**GENERAL DESCRIPTION**

---

## INTERTEK TESTING SERVICES

---

### 1.0 General Description

#### 1.1 Product Description

The equipment under test (EUT) is a WCDMA Digital Mobile Phone, Model: HUAWEI Y520-U03 with Bluetooth FHSS technology. The EUT was powered by AC/DC Adapter (input: 100-240Vac, 50/60Hz, Output: 5Vdc, 550mA).

Antenna Type: Integral antenna

Antenna Gain: 0.5 dBi

Modulation Type: GFSK,  $\pi/4$  -DQPSK and 8-DPSK

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is an application for certification of:

DSS- Part 15 Spread Spectrum Transmitter (Bluetooth FHSS portion)

Remaining portions are subject to the following procedures:

1. Bluetooth LE 4.0(2.4G band): 140710013SZN-003
2. WiFi Transceiver (2.4G band): 140710013SZN-004
3. WCDMA Digital Mobile Phone (2G&3G): 140710013SZN-001
4. PC Download (Class B personal computer and peripherals): 140710013SZN-005
5. Other function: 140710013SZN-006

#### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4: 2009 and DA 00-705. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

---

TRF No.: FCC 15C\_TX\_b

FCC ID: QISY520-U03

Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

---

### 1.4 Test Facility

The Semi-anechoic chamber and shield room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).



**EXHIBIT 2**  
**SYSTEM TEST CONFIGURATION**

---

## INTERTEK TESTING SERVICES

---

### 2.0 System Test Configuration

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4: 2009.

The EUT was powered by AC/DC Adapter (Input: 120Vac, 60Hz, Output: 5Vdc, 550mA), and only the worst case data was recorded in this report.

The simultaneous transmission spurious was tested, only the worst case data was recorded in this report.

All packets mode in modulation type GFSK,  $\pi/4$  -DQPSK and 8-DPSK with different accessories listed in next page were tested, and only the worst data was reported in this report.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

#### 2.3 Special Accessories

One shielded USB cable attached.

---

## INTERTEK TESTING SERVICES

---

### 2.4 Equipment Modification

Any modifications installed previous to testing by Huawei Technologies Co.,Ltd will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

### 2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

### 2.6 Support Equipment List and Description

Description	Manufacturer	Model No.
Earphone (Black)	Goertek	HA1-3
	Quancheng	1293#+3283# 3.5MM-150
	Lianchuang	MEMD1532B528000
Earphone (White)	Merry	EMC323-011-01
	Goertek	HG-04A
USB Cable	/	Data Cable USB A Male to Micro USB, shielded, 100cm
Battery	BYD	HB5V1 (1730mAh)
	LISHEN	
	SUNWODA	HB5V1HV (1950mAh)
	SCUD	
AC/DC Adapter (Huawei)	BYD / HuntKey	HW-050055U1W Input: 100-240Vac, 50/60Hz, 0.2A; Output: 5Vdc, 550mA
	BYD / HuntKey	HW-050055E1W Input: 100-240Vac, 50/60Hz, 0.2A; Output: 5Vdc, 550mA
	BYD / HuntKey	HW-050055B1W Input: 100-240Vac, 50/60Hz, 0.2A; Output: 5Vdc, 550mA
	BYD /UE	HW-050055A1W Input: 100-240Vac, 50/60Hz, 0.2A; Output: 5Vdc, 550mA
	BYD /UE	HW-050055R1W Input: 100-240Vac, 50/60Hz, 0.2A; Output: 5Vdc, 550mA

Note: The Model: HUAWEI Y520-U03 have five different AC/DC Adapter power suppliers, which have already arranged the test accordingly, and the worst case data was recorded in this report.

**EXHIBIT 3**  
**TEST RESULTS**

## INTERTEK TESTING SERVICES

---

### 3.0 **Test Results**

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

---

## INTERTEK TESTING SERVICES

---

### 3.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

Where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB
- AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

RA = 62.0 dB $\mu$ V  
AF = 7.4 dB  
CF = 1.6 dB  
AG = 29.0 dB  
PD = 0 dB

AV = -10 dB

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

## INTERTEK TESTING SERVICES

---

### 3.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

### 3.1.3 Radiated Emissions- FCC section 15.209

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission  
at  
30.485 MHz

Judgement: Passed by 6.4 dB

#### ***TEST PERSONNEL:***

*Sign on file*

Jenner Liu Assitant Engineer  
*Typed/Printed Name*

July 25, 2014  
*Date*

## INTERTEK TESTING SERVICES

---

Applicant: Huawei Technologies Co.,Ltd  
Date of Test: July 25, 2014  
Model: HUAWEI Y520-U03  
Sample: 1/1  
Worst-case operating Mode: BT Link  
Modulation type: GFSK  
AC/DC Adapter: UE (HW-050055R1W)

Table 1

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	30.485	33.2	20.0	10.6	23.8	40.0	-16.2
Horizontal	32.910	30.2	20.0	12.0	22.2	40.0	-17.8
Horizontal	728.885	34.6	20.0	14.7	29.3	46.0	-16.7
Vertical	30.485	34.7	20.0	18.9	33.6	40.0	-6.4
Vertical	33.395	40.5	20.0	9.2	29.7	40.0	-10.3
Vertical	46.005	42.0	20.0	7.8	29.8	40.0	-10.2

- NOTES: 1. Quasi-Peak detector is used except for others stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions are below the QP limit.

---

TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002



## INTERTEK TESTING SERVICES

---

### 3.1.4 Transmitter Spurious Emissions (Radiated) - FCC section 15.209

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission  
at  
9764.000 MHz

Judgement: Passed by 13.6 dB

#### **TEST PERSONNEL:**

*Sign on file*

Jenner Liu Assitant Engineer  
*Typed/Printed Name*

July 25, 2014  
*Date*

## INTERTEK TESTING SERVICES

Applicant: Huawei Technologies Co.,Ltd  
 Date of Test: July 25, 2014  
 Model: HUAWEI Y520-U03  
 Sample: 1/1  
 Worst-case operating Mode: Transmit-CH00 (2402MHz)  
 Modulation type: GFSK

Table 2

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	**2402.000	112.2	36.7	28.1	103.6	--	--
Vertical	*4804.000	53.5	36.1	33.0	50.4	74.0	-23.6
Vertical	*7206.000	56.9	36.8	36.7	56.8	74.0	-17.2
Vertical	*9608.000	61.1	36.8	35.9	60.2	74.0	-13.8

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4804.000	53.5	36.1	33.0	22.5	27.9	54.0	-26.1
Vertical	*7206.000	56.9	36.8	36.7	22.5	34.3	54.0	-19.7
Vertical	*9608.000	61.1	36.8	35.9	22.5	37.7	54.0	-16.3

- NOTES: 1. Peak detector is used except for others stated.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.
- \*\* Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

TRF No.: FCC 15C\_TX\_b  
 FCC ID: QISY520-U03  
 Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

Applicant: Huawei Technologies Co.,Ltd  
 Date of Test: July 25, 2014  
 Model: HUAWEI Y520-U03  
 Sample: 1/1  
 Worst-case operating Mode: Transmit-CH39 (2441MHz)  
 Modulation type: GFSK

Table 3

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	**2441.000	113.0	36.7	28.1	104.4	--	--
Vertical	*4882.000	51.8	36.1	35.0	50.7	74.0	-23.3
Vertical	*7323.000	56.0	36.2	37.3	57.1	74.0	-16.9
Vertical	*9764.000	60.7	36.2	35.9	60.4	74.0	-13.6

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4882.000	51.8	36.1	35.0	22.5	28.2	54.0	-25.8
Vertical	*7323.000	56.0	36.2	37.3	22.5	34.6	54.0	-19.4
Vertical	*9764.000	60.7	36.2	35.9	22.5	37.9	54.0	-16.1

- NOTES:
1. Peak detector is used except for others stated.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.
- \*\* Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

TRF No.: FCC 15C\_TX\_b  
 FCC ID: QISY520-U03  
 Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

Applicant: Huawei Technologies Co.,Ltd  
 Date of Test: July 25, 2014  
 Model: HUAWEI Y520-U03  
 Sample: 1/1  
 Worst-case operating Mode: Transmit-CH78 (2480MHz)  
 Modulation type: GFSK

Table 4

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	**2480.000	109.9	36.7	28.0	101.2	--	--
Vertical	*4960.000	51.4	36.1	35.0	50.3	74.0	-23.7
Vertical	*7440.000	54.6	36.2	37.3	55.7	74.0	-18.3
Vertical	*9920.000	57.5	36.2	39.0	60.3	74.0	-13.7

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4960.000	51.4	36.1	35.0	22.5	27.8	54.0	-26.2
Vertical	*7440.000	54.6	36.2	37.3	22.5	33.2	54.0	-20.8
Vertical	*9920.000	57.5	36.2	39.0	22.5	37.8	54.0	-16.2

NOTES: 1. Peak detector is used except for others stated.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

\*\* Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

TRF No.: FCC 15C\_TX\_b  
 FCC ID: QISY520-U03  
 Report No.: 140710013SZN-002

---

## INTERTEK TESTING SERVICES

---

### 3.2 Conducted Emission at Mains Terminal

#### 3.2.1 Conducted Emissions Configuration Photograph

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

#### 3.2.2 Conducted Emissions

Worst Case Conducted Configuration  
at  
2.294 MHz

Judgement: Passed by 3.1 dB margin

#### ***TEST PERSONNEL:***

*Sign on file*


Jenner Liu Assitant Engineer  
*Typed/Printed Name*

July 25, 2014  
*Date*

# INTERTEK TESTING SERVICES

Applicant: Huawei Technologies Co.,Ltd  
 Date of Test: July 25, 2014  
 Model: HUAWEI Y520-U03  
 Sample: 1/1  
 Worst-case operating Mode: BT Link  
 Modulation type: GFSK  
 Adapter: UE (HW-050055R1W)

## Conducted Emission Test - FCC



### Result Table QP

Frequency (MHz)	Average (dB µ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.206	52.1	L1	9.8	11.3	63.4
0.414	53.3	L1	9.8	4.3	57.6
0.522	52.8	L1	9.8	3.2	56.0
0.714	51.9	L1	10.0	4.1	56.0
2.206	51.7	L1	10.0	4.3	56.0
2.294	52.9	L1	10.0	3.1	56.0

### Result Table AV


Frequency (MHz)	QuasiPeak (dB µ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.206	42.7	L1	9.8	10.7	53.4
0.414	40.1	L1	9.8	7.5	47.6
0.522	37.5	L1	9.8	8.5	46.0
0.714	37.6	L1	10.0	8.4	46.0
2.206	42.2	L1	10.0	3.8	46.0
2.294	41.4	L1	10.0	4.6	46.0

TRF No.: FCC 15C\_TX\_b  
 FCC ID: QISY520-U03  
 Report No.: 140710013SZN-002

# INTERTEK TESTING SERVICES

Applicant: Huawei Technologies Co.,Ltd  
 Date of Test: July 25, 2014  
 Model: HUAWEI Y520-U03  
 Sample: 1/1  
 Worst-case operating Mode: BT Link  
 Modulation type: GFSK  
 Adapter: UE (HW-050055R1W)

## Conducted Emission Test - FCC



### Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.206	51.3	N	10.1	12.1	63.4
0.418	50.2	N	10.1	7.3	57.5
0.522	50.5	N	10.2	5.5	56.0
2.066	51.0	N	10.3	5.0	56.0
2.198	51.6	N	10.3	4.4	56.0
2.322	51.1	N	10.3	4.9	56.0

### Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.206	39.8	N	10.1	13.6	53.4
0.418	37.9	N	10.1	9.6	47.5
0.522	36.6	N	10.2	9.4	46.0
2.066	38.5	N	10.3	7.5	46.0
2.198	39.6	N	10.3	6.4	46.0
2.322	38.4	N	10.3	7.6	46.0

TRF No.: FCC 15C\_TX\_b  
 FCC ID: QISY520-U03  
 Report No.: 140710013SZN-002

---

---

## INTERTEK TESTING SERVICES

---

---

### 3.3 Peak Power

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(1)

The antenna port of the EUT was connected to the input of a spectrum analyzer. The analyzer was set for RBW > 20dB bandwidth and power was read directly in dBm.

For antenna with gains of 6dBi or less, and frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, the systems operate with an output power no greater than 125 mW.


Antenna Gain = 0.5dBi			
Modulation Type	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
GFSK	2402	8.08	6.43
	2441	8.49	7.06
	2480	8.56	7.18

Cable loss: 0.8 dB    External Attenuation: 0 dB




# INTERTEK TESTING SERVICES

Modulation Type: GFSK  
CH00




CH39



TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

# INTERTEK TESTING SERVICES

CH78



TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

### 3.4 20dB Bandwidth


Maximum 20dB RF Bandwidth, FCC Rule 15.247(a) (1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

Frequency (MHz)	20 dB Bandwidth (MHz)
2402	1.33
2441	1.33
2480	1.33

Modulation Type: 8DPSK

CH00




TRF No.: FCC 15C\_TX\_b

FCC ID: QISY520-U03


Report No.: 140710013SZN-002

# INTERTEK TESTING SERVICES

## CH39



## CH78



TRF No.: FCC 15C\_TX\_b  
 FCC ID: QISY520-U03  
 Report No.: 140710013SZN-002

# INTERTEK TESTING SERVICES

## 3.5 Channel Number (Number of Hopping Frequencies)

Minimum Number of Hopping Frequencies, FCC Rule 15.247(a) (1) (iii):


The RF passband of the EUT was divided into 3 approximately equal bands. With the analyzer set to MAX HOLD readings were taken for 2-3 minutes. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

Number of hopping channels =	79
------------------------------	----

Note: In AFH mode, this device operates using 20 channels and it's satisfied the requirement of limit of minimum of 15 hopping channels.


Modulation Type: GFSK

CH00-CH78




# INTERTEK TESTING SERVICES

## CH00-CH25




## CH26-CH53



TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

# INTERTEK TESTING SERVICES

CH54-CH78



TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

# INTERTEK TESTING SERVICES

## 3.6 Channel Separation (Carrier Frequency Separation)

Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1):


Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit:

Not less than 2/3 of 20dB bandwidth of hopping channel:  $1.33 \times 2/3 = 0.887$  MHz

Channel Separation	1.000 MHz
--------------------	-----------

Modulation Type: GFSK


Low Channel






# INTERTEK TESTING SERVICES

## Middle Channel



## High Channel



TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

---

---

## INTERTEK TESTING SERVICES

---

---

### 3.7 Dwell Time (Time of Occupancy)

Average Channel Occupancy Time, FCC Ref: 15.247(a)(1)(iii):

The spectrum analyzer center frequency was set to one of the known hopping channels. The SWEEP was set to 10ms, the SPAN was set to ZERO SPAN, and the TRIGGER was set to VIDEO. The time duration of the transmissions so captured was measured with the MARKER DELTA function.

The maximum number of hopping channels in 31.6s for DH1  
 $=1600 / 2 / 79 * 31.6=320$

The maximum number of hopping channels in 31.6s for DH3  
 $=1600 / 4 / 79 * 31.6=160$

The maximum number of hopping channels in 31.6s for DH5  
 $=1600 / 6 / 79 * 31.6=107$

Modulation Type	Packet	Max Dwell Time	Limit (s)	Result
GFSK	DH1	0.372 ms * 320= 119.04 ms	0.4	Pass
	DH3	1.627 ms * 160= 260.32 ms	0.4	Pass
	DH5	2.881 ms * 107= 308.27 ms	0.4	Pass

AFH mode:

The maximum number of hopping channels in 8s for DH1  
 $=800 / 2 / 20 * 8=160$


The maximum number of hopping channels in 8s for DH3  
 $=800 / 4 / 20 * 8=80$

The maximum number of hopping channels in 8s for DH5  
 $=800 / 6 / 20 * 8=53.33$


Modulation Type	Packet	Max Dwell Time	Limit (s)	Result
GFSK	DH1	0.372 ms * 160= 59.52 ms	0.4	Pass
	DH3	1.627 ms * 80= 130.16 ms	0.4	Pass
	DH5	2.881 ms * 53.33= 153.64 ms	0.4	Pass

# INTERTEK TESTING SERVICES

Modulation Type: GFSK  
 Packet: DH1




Packet: DH3



TRF No.: FCC 15C\_TX\_b  
 FCC ID: QISY520-U03  
 Report No.: 140710013SZN-002

# INTERTEK TESTING SERVICES

Packet: DH5



TRF No.: FCC 15C\_TX\_b  
 FCC ID: QISY520-U03  
 Report No.: 140710013SZN-002

### 3.8 Band Edge

Out of Band Conducted Emissions, FCC Rule 15.247(d):

In any 100 KHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

Furthermore, delta measurement technique for measuring bandage emissions was shown as below:

**(i) Lower channel 2402MHz:**

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot  
= 103.6dB $\mu$ v/m-55.7dB  
= 47.9dB $\mu$ v/m



**(ii) Upper channel 2480MHz:**

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot  
= 101.2dB $\mu$ v/m-59.2dB  
= 42.0 dB $\mu$ v/m

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74 dB $\mu$ v/m (Peak Limit) and 54dB $\mu$ v/m (Average Limit).

# INTERTEK TESTING SERVICES

Modulation Type: GFSK



TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

---

### 3.9 Transmitter Spurious Emissions (Conducted)



Out of Band Conducted Spurious Emissions, FCC Rule 15.247(d):

All spurious emission and up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

# INTERTEK TESTING SERVICES

Modulation Type: GFSK

CH00





TRF No.: FCC 15C\_TX\_b  
 FCC ID: QISY520-U03  
 Report No.: 140710013SZN-002



# INTERTEK TESTING SERVICES

CH39



TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002



**EXHIBIT 4**  
**EQUIPMENT PHOTOGRAPHS**

## INTERTEK TESTING SERVICES

---

### 4.0 **Equipment Photographs**

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

# **INTERTEK TESTING SERVICES**

---

## **EXHIBIT 5**

### **PRODUCT LABELLING**

---

TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

---

### 5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

# **INTERTEK TESTING SERVICES**

---

## **EXHIBIT 6**

### **TECHNICAL SPECIFICATIONS**

---

TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

---

### 6.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.



# **INTERTEK TESTING SERVICES**

---

## **EXHIBIT 7**

### **INSTRUCTION MANUAL**

---

TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

---

### 7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

# **INTERTEK TESTING SERVICES**

---

## **EXHIBIT 8**

### **MISCELLANEOUS INFORMATION**

---

TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

---

### 8.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandedge, the test procedure and calculation of factor such as pulse desensitization.

## INTERTEK TESTING SERVICES

---

### 8.1 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period ( $T_{\text{eff}}$ ) is approximately 625 $\mu\text{s}$  for Bluetooth. With a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

## INTERTEK TESTING SERVICES

---

### 8.2 Transmitter Duty Cycle Calculation, FCC Rule 15.35(b, c)

Based on the Bluetooth Specification, transmitter ON time is independent of packet type (DH1, DH3 and DH5) and packet length (single-slot and multi-slot). The maximum transmitter ON time for the Bluetooth is 625 $\mu$ s.

Each TX and RX time slot is 625 $\mu$ s in length. A TDD scheme is used where master and slave alternately transmit. For one period for a pseudo-random hopping through all 79 RF channels, for DH5:

Normal Mode:

Channel hop rate=1600 hops/second

Time of 1 hopset (5 TX slots + 1 RX slot) = 0.625 ms x 6 = 3.75 ms

Time of 1 cycle =3.75 ms x 79 = 296.25 ms

Average factor = 20 log (3.125 / 100) = -30.1 dB

AFH Mode:

Channel hop rate = 800 hops/second (AFH Mode)

Adjusted channel hop rate for DH5 mode = 133.33 hops/second

Time per channel hop = 1 / 133.33 hops/second = 7.5 ms

Time to cycle through all channels = 7.5 x 20 channels = 150 ms

Number of times transmitter hits on one channel = 100 ms / 150 ms = 1 time(s)

Worst case dwell time = 7.5 ms

Duty cycle connection factor = 20 log<sub>10</sub> (7.5ms / 100ms) = -22.5 dB

## INTERTEK TESTING SERVICES

---

### 8.3 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4: 2009.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

## INTERTEK TESTING SERVICES

---

### 8.3 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4: 2009.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.



**INTERTEK TESTING SERVICES**

---

**EXHIBIT 9**  
**CONFIDENTIALITY REQUEST**

---

TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

---

### 9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

---

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 10**  
**TEST EQUIPMENT LIST**

---

TRF No.: FCC 15C\_TX\_b  
FCC ID: QISY520-U03  
Report No.: 140710013SZN-002

## INTERTEK TESTING SERVICES

### 10.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	21-May-2014	21-May-2015
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	21-May-2014	21-May-2015
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	28-Jun-2014	28-Jun-2015
SZ185-01	EMI Receiver	R&S	ESCI	100547	10-Mar-2014	10-Mar-2015
SZ061-09	Horn Antenna	ETS	3115	00092346	16-Nov-2013	16-Nov-2014
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	27-Aug-2013	27-Aug-2014
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	29-Apr-2014	29-Apr-2015
EM031-03	EXA Spectrum Analyzer	R&S	FSV40	101506	09-Jun-2014	09-Jun-2015
SZ181-04	Preamplifier	Agilent	8449B	3008A0247 4	10-Mar-2014	10-Mar-2015
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	19-Apr-2014	19-Apr-2015
SZ062-02	RF Cable	RADIALL	RG 213U	--	19-Apr-2014	19-Oct-2014
SZ062-05	RF Cable	RADIALL	0.04-26.5GHz	--	19-Apr-2014	19-Oct-2014
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	19-Apr-2014	19-Oct-2014
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	21-May-2014	21-May-2015
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	9-Nov-2013	9-Nov-2014
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	9-Nov-2013	9-Nov-2014
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	9-Nov-2013	9-Nov-2014
SZ188-03	Shielding Room	ETS	RFD-100	4100	23-Aug-2013	23-Aug-2014

TRF No.: FCC 15C\_TX\_b  
 FCC ID: QISY520-U03  
 Report No.: 140710013SZN-002