

UC-ENGINE-Z

UC Engine for Zoom Rooms™ Collaborative Software



- Sold exclusively as part of a complete Crestron Flex UC system
- Enables Zoom Rooms™ software video conferencing and content sharing
- Employs a powerful Intel® NUC Mini PC
- Preloaded Crestron® software
- Easy to provision and manage through the Crestron XiO Cloud™ service
- Works natively with any Zoom Rooms software account
- Connects and communicates securely over any enterprise or SMB network
- Supports single or dual display configurations
- External 100-240V power adapter included

All the capabilities of a complete Zoom Rooms™ software based video conferencing and content sharing solution are empowered by the Crestron® UC Engine (UC-ENGINE-Z). For ultimate performance, Crestron employs a powerful Intel® NUC Mini PC running Zoom Rooms software with built-in Crestron XiO Cloud™ support.² The UC Engine forms the core of a complete Zoom Rooms based Crestron Flex system, providing extreme processing performance, Gigabit Ethernet, and complete connectivity for one or two HD displays, a USB camera, and one USB audio conferencing device.¹

A maximum of one [touch screen](#) or one [Crestron Mercury® UC conference console](#) may be added for room control (support for two touch screens to be implemented in the future).

Presenting and sharing AV content from a laptop PC is facilitated through the addition of a Crestron HDMI® to USB 3.0 Converter (HD-CONV-USB-200), which enables full-motion HD video and audio content ingest via a single HDMI input. As part of a complete Crestron Flex system, the UC-ENGINE-Z and HD-CONV-USB-200 are mounted together on a bracket (UC-BRKT-100-Z-ASSY), which allows for easy installation attached to a wall or to the back of the display device.¹

This product is sold exclusively as part of a complete [Crestron Flex](#) system kit:

- Refer to the Crestron Flex M150-Z system (UC-M150-Z) for a complete tabletop video conferencing solution featuring the UC Engine and Crestron Mercury® audio conference console.
- Refer to the Crestron Flex B160-Z system (UC-B160-Z) for a complete wall mount video conferencing solution

featuring the UC Engine, UC video conference smart soundbar, and tabletop touch screen.

Specifications

Intel NUC Mini PC

Model: Intel NUC Kit NUC6i7KYK

Processor: 6th generation Intel Core® i7-6770HQ processor, 2.6 to 3.5 GHz Turbo, Quad Core, 6 MB Cache

RAM: 8 GB DDR4 2400MHz

Storage: 256 GB SSD

Graphics: Intel Iris® Pro Graphics 580

Networking: Intel I219-LM 10/100/1000 Mbps Ethernet

Operating System: Windows® 10 IOT Enterprise²

UC Client: Zoom Rooms software

Management Client: Crestron XiO Cloud™ service

Communications

Ethernet: 10/100/1000 Mbps

USB: Four USB 3.0 host ports supporting USB HID, UAC, and UVC for audio conferencing device, camera, and content ingest (plus temporary keyboard/mouse for initial setup)¹

Video

Camera Input: USB UVC from a Zoom Rooms compliant USB camera¹

Content Input: USB UVC content ingest from a Zoom Rooms compliant HDMI to USB convertor¹

Display Output: DisplayPort™ 1.2 via USB Type-C® port, converted to HDMI via converter cable¹

Camera Input Resolution: HD 1080p @ 30 fps

Content Input Resolution: HD 1080p @ 60 fps

Display Output Resolution(s): HD 1080p @ 60 fps

Audio

Audio Conferencing Input/Output: USB UAC bidirectional stereo audio signals for integration with a Zoom Rooms software compliant AEC-enabled USB audio conferencing speakerphone device¹

Content Input: USB UAC stereo audio ingest from a Zoom Rooms compliant HDMI to USB convertor¹

UC-ENGINE-Z

UC Engine for Zoom Rooms™ Collaborative Software

Buttons & Indicators

Power: (1) Pushbutton with LED backlight for power on/off and reset

LAN: (2) LEDs on LAN port for Ethernet link status and activity

Connectors

SD Card Slot: (1) SDXC memory card slot with UHS-I support (not used)

SSUSB (Front): (2) USB 3.0 Type-A connectors, female; USB 3.0 host ports (one charging, one non-charging); Connect to a keyboard and mouse for setup, and to an audio conferencing device for runtime operation¹

Headset (Front): (1) 3.5 mm headphone/microphone jack (not used)

19 VDC: (1) DC power connector;
19 VDC power input;
Power adapter included

Audio/Optical: (1) 3.5 mm rear speaker/TOSLINK combo output jack (not used)

LAN: (1) 8-pin RJ45 connector, female;
10Base-T/100Base-TX/1000Base-T Ethernet port

SSUSB (Rear): (2) USB 3.0 Type-A connectors, female; USB 3.0 host ports;
Connect to camera and HDMI to USB convertor¹

USB-C: (1) USB Type-C connector, female;
Digital video output;
Connects to an optional secondary display device via a USB-C® to HDMI converter cable¹

HDMI: (1) HDMI Type A connector, female;
Digital video output (disabled);
Requires connection to an EDID emulator (UC-CONN-HD)¹

Power

Power Adapter (included): Input: 100-240 VAC, 50/60 Hz;
Output: 120 W @ 19 VDC

Construction

Enclosure: Metal and plastic, variable speed fan cooled

Mounting: VESA® mount, Kensington® lock with base security

Environmental

Operational Temperature: 32° to 104° F (0° to 40° C)

Storage Temperature: -4° to 140° F (-20° to 60° C)

Dimensions

Height: 1.10 in. (28 mm)

Width: 8.30 in. (211 mm)

Depth: 4.56 in. (116 mm)

Compliance

Product Safety: IEC 60950-1, UL 60950-1, EN 60950-1, CAN/CSA-C22.2 No. 60950-1

EMI/RF (Class B): CISPR 22; FCC CFR Title 47, Chapter I, Part 15, Subparts A, B; ICES-003, EN 55022, EN 55024, ETSI EN 300 328, ETSI EN 301 489- 1, ETSI EN 301 489-17, ETSI EN 301 893, EN 62311, AS/NZS 2772.2, AS/ NZS 4268; VCCI V-3, V-4; KN-22, KN-24, CNS 13438

Environmental: RoHS Directive 2011/65/EU, WEEE Directive 2012/19/EU, China RiHS MII Order #39

Notes:

1. Audio conferencing devices (Crestron Mercury, Crestron Avia™ DSP, or UC sound bar) are either sold separately or as part of a complete Crestron Flex system kit. The UC engine, bracket, converters, EDID emulator, camera, keyboard, and cables, are all sold exclusively as part of a complete Crestron Flex system kit. The display devices are not included.
2. Custom OS images are not supported.

This product is sold only as part of a complete system kit, which may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at <https://www.crestron.com/How-To-Buy/Find-a-Representative> or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty for 3 years. Refer to <https://www.crestron.com/warranty> for full details.

The specific patents that cover Crestron products are listed online at www.crestron.com/legal/patents.

Certain Crestron products contain open source software. For specific information, visit www.crestron.com/opensource.

Crestron, the Crestron logo, Crestron Avia, Crestron Mercury, and Crestron XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Intel, Intel Core, and Intel Iris are either trademarks or registered trademarks of Intel Corporation in the United States and/or other countries. Kensington is either a trademark or registered trademark of Acco Brands Corporation in the United States and/or other countries. Windows is either a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. USB Type-C and USB-C are either trademarks or registered trademarks of USB Implementers Forum, Inc. in the United States and/or other countries. VESA and DisplayPort are either trademarks or registered trademarks of Video Electronics Standards Association in the United States and/or other countries. Zoom Rooms is either a trademark or registered trademark of Zoom Video Communications, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2019 Crestron Electronics, Inc.