

DHI-SSD-C800A

2.5 inch SATA Solid State Drive



- · Adopts high-quality wafer level chip
- Supports SATA 3.0 protocol with transmission speed up to 550 MB/s
- View information through S.M.A.R.T
- Provides better read and write performance with TRIM and NCQ
- · Low power consumption management

System Overview

As a new generation of 2.5 inch SSD product launched by Dahua, C800A series adopts high-quality 3D wafer level chip and high-performance controller. It is consumer-grade solid state drive designed for personal desktops and notebooks. The product can process data efficiently and ensure quick start-ups. In multi-tasking, it can ensure high speed and stability.

Scene

C800A series is standard 2.5 inch consumer-grade solid state drive which is applicable to personal desktops, notebooks, all-in-one computers, and more.

| Technical Specification | | | | |
|-------------------------|--|-----------------------------------|-----------------------------------|-----------------------------------|
| Product Model | DHI-SSD- C800AS120G | DHI-SSD- C800AS240G | DHI-SSD- C800AS480G | DHI-SSD- C800AS500G |
| Capacity ¹ | 120 GB | 240 GB | 480 GB | 500 GB |
| Form Factor | 2.5 inch | | | |
| Port | SATA III 6Gb/s | | | |
| Net Weight | Max 40 g (0.09 lb) | | | |
| Product Dimensions | 100.20 mm × 69.90 mm × 7.00 mm (3.94" × 2.75" × 0.28") | | | |
| Packaging Dimensions | 140.50 mm × 105.50 mm × 15.50 mm (5.53" × 4.15" × 0.61") | | | |
| Memory Component | 3D NAND | | | |
| Power Consumption | 1195 mW (max) 415 mW (idle) | 1200 mW (max) 370 mW (idle) | 1600 mW (max) 510 mW (idle) | 1910 mW (max) 790 mW (idle) |
| S.M.A.R.T | Support | | | |
| TRIM | Support | | | |
| Garbage Collection | Support | | | |

| Sequential Read ² | Up to 550 MB/s | Up to 550 MB/s | Up to 550 MB/s | Up to 530 MB/s |
|----------------------------------|---|----------------|----------------|----------------|
| Sequential Write ² | Up to 420 MB/s | Up to 460 MB/s | Up to 470 MB/s | Up to 500 MB/s |
| 4K Random Read ² | Up to 31000 | Up to 50000 | Up to 60000 | Up to 42,000 |
| 4K Random Write ² | Up to 57000 | Up to 57000 | Up to 77000 | Up to 80,000 |
| MTBF | 1,500,000 hours | | | |
| Operating Temperature | 0°C to +70°C (+32°F to +158°F) | | | |
| Storage Temperature | -40°C to +85°C (-40°F to +185°F) | | | |
| Operating Humidity | 5%–95% (non-condensing) | | | |
| Vibration Resistance | 10-200Hz, 0.5G | | | |
| TBW | 50 TB | 100 TB | 150 TB | 200 TB |
| Warranty ³ | 3-year limited warranty | | | |
| Reference Information | 1. Capacity calculation: 1GB = 1 billion bytes (IDEMA). Actual available capacity might be reduced (due to formatting, partition, operating system applications, or other necessary usage). 2. System configuration of performance test: Intel Z390 Chipset, Intel Core 19-9900KF@3.6GHz, 16GB DDR4; operating system-Windows 10 x64; testing tool-CrystalDiskMark 6.0.0. 3. Warranty period or maximum write amount (TBW), whichever comes first. 4. High performance SLC cache has been enabled. (*Above data based on internal testing of Dahua Memory Laboratory) | | | |

| Technical Specification | | | | | |
|----------------------------------|---|--------------------------------|--------------------------------|--|--|
| Product Model | DHI-SSD- C800AS960G | DHI-SSD- C800AS1000G | DHI-SSD- C800AS2000G | | |
| Capacity ¹ | 960 GB | 1000 GB | 2000 GB | | |
| Form Factor | 2.5 inch | | | | |
| Port | SATA III 6Gb/s | | | | |
| Net Weight | Max 40 g (0.09 lb) | | | | |
| Product Dimensions | 100.20 mm × 69.90 mm × 7.00 mm (3.94" × 2.75" × 0.28") | | | | |
| Packaging Dimensions | 140.50 mm × 105.50 mm × 15.50 mm (5.53" × 4.15" × 0.61") | | | | |
| Memory Component | 3D NAND | | | | |
| Power Consumption | 2200 mW (max) 550 mW (idle) | 1960 mW (max) 840 mW (idle) | 2500 mW (max) 960 mW (idle) | | |
| S.M.A.R.T | Support | | | | |
| TRIM | Support | | | | |
| Garbage Collection | Support | | | | |
| Sequential Read ² | Up to 550 MB/s | Up to 550 MB/s | Up to 550 MB/s | | |
| Sequential Write ² | Up to 490 MB/s | Up to 500 MB/s | Up to 460 MB/s | | |
| 4K Random Read ² | Up to 63000 | Up to 67,000 | Up to 44000 | | |
| 4K Random Write ² | Up to 77000 | Up to 81,000 | Up to 78600 | | |
| MTBF | 1,500,000 hours | | | | |
| Operating Temperature | 0°C to +70°C (+32°F to +158°F) | | | | |
| Storage Temperature | -40°C to +85°C (-40°F to +185°F) | | | | |
| Operating Humidity | 5%–95% (non-condensing) | | | | |
| Vibration Resistance | 10-200 Hz, 0.5G | | | | |
| TBW | 310 TB | 400 TB | 800 TB | | |
| Warranty ³ | 3-year limited warranty | | | | |
| Reference Information | 1. Capacity calculation: 1GB = 1 billion bytes (IDEMA). Actual available capacity might be reduced (due to formatting, partition, operating system applications, or other necessary usage). 2. System configuration of performance test: Intel Z390 Chipset, Intel Core 19-9900KF@3.6GHz, 16GB DDR4; operating system-Windows 10 x64; testing tool-CrystalDiskMark 6.0.0. 3. Warranty period or maximum write amount (TBW), whichever comes first. 4. High performance SLC cache has been enabled. (*Above data based on internal testing of Dahua Memory Laboratory) | | | | |

| Ordering Information | | | | |
|----------------------|---------------------|---|--|--|
| Туре | Model | Description | | |
| | DHI-SSD-C800AS120G | Dahua 2.5 inch SATA SSD DHI-SSD- C800AS120G | | |
| | DHI-SSD-C800AS240G | Dahua 2.5 inch SATA SSD DHI-SSD- C800AS240G | | |
| | DHI-SSD-C800AS480G | Dahua 2.5 inch SATA SSD DHI-SSD- C800AS480G | | |
| C800 Series | DHI-SSD-C800AS500G | Dahua 2.5 inch SATA SSD DHI-SSD- C800AS500G | | |
| | DHI-SSD-C800AS960G | Dahua 2.5 inch SATA SSD DHI-SSD- C800AS960G | | |
| | DHI-SSD-C800AS1000G | Dahua 2.5 inch SATA SSD DHI-SSD- C800AS1000G | | |
| | DHI-SSD-C800AS2000G | Dahua 2.5 inch SATA SSD DHI-SSD- C800AS2000G | | |

Installation

Install by Cable Connection







Dimensions (mm[inch])





