

TEST REPORT

Reference No...... : WTF24D04087570W003
FCC ID : 2BF9G-BMS04
Applicant..... : Energy Battery Asia Company Limited
Address..... : Suite E,22/F, Ford Glory Plaza, 37 Wing Hong Street Lai Chi Kok,
Kowloon, Hong Kong
Manufacturer : JIAHUA DIAN ZHI YOU XIAN GONG SHI
Address..... : Chang Pu Industrial Zone, Jiasheng Town, Shanwei, China
Product..... : Battery Monitor System
Model(s) : BMS04
Standards..... : FCC 47CFR Part 2 Subpart J Section 2.1091
Date of Receipt sample : 2024-04-23
Date of Test : 2024-07-10 to 2024-07-25
Date of Issue..... : 2024-08-23
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:
Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China
Tel: +86-769-2267 6998
Fax: +86-769-2267 6828

Compiled by:

James Cheng

James Cheng / Project Engineer

Approved by:


The logo is circular with 'WALTEK TESTING GROUP CO., LTD.' around the perimeter and 'WALTEK' in the center. A signature 'Deval Qin' is written across the logo.

Deval Qin / Designated Reviewer

2. Contents

	Page
1 COVER PAGE.....	1
2. CONTENTS.....	2
3. REVISION HISTORY.....	3
4. GENERAL INFORMATION.....	4
4.1. GENERAL DESCRIPTION OF E.U.T.....	4
4.2. DETAILS OF E.U.T.	4
4.3. TEST FACILITY	5
4.4. SUBCONTRACTED	5
4.5. ABNORMALITIES FROM STANDARD CONDITIONS.....	5
5. TEST SUMMARY.....	6
6. RF EXPOSURE.....	7
6.1. REQUIREMENTS	7
6.2. THE PROCEDURES / LIMIT	7
6.3. MPE CALCULATION METHOD.....	8
6.4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION.....	8

3. Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTF24D04087570W003	2024-04-23	2024-07-10 to 2024-07-25	2024-08-23	Original	-	Valid

4. General Information

4.1. General Description of E.U.T.

Product:	Battery Monitor System
Model(s):	BMS04
Model Description:	N/A
Test Sample No.:	1-1/1
Wi-Fi Specification:	2.4G-802.11b/g/n HT20
LTE Band(s):	FDD Band 2/4/5/12/13
Hardware Version:	BMS04-MP
Software Version:	Ver16.0

4.2. Details of E.U.T.

Operation Frequency:	2.4G Wi-Fi: 802.11b/g/n HT20: 2412~2462MHz FDD-LTE Band 2: Tx: 1850-1910MHz, FDD-LTE Band 4: Tx: 1710-1755MHz, FDD-LTE Band 5: Tx: 824-849MHz, FDD-LTE Band 12: Tx: 699-716MHz, FDD-LTE Band 13: Tx: 777-787MHz
Max. RF output power:	2.4G Wi-Fi: 17.59dBm FDD-LTE Band 2: 18.83dBm, FDD-LTE Band 4: 18.75dBm, FDD-LTE Band 5: 17.76dBm, FDD-LTE Band 12: 18.90dBm, FDD-LTE Band 13: 18.29dBm
Modulation Technology:	2.4G Wi-Fi: DSSS, CCK, OFDM LTE:QPSK,16QAM
Antenna installation:	2.4G Wi-Fi: PCB Antenna LTE: External Antenna
Antenna Gain:	2.4G Wi-Fi: 2dBi LTE Band 2: 1.79dBi LTE Band 4: -0.12dBi LTE Band 5: -1.56dBi LTE Band 12: -2.76dBi LTE Band 13: -1.28dBi

Note:

#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTEK lab has not verified the authenticity of its information.

Ratings: Input: DC 8-72V

4.3. Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

4.4. Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

Yes No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

4.5. Abnormalities from Standard Conditions

None.

5. Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	FCC Part 2.1091	PASS

6. RF Exposure

Test Requirement: FCC 47CFR Part 2 Subpart J Section 2.1091

Evaluation Method: FCC 47CFR Part 1 Subpart I Section 1.1310,

KDB 447498 D01 General RF Exposure Guidance v06

6.1. Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

6.2. The procedures / limit

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

6.3. MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, R=20cm, as well as the gain of the used antenna, the RF power density can be obtained

6.4. Radio Frequency Radiation Exposure Evaluation

Band	Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2.4G Wi-Fi	2.00	1.58	17.59	57.41	0.018100	1.0
LTE Band2	1.79	1.51	18.83	76.38	0.022944	1.0
LTE Band4	-0.12	0.97	18.75	74.99	0.014510	1.0
LTE Band5	-1.56	0.70	17.76	59.70	0.008292	0.55
LTE Band12	-2.76	0.53	18.9	77.62	0.008179	0.47
LTE Band13	-1.28	0.74	18.29	67.45	0.009992	0.52

The worst case is LTE Band2 and 2.4G WIFI transmitting simultaneously, the result as below:

Evaluation mode	Power density/limit	Sum of the MPE rate	limit
LTE Band2	0.022944	0.041044	1
2.4G WIFI	0.018100		

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.

Conclusion:

RF Exposure is FCC compliant.

=====End of Report=====