

*EXHIBIT 1*

*Label Drawing*

Label Drawing

Model No: 5GLR+

**AOC** COLOR MONITOR

Model No:5GLr+

Power Rating: 100-240V-50/60Hz 1.5A

**FCC ID: ARSCM569E**

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This Class B digital apparatus meets all requirements of the Canadian Interference - Causing Equipment Regulations.  
Cet appareil numérique de la classe B respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.

**THIS DEVICE COMPLIES WITH FDA RADIATION PERFORMANCE STANDARDS, 21 CFR SUBCHAPTER J.**

Die in diesem Gerät entstehende Röntgenstrahlung ist ausreichend abgeschirmt.  
Beschleunigungsspannung: max. 26KV

Cathode Ray Tube intrinsically safe according to appendix III Röntgenverordnung  
Eigensichere Kathodenstrahlröhre nach Anlage III Röntgenverordnung

Made in China  
40A155-051



Please refer Exhibit 2 Figure 2 for Label Placement Location

Label Drawing

Model No.: 5GLR

**AOC** COLOR MONITOR

Model No: 5Glr

Power Rating: 100-240V-50/60Hz 1.5A

Gepriift nach Tested Acc. to  
MPR II: MPR 1990:8/1990:10

Made in China  
40A155-041-01

**FCC ID: ARSCM569E**

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This Class B digital apparatus meets all requirements of the Canadian Interference - Causing Equipment Regulations.  
Cet appareil numérique de la classe B respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.

**THIS DEVICE COMPLIES WITH FDA RADIATION PERFORMANCE STANDARDS, 21 CFR SUBCHAPTER J.**

Die in diesem Gerät entstehende Röntgenstrahlung ist ausreichend abgeschirmt  
Beschleunigungsspannung: max. 26KV  
Cathode Ray Tube intrinsically safe according to appendix III Röntgenverordnung  
Eigensichere Kathodenstrahlröhre nach Anlage III Röntgenverordnung



Please refer Exhibit 2 Figure 2 for Label Placement Location

Label Drawing

Model No.: 5GLRA+

**AOC** COLOR MONITOR

Model No: 5GLRA+

Power Rating: 100-240V-50/60Hz 1.5A

Geprüft nach Tested Acc. to  
MPR II: MPR 1990:2/1990:10

Made in China  
40A155-052

**FCC ID: ARSCM569E**

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This Class B digital apparatus meets all requirements of the Canadian Interference - Causing Equipment Regulations.  
Cet appareil numérique de la classe B respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.

**THIS DEVICE COMPLIES WITH FDA RADIATION PERFORMANCE STANDARDS, 21 CFR SUBCHAPTER J.**

Die in diesem Gerät entstehende Röntgenstrahlung ist ausreichend abgeschirmt.  
Beschleunigungsspannung: max. 26KV  
Cathode Ray Tube intrinsically safe according to appendix III Röntgenverordnung  
Eigensichere Kathodenstrahlröhre nach Anlage III Röntgenverordnung



Please refer Exhibit 2 Figure 2 for Label Placement Location

Label Drawing

Model No.: 5GLRA

**AOC** COLOR MONITOR

Model No: SGIrA

Power Rating: 100-240V-50/60Hz 1.5A

Geprüft nach Tested Acc. to  
MPR II: MPR 1990:2/1990:10

Made in China  
40A155-052

**FCC ID: ARSCM569E**

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This Class B digital apparatus meets all requirements of the Canadian Interference - Causing Equipment Regulations.  
Cet appareil numérique de la classe B respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.

**THIS DEVICE COMPLIES WITH FDA RADIATION PERFORMANCE STANDARDS, 21 CFR SUBCHAPTER J.**

Die in diesem Gerät entstehende Röntgenstrahlung ist ausreichend abgeschirmt.  
Beschleunigungsspannung: max. 26KV  
Cathode Ray Tube intrinsically safe according to appendix III Röntgenverordnung  
Eigensichere Kathodenstrahlröhre nach Anlage III Röntgenverordnung



Please refer Exhibit 2 Figure 2 for Label Placement Location