

ProLED Quick Reference Guide

Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CRI	Lumens	CBCP	Useful Life*	Pkg. Qty.	Beam Spread	MOL	Wattage Equivalent
A19														
4 Watt	Med.	80149	A19FR4/827/LED	A-Shape Dimmable	120	2700	82	250	-	40000	1/6	-	4.25"	25
4 Watt	Med.	80150	A19FR4/830/LED	A-Shape Dimmable	120	3000	82	260	-	40000	1/6	-	4.25"	25
5 Watt	Med.	80020	A19FR5/830/LED	A-Shape Dimmable	120	3000	82	260	-	25000	1/6	-	4.25"	25
6 Watt	GU24	80151	A19FR6/827/GU24/LED	A-Shape Dimmable	120	2700	82	450	-	40000	1/6	-	4.25"	40
6 Watt	Med.	80152	A19FR6/827/LED	A-Shape Dimmable	120	2700	82	450	-	40000	1/6	-	4.25"	40
6 Watt	Med.	80153	A19FR6/830/LED	A-Shape Dimmable	120	3000	82	470	-	40000	1/6	-	4.25"	40
6 Watt	Med.	80817	A19FR6/840/LED	A-Shape Dimmable	120	4000	82	490	-	40000	1/6	-	4.25"	40
6 Watt	Med.	80816	A19FR6/850/LED	A-Shape Dimmable	120	5000	82	510	-	40000	1/6	-	4.25"	40
8 Watt	GU24	80144	A19FR8/827/GU24/LED	A-Shape Dimmable	120	2700	82	450	-	25000	1/6	-	4.25"	40
8 Watt	Med.	80140	A19FR8/827/LED	A-Shape Dimmable	120	2700	82	450	-	25000√	1/6	-	4.25"	40
8 Watt	Med.	80022	A19FR8/830/LED	A-Shape Dimmable	120	3000	82	450	-	35000√	1/6	-	4.25"	40
10 Watt	Med.	80146	A19FR10/827/LED	A-Shape Dimmable	120	2700	82	800	-	25000√	1/6	-	4.41"	60
10 Watt	Med.	80132	A19FR10/830/LED	A-Shape Dimmable	120	3000	82	830	-	40000	1/6	-	4.41"	60
11.5 Watt	Med.	80826	A19FR11/827/OMNI/LED	A-Shape Dimmable, Omnidirectional	120	2700	82	800	-	25000√	1/6	-	4.25"	60
11.5 Watt	Med.	80827	A19FR11/830/OMNI/LED	A-Shape Dimmable, Omnidirectional	120	3000	82	800	-	25000√	1/6	-	4.25"	60
B11														
2 Watt	Cand.	80014	B11/2WW/LED	Chandelier, Cream Finish	120	3000	82	65	-	40000	1/10	-	3.94"	15
3 Watt	Cand.	80094	B11CL3/827/LED	Chandelier Dimmable, Cream Finish	120	2700	82	180	-	25000	1/10	-	3.78"	25
3 Watt	Cand.	80789	B11CL3/827/BR/LED	Chandelier Dimmable, Brass Finish	120	2700	82	180	-	25000	1/10	-	3.78"	25
3 Watt	Cand.	80790	B11CL3/827/CHR/LED	Chandelier Dimmable, Chrome Finish	120	2700	82	180	-	25000	1/10	-	3.78"	25
5 Watt	Cand.	80820	B11CL5/827/LED	Chandelier Dimmable, Cream Finish	120	2700	82	300	-	25000	1/10	-	3.78"	40
5 Watt	Med.	80168	B11CL5/827/E26/LED	Chandelier Dimmable, Cream Finish	120	2700	82	300	-	25000	1/10	-	3.78"	40
BR30														
9 Watt	GU24	80158	BR30FL9/827/GU24/LED	Reflector Dimmable	120	2700	82	650	-	40000	1/6	-	5.12"	65
9 Watt	Med.	80159	BR30FL9/827/LED	Reflector Dimmable	120	2700	82	650	-	25000√	1/6	-	5.12"	65
9 Watt	Med.	80160	BR30FL9/830/LED	Reflector Dimmable	120	3000	82	670	-	40000	1/6	-	5.12"	65
9 Watt	Med.	80161	BR30FL9/840/LED	Reflector Dimmable	120	4000	82	700	-	40000	1/6	-	5.12"	65
9 Watt	Med.	80162	BR30FL9/850/LED	Reflector Dimmable	120	5000	82	730	-	40000	1/6	-	5.12"	65
9 Watt	Med.	80166	BR30FL9/PNK/LED	Reflector Pink Dimmable	120	-	-	-	-	40000	1/6	-	5.12"	65
11 Watt	Med.	80086	BR30FL11/827/LED	Reflector Dimmable	120	2700	82	730	-	25000√	1/6	-	5.12"	65
11 Watt	Med.	80088	BR30FL11/830/LED	Reflector Dimmable	120	3000	82	750	-	25000√	1/6	-	5.12"	65
11 Watt	Med.	80090	BR30FL11/840/LED	Reflector Dimmable	120	4000	82	780	-	40000	1/6	-	5.12"	65
11 Watt	Med.	80092	BR30FL11/850/LED	Reflector Dimmable	120	5000	82	810	-	40000	1/6	-	5.12"	65
BR40														
13 Watt	Med.	80116	BR40FL13/827/LED	Reflector Dimmable	120	2700	82	850	-	25000√	1/6	-	6.46"	85
13 Watt	Med.	80118	BR40FL13/830/LED	Reflector Dimmable	120	3000	82	880	-	25000√	1/6	-	6.46"	85
13 Watt	Med.	80120	BR40FL13/840/LED	Reflector Dimmable	120	4000	82	920	-	40000	1/6	-	6.46"	85
13 Watt	Med.	80122	BR40FL13/850/LED	Reflector Dimmable	120	5000	82	950	-	40000	1/6	-	6.46"	85
18 Watt	Med.	80124	BR40FL18/827/LED	Reflector Dimmable	120	2700	82	1200	-	40000	1/6	-	6.46"	120
18 Watt	Med.	80126	BR40FL18/830/LED	Reflector Dimmable	120	3000	82	1230	-	25000√	1/6	-	6.46"	120
18 Watt	Med.	80128	BR40FL18/840/LED	Reflector Dimmable	120	4000	82	1280	-	40000	1/6	-	6.46"	120
18 Watt	Med.	80130	BR40FL18/850/LED	Reflector Dimmable	120	5000	82	1320	-	40000	1/6	-	6.46"	120
Linear T8														
18 Watt	G13	80171	T8FR18/840/LED	Linear T8 Tube	120-277	4000	80	1800	-	40000	1/12	120°	48"	-
18 Watt	G13	80170	T8FR18/850/LED	Linear T8 Tube	120-277	5000	80	1800	-	40000	1/12	120°	48"	-
B10														
1 Watt	Cand.	80172	B10CL1/827/LED	Clear Dimmable, IP65 Rated	120	2700	82	25	-	25000	1/25	-	3.77"	-
1 Watt	Cand.	80173	B10CL1/724/LED	Clear Dimmable, IP65 Rated	120	2400	72	20	-	25000	1/25	-	3.77"	-
CA10														
1 Watt	Cand.	80174	CA10CL1/827/LED	Clear Dimmable, IP65 Rated	120	2700	82	25	-	25000	1/25	-	4.00"	-
1 Watt	Cand.	80175	CA10CL1/724/LED	Clear Dimmable, IP65 Rated	120	2400	72	20	-	25000	1/25	-	4.00"	-

ProLED Quick Reference Guide



Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CRI	Lumens	CBCP	Useful Life*	Pkg. Qty.	Beam Spread	MOL	Wattage Equivalent
G25														
8 Watt	Med.	80018	G25/8WW/LED	Globe Dimmable	120	3000	82	430	-	25000 ✓	1/6	-	4.25"	40
JC10														
1.5 Watt	G4	80693	JC10/1WW/LED	Omnidirectional	10-18	3000	82	120	-	20000	1/40	-	1.21"	10
1.5 Watt	G4	80776	JC10/1WW/LED2	Omnidirectional, IP65 Rated	10-18	3000	82	100	-	40000	1/10	-	1.75"	10
1.5 Watt	BA15s	80692	JC10/1WW/BA15S/LED	Omnidirectional	10-18	3000	82	120	-	20000	1/40	-	1.70"	10
1.5 Watt	BA15s	80810	JC10/1WW/BA15S/LED2	Omnidirectional, IP65 Rated	10-18	3000	82	100	-	40000	1/10	-	1.93"	10
JC20														
1.8 Watt	G4	80782	JC20/2AMB/LED	Omnidirectional Amber	10-18	-	-	-	-	20000	1/40	-	1.81"	-
1.8 Watt	G4	80780	JC20/2BLU/LED	Omnidirectional Blue	10-18	-	-	-	-	20000	1/40	-	1.81"	-
1.8 Watt	G4	80779	JC20/2GRN/LED	Omnidirectional Green	10-18	-	-	-	-	20000	1/40	-	1.81"	-
1.8 Watt	G4	80781	JC20/2RED/LED	Omnidirectional Red	10-18	-	-	-	-	20000	1/40	-	1.81"	-
2.4 Watt	G4	80690	JC20/2WW/LED	Omnidirectional	10-18	3000	82	200	-	20000	1/40	-	1.81"	20
2.4 Watt	G4	80815	JC20/2NW/LED	Omnidirectional	10-18	5000	72	230	-	20000	1/40	-	1.81"	20
2.4 Watt	G4	80833	JC2/827/LED	Omnidirectional	10-18	2700	82	190	-	20000	1/40	-	1.81"	20
2.4 Watt	BA15s	80691	JC20/2WW/BA15S/LED	Omnidirectional	10-18	3000	82	200	-	20000	1/40	-	2.01"	20
2.5 Watt	G4	80774	JC20/2WW/LED2	Omnidirectional, IP65 Rated	10-18	3000	82	140	-	40000	1/10	-	1.75"	20
2.5 Watt	BA15s	80775	JC20/2WW/BA15S/LED2	Omnidirectional, IP65 Rated	10-18	3000	82	140	-	40000	1/10	-	2.25"	20
JC35														
4.5 Watt	GY6.35	80830	JC35/4WW/LED	Omnidirectional	10-18	3000	82	450	-	20000	1/30	-	2.03"	35
MR11														
2.2 Watt	GU4	80703	MR11/2NW/FL/LED	Flood Dimmable	10-18	5000	72	150	420	40000	1/10	30°	1.42"	15
2.2 Watt	GU4	80705	MR11/2WW/FL/LED	Flood Dimmable	10-18	2700	82	110	330	40000	1/10	30°	1.42"	15
2.2 Watt	GU4	80704	MR11/2WW/NFL/LED	Narrow Flood Dimmable	10-18	2700	82	110	860	40000	1/10	18°	1.42"	15
3.5 Watt	BA15d	80169	MR11FTD/827/LED	Flood	10-15	2700	82	230	1135	40000	1/10	30°	1.89"	20
MR16														
3 Watt	GU5.3	80807	MR16SPI0/827/LED	Spot Dimmable	10-15	2700	82	140	1180	40000	1/10	15°	2.02"	10
3 Watt	GU5.3	80806	MR16NFL10/827/LED	Narrow Flood Dimmable	10-15	2700	82	150	480	40000	1/10	25°	2.02"	10
3 Watt	GU5.3	80801	MR16FL10/827/LED	Flood Dimmable	10-15	2700	82	150	300	40000	1/10	40°	2.02"	10
3 Watt	GU5.3	80808	MR16WFL10/827/LED	Wide Flood Dimmable	10-15	2700	82	140	170	40000	1/10	50°	2.02"	10
3 Watt	GU5.3	80813	MR16FL10/750/LED	Flood Dimmable	10-15	5000	72	160	360	40000	1/10	40°	2.02"	10
3 Watt	GU5.3	80000	MR16/3WW/FL/LED2	Flood	12	3000	82	150	360	40000	1/10	38°	1.97"	10
3.3 Watt	GU5.3	80709	MR16/3WW/FL/LED	Flood Dimmable	10-18	2700	82	150	380	40000	1/10	34°	2.20"	10
4 Watt	GU10	80819	MR16FL4/830/GU10/LED	Flood Dimmable	120	3000	82	220	480	40000	1/10	40°	2.17"	20
4 Watt	GU5.3	80728	MR16/5RGB/FL/LED	Flood Color Changing Red, Green, Blue	10-18	-	-	-	-	40000	1/10	31°	2.17"	-
		80649	RGB/REMOTE	Remote Control for Color Changing Lamps										
4.5 Watt	GU5.3	80795	MR16ESX/827/LED	Spot Dimmable	10-15	2700	82	200	1260	40000	1/10	15°	2.02"	20
4.5 Watt	GU5.3	80793	MR16BBF/827/LED	Narrow Flood Dimmable	10-15	2700	82	220	750	40000	1/10	25°	2.02"	20
4.5 Watt	GU5.3	80792	MR16BAB/827/LED	Flood Dimmable	10-15	2700	82	220	400	40000	1/10	40°	2.02"	20
4.5 Watt	GU5.3	80794	MR16WFL20/827/LED	Wide Flood Dimmable	10-15	2700	82	200	240	40000	1/10	60°	2.02"	20
4.5 Watt	GU5.3	80811	MR16BAB/750/LED	Flood Dimmable	10-15	5000	72	250	480	40000	1/10	40°	2.02"	20
4.5 Watt	GU5.3	80702	MR16/3M4WW/FL/LED	Flood Dimmable	10-18	2700	82	200	560	40000	1/10	34°	2.20"	20
4.5 Watt	GU5.3	80724	MR16/3M4AMB/NFL/LED	Narrow Flood Amber	10-18	-	-	-	-	40000	1/10	22°	2.20"	-
4.5 Watt	GU5.3	80727	MR16/3M4BLU/NFL/LED	Narrow Flood Blue	10-18	-	-	-	-	40000	1/10	22°	2.20"	-
4.5 Watt	GU5.3	80726	MR16/3M4GRN/NFL/LED	Narrow Flood Green	10-18	-	-	-	-	40000	1/10	22°	2.20"	-
4.5 Watt	GU5.3	80725	MR16/3M4RED/NFL/LED	Narrow Flood Red	10-18	-	-	-	-	40000	1/10	22°	2.20"	-
6 Watt	GU5.3	80805	MR16FRB/827/LED	Spot Dimmable	10-15	2700	82	320	1650	40000	1/10	18°	2.02"	35
6 Watt	GU5.3	80804	MR16FRA/827/LED	Narrow Flood Dimmable	10-15	2700	82	350	1500	40000	1/10	25°	2.02"	35
6 Watt	GU5.3	81044	MR16NFL6/830/LED	Narrow Flood Dimmable	12	3000	82	350	940	40000	1/10	25°	2.02"	35
6 Watt	GU5.3	80825	MR16FL6/830/LED	Flood Dimmable	12	3000	82	350	800	25000 ✓	1/10	38°	2.02"	35
6 Watt	GU5.3	80802	MR16FMW/827/LED	Flood Dimmable	10-15	2700	82	350	600	40000	1/10	40°	2.02"	35
6 Watt	GU5.3	80814	MR16FMW/750/LED	Flood Dimmable	10-15	5000	72	410	720	40000	1/10	40°	2.02"	35
6 Watt	GU5.3	80809	MR16WFL35/827/LED	Wide Flood Dimmable	10-15	2700	82	320	250	40000	1/10	60°	2.02"	35
6 Watt	GU10	80084	MR16FL6/830/GU10/LED	Flood Dimmable	120	3000	82	370	620	40000	1/10	40°	3.11"	35

ProLED Quick Reference Guide

Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CRI	Lumens	CBCP	Useful Life*	Pkg. Qty.	Beam Spread	MOL	Wattage Equivalent
MR16 Continued														
7 Watt	GU10	80167	MR16FL7/830/GU10/LED	Flood Dimmable	120	3000	82	520	1100	25000	1/10	40°	2.17"	50
8 Watt	GU5.3	80799	MR16EXT/827/LED	Spot Dimmable	10-15	2700	82	450	2000	40000	1/10	18°	2.02"	50
8 Watt	GU5.3	80800	MR16EXZ/827/LED	Narrow Flood Dimmable	10-15	2700	82	500	1700	40000	1/10	25°	2.02"	50
8 Watt	GU5.3	81043	MR16NFL8/830/LED	Narrow Flood Dimmable	12	3000	82	500	1360	25000	1/10	25°	2.02"	50
8 Watt	GU5.3	81042	MR16FL8/830/LED	Flood Dimmable	12	3000	82	500	1140	25000√	1/10	38°	2.02"	50
8 Watt	GU5.3	80798	MR16EXN/827/LED	Flood Dimmable	10-15	2700	82	500	850	40000	1/10	40°	2.02"	50
8 Watt	GU5.3	80803	MR16FNV/827/LED	Wide Flood Dimmable	10-15	2700	82	500	390	40000	1/10	60°	2.02"	50
8 Watt	GU5.3	80812	MR16EXN/750/LED	Flood Dimmable	10-15	5000	72	580	1020	40000	1/10	40°	2.02"	50
PAR16														
3.6 Watt	Med.	80732	PAR16/4AMB/NFL/LED	Narrow Flood Amber	120	-	-	-	-	40000	1/6	22°	2.99"	-
3.6 Watt	Med.	80729	PAR16/4RED/NFL/LED	Narrow Flood Red	120	-	-	-	-	40000	1/6	22°	2.99"	-
4.5 Watt	Med.	80731	PAR16/4GRN/NFL/LED	Narrow Flood Green	120	-	-	-	-	40000	1/6	22°	2.99"	-
6 Watt	Med.	81038	PAR16FL6/827/W/LED	Flood Dimmable	120	2700	82	370	780	40000	6/24	40°	2.75"	35
6 Watt	Med.	81039	PAR16FL6/830/W/LED	Flood Dimmable	120	3000	82	380	780	25000√	6/24	40°	2.75"	35
6 Watt	Med.	81040	PAR16FL6/840/W/LED	Flood Dimmable	120	4000	82	400	780	40000	6/24	40°	2.75"	35
6 Watt	Med.	81041	PAR16FL6/850/W/LED	Flood Dimmable	120	5000	82	415	780	40000	6/24	40°	2.75"	35
PAR20														
8 Watt	Med.	80638	PAR20/8RGB/NFL/LED	Narrow Flood Color Changing Red, Green, Blue	120	-	-	-	-	40000	1/6	25°	3.50"	-
		80649	RGB/REMOTE	Remote Control for Color Changing Lamps										
8 Watt	Med.	81032	PAR20NFL8/827/W/LED	Narrow Flood Dimmable	120	2700	82	460	1520	25000√	6/24	25°	3.39"	50
8 Watt	Med.	81034	PAR20NFL8/830/W/LED	Narrow Flood Dimmable	120	3000	82	470	1580	25000√	6/24	25°	3.39"	50
8 Watt	Med.	81036	PAR20NFL8/840/W/LED	Narrow Flood Dimmable	120	4000	82	500	1620	40000	6/24	25°	3.39"	50
8 Watt	Med.	81037	PAR20NFL8/850/W/LED	Narrow Flood Dimmable	120	5000	82	500	1710	40000	6/24	25°	3.39"	50
8 Watt	Med.	81033	PAR20FL8/827/W/LED	Flood Dimmable	120	2700	82	460	780	25000√	6/24	40°	3.39"	50
8 Watt	Med.	81035	PAR20FL8/830/W/LED	Flood Dimmable	120	3000	82	470	820	25000√	6/24	40°	3.39"	50
PAR30 Long Neck														
14 Watt	Med.	81016	PAR30NFL14L/827/W/LED	Narrow Flood Dimmable, IP65 Rated	120	2700	82	800	3300	25000√	6/24	25°	4.61"	75
14 Watt	Med.	81018	PAR30NFL14L/830/W/LED	Narrow Flood Dimmable, IP65 Rated	120	3000	82	835	3360	25000√	6/24	25°	4.61"	75
14 Watt	Med.	81020	PAR30NFL14L/840/W/LED	Narrow Flood Dimmable, IP65 Rated	120	4000	82	860	3510	40000	6/24	25°	4.61"	75
14 Watt	Med.	81022	PAR30NFL14L/850/W/LED	Narrow Flood Dimmable, IP65 Rated	120	5000	82	870	3680	40000	6/24	25°	4.61"	75
14 Watt	Med.	81017	PAR30FL14L/827/W/LED	Flood Dimmable, IP65 Rated	120	2700	82	800	1440	25000√	6/24	40°	4.61"	75
14 Watt	Med.	81019	PAR30FL14L/830/W/LED	Flood Dimmable, IP65 Rated	120	3000	82	835	1640	25000√	6/24	40°	4.61"	75
14 Watt	Med.	81021	PAR30FL14L/840/W/LED	Flood Dimmable, IP65 Rated	120	4000	82	860	1710	40000	6/24	40°	4.61"	75
14 Watt	Med.	81023	PAR30FL14L/850/W/LED	Flood Dimmable, IP65 Rated	120	5000	82	870	1760	40000	6/24	40°	4.61"	75
PAR30 Short Neck														
14.5 Watt	Med.	81025	PAR30NFL14S/827/W/LED	Narrow Flood Dimmable	120	2700	82	800	3020	25000√	6/24	25°	3.35"	75
14.5 Watt	Med.	81027	PAR30NFL14S/830/W/LED	Narrow Flood Dimmable	120	3000	82	850	3250	25000√	6/24	25°	3.35"	75
14.5 Watt	Med.	81028	PAR30NFL14S/840/W/LED	Narrow Flood Dimmable	120	4000	82	860	3370	40000	6/24	25°	3.35"	75
14.5 Watt	Med.	81030	PAR30NFL14S/850/W/LED	Narrow Flood Dimmable	120	5000	82	870	3590	40000	6/24	25°	3.35"	75
14.5 Watt	Med.	81024	PAR30FL14S/827/W/LED	Flood Dimmable	120	2700	82	800	1320	25000√	6/24	40°	3.35"	75
14.5 Watt	Med.	81026	PAR30FL14S/830/W/LED	Flood Dimmable	120	3000	82	850	1380	25000√	6/24	40°	3.35"	75
14.5 Watt	Med.	81029	PAR30FL14S/840/W/LED	Flood Dimmable	120	4000	82	860	1460	40000	6/24	40°	3.35"	75
14.5 Watt	Med.	81031	PAR30FL14S/850/W/LED	Flood Dimmable	120	5000	82	870	1570	40000	6/24	40°	3.35"	75
PAR36														
6.5 Watt	MP Term	80106	PAR36/6WW/SP/LED	Spot, IP67 Rated	10-15	2700	82	260	1820	40000	1/6	15°	2.40"	20
6.5 Watt	MP Term	80768	PAR36/6WW/WFL/LED2	Wide Flood, IP67 Rated	10-15	2700	82	260	680	40000	1/6	32°	2.40"	20
10 Watt	MP Term	80783	PAR36/10WW/SP/LED	Spot, IP67 Rated	10-15	2700	82	420	4200	40000	1/6	15°	2.40"	35
10 Watt	MP Term	80769	PAR36/10WW/WFL/LED2	Wide Flood, IP67 Rated	10-15	2700	82	420	920	40000	1/6	32°	2.40"	35
10 Watt	MP Term	80784	PAR36/10AMB/WFL/LED	Wide Flood Amber, IP67 Rated	10-15	-	-	-	-	40000	1/6	32°	2.40"	-
10 Watt	MP Term	80786	PAR36/10BLU/WFL/LED	Wide Flood Blue, IP67 Rated	10-15	-	-	-	-	40000	1/6	32°	2.40"	-

ProLED Quick Reference Guide

Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CRI	Lumens	CBCP	Useful Life*	Pkg. Qty.	Beam Spread	MOL	Wattage Equivalent
PAR36 Continued														
❖ 10 Watt	MP Term	80785	PAR36/10GRN/WFL/LED	Wide Flood Green, IP67 Rated	10-15	-	-	-	-	40000	1/6	32°	2.40"	-
❖ 10 Watt	MP Term	80787	PAR36/10RED/WFL/LED	Wide Flood Red, IP67 Rated	10-15	-	-	-	-	40000	1/6	32°	2.40"	-
⊛ 13.5 Watt	MP Term	80165	PAR36FL14/827/LED	Flood ▲	12	2700	82	870	1830	40000	1/6	32°	2.17"	50
❖ 18 Watt	MP Term	80788	PAR36/18WW/SP/LED	Spot, IP67 Rated	10-15	2700	82	720	3000	40000	1/6	20°	2.40"	50
❖ 18 Watt	MP Term	80770	PAR36/18WW/WFL/LED2	Wide Flood, IP67 Rated	10-15	2700	82	720	1800	40000	1/6	32°	2.40"	50
PAR38														
⊛ 16 Watt	Med.	81000	PAR38NFL16/827/W/LED	Narrow Flood Dimmable, IP65 Rated	120	2700	82	950	4300	25000 ✓	6/24	25°	5.08"	75
⊛ 16 Watt	Med.	81002	PAR38NFL16/830/W/LED	Narrow Flood Dimmable, IP65 Rated	120	3000	82	970	4600	25000 ✓	6/24	25°	5.08"	75
⊛ 16 Watt	Med.	81004	PAR38NFL16/840/W/LED	Narrow Flood Dimmable, IP65 Rated	120	4000	82	1035	4730	40000	6/24	25°	5.08"	75
⊛ 16 Watt	Med.	81006	PAR38NFL16/850/W/LED	Narrow Flood, IP65 Rated	120	5000	82	1040	4800	40000	6/24	25°	5.08"	75
⊛ 16 Watt	Med.	81001	PAR38FL16/827/W/LED	Flood Dimmable, IP65 Rated	120	2700	82	950	1700	25000 ✓	6/24	40°	5.08"	75
⊛ 16 Watt	Med.	81003	PAR38FL16/830/W/LED	Flood Dimmable, IP65 Rated	120	3000	82	970	1750	25000 ✓	6/24	40°	5.08"	75
⊛ 16 Watt	Med.	81005	PAR38FL16/840/W/LED	Flood Dimmable, IP65 Rated	120	4000	82	1035	1960	40000	6/24	40°	5.08"	75
⊛ 16 Watt	Med.	81007	PAR38FL16/850/W/LED	Flood Dimmable, IP65 Rated	120	5000	82	1040	2000	40000	6/24	40°	5.08"	75
⊛ 19 Watt	Med.	81008	PAR38NFL19/827/W/LED	Narrow Flood Dimmable, IP65 Rated	120	2700	82	1200	4350	25000 ✓	6/24	25°	5.08"	90
⊛ 19 Watt	Med.	81010	PAR38NFL19/830/W/LED	Narrow Flood Dimmable, IP65 Rated	120	3000	82	1250	4650	25000 ✓	6/24	25°	5.08"	90
⊛ 19 Watt	Med.	81012	PAR38NFL19/840/W/LED	Narrow Flood Dimmable, IP65 Rated	120	4000	82	1260	4750	40000	6/24	25°	5.08"	90
⊛ 19 Watt	Med.	81014	PAR38NFL19/850/W/LED	Narrow Flood Dimmable, IP65 Rated	120	5000	82	1265	4800	40000	6/24	25°	5.08"	90
⊛ 19 Watt	Med.	81009	PAR38FL19/827/W/LED	Flood Dimmable, IP65 Rated	120	2700	82	1200	2550	25000 ✓	6/24	40°	5.08"	90
⊛ 19 Watt	Med.	81011	PAR38FL19/830/W/LED	Flood Dimmable, IP65 Rated	120	3000	82	1250	2650	25000 ✓	6/24	40°	5.08"	90
⊛ 19 Watt	Med.	81013	PAR38FL19/840/W/LED	Flood Dimmable, IP65 Rated	120	4000	82	1260	2700	40000	6/24	40°	5.08"	90
⊛ 19 Watt	Med.	81015	PAR38FL19/850/W/LED	Flood Dimmable, IP65 Rated	120	5000	82	1265	2760	40000	6/24	40°	5.08"	90
R12														
2.6 Watt	BA15d	80756	GBF/3WW/LED	Elevator Lamp	10-18	2700	82	145	410	40000	1/10	-	2.52"	20
2.6 Watt	BA15s	80701	1383/3WW/LED	Elevator Lamp	10-18	2700	82	145	410	40000	1/10	-	2.52"	20
R20														
⊛ 5 Watt	Med.	80108	R20FL5/830/LED	Reflector Dimmable •	120	3000	82	310	-	40000	1/6	-	3.94"	30
⊛ 5 Watt	Med.	80110	R20FL5/850/LED	Reflector Dimmable •	120	5000	82	335	-	40000	1/6	-	3.94"	30
⊛ 8 Watt	Med.	80818	R20FL8/827/LED	Reflector Dimmable •	120	2700	82	500	-	25000 ✓	1/6	-	3.94"	50
⊛ 8 Watt	Med.	80112	R20FL8/830/LED	Reflector Dimmable •	120	3000	82	520	-	25000 ✓	1/6	-	3.94"	50
⊛ 8 Watt	Med.	80114	R20FL8/850/LED	Reflector Dimmable •	120	5000	82	560	-	40000	1/6	-	3.94"	50
Plastic Wedge														
1 Watt	Plastic Wedge	80791	912/1WW/LED	Mini-Wedge	10-18	3000	-	50	-	20000	1/50	-	1.18"	-
2.5 Watt	Plastic Wedge	80777	3155/2WW/LED	Wedge, IP65 Rated	10-18	3000	82	140	-	40000	1/10	-	2.40"	20
S14														
⊛ 1.4 Watt	Med.	80517	S14RED1C/LED	Red Dimmable, IP65 Rated	120	-	-	-	-	40000	1/25	-	3.35"	-
⊛ 1.4 Watt	Med.	80518	S14BLU1C/LED	Blue Dimmable, IP65 Rated	120	-	-	-	-	40000	1/25	-	3.35"	-
⊛ 1.4 Watt	Med.	80519	S14GRN1C/LED	Green Dimmable, IP65 Rated	120	-	-	-	-	40000	1/25	-	3.35"	-
⊛ 1.4 Watt	Med.	80520	S14YEL1C/LED	Yellow Dimmable, IP65 Rated	120	-	-	-	-	40000	1/25	-	3.35"	-
⊛ 1.4 Watt	Med.	80521	S14WH1C/LED	White Dimmable, IP65 Rated	120	-	-	-	-	40000	1/25	-	3.35"	-
⊛ 1.4 Watt	Med.	80522	S14CL1C/827/LED	Clear Dimmable, IP65 Rated	120	2700	82	35	-	40000	1/25	-	3.35"	-

⊛ NEW ITEM!

Represents lamps that are ENERGY STAR approved. ● Identifies lamps pending ENERGY STAR approval.

✓ ENERGY STAR mandates that all directional lamps may only be listed at 25,000 hour life with 3,000 hour actual life test data, 6,000 hour LM80 data and in-situ temperature measurements. Upon completion of full lifetime testing, ProLED ENERGY STAR listed lamps will be listed at their full lifetime.

• May not be compatible with all dimming systems, dimming performance may vary by system. Use on incompatible systems may shorten lamp life. Lamps should be tested in the application for compatibility prior to full installations on circuits using such devices.

❖ Rated for Outdoor Use Only.

▲ Rated for Indoor Use Only.

IP65 rating classifies the lamp is protected against the entry of dust in sufficient quantity to interfere with satisfactory operation of equipment and is intended for indoor or outdoor use primarily to provide a degree of protection against hose directed water from all practical directions.

IP67 rating classifies the lamp is protected against the effects of temporary immersion between 15cm (5.9in) and 1m (3.28ft) and is intended for indoor or outdoor use primarily to provide a degree of protection against hose directed water, the entry of water during occasional temporary submersion at a limited depth, and damage from external ice formation.

Halco Lighting Technologies | 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612 | Fax 800.880.0822 | halcolighting.com | Atlanta | Carlstadt | Cleveland | Houston | Los Angeles | Phoenix

© 2014 Halco Lighting Technologies, LLC. All rights reserved. 'where there's light, there's halco', Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change. Online Edition 03-25-14.