



SMART PLUG

HS100 / HS110*

*Smart Plug with Energy Monitoring.



1 Download TP-LINK Kasa app



OR



2 Connect mobile device to your Wi-Fi network



OR



Note: The Smart Plug can only connect to 2.4GHz network.

3 Launch Kasa and follow the app instructions



Quick Setup



Enjoy

Button



Press and hold until the Wi-Fi LED blinks amber and green alternately (about 5 seconds) to initiate the App-Config process.

Press and hold until the Wi-Fi LED blinks amber quickly (about 10 seconds) to reset the Smart Plug to factory defaults.

LEDs



Wi-Fi

Blinking Amber and Green: App-Config mode initiated.

Quick Blinking Green: Connecting to the network.

Solid Green: Connected to the network.

Quick Blinking Amber: Factory reset.

Solid Amber: Rebooting.

Solid Red: No network connection.

Power

Solid Green: The Smart Plug is switched on.

Off: The Smart Plug is switched off.

Frequently Asked Questions (FAQs)

1. What devices can I control with the Smart Plug?

You can control lights, fans, humidifiers, portable heaters, and any small appliances in accordance with the Smart Plug's specifications.

2. What should I do when I can't turn devices on or off?

Make sure that the devices connected to the Smart Plug are turned on, and that the Smart Plug is connected to the network.

3. What should I do when the Wi-Fi LED is lit solid red?

A solid red indicates no network connection, or that the App-Config process has failed. You can:

- Check for interference or relocate the Smart Plug to another location within the signal range.
- Make sure that you connect the Smart Plug to the 2.4GHz network.
- Repeat the App-Config process.
- Factory reset the Smart Plug and try to add it again.

Technical Support



For technical support, advanced features, and usage tips for the Smart Plug, visit www.tp-link.com.