



PCOM-B880VG2

COM-HPC® Client module Size C module with Intel® 10th Gen socket type processor (Comet Lake-S) DDR4 SO-DIMM, DDI, PCIe Gen3, USB 3.2 Gen2, 2.5 Gigabit TSN Ethernet, discrete TPM 2.0, eDP, SATA III



FEATURES

- 10th Gen Intel® Xeon, Core™ i9/i7/i5/i3, Pentium and Celeron 14nm lithography(Comet Lake-S)
- 2x Non-ECC/ECC SO-DIMM up to 2933MT/s, and up to 64GB capacities
- 2x 2.5G Ethernet with TSN Capability
- 4x USB3.2 Gen 2, 8x USB2.0, 2x SATAIII, 3x DDI, eDP



PCOM-B880VG2 is Intel® Comet Lake-S platform COM-HPC® Client, Size C module. The COM-HPC® Client Formfactor support more I/O interface and power for desktop level CPU for wider computing demand applications. The desktop CPU on module offers customer higher computing power but lower cost comparing to mobile solutions. PCOM-B880VG2 supports both ECC and Non-ECC DDR4 by different PCH SKUs (Q470E/W480E), which can be adapted to different applications. This module provides one PCIe x16, four USB 3.2 Gen2, two SATA III, PCIe storage and up to 20 PCIe x1 lanes.

CPU and General

PCOM-B880VG2										
COM HPC Client, Size C										
Product	PCOM-B880VG2									
Form Factor	COM HPC Client, Size C									
CPU SKU	TDP	Core	Threads	Cache	Base Freq	Max Turbo Freq	Max Memory MT/s	W480E	Q470E	ECC
Xeon W-1250E	80W	6	12	12MB	3.5GHz	4.7GHz	2933 MT/s	Yes	No	Yes
Xeon W-1290TE	35W	10	20	20MB	1.8GHz	4.5GHz				
Xeon W-1270TE	35W	8	16	16MB	2.0GHz	4.4GHz				
Xeon W-1250TE	35W	6	12	12MB	2.4GHz	3.8GHz				
i9-10900TE	35W	10	20	20MB	1.8GHz	4.5GHz	2666 MT/s	Yes	Yes	No
i7-10700TE	35W	8	16	16MB	2.0GHz	4.4GHz				
i5-10500E	65W	6	12	12MB	3.1GHz	4.2GHz				
i5-10500TE	35W	6	12	12MB	2.3GHz	3.7GHz				
i3-10100E	65W	4	8	6MB	3.2GHz	3.8GHz	2400 MT/s	No	Yes	Yes
i3-10100TE	35W	4	8	6MB	2.3GHz	3.6GHz				
Pentium G6400E	65W	2	4	4MB	3.8GHz	3.8GHz				
Pentium G6400TE	35W	2	4	4MB	3.2GHz	3.2GHz				
Celeron G5900E	65W	2	2	2MB	3.2GHz	3.2GHz	2400 MT/s	No	No	No
Celeron G5900TE	35W	2	2	2MB	3.0GHz	3.0GHz				

I/O Interface

SATA	2 x SATA III		
NVME	2x PCIe NVME Gen3 x4, with Intel® RST		
USB	4x USB 3.2 Gen2 8x USB 2.0		
Ethernet	Intel® I225LM x2		
AUDIO	HDA		
Serial I/O	GPIO	12 bit GPIO (default 6 input / 6 output)	
	I ² C	Baud Rate : 400KHz	
	SMBus	Baud Rate : 100KHz	
	eSPI		
	UART	2x TX/RX signal only	
PEG	1x Gen3 x16 (Group 1) (Bifurcation Support: 2 x8, or 1x8 + 2x4)		
PCI Express	8x Gen3 x1 (Group 0 Low) 2x Gen3 x4 (Group 0 High) 1x Gen3 x4 (Group 2, #32 ~ #35)		
Display	Default	Options	Resolution
	eDP 1.4	DP 1.4	4096 x 2304@60Hz
	DDI 1, 2, 3	HDMI 2.0a	4096 x 2304@60Hz
HDMI 1.4		4096 x 2160@30Hz	
Security	TPM 2.0		

