

DESTINI125



- STOPS WHEN IDLE
- SAVES FIIFI
- SAVES FUEL

THINK AHEAD RIDE AHEAD



TECHNICAL SPECIFICATIONS

ENGINE

Type Displacement

Max Power
Max Torque

Starting

TRANSMISSION

Clutch Gear Box

SUSPENSION

Front Rear

DIMENSIONS

Length Width Height Wheelbase Ground Clearance

ELECTRICALS

Battery Tail Lamp Head Lamp

Turn Signal Lamp

TYRES

Front Tyre Rear Tyre

WEIGHT

Kerb Weight Maximum Payload Air-cooled, 4-stroke, SI engine

124.6 cc

6.5 kW (8.7 bhp) @ 6750 Revolutions Per Minute (rpm) 10.2 Nm @ 5000 Revolutions Per Minute (rpm) Self-Start / Kick-Start

> Dry, Centrifugal Variomatic Drive

Telescopic, Hydraulic Shock Absorbers Single Coil Spring Hydraulic Type

> 1809 mm 729 mm 1154 mm 1245 mm 155 mm

12 V - 4 Ah (MF Battery)
12 V - 5/21 W (Multi-Reflector Type)

12 V - 35 W/35 W - Halogen Bulb (Multi-Reflector Type)
12 V - 10 W x 4 nos. - (MFR - Clear Lens - Amber Bulb)

90/100 - 10 90/100 - 10

111.5 kg 130 kg

COMES IN 2 VARIANTS

FEATURES

Mobile Charging Port Wheels Boot Lamp Rear-view Mirrors

Seat

VX

Standard
Alloy
Standard
Body Colored

Dual Textured

LX

Optional
Sheet Metal
Optional
Textured Black

Mono Textured

OPTIONAL ACCESSORIES

Side Stand | Side Stand Switch | Glove Box | Step Saree Kit



Revolutionary i_3s Technology
for Great Mileage



125cc Energy Boost Engine for a Power Packed Performance



Telescopic Front Suspension

for a Smooth Ride



Elegant Metallic Body and Premium Chrome
Finish for a majestic road presence



External Fuel Filling, Mobile Charging Port, Service Reminder and many more

ATTRACTIVE COLORS



Noble Red (only in VX)



Chestnut Bronze



Pearl Silver White



Panther Black

него

Regd. Office: Hero MotoCorp Ltd. 34, Community Centre, Basant Lok, Vasant Vihar, New Delhi- 110057, India. CIN: L35911DL1984PLC017354. **Authorized Outlet**

It is our endeavour to improve our product. This could lead to changes in product specifications without notice. Accessories and features shown may not be a part of the standard fitment. Always wear a helmet while riding a two-wheeler.

*i3s Technology - Stops when scooter is idle, crank rotation up to 2000 RPM, irrespective of speed. Restarts with the press of the left brake lever. For further information, please contact the nearest Hero Motocoro's authorized outlet(s) or call Toll Free No: 1800-266-0018 or visit website www.heromotocoro.com