

Testing Report

Customer Name: Xiamen VBeT Electronics Co., Ltd

Product Name: 1.9GHz Antenna

Sample Model: W320BS A

Reference Standard: *GB/T 9410-2008; ANSI/IEEE Std 149-2021*

Issue Date: 2023.3.8

Engineer: Zkmis	Date: 2023.3.7
Auditor: Eason	Date: 2023.3.8
Approver: Janson	Date: 2023.3.08



Version

Version No.	Date	Description	Formulate	Approval
A0	2023.3.8	For the first time, formulate	Zkris	Eason

Contents

1.General Information3

 1.1 General information of testing institutions3

 1.2 Testing principle 3

 1.3 Test equipment4

 1.4 Test environment4

 1.5 Statement 4

2.Sample Information 5

 2.1 Client information5

 2.2 Description of EUT(S)5

 2.3 EUT appearance6

 2.4 EUT setup photo of free space OTA tesing 6

3.Test Results 7

 3.1 Test standard 7

 3.2 Test uncertainty7

 3.3 Test data 8

 3.3.1 VSWR parameters 8

 3.3.2 VSWR data 8

 3.3.3 Typical free space efficiency and gain 8

 3.3.4 Typical free space radiation pattern9

 (The following is blank) 10

1.General Information

1.1 General information of testing institutions

Name	Shenzhen RFI-LAB Communication Technology Co., Ltd.
Address	10/F A, Lingyun Bld, Liufang Rd, Baoan District, SZ
Tel	/
E-mail	/
Equipment	All the equipment used in the report is fixed in Zone B, West Side of 1/F, Building 1, Tingwei Industrial Park, No.6 Liufang Road, Bao 'an District, Shenzhen

1.2 Testing principle



1.3 Test equipment

Equipment	Model No.	Serial No.	Manufacturer	Calibration date	Next calibration date
OTA Test System	RayZone-5000	RFI-LAB-RF-D00	GTS	2021.3.15	2023.3.14
Network Analyzer	E5071C	RFI-LAB-RF-D01	KEYSIGHT	2022.5.13	2023.5.12

1.4 Test environment

Temperature	23.4°C
Humidity	58%RH
Pressure	100.14kPa

1.5 Statement

- (1) The test results in the report are only applicable to the tested samples and the tested samples work under the environment described in the report.
- (2) Only Shenzhen RFI-LAB Communication Technology Co., Ltd. have the right to modify the report, and the modification information shall be annotated in the revision form.
- (3) Any objection to this report shall be raised within 30 days after formal confirmation of the report.
- (4) This report is invalid if there is any evidence that the sample information provided is falsified.
- (5) The report is invalid without the signature of the auditor and approver.

2. Sample Information


2.1 Client information

Name	Xiamen VBeT Electronics Co., Ltd
Address	N403, Weiye Building, Xiamen Pioneering Park for Overseas Chinese Scholars, PRC
Contacts	Manager Lin
Tel	18850172684
E-mail	lingyang.lin@vbet.cn
Manufacturer	/

2.2 Description of EUT(S)


Product Name	1.9GHz Antenna
Sample Model	W320BS A
Antenna Size	/
Serial No.	/
Antenna Type	PCB Antenna
Test Item	VSWR; Antenna gain; Efficiency; Radiation pattern
Frequency Range	1910-1930MHz
Received Date	2023.3.6
Test Date	2023.3.7
Remark	The length of the RF cable is 90mm

2.3 EUT appearance




2.4 EUT setup photo of free space OTA testing

Planform



Front view



3. Test Results

3.1 Test standard

Name	Parameter	Method	Standard no.
Mobile communication antenna	Antenna gain	Generic specification for antennas used in the mobile communications	GB/T 9410-2008
	Radiation pattern		
	VSWR		
Antenna	Radiation efficiency	IEEE Standard Test Procedures for Antennas	ANSI/IEEE Std 149-2021
	Gain and directivity		


3.2 Test uncertainty

The uncertainty was calculated on the basis of the GUM published by ISO, using the inclusion factor of $K=2$ and the 95% confidence level to express the extended uncertainty.

Item	Uncertainty
VSWR	± 0.3
Antenna gain	$\pm 1\text{dB}$
Radiation efficiency	$\pm 10\%$

3.3 Test data

3.3.1 VSWR parameters



3.3.2 VSWR data


Frequency/MHz	1910	1920	1930
VSWR	15.824	14.365	13.089

3.3.3 Typical free space efficiency and gain


Frequency/MHz	1910	1912	1914	1916	1918	1920	1922	1924	1926	1928	1930
Peak Gain/dBi	-14.34	-14.46	-14.36	-14.03	-13.51	-13.25	-13.32	-13.37	-13.21	-12.76	-12.48
Efficiency/%	0.93	0.92	0.96	1.05	1.16	1.21	1.22	1.23	1.28	1.39	1.48

3.3.4 Typical free space radiation pattern


(1) X-Z Plane(unit:dBi):




(2) Y-Z Plane(unit:dBi):



(3) X-Y Plane(unit:dBi):



(4) Typical Free Space 3D Radiation Pattern at 1930MHz(unit:dBi):



End

(The following is blank)