



Sunlite 88124-SU LED Canopy Light Fixture, 75 Watts (250-400W Equivalent), 120-277 Volts, 7900 Lumens, ETL and DLC Listed, Bronze Finish, 50K - Super White

- o UPGRADE TO LED - Sunlite LED Canopy Light Fixtures provide ample illumination and high visibility while saving energy compared to halogen, metal halide, or high pressure sodium lights. They are instant on at full brightness with no warm up time. Integrated LEDs mean no bulbs to replace.
- o ENERGY EFFICIENT - Using 75 watts of energy these fixtures have a low estimated annual energy cost of \$9.03. (Based on 3 hours/day use at \$0.11/kWh) With a 50,000 hour lifespan these fixtures will provide significant savings in electricity over their lifetime and require no maintenance.
- o HIGH LUMEN OUTPUT - Each fixture contains 96 high output LEDs and gives off a bright 8500 lumen output with 5000K daylight color temperature.
- o MULTIPLE OUTDOOR USES - These commercial grade fixtures are made from weatherproof aluminum with a bronze finish and a polycarbonate lens. Wide 120 degree beam angle. These vandalproof fixtures are ideal for gas station canopies, parking structures, underpasses, security lighting, and more.
- o ETL AND DLC LISTED - These fixtures are ETL Listed for wet location installation and not rated for enclosed fixtures and DLC Listed for quality and efficiency. They operate on 120-277 volt service.



General Characteristics

Fixture Life Hours	50000 Hours
Material	Aluminum & Polycarbonate
Lens Material	Polycarbonate
Lens Finish	Clear
Bulb	Integrated LED
Finish	Bronze
Lumens Per Watt (LPW)	105.33
Life (based on 3hr/day)	45.7
Estimated Energy Cost	\$9.03 per Year
Safety Rating	ETL Listed - Wet Location
DLC	True

Fixture Characteristics

Shape	Square
Number of Lights	1 - Light
Mounting	Surface
Use Location	Outdoor

Electrical Characteristics

Watts	75
Volts	120-277
Equivalent Watts	250-400W
LED Chip Manufacturer	Philips 3030
Number of LEDs	96
Power Factor	0.92
Operating Temperature	-40° to 40° C

Light Characteristics

Brightness	7900 Lumens
Color Accuracy (CRI)	70
Light Appearance	Super White
Color Temperature	5000K
Beam Angle	120°

Product Dimensions

Item Dimensions (in)	(W) 10.50 (H) 2.96 (D) 10.50
Package Dimensions (in)	(W) 10.90 (H) 11.10 (D) 4.90

Product Data

Item Number	88124-SU
Case Quantity	4
Barcode on SKU	653703881249
Barcode on Case	10653703881246
Brand	SUNLITE
Description	LFX/MCM/75W/50K
DLC File Number	PQS0L2E8